KOSOVA RADAR — MASTER ROADMAP

Planifikim profesional nga V1 deri në produktin final • 02 Tetor 2026

1. Product Vision

Kosova Radar është një platformë web/mobile-ready që mbledh, verifikon, normalizon dhe shfaq në kohë të afërt reale evente, oferta, zbritje, price drops, aktivitete dhe njoftime relevante në Kosovë.

Parimi kryesor: data first, verification first, automation gradually. AI përdoret si shtresë extraction/classification/verification, jo si burim i pakontrolluar që publikon direkt.

2. Version Map

V1 — Private Beta / Real Client: event discovery + deals bazë + source monitoring + AI extraction + verification + admin review + public feed. Synim: produkt real që përdoret nga klientë.

V1.1 — Reliability: duplicate detection, expiry, stale-data handling, source health, better search/filtering, analytics.

V2 — Automation: më shumë burime, automatic publishing me confidence thresholds, price monitoring, notifications, saved items.

V3 — Intelligent Radar: AI agent për source discovery/monitoring, personalized feed, recommendations, natural-language search.

V4 — Platform: merchant/venue portal, submissions, paid promotion, dashboards, APIs, partnerships.

V5 — Scale: mobile apps/PWA hardening, multi-city/multi-country architecture, advanced observability, billing and enterprise integrations.

3. V1 — Foundation

Frontend: React + TypeScript. Backend: ASP.NET Core Web API. Database: SQL Server. Background jobs: Hangfire ose alternativë e ngjashme. Authentication: ASP.NET Core Identity/JWT. Deployment: Docker-ready.

Core domains: Users, Sources, Events, Deals, Categories, Venues, Cities, Tags, Media, Verification, Audit, Notifications, Jobs.

V1 duhet të ketë dev/staging/production configuration dhe environment variables për secrets.

4. V1 — Data Pipeline

Source registry → scheduled fetch → raw capture → parser/extractor → normalized candidate → AI classification/extraction → validation → duplicate matching → review/publish → expiry/refresh.

Çdo record ruan sourceUrl, sourceName, fetchedAt, lastVerifiedAt, confidence, status, startsAt/endsAt kur aplikohet dhe audit history.

Statuset minimale: Draft, Candidate, NeedsReview, Published, Stale, Expired, Rejected.

5. V1 — Public Product

Home feed me tabs/filters: Sot, Evente, Oferta. City filter, category filter, date filter dhe search.

Event card: title, venue, city, date/time, image, price kur ekziston, source, verification timestamp dhe CTA.

Deal card: product/service, old/new price kur ekzistojnë, discount, merchant, validity, source dhe CTA.

Detail pages SEO-friendly dhe shareable.

6. V1 — Admin

Dashboard: candidate items, review queue, source health, published/expired counts, errors.

Admin review: approve, reject, edit, merge duplicates, expire, mark source unreliable.

Source management: enable/disable, URL, type, polling interval, parser strategy, last success, last error.

7. V1 — AI

Extraction schema të strukturuara; AI nuk duhet të shpikë fusha. Unknown = null.

Verification checks: Kosovo relevance, date validity, source consistency, completeness, duplicate likelihood.

Confidence thresholds: high-confidence can be queued for auto-publish only after enough V1 data exists; initially keep human approval as default.

AI calls duhet të jenë observable, retryable dhe me cost limits.

8. V1 — Testing

Unit tests: domain rules, parsers, validators, deduplication, expiry.

Integration tests: API + SQL Server, authentication, background jobs.

E2E tests: source ingestion → review → publish → public display → expiry.

Failure tests: malformed source, timeout, duplicate event, missing date, invalid URL, AI timeout, database outage.

Manual acceptance test me klientë realë para public launch.

9. V1 — Security & Operations

Secrets vetëm në environment/secret store; input validation; rate limiting; structured logging; error handling; role-based admin access; backups.

Source fetching duhet të respektojë terms/robots/access rules dhe rate limits. Për rrjete sociale përdoren vetëm rrugë të lejuara nga platformat/API-të; mos u var nga scraping agresiv.

Monitoring: API health, job failures, source freshness, AI failures, database errors.

10. V1 Launch Gate

Zero critical security issues; migrations reproducible; automated tests green; backups verified; source monitoring stable; no expired content displayed as active; admin can recover failed ingestion; at least one complete production-like ingestion flow verified.

Beta launch: limited users/clients. Collect real feedback and logs for 2–4 weeks before expanding automation.

11. V1.1 — Reliability

Automatic duplicate clustering, better entity matching, source-specific parsers, change detection, stale alerts, source reliability metrics, richer admin analytics, improved search.

12. V2 — Automation

Expand source coverage; automatic refresh; price-drop detection; notification engine; user accounts; saved events/deals; personalized alerts; automatic publishing for high-confidence sources with audit trail.

13. V3 — Intelligent Radar

Agent discovers candidate sources, proposes new sources for approval, monitors source changes, detects emerging events/deals, summarizes daily radar, and supports natural-language queries.

Agent actions remain constrained by tools, schemas, permissions, rate limits and approval policies.

14. V4 — Business Platform

Venue/merchant accounts, self-service submission, claim/verify business, promotional listings, analytics dashboard, subscription/billing layer, partner API.

15. V5 — Scale

Mobile apps/PWA optimization, queue/event architecture if needed, caching/search infrastructure, multi-region readiness, multi-country localization, advanced observability and enterprise API.

16. Suggested Timeline

V1 foundation + ingestion: 4–6 weeks; hardening/admin/testing: 2–3 weeks; controlled beta: 2–4 weeks.

V1.1: 3–5 weeks. V2: 6–10 weeks. V3: 8–12+ weeks depending on source complexity. V4/V5 should be driven by measured demand rather than calendar alone.

17. Definition of Done for the Product

Kosova Radar is considered mature when content can be discovered with minimal manual effort, verified with traceable sources, expired automatically, searched quickly, monitored operationally, and safely extended with new source adapters without rewriting the core system.