

Codebrag Installation Guide

Prerequisites

- Java 1.7 installed. [Download here](#) or install package for your server's OS.
- MongoDB version 2.4.x installed. [Download here](#) or install package for your server's OS.

Configuring Codebrag

Codebrag has one configuration file `codebrag.conf` provided with distribution. Edit the following settings accordingly.

"mongo" section

Set `servers` and `database` properties to point your MongoDB installation.

"repository" section

Codebrag can work with VCS repositories in three modes. You need to set one using `type` property:

- `git-https` - git via https (with user/password provided)
- `git-ssh` - git via ssh (with keys)
- `svn` - experimental

Git repository via SSH

To use Codebrag with git repository with authentication via ssh (keys) please configure repository section as follows. Also remember to have ssh keys properly configured (leave passphrase empty if there is no passphrase for your keystore).

NOTE: Test you repository ssh connection and add host to `known-hosts` otherwise Codebrag will not be able to authenticate. You may also want to create ssh configuration in `~/.ssh/config` file.

```
repository {
  type = "git-ssh"
  git-ssh {
    name = "..."/>

```

Git repository via HTTPS

To use Codebrag with git via https (user/password required) please configure repository section as follows (leave username and password empty for public repositories):

```
repository {
  type = "git-https"
  git-https {
    name = "..."/>

```

SVN repository (experimental)

You can also use Codebrag with SVN repositories although **this is experimental feature** still in development. To do that, please change your repository configuration section to this:

```
repository {
  type = "svn"
  svn {
    name = "..."/>

```

"email" section

Setup your email server/account so Codebrag can send emails with invitations and other notificaitons to users.

```
email {
  smtp-host = "smtp.gmail.com"
  smtp-port = "465"
  smtp-username = "user@mydomain.com"
  smtp-password = "myPassword"
  from = "user@mydomain.com"
  encoding = "UTF-8"
}
```

"codebrag" section

applicationUrl

Please specify `codebrag.applicationUrl` property. It should indicate URL that users would access to use Codebrag. It is used to create registration link.

```
applicationUrl = "http://codebrag.mydomain.com:8080"
```

local-git-storage-path

Codebrag needs to store repository data somewhere on your server. Edit `local-git-storage-path` accordingly. Codebrag will create directory called `repos` under provided location. Remember to set access rights accordingly so that Codebrag can read and write to this location.

"web-server" section

By default Codebrag starts on port 8080. If you want to change that, edit `port` property accordingly.

Running Codebrag

Assuming your MongoDB is working and java is installed Codebrag can be run with

```
./run.sh
```

Logs will be written to `codebrag.log`

Logging into codebrag

First user that access Codebrag after installation will be asked to register his account. Either email address or name provided have to match corresponding fields in `git log` in order to match commits with given user. Codebrag uses [Gravatar](#) to display user avatars in application.

Other users can be invited to Codebrag by choosing "Invite friends" link from menu in upper left corner.

Contact us if you want

If you experience any issues with Codebrag, do not hesitate to contact us via (email/forum/uservoice/irc). Also if want to let us know your feelings about Codebrag, drop us a line too.