



SILKSCREEN TOP SIDE
31-0009 REV 1




DRILL CHART			
SYMBOL	SIZE	QTY	PLATED TYPE
+	0.010 +0/-0.005	24	PLATED
X	0.035 +/-0.003	10	PLATED
□	0.043 +/-0.003	9	PLATED
A	0.096 +/-0.003	4	NON-PLATED
B	0.126 +/-0.003	2	PLATED


NOTES:

1. MAT'L: 0.062 THK. FR4 COPPERCLAD LAMINATE.
2. ALL HOLES TO BE PLATED THRU WITH A MINIMUM WALL THICKNESS OF 0.001.
3. BOARDS TO BE LPIOBC ON BOTH SIDES - GREEN COLOR.
4. BOARDS TO BE ENIG FINISH AFTER SOLDERMASK.
5. BOARDS TO BE SILKSCREENED ON TOP SIDE WITH PERMANENT, WHITE EPOXY (CHEMICAL AND SCRATCH RESISTANT).
6. BOARDS TO BE ELECTRICALLY TESTED FOR SHORTS AND OPENS.
7. BOARDS SHALL BE MADE FROM UNDERWRITER LABORATORY RECOGNIZED MATERIAL AND THE FINISHED BOARD MUST CARRY THE VENDOR'S U.L. LOGO AND DATE CODE.
8. ALL DRAWINGS AND FILMS VIEWED FROM TOP SIDE.






SOLDERPASTE
31-0009 REV 1




SILKSCREEN TOP SIDE
31-0009 REV 1




SOLDERMASK TOP SIDE

31-0009 REV 1




TOP SIDE


31-0009 REV 1




LAYER 2 SIGNAL
31-0009 REV 1



LAYER 3 SIGNAL
31-0009 REV 1



BOTTOM SIDE
31-0009 REV 1



31-0009 REV 1
SOLDERMASK BOTTOM SIDE