



SILKSCREEN
31-0007 REV 1




NOTES:

1. MAT'L: 0.062 THK. FR4 COPPERCLAD LAMINATE.
2. ALL HOLES TO BE PLATED THRU WITH A MINIMUM WALL THICKNESS OF 0.001.
3. BOARDS TO BE LPIOBC ON BOTH SIDES – GREEN COLOR.
4. BOARDS TO BE ENIG FINISH AFTER SOLDERMASK.
5. BOARDS TO BE SILKSCREENED ON TOP SIDE WITH PERMANENT, WHITE EPOXY (CHEMICAL AND SCRATCH RESISTANT).
6. BOARDS TO BE ELECTRICALLY TESTED FOR SHORTS AND OPENS.
7. BOARDS SHALL BE MADE FROM UNDERWRITER LABORATORY RECOGNIZED MATERIAL AND THE FINISHED BOARD MUST CARRY THE VENDOR'S U.L. LOGO AND DATE CODE.
8. ALL DRAWINGS AND FILMS VIEWED FROM TOP SIDE.




DRILL CHART			
SYMBOL	SIZE	QTY	PLATED TYPE
+	0.015 +0/-0.005	55	PLATED
x	0.035 +/-0.003	10	PLATED
□	0.043 +/-0.003	38	PLATED
A	0.126 +/-0.003	4	PLATED
B	0.134 +/-0.003	4	PLATED




SOLDERPASTE

31-0007 REV 1




SILKSCREEN

31-0007 REV 1




SOLDERMASK TOP SIDE

31-0007 REV 1




TOP SIDE
31-0007 REV 1




LAYER 2 GROUND


31-0007 REV 1



LAYER 3 POWER
31-0007 REV 1



31-0007 REV 1
BOTTOM SIDE



31-0007 REV 1
SOLDERMASK BOTTOM SIDE