

# Practical AI: NLP. Semantics part 2

Stanislav Protasov for  
Harbour.Space University




# Before we start...

Small challenge!

# TF-IDF

$$w_{i,j} = tf_{i,j} \times \log \left( \frac{N}{df_i} \right)$$

# Search engine




$$\text{similarity} = \cos(\theta) = \frac{A \cdot B}{\|A\| \|B\|} = \frac{\sum_{i=1}^n A_i B_i}{\sqrt{\sum_{i=1}^n A_i^2} \sqrt{\sum_{i=1}^n B_i^2}}$$

# Documents to vectors (LSA)

- 1) Build terms-document matrix
- 2) Reduce dimensions (LSA) preserving similarity measure
- 3) Profit!

**Latent semantic analysis** can be easily performed using **PCA** (principal component analysis) which can be performed using **SVD** (singular value decomposition) of terms-document matrix. Or other algorithm :)

$$\begin{pmatrix} & X & \\ \begin{pmatrix} x_{11} & x_{12} & \dots & x_{1n} \\ x_{21} & x_{22} & \dots & \\ \vdots & \vdots & \ddots & \\ x_{m1} & & & x_{mn} \end{pmatrix} & = & \begin{pmatrix} U & \\ \begin{pmatrix} u_{11} & \dots & u_{1r} \\ \vdots & \ddots & \\ u_{m1} & & u_{mr} \end{pmatrix} & \begin{pmatrix} S & \\ \begin{pmatrix} s_{11} & 0 & \dots \\ 0 & \ddots & \\ \vdots & & s_{rr} \end{pmatrix} & \begin{pmatrix} V^T & \\ \begin{pmatrix} v_{11} & \dots & v_{1n} \\ \vdots & \ddots & \\ v_{r1} & & v_{rn} \end{pmatrix} \end{pmatrix} \\ m \times n & m \times r & r \times r & r \times n \end{pmatrix}$$



# Lab #1. Document to smaller vector (reading)

Study this example

<https://github.com/str-anger/hsu.ai/blob/master/code/05.%20SVD%20and%20PCA%20magic.ipynb>

Apply provided techniques to reduce number of dimensions in term-document matrix.

What do you need to run search engine?

# Considering context: word2vec

**CBoW (Continuous bag of words)** - predict a word given a context

**N-skip-grams** - predict a context given a word

In both models word order doesn't matter.

These models are trained in **reduced** space.

**Word2vec** is a tool to train such models.

Deep Structured Semantic Model ([DSSM](#)) - cooler version of semantic analysis from Microsoft.

There are also **sent2vec**, **text2vec**, ...



# Homework #1: replace PCA in your search engine with doc2vec

PCA considers **text as a bag of words**. For short texts this works ok, but for longer texts it doesn't catch the difference between "A killed B" and "B killed A", although it encodes the fact of murder.

\*2vec methods consider word appearances in relatively small surrounding, that brings order into context. Advances methods like DSSM also work with 3-trams.

Your hometask is to sum up results of today's labs and build **search engine** powered with **doc2vec** technology.

# Lab #2. Embedding with doc2vec.

Solve at least 1&2 out of 3.

<https://github.com/hsu-ai-course/hsu.ai/blob/master/code/05.%20NLP%20Semantics%20with%20word2vec%20and%20doc2vec.ipynb>

1. Train doc2vec using “war and peace” sentences.
2. Write a function that embed a string using a model created.
3. (\*) Implement search engine for Jeopardy questions.

# Machine translation today

Companies move from distributional models to more accurate **semantic models**.

Semantics is **shared among languages**.

See example to try machine translation.

## Lab #3. Machine translation

1. Obtain developer's key at

<https://translate.yandex.com/developers>

2. Run this code

<https://github.com/hsu-ai-course/hsu.ai/blob/master/code/05.%20Machine%20translation.ipynb>

# Hometask: Speak with AI in your language

- 1) Write a search engine that accepts queries in Spanish, but can search texts in English.
- 2) Build a database for <https://github.com/hsu-ai-course/hsu.ai/blob/master/code/datasets/nlp/facts.txt>: stem words, prepare TDM using doc2vec.
- 3) Implement search algorithm similar to hometask 05.
- 4) Add translation of queries **es->en**.
- 5) Test your solution for queries:
  - a) ¿Por qué las nutrias de mar se dan la mano así?
  - b) ¿Dime algo sobre los gorilas?