

Multimedia Communication Services


Lab experience n. 8

Sub-band filtering

Consider the filter bank with the following perfect reconstruction Haar analysis and synthesis filters

$$h_L = \begin{bmatrix} \frac{\sqrt{2}}{2} & \frac{\sqrt{2}}{2} \end{bmatrix} \quad h_H = \begin{bmatrix} \frac{\sqrt{2}}{2} & -\frac{\sqrt{2}}{2} \end{bmatrix} \quad g_L = \begin{bmatrix} \frac{\sqrt{2}}{2} & \frac{\sqrt{2}}{2} \end{bmatrix} \quad g_H = \begin{bmatrix} -\frac{\sqrt{2}}{2} & \frac{\sqrt{2}}{2} \end{bmatrix} \quad (1)$$

Consider then the separable application of these filter bank to an image according to the following scheme for horizontal and vertical filtering and sub-sampling



1. Implement the analysis bank by filtering the signal X first by columns, so obtaining X_L and X_H , and then filtering by rows those two signals to obtain X_{LL} , X_{LH} , X_{HL} , X_{HH} .
2. Display the four sub-bands X_{LL} , X_{LH} , X_{HL} , X_{HH} and observe the different content of each sub-band.
3. Implement the synthesis bank and check that the filter bank is perfect-reconstruction.
4. Evaluate the quality of the image obtained by only using the LL sub-band in the synthesis phase (quantize the remaining sub-bands to zero).
5. Iterate the sub-band analysis and synthesis process on the LL sub-band, and repeat the experiment of the previous two points.

Bonus: Apply a uniform (non-zero) quantization to different sub-bands and study its effect on the quality of the reconstructed image.