ShZZaM: An LLM+ATP Natural Language to Logic Translator

Geoff Sutcliffe, Danial Haroon
University of Miami, Coral Gables, USA

Abstract

This paper describes ShZZaM, a tool that translates natural language to typed first-order logic, using Large Language Models (LLMs) and Automated Theorem Proving (ATP).

1 Introduction

Large Language Models (LLMs) (Peykani et al. 2025) have shown themselves to be useful in a broad range of applications (Sajjadi Mohammadabadi et al. 2025). However, it is well known that LLMs make mistakes (Huang et al. 2025), and this is acknowledged on LLMs' web interfaces. In the face of such unreliability, the results from LLMs used in mission-critical applications require verification. One approach is to translate the LLM input and output to a logical form that can be checked using Automated Theorem Proving (ATP) tools, e.g., (Yang et al. 2025; Cheng et al. 2025).[1] A key step in this verification pipeline is faithful translation of the natural language to a logical form. This is difficult due to the ambiguous nature of natural language statements, especially informally expressed statements. Work in this area includes LINC (Olausson et al. 2023), FOLIO (Han et al. 2024), and LINA (Li et al. 2024). This paper makes another contribution, taking a new iterative approach to the translation process, zigzagging between natural language and logic until convergence is achieved. A key feature of ShZZaM is its use of LLMs and Automated Theorem Proving (ATP), which complement each other in the translation steps.

2 Architecture

Figure 1 shows the overall process of ShZZaM. Initially LLM-N is used to normalize the text, breaking down long sentences, converting metaphors to their literal meaning, etc. Each of the following "ZigZag"s uses a combination of LLMs and ATP tools to translate natural language to logic and back to natural language. LLM-L+ATP is used to translate the natural language to typed first-order logic in the TFF syntax (Blanchette and Paskevich 2013) of the TPTP World (Sutcliffe 2024). LLM-NL is used to translate the logic back to natural language. LLM-S is then used to judge the similarity in meaning of the new and previous natural language statements. If they are adequately similar - above a "convergence threshold", the logic in between them is accepted as the translation. If not another zigzag is performed. This zizagging continues until the natural language pairs converge to the required level of similarity (or a limit is reached). Upon convergence the logic is sent to an ATP system, either a theorem prover if there is a conjecture, or a model finder if there are only axioms. If the similarity between the final natural language and the original natural language is above the "zigzagging sequence threshold" the translation is complete. Otherwise another zigzagging sequence is performed (or a limit is reached). This outermost zigzagging sequence loop ensures that the final natural language is adequately similar in meaning to the original natural language.

The translation from natural language to logic and back - one zigzag, is an iterative one involving LLMs and ATP tools. Figure 2 shows the details. LLM-L is used to translate from natural language to logic. The translation is successively checked by ATP tools for syntax errors and type errors. If an error occurs the error message is captured and passed back into the LLM-L for another attempt. When syntactically and type correct logic is created, LLM-NL translates the logic back to the provisional natural language, and LLM-S is used to compare this to the original natural language. If the similarity is above an "acceptance threshold" the provisional natural language becomes the accepted result of the zigzag. It is this accepted natural language that is compared to the previous natural language for convergence, as explained above. If the similarity is below the acceptance threshold then the provisional natural language is rejected, and the error is passed back into the LLM-L for another attempt. This check prevents the natural language straying too far in meaning from the original natural language over multiple zigzags.

LLMs can translate between natural language and TPTP format TFF logic because they are exposed to enough of each in their training. The former is the natural result of scraping the world's web sites, etc. The latter might be surprising, as TFF is a comparatively small fragment of the data

Copyright © 2026 by the authors. Open access article published under the Creative Commons Attribution-NonCommercial 4.0 International License (CC BY-NC 4.0).

[1] For a more comprehensive survey, just ask your favourite LLM to "show me some research on how LLMs make mistakes, and the need for symbolic checking of LLM output".



Figure 1: ShZZaM process



Figure 2: Details of one zigzag

used to train LLMs. Evidently there are adequate corpora that use TFF that are exposed on the web, e.g., the TPTP problem library (Sutcliffe 2017), exports from the Isabelle Archive of Formal Proofs (Blanchette et al. 2015), and exports of the Mizar Mathematical Library (Urban 2003), etc.

3 Implementation and Testing

ShZZaM is implemented in Python. The LLMs available are ChatGPT, Gemini, Claude, and DeepSeek. Access to ATP is provided via the TPTP World's SystemOnTPTP service (Sutcliffe 2000). ShZZaM has parameters that allow the selection of LLMs (default ChatGPT) and ATP systems (default Vampire (Bártek et al. 2025) for both theorem proving and model finding), setting the acceptance, convergence, and zigzagging sequence thresholds (defaults 0.74, 0.94, 0.94), setting the maximal numbers of failures in a Zig (default 10), zigzags in a sequence (default 10), and zigzagging sequence repetitions (default 3). ShZZaM is available, with test files and the results discussed below, from `https://github.com/TPTPWorld/ShZZaM`. It can also be run in default mode in SystemB4TPTP, at `https://tptp.org/cgi-bin/SystemB4TPTP`. An API key has to be provided in an initial comment line, e.g.,

```
# OPENAI_API_KEY=the_user_api_key
Show me that Socrates was mortal.
```

Initial testing has been done on 12 test texts from SUMO-based research (Niles and Pease 2001; Thompson et al. 2025). There are four texts that are expected to produce axioms with a provable conjecture, three texts that that are expected to produce axioms with an unprovable conjecture, and five contradictory texts that are expected to produce unsatisfiable axioms. An example of the first type is: "If a country is a member of NATO, it will protect any member that is attacked. Sweden is a member of NATO. Germany is a member of NATO. Russia attacked Germany. Show that Sweden will protect Germany.". An example of the second type is: "Terry possesses a Traditional Savings Account. Terry withdrew from the Traditional Savings Account. The bank penalized Terry. Show that the withdrawal caused penalty.". An example of the third type is: "The tornado damaged the house. The tornado did not damage the house.". Testing used the default settings, except that Gemini was used for the language translations. Each test was run three times so that stochastic variations could be analysed, for a total of 72 runs. Of the 72 runs, 65 ended in convergence, 36 converged above the zigzagging sequence threshold, 26 required only one zigzagging sequence, 6 required two sequences, and 40 used all three sequences. The ATP system confirmed the logical status in 21 of the 24 theorem runs, 17 of the 18 non-theorem runs, and 18 of the 30 unsatisfiable axiom set runs. ChatGPT produced the best results, with 32 of its 36 results confirmed by the ATP system, while Gemini achieved 24 out of 36. In two examples Gemini used typed extended first-order logic (Sutcliffe and Kotelnikov 2018), i.e., with boolean terms. The stochastic variations are interesting: Of the 24 sets of three test runs, 10 ChatGPT sets and 7 Gemini sets were confirmed by the ATP system in all three runs. Manual inspection of the logic outputs showed that only 6 of the ChatGPT sets and 1 of the Gemini sets produced essentially the same logic in each of the three runs. Thus repeatability is low.

4 Conclusion

Future work includes adding access to more LLMs, e.g., Grok, testing over larger datasets, e.g., the FOLIO (Han et al. 2024) and ProofWriter (Tafjord, Mishra, and Clark 2021) datasets. The main weakness of ShZZaM (and speculatively all other LLM-based natural language to logic translators) is its stochastic nature – the logic produced typically varies between runs. This is a matter for further and deeper research.

References

Blanchette, J., and Paskevich, A. 2013. TFF1: The TPTP Typed First-order Form with Rank-1 Polymorphism. In Bonacina, M., ed., *Proceedings of the 24th International Conference on Automated Deduction*, number 7898 in Lecture Notes in Artificial Intelligence, 414–420. Springer-Verlag.

Blanchette, J.; Haslbeck, M.; Matichuk, D.; and Nipkow, T. 2015. Mining the Archive of Formal Proofs. In Kerber, M.; Carette, J.; Kaliszyk, C.; Rabe, F.; and Sorge, V., eds., *Proceedings of the 8th Conference on Intelligent Computer Mathematics*, number 9150 in Lecture Notes in Computer Science, 3–17. Springer-Verlag.

Bártek, F.; Bhayat, A.; Coutelier, R.; Hajdu, M.; Hetzenberger, M.; Hozzová, P.; Kovács, L.; Rath, J.; Rawson, M.; Reger, G.; Suda, M.; Schoisswohl, J.; and Voronkov, A. 2025. The Vampire Diary. In Piskac, R., and Rakamaric, Z., eds., *Proceedings of the 37th International Conference on Computer Aided Verification*, number 15933 in Lecture Notes in Computer Science, 57–71.

Cheng, F.; Li, H.; Liu, F.; Van Rooij, R.; Zhang, K.; and Lin, Z. 2025. Empowering LLMs with Logical Reasoning: A Comprehensive Survey. In Kwok, J., ed., *Proceedings of the 34th International Joint Conference on Artificial Intelligence*, 10400–10408. AAAI Press.

Han, S.; Schoelkopf, H.; Zhao, Y.; Qi, Z.; Riddell, M.; Zhou, W.; Coady, J.; Peng, D.; Qiao, Y.; Benson, L.; Sun, L.; Wardle-Solano, A. Szabó, H.; Zubova, E.; Burtell, M.; Fan, J.; Liu, Y.; Wong, B.; Sailor, M.; Ni, A.; Nan, L.; Kasai, J.; Yu, T.; Zhang, R.; Fabbri, A.; Kryscinski, W.; Yavuz, S.; Liu, Y.; Lin, X.; Joty, S.; Zhou, Y.; Xiong, C.; Ying, R.; Cohan, A.; and Radev, D. 2024. FOLIO: Natural Language Reasoning with First-Order Logic. In Al-Onaizan, Y.; Bansal, M.; and Chen, Y.-N., eds., *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, 22017–22031. Association for Computational Linguistics.

Huang, L.; Yu, W.; Ma, W.; Zhong, W.; Feng, Z.; Wang, H.; Chen, Q.; Peng, W.; Feng, X.; Qin, B.; and Liu, T. 2025. A Survey on Hallucination in Large Language Models: Principles, Taxonomy, Challenges, and Open Questions. *ACM Transactions on Information Systems* 42:1–55.

Li, Q.; Li, J.; Liu, T.; Zeng, Y.; Cheng, M.; Huang, W.; and Liu, Q. 2024. Leveraging LLMs for Hypothetical Deduction in Logical Inference: A Neuro-Symbolic Approach.

Niles, I., and Pease, A. 2001. Towards A Standard Upper Ontology. In Welty, C., and Smith, B., eds., *Proceedings of the 2nd International Conference on Formal Ontology in Information Systems*, 2–9.

Olausson, T.; Gu, A.; Lipkin, B.; Zhang, C.; Solar-Lezama, A.; Tenenbaum, J.; and Levy, R. 2023. LINC: A Neurosymbolic Approach for Logical Reasoning by Combining Languag Models with First-Order Logic Provers. In Pino, J., and Bali, K., eds., *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, 5153–5176. Association for Computational Linguistics.

Peykani, P.; Ramezanlou, F.; Tanasescu, C.; and Ghanidel, S. 2025. Large Language Models: A Structured Taxonomy and Review of Challenges, Limitations, Solutions, and Future Directions. *Applied Sciences* 15(14):8103.

Sajjadi Mohammadabadi, S.; Kara, B.; Eyupoglu, C.; Uzay, C.; Tosun, M.; and Karakuş, O. 2025. A Survey of Large Language Models: Evolution, Architectures, Adaptation, Benchmarking, Applications, Challenges, and Societal Implications. *Electronics* 14(18):3580.

Sutcliffe, G., and Kotelnikov, E. 2018. TFX: The TPTP Extended Typed First-order Form. In Konev, B.; Urban, J.; and Schulz, S., eds., *Proceedings of the 6th Workshop on Practical Aspects of Automated Reasoning*, number 2162 in CEUR Workshop Proceedings, 72–87.

Sutcliffe, G. 2000. SystemOnTPTP. In McAllester, D., ed., *Proceedings of the 17th International Conference on Automated Deduction*, number 1831 in Lecture Notes in Artificial Intelligence, 406–410. Springer-Verlag.

Sutcliffe, G. 2008. The SZS Ontologies for Automated Reasoning Software. In Sutcliffe, G.; Rudnicki, P.; Schmidt, R.; Konev, B.; and Schulz, S., eds., *Proceedings of the LPAR Workshops: Knowledge Exchange: Automated Provers and Proof Assistants, and the 7th International Workshop on the Implementation of Logics*, number 418 in CEUR Workshop Proceedings, 38–49.

Sutcliffe, G. 2017. The TPTP Problem Library and Associated Infrastructure. From CNF to TH0, TPTP v6.4.0. *Journal of Automated Reasoning* 59(4):483–502.

Sutcliffe, G. 2024. Stepping Stones in the TPTP World. In Benzmüller, C.; Heule, M.; and Schmidt, R., eds., *Proceedings of the 12th International Joint Conference on Automated Reasoning*, number 14739 in Lecture Notes in Artificial Intelligence, 30–50.

Tafjord, O.; Mishra, B.; and Clark, P. 2021. ProofWriter: Generating Implications, Proofs, and Abductive Statements over Natural Language. In Zong, C.; Xia, F.; Li, W.; and Navigli, R., eds., *Proceedings of the Joint Conference of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing and Reasoning*, 3621–3634. Association for Computational Linguistics.

Thompson, R.; Pease, A.; Kölsch, M.; and Toutsios, A. 2025. Grounding Terms from an Ontology for use in Autoformalization: Tokenization is All You Need. In Giunchiglia, E.; Hitzler, P.; and van Krieken, E., eds., *Proceedings of the 19th International Conference on Neurosymbolic Learning and Reasoning*.

Urban, J. 2003. Translating Mizar for First Order Theorem Provers. In Asperti, A.; Buchberger, B.; and Davenport, J., eds., *Proceedings of the 2nd International Conference on Mathematical Knowledge Management*, number 2594 in Lecture Notes in Computer Science, 203–215. Springer-Verlag.

Yang, X.-W.; J-J., S.; Guo, L.-Z.; Zhang, B.-W.; Zhou, Z.; Jia, L.-H.; Dai, W.-Z.; and Li, Y.-F. 2025. Neuro-Symbolic Artificial Intelligence: Towards Improving the Reasoning

Abilities of Large Language Models. In Kwok, J., ed., *Proceedings of the 34th International Joint Conference on Artificial Intelligence*, 10770–10778. AAAI Press.