


# Cost of Hospital Care

Analysing factors that drive cost of care for  
hospitalized patients



# Table of contents

- 01 → Task & Approach
- 02 → Data Processing & Analysis
- 03 → Modelling & Evaluation
- 04 → Discussion & Concluding Statement

01 →

# Task & Approach

# 01: What's the Task

Goals – To find out:

**Qn. A**

**What factors drive cost of care?**

Plan: The driving factors will be identified through Data Analysis and evaluate post-modelling feature importance

Data Analysis

Post-Modelling  
Evaluation

**Qn. B**

**What are the ways to estimate/predict cost of care?**

Plan: Different modelling techniques will be explored to produce one that can estimate cost accurately  
(Target: R2 score > 90%, MAPE score <10%)

Modelling

# 01: Some Background

## Parkway Pantai hospitals launch AI-powered predictive hospital bill estimation system in Singapore

The new estimation system, which has been in use since November 2018, has made more than 10,000 predictions so far.

By [Dean Koh](#) | December 19, 2018 | 04:59 AM



Reference: <https://www.healthcareitnews.com/news/asia/parkway-pantai-hospitals-launch-ai-powered-predictive-hospital-bill-estimation-system>



ELSEVIER

Contents lists available at [ScienceDirect](#)

Informatics in Medicine Unlocked

journal homepage: [www.elsevier.com/locate/imu](http://www.elsevier.com/locate/imu)



### Comparison of linear, penalized linear and machine learning models predicting hospital visit costs from chronic disease in Thailand

Wichayaporn Thongpeth, M.N.S.<sup>a</sup>, Apiradee Lim, Ph.D.<sup>a,\*</sup>, Akemat Wongpairin, M.P.H.<sup>a</sup>, Thaworn Thongpeth, M.D.<sup>b</sup>, Santhana Chaimontree, Ph.D.<sup>a</sup>

<sup>a</sup> Department of Mathematics and Computer Science, Faculty of Science and Technology, Prince of Songkla University, Pattani Campus, Mueang, Pattani, 94000, Thailand

<sup>b</sup> Orthopedic Surgery and Preventive Medicine, Surathani Hospital, Ministry of Public Health, Mueang, Surat Thani, 84000, Thailand

Reference: <https://www.sciencedirect.com/science/article/pii/S2352914821002434>

Use of AI in predicting hospital bill has been studied and even implemented in Singapore

# 01: What's the Approach

## Data

### What we have

Billing data  
Clinical data  
Demographic data

### Data Processing

Merging data  
Clean data  
Feature engineering

## Analysis

### Type of analysis

Univariate Analysis  
Multivariate Analysis

### Data Visualisation:

Matplotlib  
Seaborn

## Modelling

### Data Processing

RobustScaler  
OneHotEncoder

### Models

Statistical Models  
(Linear Regression)  
(Penalised Regressions)

Machine Learning Models  
(RandomForestRegressor)  
(XGBRegressor)

## Post-Modelling Evaluation

### Model Performance Metric

R2 (target>90%)  
MAPE (target<10%)  
RMSE

### Feature Importance

*Dependent on model type*

02 →

# Data Processing & Analysis






# 02: Our Data

## Key Notes:

- 3000 unique patients
- 3400 unique hospitalisations from 2011-2015
- Some patients have multiple admissions
- Some patients have multiple bills per admission
- Each **bill** represented by 'billing\_id'
- Each **hospitalisation** represented by 'patient\_id' and 'date\_of\_admission'
- Each **patient** represented by 'patient\_id'

## Legend:

-  Dataset obtained
-  Interim dataset created
-  Desired combined dataset created

**billing\_amt**

contain  
bill\_id,  
bill amount

**billing\_id**

contain  
bill\_id,  
patient\_id  
date\_of\_admission

Join on  
'billing\_id'

**billing\_df**

- Each row represents a bill
- Each hospitalisation has 1 or more bills
- Data aggregated by sum of bill per hospitalisation ('total\_hosp\_bill')

**clinical\_df**

Contain patient clinical features

Join on  
'patient\_id'  
'date\_of\_admission'

**hospitalisation\_df**

Each row is a unique hospitalisation case of a patient

**demographic\_df**

Contain patient demographic information

Join on  
'patient\_id'

**merged\_df**

Each row is a unique hospitalization case of a patient



## 02: Data Processing

merged\_df

Data Processing

**3400 rows, 38 columns**



Features include demographics, clinical features, hospitalisation information

Data Checking & Cleaning	
Duplicate Data	Each row is unique hospitalisation of a patient.
Missing Data	Found in 'medical_history' columns Assume patient do not have the medical history, as it is inappropriate to assume a patient had the medical history if it is not reported Impute '0'
Data Type	Ensure data in write data type for further processing and analysis: E.g. 'medical_history_3' is in <i>string</i> format when it should be <i>integer</i> format
Data Values	Check Categorical columns unique elements Check Quantitative columns value range

7 New Columns	
`total_hosp_bill`	Created earlier on before creating `merged_df` when aggregating the billing data
`had_prev_admission`	Boolean if patient had another admission prior
`Age_upon_admission`	Using patient `date_of_birth` and `date_of_admission`
`BMI`	Using patient `weight` and `height` To reflect if a patient has healthy body weight
`sum_medical_history` `sum_symptoms` `sum_medications`	Reflects total number of medical histories, symptoms and pre-op medications patient have respectively

# 02 Data Analysis


## Univariate Demographic Analysis



Age	Two bimodal distribution Younger group with median about 40yo Older group with median about 65yo
Gender	Balanced distribution between male and female
Race	Chinese-dominant, with smallest group being `Other` at 5.4%
Resident Status	80% Singaporeans, <5% Foreigners


# 02 Data Analysis

## Univariate Clinical Analysis



[https://www.cdc.gov/healthyweight/assessing/bmi/adult\\_bmi/index.html](https://www.cdc.gov/healthyweight/assessing/bmi/adult_bmi/index.html)

$$\text{BMI} = \frac{\text{Weight (in kilograms)}}{\text{Height}^2 \text{ (in meters)}}$$




- Body mass index (BMI) allows easy screening if a person body weight is healthy
- BMI appears to be as strongly correlated with various metabolic and disease outcomes
- In our patient group, most of our patients are considered to not have healthy BMI levels (IQR 26.2-31.7). They are mostly overweight and close to half of them obese (median = 28.9)

# 02 Data Analysis

## Univariate Clinical Analysis


### Boxplot for Lab Results



- Some outliers observed in the lab results.
- However, unable to comment about the lab result distribution as it is not to our knowledge what lab results are these. It is not clear how the lab results reflect a patient's health.


Patients tend to have 1-2 medical histories, 2-4 symptoms, and 3 or more pre-op medications

Most prevailing observations are medical\_history\_2, symptom\_4 and pre-op medication 3 and 5



# 02 Data Analysis



## Univariate Hospitalisation Analysis



- The hospitalization bill distribution is positively skewed as the histogram shows it tails off on the right.
- As the **Shapiro-Wilk** test shows  $p < 0.05$ , we reject the null hypothesis that the distribution is not normal → it follows a normal distribution.
- The bill ranges from ~\$2.9K to ~\$99K.
- Average bill is about \$20K.
- 2.8% of the bill is very large and are outliers (>\$44.5K)

# 02 Data Analysis

## Univariate Hospitalisation Analysis



Most patients were admitted once between 2011-2015, while some are admitted more than 3x.



Hospitalization days range 1-20 days, most 1-2weeks durations



# 02 Data Analysis

## Factors correlating with Hospitalization bill

Correlation Heatmap



### FACTORS DRIVING COST OF CARE:

- It appears that `sum_symptoms` has the greatest correlation, with moderate positive correlation with hospital bill ( $r=0.51$ )
- It is followed by `Age_upon_admission` which has weak positive correlation with bill at  $r = 0.33$ .
- We can infer that patients older in age and patients with more symptoms tend to have higher hospital bill, likely due to greater medical care needed.

# 02 Data Analysis

## Factors correlating with Hospitalization bill

### FACTORS DRIVING COST OF CARE:


**Mann-Whitney U Test** is used to compare difference in hospital bill between groups.

Genders, race, resident status and specific symptom, medical history and medications (12 categorical features) showed significant difference using the statistical test ( $p < 0.05$ )

However, visual inspection on the violin plots, the difference in bill is more distinctly, observed among **race**, **resident status**, and between patients with and without **symptom 5**.

	Column_name	Category 1	Category 2	p-value
0	symptom_5	1	0	0.00000
1	race	Malay	Indian	0.00000
2	race	Malay	Chinese	0.00000
3	race	Malay	Others	0.00000
4	race	Indian	Chinese	0.00000
5	symptom_3	1	0	0.00000
6	symptom_2	0	1	0.00000
7	resident_status	Singapore citizen	PR	0.00000
8	resident_status	Singapore citizen	Foreigner	0.00000
9	resident_status	PR	Foreigner	0.00000
10	symptom_1	0	1	0.00000
11	medical_history_1	0	1	0.00000
12	medical_history_6	0	1	0.00000
13	symptom_4	1	0	0.00000
14	gender	Female	Male	0.00021
15	race	Indian	Others	0.00043
16	race	Chinese	Others	0.00519
17	preop_medication_2	1	0	0.02228
18	preop_medication_6	0	1	0.04031

Hospital Bill distribution between Categorical Classes  
(Featuring only those with MannWhitney Test  $p < 0.05$ )



## 02 Data Feature Selections

Column Set	Description
`allcol`	All original features included.
`sub1col`	Exclude categorical features where there is no significant hospital bills between the classes  18 features (12 categorical + all 6 quantitative)
`sub2col`	Exclude categorical features where there is no significant hospital bills between the classes AND quantitative features showed poor correlation with hospital bill ( $ r  < 0.3$ ).  14 features (12 categorical + 2 quantitative)

We will be using insights gathered from the analysis to create three sets of feature columns to compare model's performance when different set of features are used.

12 Categorical features	2 Quantitative features
'gender', 'medical_history_1', 'medical_history_6', 'preop_medication_2', 'preop_medication_6', 'race', 'resident_status', 'symptom_1', 'symptom_2', 'symptom_3', 'symptom_4', 'symptom_5',	'sum_symptoms' 'Age_upon_admission'

03 →

# Modelling & Evaluation

(AI)

# 03: Approach

merged\_df

*Train-test-split (70:30)*

X\_train, X\_test, y\_train, y\_test

*Bootstrapping to create data with 3 different sizes (original/ 2fold/ 4fold)  
Created data with 3 different sets of X features (allcol, sub1col, sub2col)*

9 X\_train of different size and columns  
9 X\_test of different size and columns  
3 y\_train of different data size  
1 y\_test

*RobustScaler quantitative columns  
OneHotEncode categorical columns*

9 transformed X\_train of different size and columns  
9 transformed X\_test of different size and columns  
3 y\_train of different data size  
1 y\_test

## Statistical Models

(Linear Regression)  
(Penalised Regressions (L1,L2,ElasticNet))

9 Datasets, 4 model types = 36 trained models

## Created new X datasets

Using selected features using coefficient values  
from statistical model

Different X features: *allcol, sub1col, sub2col, sub3col*  
*Creating to total 12 sets of X data*

## Selected 4 data sets

Size: 4fold

Column sets: *allcol, sub1col, sub2col, sub3col*

## Machine Learning Models

(RandomForestRegressor)  
(XGBRegressor)

4 Datasets, 4 model types = 8 trained models

### Metric

R2  
RMSE  
MAPE

### Hyperparameter Tuning

RandomSearchCH  
GridSearchCV

## 03 Statistical Model

- 4 Model types: Linear Regression, LassoCV, RidgeCV, ElasticNetCV
- 9 X data sets used
- Total 36 trained statistical models

### Top 5 performing models based on R2 score on test set

Model	Model_type	Data_size	Column_set	R2_train	R2_test	MAPE_train	MAPE_test	RMSE_train	RMSE_test
ElasticNet_4fold_sub1col	ElasticNet	4fold	sub1col	91.988	93.577	9.952	9.734	2990.76526	2251.15433
ElasticNet_4fold_allcol	ElasticNet	4fold	allcol	92.091	93.700	9.877	9.755	2971.48339	2229.45249
ElasticNet_original_allcol	ElasticNet	original	allcol	92.316	93.686	9.648	9.806	2922.14372	2231.91596
ElasticNet_original_sub1col	ElasticNet	original	sub1col	92.221	93.543	9.765	9.819	2940.12220	2257.09867
Lasso_4fold_allcol	Lasso	4fold	allcol	92.118	93.406	9.984	9.883	2966.32151	2280.88374



# 03 Statistical Model Performance

Generally, all the model performance are **relatively similar**.

There are not overfitting: Differenced in train and test R2 score **<5%**

There are not underfitting: The models have **>90% test R2 score** with very similar performance (**R2: 90-94%**)

## General observation:

- All columns appear to give better model performance.
- 4-fold data size appear to give better model performance.
- Elastic Net appear to perform better than other statistical models.


## This make sense as:

- All columns allows more columns subjected to the regularization.
- 4-fold all model to train better with better representation of the population
- Elastic Net allow use of L1 and L2 regularization




# 03 Statistical Model Feature Importance

Absolute Coefficient value - Model ElasticNet\_4fold\_allcol



Coefficient value - Model ElasticNet\_4fold\_allcol



- We look at **ElasticNet\_4fold\_allcol** model coefficients and its absolute values
- Identified 18 transformed features to form a new columns set: **'sub3col'** by excluding features with coefficient values close to 0

Further discussion on feature importance include in later slide

# 04 Machine Learning Models

- 2 Model types: RandomForestRegressor, XGBRegressor
- 4 X data sets used (Datasize: 4fold, Column set: 'allcol', 'sub1col', 'sub2col', 'sub3col')
- Total 8 trained machine learning models

Model	R2_train	R2_test	MAPE_train	MAPE_test	RMSE_train	RMSE_test
RandomForestRegressor_4fold_allcol	96.978	87.576	4.380	12.034	1836.77105	3130.89750
RandomForestRegressor_4fold_sub1col	95.571	90.485	5.577	9.959	2223.63392	2739.98994
RandomForestRegressor_4fold_sub2col	94.954	90.079	6.551	9.803	2373.40365	2797.87660
RandomForestRegressor_4fold_sub3col	97.339	92.545	4.265	8.363	1723.51501	2425.28883
XGBRegressor_4fold_allcol	99.987	97.732	0.375	4.932	120.78346	1337.71927
XGBRegressor_4fold_sub1col	99.985	97.804	0.454	4.616	128.17734	1316.16081
XGBRegressor_4fold_sub2col	99.935	92.694	0.660	8.758	269.56463	2400.98342
XGBRegressor_4fold_sub3col	99.979	97.798	0.554	4.764	151.68395	1318.01607

Compared to statistical models  
(with R2 test score 90-94%):

**RandomForestRegressor** appear to perform poorer:

- Best R2 score – 92.5%
- It also has overfitting model with greatest train test R2 difference of 9%

**XGBRegressor** appear to perform best:

- Best R2 score – 98%
- $\frac{3}{4}$  model not overfitting with train test R2 ~2% difference

## 03 Machine Learning Model


### Other Observations:

- RandomForestRegressor performs better when trained on specific important features, ('sub3col' columns)
- While XGBRegressor showed better performance when more columns (it perform least well on sub2col which had least columns)

### Remarks:

- We can infer **XGBRegressor is better selecting important features**, and this is make sense.
- XGBoost offers the ability to adjust regularization parameters, granting users precise control to fine-tune the complexity of the model. It provides choices like L1 and L2 regularization, which aid in mitigating overfitting and enhancing generalization.
- In contrast, Random Forest Regressor relies on the natural randomness inherent in its ensemble construction to regulate the model, lacking direct influence over regularization parameters.

# 03 Feature Importance Across Models



'Resident Status, Race (Malay), Sum of symptoms and Symptom\_5 appear to be top few most common features across models

# 03 Potential Cost Driving Factors

	Correlation Heat Map	Mann-Whitney U Test	Machine Learning Models	
Analysis	<i>Using Pearson correlation to identify linear relationship between quantitative variable with hospital bill</i>	Identify categorical categories that have significant difference in hospital bill between the classes	<b>Models and feature importance:</b> ElasticNet – Absolute Coefficient values Random Forest Regressor – Impurity-based Feature Importance value XGBoost Regressor – ‘gain’ score Feature Importance value	
Identified Potential Cost Driving Factors	‘sum_symptoms’ ‘Age_upon_admission’	‘gender’, ‘medical_history_1’, ‘medical_history_6’, ‘preop_medication_2’, ‘preop_medication_6’, ‘race’, ‘resident_status’, ‘symptom_1’, ‘symptom_2’, ‘symptom_3’, ‘symptom_4’, ‘symptom_5’,	<b>Common Top 10 Features:</b> ‘medical_history_6_1’, ‘resident_status_PR’, ‘medical_history_1_1’, ‘race_Malay’, ‘Age_upon_admission’, ‘resident_status_Singapore citizen’, ‘sum_symptoms’, ‘symptom_5_1’	<b>Common Top 5 Features:</b> ‘resident_status_PR’, ‘race_Malay’, ‘resident_status_Singapore citizen’, ‘sum_symptoms’, ‘symptom_5_1’

- Generally, top features identified post-modelling are also identified in the analysis conducted during data analysis.
- Most notable features are ‘Resident Status’, ‘Race (Malay)’, ‘Sum of symptoms’ and ‘Symptom\_5’
- Medically, a patient tend to have higher bill if they have more symptoms, or particularly symptom 5, as they would require more treatments or more complex treatments.
- Resident Status evidently affects hospital bill as we are aware it affects one’s eligibility to subsidies
- Malay patients may observe higher hospital bills, possibly due to higher prevalence of certain medical conditions and treatment needed that are more costly. However, more medical background information would be preferable to assess this possibility.


04 →

# Discussion & Conclusion

(AI)



## 04 Recap: Task Goal



**Qn. A**

**What factors drive cost of care?**

Plan: The driving factors will be identified through Data Analysis and evaluate post-modelling feature importance

Data Analysis

Post-Modelling  
Evaluation

**Qn. B**

**What are the ways to estimate/predict cost of care?**

Plan: Different modelling techniques will be explored to produce one that can estimate cost accurately  
(Target: R2 score > 90%, MAPE score <10%)

Modelling



# 04 Our Findings:

## Key factors influence cost

### **Cost tends to be higher when:**

- Patient is foreigner
- Patient is Malay (likely due to higher prevalence of medical issues and need for costly medical attentions)
- Patient has more symptoms
- Patient has symptom 5

## Model

- Best model: XGBRegressor\_4fold\_sub3col
- R2 score: 97.8%
- MAPE score: 4.76%
- R2 score: 1318

### **What this translates to is:**

Given a patient information during hospitalization (found in sub3col), it is able to estimate the hospital bill with about ~5% and \$1.3K off the true bill value.

# 04 Limitations & Future Work

1. Did not explore non-linear relationship between hospitalisation bill with other quantitative features:
  - Such non-linear relationships if identified will allow us to obtain other prominent quantitative cost driving factors, as we observed minimal of among the other important features assessed post-modelling.
  - We can achieve this by transforming the quantitative variables (log2, exponential, square root, polynomial transformations) and assess their correlation with the hospital bill
2. Patient's personal and family financial well-being not accounted for:
  - This affects the level of subsidy a patient is eligible for, which will significantly affects a patient's bill (as high as 80% subsidies)
3. Patient preference:
  - Patient's performance in choice of basic VS premium services affected the hospitalization cost
  - For example, in Singapore General Hospital, a class C ward which has 8 beds in a room cost SGD37 a day, compared that to class A ward which is a single room cost SGD 540 a day

## 04 Concluding Statements

We have achieved what the task set out to do. We also identify there is limited information in the data set and further analysis that could have been explored.

The use of other advanced machine learning models could be further explored as well (such as deep learning models), which has also shown great results as seen in [price estimator model by UCARE.AI](#).

AI has so much potential in not only in the advancement of medical treatments, but also in the delivery of these treatments through our healthcare systems. We can look forward to discovery new innovative ways to advance our healthcare systems as the world continues to see rising demands of medical needs.

