

# OGC GeoTIFF Standard

# Open Geospatial Consortium

Submission Date: 2019-06-05

Approval Date: 2019-09-10

Publication Date: 2019-09-14

External identifier of this OGC® document: <http://www.opengis.net/doc/IS/GeoTIFF/1.1>

Internal reference number of this OGC® document: 19-008r4

Version: 1.1

Category: OGC® Implementation Standard

Editors: Emmanuel Devys, Ted Habermann, Chuck Heazel, Roger Lott, Even Rouault

## OGC GeoTIFF Standard

### Copyright notice

Copyright © 2019 Open Geospatial Consortium

To obtain additional rights of use, visit <http://www.opengeospatial.org/legal/>

### Warning

This document is an OGC Member approved international standard. This document is available on a royalty free, non-discriminatory basis.

Recipients of this document are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Document type: OGC® Standard

Document subtype:

Document stage: Approved

Document language: English

## License Agreement

Permission is hereby granted by the Open Geospatial Consortium, ("Licensor"), free of charge and subject to the terms set forth below, to any person obtaining a copy of this Intellectual Property and any associated documentation, to deal in the Intellectual Property without restriction (except as set forth below), including without limitation the rights to implement, use, copy, modify, merge, publish, distribute, and/or sublicense copies of the Intellectual Property, and to permit persons to whom the Intellectual Property is furnished to do so, provided that all copyright notices on the intellectual property are retained intact and that each person to whom the Intellectual Property is furnished agrees to the terms of this Agreement.

If you modify the Intellectual Property, all copies of the modified Intellectual Property must include, in addition to the above copyright notice, a notice that the Intellectual Property includes modifications that have not been approved or adopted by LICENSOR.

THIS LICENSE IS A COPYRIGHT LICENSE ONLY, AND DOES NOT CONVEY ANY RIGHTS UNDER ANY PATENTS THAT MAY BE IN FORCE ANYWHERE IN THE WORLD.

THE INTELLECTUAL PROPERTY IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NONINFRINGEMENT OF THIRD PARTY RIGHTS. THE COPYRIGHT HOLDER OR HOLDERS INCLUDED IN THIS NOTICE DO NOT WARRANT THAT THE FUNCTIONS CONTAINED IN THE INTELLECTUAL PROPERTY WILL MEET YOUR REQUIREMENTS OR THAT THE OPERATION OF THE INTELLECTUAL PROPERTY WILL BE UNINTERRUPTED OR ERROR FREE. ANY USE OF THE INTELLECTUAL PROPERTY SHALL BE MADE ENTIRELY AT THE USER'S OWN RISK. IN NO EVENT SHALL THE COPYRIGHT HOLDER OR ANY CONTRIBUTOR OF INTELLECTUAL PROPERTY RIGHTS TO THE INTELLECTUAL PROPERTY BE LIABLE FOR ANY CLAIM, OR ANY DIRECT, SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES, OR ANY DAMAGES WHATSOEVER RESULTING FROM ANY ALLEGED INFRINGEMENT OR ANY LOSS OF USE, DATA OR PROFITS, WHETHER IN AN ACTION OF CONTRACT, NEGLIGENCE OR UNDER ANY OTHER LEGAL THEORY, ARISING OUT OF OR IN CONNECTION WITH THE IMPLEMENTATION, USE, COMMERCIALIZATION OR PERFORMANCE OF THIS INTELLECTUAL PROPERTY.

This license is effective until terminated. You may terminate it at any time by destroying the Intellectual Property together with all copies in any form. The license will also terminate if you fail to comply with any term or condition of this Agreement. Except as provided in the following sentence, no such termination of this license shall require the termination of any third party end-user sublicense to the Intellectual Property which is in force as of the date of notice of such termination. In addition, should the Intellectual Property, or the operation of the Intellectual Property, infringe, or in LICENSOR's sole opinion be likely to infringe, any patent, copyright, trademark or other right of a third party, you agree that LICENSOR, in its sole discretion, may terminate this license without any compensation or liability to you, your licensees or any other party. You agree upon termination of any kind to destroy or cause to be destroyed the Intellectual Property together with all copies in any form, whether held by you or by any third party.

Except as contained in this notice, the name of LICENSOR or of any other holder of a copyright in all or part of the Intellectual Property shall not be used in advertising or otherwise to promote the sale, use or other dealings in this Intellectual Property without prior written authorization of LICENSOR or such copyright holder. LICENSOR is and shall at all times be the sole entity that may authorize you or any third party to use certification marks, trademarks or other special designations to indicate compliance with any LICENSOR standards or specifications. This Agreement is governed by the laws of the Commonwealth of Massachusetts. The application to this Agreement of the United Nations Convention on Contracts for the International Sale of Goods is hereby expressly excluded. In the event any provision of this Agreement shall be deemed unenforceable, void or invalid, such provision shall be modified so as to make it valid and enforceable, and as so modified the entire Agreement shall remain in full force and effect. No decision, action or inaction by LICENSOR shall be construed to be a waiver of any rights or remedies available to it.

# Table of Contents

1. Scope .....	9
2. Conformance .....	10
3. References .....	11
4. Terms and Definitions .....	12
4.1. band .....	12
4.2. cell .....	12
4.3. code .....	12
4.4. coordinate .....	12
4.5. coordinate epoch .....	12
4.6. coordinate reference system .....	13
4.7. coordinate system .....	13
4.8. correspondence model .....	13
4.9. datum .....	13
4.10. device space .....	13
4.11. double .....	14
4.12. dynamic CRS .....	14
4.13. ellipsoid .....	14
4.14. flattening .....	14
4.15. geocoding .....	14
4.16. geographic coordinate reference system .....	15
4.17. geokey .....	15
4.18. georectified .....	15
4.19. georeferencing .....	15
4.20. GeoTIFF .....	16
4.21. grid .....	16
4.22. imagery .....	16
4.23. meridian .....	16
4.24. metadata .....	16
4.25. model space .....	17
4.26. mosaic .....	17
4.27. orthoimage .....	17
4.28. orthorectified grid .....	17
4.29. parallel .....	17
4.30. pixel .....	17
4.31. prime meridian .....	18
4.32. projected coordinate reference system .....	18
4.33. projection .....	18
4.34. raster .....	18

4.35. rational	19
4.36. rectified grid	19
4.37. referenceable grid	19
4.38. short	19
4.39. tag	19
4.40. vertical coordinate reference system	20
5. Abbreviations	21
6. Clauses not Containing Normative Material	22
7. Requirements	23
7.1. Underlying TIFF Requirements	23
7.1.1. Requirements Class TIFF	23
7.1.2. Requirements Class GeoKeyDirectoryTag	24
7.1.3. Requirements Class GeoKeyCode	27
7.1.4. Requirements Class GeoShortParamsTag	27
7.1.5. Requirements Class GeoDoubleParamsTag	27
7.1.6. Requirements Class GeoAsciiParamsTag	28
7.2. GeoTIFF Configuration GeoKeys	29
7.2.1. Requirements Class GTRasterTypeGeoKey	29
7.2.2. Requirements Class GTModelTypeGeoKey	29
7.3. Raster to Model Coordinate Transformation Requirements	32
7.3.1. Requirements Class ModelTiepointTag	32
7.3.2. Requirements Class ModelPixelScaleTag	32
7.3.3. Requirements Class ModelTransformationTag	33
7.4. Requirements for definition of Model CRS (when Model is from GeoTIFF CRS register)	33
7.4.1. Overview	33
7.4.2. Requirements Class ProjectedCRSGeoKey	34
7.4.3. Requirements Class GeodeticCRSGeoKey	35
7.4.4. Requirements Class VerticalGeoKey	36
7.4.5. Requirements Class Citation GeoKeys	36
7.5. Requirements for definition of user-defined Model CRS	37
7.5.1. Requirements Class Units GeoKeys	37
7.5.2. Requirements Class Unit Size GeoKeys	40
7.5.3. Geodetic Datum	40
7.5.4. Requirements Class Vertical Datum	45
7.5.5. Map Projection GeoKeys	46
7.6. Requirements for dynamic CRS	49
8. Media Types for GeoTIFF data encoding	51
Annex A: Abstract Test Suite (Normative)	52
A.1. General Approach	52
A.2. Conformance Class TIFF	52
A.2.1. TIFF Core Test	52

A.2.2. TIFF Tags Test .....	53
A.2.3. GeoKey Directory Test .....	55
A.2.4. Short Parameters Test .....	57
A.2.5. Double Parameters Test .....	60
A.2.6. ASCII Parameters Test .....	62
A.3. Conformance Class Raster2Model_CoordinateTransformation_GeoKey .....	64
A.3.1. ModelPixelScaleTag Test .....	64
A.3.2. ModelTiepointTag Test .....	65
A.3.3. ModelTransformationTag Test .....	65
Annex B: GeoTIFF File Structure and GeoTIFF CRS and models principles (Informative) .....	67
B.1. The GeoTIFF File Structure .....	67
B.1.1. Introduction .....	67
B.1.2. GeoTIFF Design Considerations .....	67
B.1.3. GeoTIFF Software Requirements .....	68
B.1.4. GeoTIFF File and "Key" Structure .....	68
B.2. Coordinate Reference Systems in GeoTIFF .....	72
B.2.1. Device Space and GeoTIFF .....	72
B.2.2. Raster Space .....	73
B.2.3. Model Coordinate Reference Systems (Model space) .....	74
B.3. Defining Model Coordinate Reference Systems .....	77
B.3.1. Standard Model Coordinate Reference Systems .....	77
B.3.2. User-defined Model Coordinate Reference Systems .....	77
B.4. Model CRS Reference Parameters .....	81
B.4.1. EPSG coding of objects .....	82
B.5. Coordinate Transformations .....	83
B.6. GeoTIFF Tags for Coordinate Transformations .....	83
B.7. Cookbook for Defining Transformations .....	86
B.8. Geocoding Raster Data .....	87
Annex C: GeoTIFF Map Projection Method codes (Normative) .....	89
C.1. Map Projection methods .....	89
C.2. Map Projection parameters .....	90
Annex D: Recommendations for including height in model CRS definitions (Informative) .....	92
D.1. Introduction .....	92
D.2. Compound CRSs .....	92
D.3. Temporary provisions for including ellipsoidal height as one of the coordinates in GeoTIFF .....	92
Annex E: Summary of GeoKey IDs and names .....	95
Annex F: Examples .....	98
F.1. Introduction .....	98
F.2. Common Examples .....	98
F.2.1. UTM Projected Aerial Photo .....	98

F.2.2. United States State Plane zone.....	99
F.2.3. Lambert Conformal Conic Aeronautical Chart .....	99
F.2.4. DMA ADRG Raster Graphic Map .....	100
F.3. Less Common Examples .....	100
F.3.1. Unrectified Aerial photo, known tiepoints, in degrees.....	100
F.3.2. Rotated Scanned Map .....	100
F.3.3. Digital Elevation Model .....	101
F.3.4. Spherical Moon Example .....	102
Annex G: Deprecated and deleted EPSG codes .....	104
Annex H: Backward compatibility .....	117
Annex I: Revision History .....	118
Annex J: Bibliography .....	119

## **i. Abstract**

This OGC Standard defines the Geographic Tagged Image File Format (GeoTIFF) by specifying requirements and encoding rules for using the Tagged Image File Format (TIFF) for the exchange of georeferenced or geocoded imagery. The OGC GeoTIFF 1.1 standard formalizes the existing community GeoTIFF specification version 1.0 and aligns it with the continuing addition of data to the EPSG Geodetic Parameter Dataset.

## **ii. Keywords**

The following are keywords to be used by search engines and document catalogues.

ogcdoc, OGC document, geotiff, tiff

## **iii. Preface**

The GeoTIFF format was initially developed during the early 1990's (N. Ritter & Ruth, 1997). The objective was to leverage a mature platform independent file format (TIFF) by adding metadata required for describing and using geographic image data. TIFF met the requirements for an underlying format, as it was - and still is (though JPEG compression was added) - lossless and extensible. In September 1994, SPOT Image Corp proposed a GeoTIFF structure that was limited to Universal Transverse Mercator (N. Ritter & Ruth, 1997). The proposed GeoTIFF specification was further augmented and formalized by Ritter and Ruth as Revision 1.0, specification version 1.8.2 in November 1995 (N. Ritter & Ruth, 1995), with minor adjustments published in 2000, available at <http://geotiff.maptools.org/spec/geotiffhome.html>, which is the official GeoTIFF specification version 1.0.

The GeoTIFF format is used throughout the geospatial and earth science communities to share geographic image data. That usage inevitably leads to identification of new requirements and needs for profiles, extensions, and improvements to the original GeoTIFF Specification. The OGC is well established as a forum for standardization in the GeoTIFF producer and user communities and, as such, it provides an inclusive standardization process for those communities. This document is the first step in the process of integration of the GeoTIFF specification into that standardization process, with the adjustment of a minor revision in order to allow the use of modern EPSG register and still allowing backward compatibility with Revision 1.0. Moving forward within the OGC, the standard can be evolved using a formal process.

Suggested additions, changes, and comments on this standard are welcome and encouraged. Such suggestions may be submitted by email message or by submitting an official OGC Change Request using the online OGC Change Request application: <http://www.opengeospatial.org/standards/cr>. The requests may also be sent to OGC - CIO StandardsTracker: <http://ogc.standardstracker.org/>

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. The Open Geospatial Consortium shall not be held responsible for identifying any or all such patent rights.

Recipients of this document are requested to submit, with their comments, notification of any relevant patent claims or other intellectual property rights of which they may be aware that might be infringed by any implementation of the standard set forth in this document, and to provide



supporting documentation.

#### iv. Submitting organizations

The following organizations submitted this Document to the Open Geospatial Consortium (OGC):

- IGN
- The HDF Group
- Heazeltech LLC
- International Association of Oil & Gas Producers (IOGP)
- Spatialys
- U.S. National Aeronautics and Space Administration (NASA)
- U.S. National Geospatial-Intelligence Agency (NGA)
- U.S. Army Geospatial Center (AGC)

#### v. Submitters

All questions regarding this submission should be directed to the editor or the submitters:

Name	Affiliation
Emmanuel Devys	IGN
Ted Habermann	The HDF Group
Charles Heazel	Heazeltech LLC
Roger Lott	IOGP
Even Rouault	Spatialys
Stephen Olding	NASA
Sylvester Hagler	NGA
Amy Youmans	AGC

# Chapter 1. Scope

This OGC® Standard defines the Geographic Tagged Image File Format (GeoTIFF) by specifying the content and structure of a group of industry-standard tag sets for the management of georeferenced or geocoded raster imagery using Aldus-Adobe's publicly available Tagged Image File Format (TIFF). This OGC Standard specifies the requirements to which every GeoTIFF file shall adhere.

GeoTIFF defines a set of TIFF tags provided to describe all "Cartographic" information associated with TIFF imagery that originates from satellite imaging systems, scanned aerial photography, scanned maps, digital elevation models, or as a result of geographic analyses. The goal is to provide a consistent mechanism for referencing a raster image to a known model space or earth-based coordinate reference system and for describing those coordinate reference systems.

The tags documented in this standard are to be considered completely orthogonal (i.e., independent) to the raster-data descriptions of the TIFF specification, and impose no restrictions on how the standard TIFF tags are to be interpreted, which color spaces or compression types are to be used, and so forth.

This OGC Standard is a minor revision of GeoTIFF focused on updating the current GeoTIFF community specification and aligning it with current OGC standardization practice. This includes enabling the use of coordinate reference systems that have been included in EPSG register since the GeoTIFF 1.0 specification dating from 1995. As such, the OGC GeoTIFF Standard should be backward compatible with the 1.0 version, both for coordinate reference systems based on EPSG register codes, or user-defined coordinate reference systems. [Backward compatibility](#) documents this backward compatibility and the evolutions of the 1.1 revision.

# Chapter 2. Conformance

This standard defines 150 Requirements grouped into 31 Requirements Classes.

These Requirements address five (5) standardization target types:

- Underlying TIFF Requirements;
- GeoTIFF Configuration GeoKeys;
- Raster to Model Coordinate Transformation Requirements;
- Requirements for definition of Model CRS when the Model CRS is from GeoTIFF CRS register;  
and
- Requirements for definition of user-defined Model CRS.

Conformance with this standard shall be checked using all the relevant tests specified in Annex A (normative) of this document. The framework, concepts, and methodology for testing, and the criteria to be achieved to claim conformance are specified in the OGC Compliance Testing Policies and Procedures and the OGC Compliance Testing web site.

In order to conform to this OGC® encoding standard, a software implementation shall comply with all of the conformance classes specified in Annex A (normative).

# Chapter 3. References

The following normative documents contain provisions that, through reference in this text, constitute provisions of this document. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. For undated references, the latest edition of the normative document referred to applies.

- Association Adobe Developers: *TIFF Specification Revision 6.0*, June 3, 1992
- OGC: *OGC Abstract Topic 2: Referencing by coordinates* (equivalent to ISO 19111:2019 Geographic information — Referencing by coordinates), 2019

# Chapter 4. Terms and Definitions

For the purposes of this document, the following additional terms and definitions apply.

## NOTE

For GeoTIFF Format Specification 1.0, see <http://geotiff.maptools.org/spec/geotiffhome.html>

## 4.1. band

Range of wavelengths of electromagnetic radiation that produce a single response by a sensing device.

[Source: ISO 19101-2:2018, 3.1]

Note: At the pixel level, a band is represented as one of the vector values of the pixel. At image level, band  $i$  of an image is the rectangular array of  $i^{\text{th}}$  sample values from the pixel vectors.

## 4.2. cell

Rectangular area in raster space, in which a single pixel value is filled.

[Source: GeoTIFF Format Specification 1.0]

## 4.3. code

Representation of a label according to a specified scheme.

[Source: ISO 19118:2011, 4.3]

## 4.4. coordinate

One of a sequence of numbers designating the position of a point.

[Source: ISO 19111:2019, 3.1.5]

Note: In a spatial coordinate reference system, the coordinate numbers are qualified by units.

## 4.5. coordinate epoch

Epoch to which coordinates in a dynamic coordinate reference system are referenced

[Source: ISO 19111:2019, 3.1.7]

## 4.6. coordinate reference system

Coordinate system that is related to an object by a datum.

[Source: ISO 19111:2019, 3.1.9]

Note 1: Geodetic and vertical datums are referred to as reference frames.

Note 2: For geodetic and vertical reference frames, the object will be the Earth. In planetary applications, geodetic and vertical reference frames may be applied to other celestial bodies.

### NOTE

This term is also called Model Coordinate Reference system in the context of this document, and was called Model Coordinate System in the 1995 GeoTIFF v1.0.

## 4.7. coordinate system

Set of mathematical rules for specifying how coordinates are to be assigned to points.

[Source: ISO 19111:2019, 3.1.11]

## 4.8. correspondence model

Functional relationship between ground and image coordinates based on the correlation between a set of ground control points and their corresponding image coordinates.

[Source: ISO/TS 19130:2010, 4.3]

## 4.9. datum

*reference frame*

Parameter or set of parameters that realize the position of the origin, the scale, and the orientation of a coordinate system.

[Source: ISO 19111:2019, 3.1.15]

## 4.10. device space

Coordinate space referencing scanner, printers and display devices.

[Source: GeoTIFF Format Specification 1.0]

## 4.11. double

8-byte IEEE double precision floating point.

## 4.12. dynamic CRS

CRS into which coordinates of a point on the surface of the Earth may change with time. [Source: ISO 19111:2019, B.4.3]

## 4.13. ellipsoid

*reference ellipsoid*

<geodesy> Geometric reference surface embedded in 3D Euclidean space formed by an ellipse that is rotated about a main axis.

[Source: ISO 19111:2019, 3.1.22]

Note: For the Earth the ellipsoid is bi-axial with rotation about the polar axis. This results in an oblate ellipsoid with the midpoint of the foci located at the nominal centre of the Earth.

## 4.14. flattening

*f*

Ratio of the difference between the semi-major (a) and semi-minor axis (b) of an ellipsoid to the semi-major axis;  $f = (a - b)/a$ .

[Source: ISO 19111:2019, 3.1.28]

Note: Sometimes inverse flattening  $1/f = a/(a - b)$  is given instead;  $1/f$  is also known as reciprocal flattening.

## 4.15. geocoding

Translation of one form of location into another.

[Source: ISO 19133:2005, 4.4]

**NOTE**

In the 1995 GeoTIFF v1.0, "an image is geocoded if a precise algorithm for determining the earth-location of each point in the image is defined".

## 4.16. geographic coordinate reference system

Coordinate reference system that has a geodetic reference frame and an ellipsoidal coordinate system.

[Source: ISO 19111:2019, 3.1.35]

Note: This allows the assignment of a Latitude-Longitude vector to a location on earth (plus optionally a geodetic height).

**NOTE**

In the 1995 GeoTIFF v1.0, this term was "geographic coordinate system"

## 4.17. geokey

In GeoTIFF, a GeoKey is equivalent in function to a TIFF tag, but uses a different storage mechanism.

[Source: GeoTIFF Format Specification 1.0]

## 4.18. georectified

Corrected for positional displacement with respect to the surface of the Earth.

[Source: ISO 19115-2:2019, 3.11]

## 4.19. georeferencing

Geopositioning an object using a Correspondence Model derived from a set of points for which both ground and image coordinates are known.

[Source: ISO 19130:2010, 4.37]

**NOTE**

In the 1995 GeoTIFF v1.0, "An image is georeferenced if the location of its pixels in some model space is defined, but the transformation tying model space to the earth is not known."



## 4.20. GeoTIFF

Standard for storing georeference and geocoding information in a TIFF 6.0 compliant raster file.

[Source: GeoTIFF Format Specification 1.0]

## 4.21. grid

Network composed of two or more sets of curves in which the members of each set intersect the members of the other sets in an algorithmic way.

[Source: ISO 19123:2005, 4.1.23]

Note: The curves partition a space into grid cells.

## 4.22. imagery

Representation of phenomena as images produced electronically and/or optical techniques.

[Source: ISO 19101-2:2018, 3.14]

Note: In this document, it is assumed that the phenomena have been sensed or detected by one or more devices such as radar, cameras, photometers, and infra-red and multispectral scanners.

Note: In this document, imagery also includes the result of geographic analysis and processing, e.g., digital elevation models.

## 4.23. meridian

Intersection of an ellipsoid by a plane containing the shortest axis of the ellipsoid.

[Source: ISO 19111:2019, 3.1.42]

Note: This term is generally used to describe the pole-to-pole arc rather than the complete closed figure.

## 4.24. metadata

Information about a resource.

[Source: ISO 19115-1:2014, 4.10]

## 4.25. model space

Space in a coordinate reference system related to the earth or a part of the earth.

## 4.26. mosaic

An image composed of two or more separately collected (sensed) images.

Note: Additional metadata may be used to identify the cut-lines (boundaries and parameters for the images used to compose the mosaic).

## 4.27. orthoimage

Image in which by orthogonal projection to a reference surface, displacement of image points due to sensor orientation and terrain relief has been removed.

[Source: ISO 19101-2:2018, 3.25]

Note: The amount of displacement depends on the resolution and the level of detail of the elevation information and on the software implementation.

## 4.28. orthorectified grid

Georectified grid created using ground control points and elevation data where constant scale is maintained throughout the grid.

## 4.29. parallel

Line of constant latitude, parallel to the equator.

[Source: GeoTIFF Format Specification 1.0]

## 4.30. pixel

Smallest element of a digital image to which attributes are assigned.

[Source: ISO 19101-2:2008, 3.28]

Note 1: This term originated as a contraction of “picture element.”

Note 2: Related to the concept of a grid cell.

## 4.31. prime meridian

Meridian from which the longitudes of other meridians are quantified.

[Source: ISO 19111:2019, 3.1.50]

## 4.32. projected coordinate reference system

Coordinate reference system derived from a geographic coordinate reference system by applying a map projection.

[Source ISO 19111:2019, 3.1.51]

Note 1: May be two- or three-dimensional, the dimension being equal to that of the geographic coordinate reference system from which it is derived.

Note 2: In the three-dimensional case the horizontal coordinates (geodetic latitude and geodetic longitude coordinates) are projected to northing and easting and the ellipsoidal height is unchanged.

**NOTE** In the 1995 GeoTIFF v1.0, this term was "projected coordinate system."

## 4.33. projection

Projected coordinate reference system.

Coordinate conversion from an ellipsoidal coordinate system to a plane.

[Source: ISO 19111:2019, 3.1.40]

## 4.34. raster

*raster space*

Usually rectangular pattern of parallel scanning lines forming or corresponding to the display on a cathode ray tube.

[Source: ISO 19123:2005, 4.1.30]

Note: A raster is a type of grid.

**NOTE**

In the 1995 GeoTIFF v1.0, "A continuous planar space in which pixel values are visually realized."

## 4.35. rational

In TIFF format, a *rational* value is a fractional value represented by the ratio of two unsigned 4-byte integers.

[Source: GeoTIFF Format Specification 1.0]

## 4.36. rectified grid

*georectified grid*

Grid for which there is an affine transformation between the grid coordinates and the coordinates of an external coordinate reference system.

[Source: ISO 19123:2005, 4.1.32]

Note: If the coordinate reference system is related to the earth by a datum, the grid is a georectified grid.

## 4.37. referenceable grid

Grid associated with a transformation that can be used to convert grid coordinate values to values of coordinates referenced to an external coordinate reference system.

[Source: ISO 19123:2005, 4.1.33]

Note: If the coordinate reference system is related to the earth by a datum, the grid is a georeferenceable grid.

## 4.38. short

2-byte IEEE signed integer.

## 4.39. tag

In TIFF format, a tag is packet of numerical or ASCII values, which have a numerical "Tag" ID indicating their information content.

[Source: GeoTIFF Format Specification 1.0]

## **4.40. vertical coordinate reference system**

One-dimensional coordinate reference system based on a vertical reference frame.

[Source: ISO 19111:2019, 3.1.70]

# Chapter 5. Abbreviations

**ASCII** [American Standard Code for Information Interchange] The character set encoding standard for electronic communication, which was developed in the US and based on the typographical symbols predominantly in use there.

**CRS** Coordinate Reference System

**EPSG** Geodetic parameter dataset initiated by the now-disbanded European Petroleum Survey Group and now maintained at <http://www.epsg-registry.org> by the International Association of Oil and Gas Producers (IOGP).

**IEEE** Institute of Electrical and Electronics Engineers, Inc.

**IFD** In TIFF format, an Image File Directory, containing all the TIFF tags for one image in the file (there may be more than one).

**SI** International System of Units

**TIFF** Acronym for Tagged Image File Format; a platform-independent, extensive specification for storing raster data and ancillary information in a single file.

**URI** Uniform Resource Identifier

**USGS** United States Geological Survey

**2D** two-dimensional

**3D** three-dimensional

**Identifiers** The normative provisions in this specification are denoted by the URI <http://www.opengis.net/spec/geotiff/1.1>

All requirements and conformance tests that appear in this document are denoted by partial URIs which are relative to this base.

# Chapter 6. Clauses not Containing Normative Material

The following sections of this standard are included for informative purposes only. These sections serve to assist in correct implementation of this standard but do not impose any additional requirements.

- [Media Types for GeoTIFF data encoding](#): This informative clause documents the MIME type usages for GeoTIFF files.
- [Annex B: The GeoTIFF File Structure](#): This Annex provides a description of the community GeoTIFF specification and supporting information on how various elements of that specification should be used.
- [Annex D: Recommendations for describing compound and geographic 3D CRSs](#): This Annex provides recommendations for describing 3D Model CRS subtypes to which heights are referenced (compound and geographic 3D) that are not fully supported in this community specification.
- [Annex E: Summary of GeoKey IDs and names](#): This Annex lists the names and IDs of all GeoKeys supported in this specification.
- [Annex F: Examples](#): This Annex contains a set of illustrative examples of GeoTIFF tags' contents.
- [Annex G: Deprecated and deleted EPSG codes](#): This Annex documents EPSG codes explicitly cited in the 1995 v1.0 GeoTIFF specification that are no longer valid.
- [Annex H: Backward compatibility](#): This Annex documents backward compatibility of this minor revision with revision 1.0 of GeoTIFF and the changes in this document from the 1995 v1.0 GeoTIFF specification.

# Chapter 7. Requirements

This document uses the terms defined in Sub-clause 5.3 of [OGC 06-121r8], which is based on the ISO/IEC Directives, Part 2, Rules for the structure and drafting of International Standards. In particular, the word “shall” (not “must”) is the verb form used to indicate a requirement to be strictly followed to conform to this standard.

NOTE	Enumerated Geokey values 32768 or higher are reserved for private usage (for organizations), according to TIFF practice for TIFF tags. This appears later in this specification for the requirements on the range of Geokey values reserved for private usage.
------	--

## 7.1. Underlying TIFF Requirements

This Standardization Target addresses the core TIFF Requirements Class applicable to all GeoTIFF instances (i.e., files).

A GeoTIFF file is a TIFF 6.0 file and inherits the file structure as described in the corresponding portion of the TIFF specification. In addition, all GeoTIFF specific information is encoded in reserved TIFF tags. The following requirements formalize compliance with TIFF and the GeoTIFF reserved tag structure.

### 7.1.1. Requirements Class TIFF

A GeoTIFF file is a valid TIFF 6.0 file.

Requirements Class 1.0: TIFF	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/Core">http://www.opengis.net/spec/GeoTIFF/1.1/req/Core</a>	
Requirement 1.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/TIFF">http://www.opengis.net/spec/GeoTIFF/1.1/req/TIFF</a> <i>A GeoTIFF file SHALL be compliant with the TIFF 6.0 specification</i>



Requirement 1.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/DataGeoTags">http://www.opengis.net/spec/GeoTIFF/1.1/req/DataGeoTags</a> <i>GeoTIFF files SHALL encode all GeoTIFF specific information using the following specified reserved TIFF tags</i> <ul style="list-style-type: none"> <li>- 34735 GeoKeyDirectoryTag (mandatory)</li> <li>- 34736 GeoDoubleParamsTag (optional)</li> <li>- 34737 GeoAsciiParamsTag (optional)</li> <li>- 33550 ModelPixelScaleTag (optional)</li> <li>- 33922 ModelTiepointTag (conditional)</li> <li>- 34264 ModelTransformationTag (conditional)</li> </ul> <i>The conditional tags shall follow the following rules:</i> <ul style="list-style-type: none"> <li>- One of ModelTiepointTag or ModelTransformationTag SHALL be included in an Image File Directory (IFD)</li> <li>- If the ModelTransformationTag is included in an IFD, then a ModelPixelScaleTag SHALL NOT be included</li> <li>- If the ModelPixelScaleTag is included in an IFD, then a ModelTiepointTag SHALL also be included.</li> </ul>
Requirement 1.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/DataTypes">http://www.opengis.net/spec/GeoTIFF/1.1/req/DataTypes</a> <i>GeoTIFF implementation software SHALL support all documented TIFF 6.0 tag data-types, and in particular ASCII, SHORT and the IEEE double-precision floating point "DOUBLE" types</i>
Requirement 1.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ByteOrder">http://www.opengis.net/spec/GeoTIFF/1.1/req/ByteOrder</a> <i>GeoTIFF implementation software SHALL honor the 'byte-order' indicator by performing byte swaps as necessary to provide an accurate in-memory representation of the values encoded in the GeoTIFF file</i>
Requirement 1.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/TagSort">http://www.opengis.net/spec/GeoTIFF/1.1/req/TagSort</a> <i>The TIFF tags in a GeoTIFF file SHALL be written out to the file with the tag-IDs sorted in ascending order</i>
Requirement 1.6	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeySort">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeySort</a> <i>The GeoKey entries in a GeoTIFF file SHALL be written out to the file with the key-IDs sorted in ascending order</i>

### 7.1.2. Requirements Class GeoKeyDirectoryTag

The GeoKeyDirectoryTag Requirements Class specifies the requirements for implementing the reserved GeoKeyDirectoryTag TIFF tag.

A GeoTIFF file stores projection parameters in a set of "Keys" which are virtually identical in function to a TIFF tag, but have one more level of abstraction above TIFF. Like a tag, a Key has an ID number ranging from 0 to 65535, but unlike TIFF tags, all key ID's are available for use in GeoTIFF parameter definitions.

The Keys in GeoTIFF (also called "GeoKeys") are all referenced from the GeoKeyDirectoryTag tag. The first four keys form the GeoKey Directory Header. The keys which make up this header are: KeyDirectoryVersion, KeyRevision, MinorRevision, and NumberOfKeys.

The GeoKey Directory Header is followed by <NumberOfKeys> Key Entries. Each Key Entry consists of four values.

- "KeyID" gives the key-ID value of the Key (identical in function to TIFF tag ID, but completely independent of TIFF tag-space).
- "TIFFTagLocation" indicates which TIFF tag contains the value(s) of the Key: if TIFFTagLocation is 0, then the value is SHORT, and is contained in the "ValueOffset" entry. Otherwise, the type (format) of the value is implied by the TIFF-Type of the tag containing the value.
- "Count" indicates the number of values in this key.
- "ValueOffset" ValueOffset indicates the index- offset **into** the TagArray indicated by TIFFTagLocation, if it is nonzero. If TIFFTagLocation=0, then ValueOffset contains the actual (SHORT) value of the Key, and Count=1 is implied. Note that the offset is not a byte-offset, but rather an index based on the natural data type of the specified tag array.

#### Requirements Class 2.0: GeoKeyDirectoryTag

<http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag>

Requirement 2.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.ID</a> <i>The GeoKeyDirectoryTag SHALL have ID = 34735</i>
Requirement 2.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.type</a> <i>The GeoKeyDirectoryTag SHALL have type = SHORT (2-byte unsigned integer)</i>
Requirement 2.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.count">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.count</a> <i>The GeoKeyDirectoryTag SHALL include at least 4 keys (short integers) as header information</i>
Requirement 2.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyDirectoryVersion">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyDirectoryVersion</a> <i>The first unsigned short integer in the GeoKeyDirectoryTag SHALL hold the KeyDirectoryVersion.</i>
Requirement 2.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyDirectoryVersionValue">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyDirectoryVersionValue</a> <i>The value of KeyDirectoryVersion SHALL be 1.</i>
Requirement 2.6	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyRevision">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyRevision</a> <i>The second unsigned short integer in the GeoKeyDirectoryTag SHALL hold the KeyRevision.</i>
Requirement 2.7	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyRevisionValue">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyRevisionValue</a> <i>The value of KeyRevision SHALL be 1.</i>
Requirement 2.8	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.minorRevision">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.minorRevision</a> <i>The third unsigned short integer in the GeoKeyDirectoryTag SHALL hold the MinorRevision.</i>

Requirement 2.9	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.minorRevisionValue">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.minorRevisionValue</a> <i>The MinorRevision for this standard SHALL be 0 or 1.</i>  0 = GeoTIFF 1.0 version. Accepted for existing files (GeoTIFF 1.0) that do not use values / codes that are suppressed in this version  1 = this version 1.1. Recommended for production / writing a GeoTIFF file according to this standard (and developing software). Shall be used for files keys and codes not covered by GeoTIFF 1.0 (e.g. VerticalGeoKey).
Requirement 2.10	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.numberOfKeys">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.numberOfKeys</a> <i>The fourth unsigned short integer in the GeoKeyDirectoryTag SHALL hold the NumberOfKeys defined in the rest of the GeoKeyDirectoryTag.</i>
Requirement 2.11	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntrySetCount">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntrySetCount</a> <i>The GeoKeyDirectoryTag SHALL hold NumberOfKeys KeyEntry Sets in addition to the header information</i>
Requirement 2.12	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntry">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntry</a> <i>Each Key Entry in the Key Entry Set SHALL include 4 unsigned short integer values</i>
Requirement 2.13	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryKeyID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryKeyID</a> <i>The first unsigned short integer in the Key Entry SHALL hold the key identifier.</i>
Requirement 2.14	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryTIFFTagLocation">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryTIFFTagLocation</a> <i>The second unsigned short integer in the Key Entry SHALL hold the TIFF Tag Location. The value of this entry shall be a valid GeoTIFF tag identifier or a zero (0)</i>
Requirement 2.15	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryKeyCount">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryKeyCount</a> <i>The Third unsigned short integer in the Key Entry SHALL indicate the number of values associated with this key.</i>
Requirement 2.16	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryValueOffset">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryValueOffset</a> <i>The fourth unsigned short integer in the Key Entry SHALL hold either the key value (if TIFF Tag location = 0) or the index into the tag indicated by the TIFF Tag Location value.</i>

### 7.1.3. Requirements Class GeoKeyCode

For consistency, several key codes have the same meaning in all implemented GeoKeys

Requirements Class 3.0: GeoKeyCode	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyCode">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyCode</a>	
Requirement 3.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyCode.undefined">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyCode.undefined</a> <i>GeoKeys with a value of 0 SHALL indicate intentionally omitted parameters</i>
Requirement 3.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyCode.userDefined">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyCode.userDefined</a> <i>GeoKeys with a value of 32767 SHALL indicate user-defined parameters</i>

The "undefined" code means that this parameter is intentionally omitted or unknown.

In some cases, additional GeoKeys are required when the "User-Defined" value is used. Those requirements are included within a Requirements Class, where appropriate.

### 7.1.4. Requirements Class GeoShortParamsTag

The following requirements govern the storage of parameter values when there are two or more values of type Short.

Requirements Class 4.0: GeoShortParamsTag	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoShortParamsTag">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoShortParamsTag</a>	
Requirement 4.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoShortParamsTag.Criteria">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoShortParamsTag.Criteria</a> <i>In the case where a Parameter of type Short has more than one value, those values SHALL be stored in the GeoKeysDirectory</i>
Requirement 4.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoShortParamsTag.Location">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoShortParamsTag.Location</a> <i>Parameter values stored in the GeoKeysDirectory SHALL appear after the last Key Entry</i>

### 7.1.5. Requirements Class GeoDoubleParamsTag

The following requirements govern the storage of parameter values when the values are of type Double.

Requirements Class 5.0: GeoDoubleParamsTag	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag</a>	
Requirement 5.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag.ID</a> <i>The GeoDoubleParamsTag SHALL have ID = 34736</i>

Requirement 5.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag.count">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag.count</a> <i>The GeoDoubleParamsTag MAY hold any number of key parameters with type = Double.</i>
-----------------	--

## 7.1.6. Requirements Class GeoAsciiParamsTag

The following requirements govern the storage of parameter values when the values are of type ASCII. All text values in a TIFF file must be null-terminated ASCII.

Requirements Class 6.0: GeoAsciiParamsTag	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag</a>	
Requirement 6.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.ID</a> <i>The GeoAsciiParamsTag SHALL have ID = 34737</i>
Requirement 6.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.count">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.count</a> <i>The GeoAsciiParamsTag SHALL contain the values of the key parameters of type = ASCII referenced by the GeoKeyDirectoryTag. If there is no key parameters of type = ASCII, it SHALL not be present</i>
Requirement 6.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.terminator">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.terminator</a> <i>The pipe character   in the GeoAsciiParamsTag SHALL be used as the character to terminate a string written in as ASCII tag</i>  NOTE: If multiple strings are written in the same tag, this terminator character also serves as a separator.  NOTE: This requirement only applies for the content of the tag. The TIFF specification requires that the last byte of a TIFF tag of type ASCII is NULL.
Requirement 6.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.NULLWrite">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.NULLWrite</a> <i>NULL (ASCII code = 0) characters SHALL not be present in the string content written in the GeoAsciiParamsTag</i>  NOTE: this requirement only applies for the content of the tag. The TIFF specification requires that the last byte of a TIFF tag of type ASCII is NULL.
Requirement 6.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.type</a> <i>The GeoAsciiParamsTag SHALL have type = ASCII</i>

Example of a GeoAscii tag containing only one string: "NAD27 / UTM zone 11N|{NULL}" (where {NULL} is the ASCII character of code 0)

Example of a GeoAscii tag containing two strings: "NAD27 / UTM zone 11N|NAD27|{NULL}"

## 7.2. GeoTIFF Configuration GeoKeys

This Standardization Target addresses encoding of Configuration values essential for interpreting the rest of the GeoKeys.

### 7.2.1. Requirements Class GTRasterTypeGeoKey

This requirements class establishes the Raster Space used. There are currently only two options: *RasterPixelsPoint* and *RasterPixelsArea*. No user-defined raster spaces are currently supported. For variance in imaging display parameters, such as pixel aspect-ratios, use the standard TIFF 6.0 device-space tags.

The use of this geokey is **highly recommended** for accurate georeferencing of raster.

Requirements Class 7.0: GTRasterTypeGeoKey	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey</a>	
Requirement 7.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey.ID</a> <i>The GTRasterTypeGeoKey SHALL have ID = 1025</i>
Requirement 7.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey.type</a> <i>The GTRasterTypeGeoKey SHALL have type = SHORT</i>
Requirement 7.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey.value">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey.value</a> <i>The GTRasterTypeGeoKey value SHALL be:</i>  * 0 to indicate that the Raster type is undefined or unknown; or  * 1 to indicate that the Raster type is PixelsArea; or  * 2 to indicate that the Raster type is PixelsPoint; or  * 32767 to indicate that the Raster type is user-defined.  Recommendation: the use of 0 (undefined) or 32767 (user-defined) is not recommended
Requirement 7.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey.reserved">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey.reserved</a> <i>GTRasterTypeGeoKey values in the range 3-32766 SHALL be reserved</i>
Requirement 7.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey.private">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey.private</a> <i>GTRasterTypeGeoKey values in the range 32768-65535 SHALL be private</i>

### 7.2.2. Requirements Class GTModelTypeGeoKey

This GeoKey defines the type of Model coordinate reference system used, to which the

transformation from the raster space is made:

- Model CRS is unknown or unspecified;
- Model CRS is a Geographic 2D CRS;
- Model CRS is a Geocentric CRS;
- Model CRS is a Projected CRS; and
- Model CRS is user-defined.

If the Model coordinate reference system is from the GeoTIFF standard CRS register (i.e., EPSG register), then only the registered CRS code need be specified. See [Requirements for definition of Model CRS \(when Model is from GeoTIFF CRS register\)](#).

If the Model coordinate reference system is not from the GeoTIFF standard CRS register, then it requires the specification of some or all CRS elements. See [Requirements for definition of user-defined Model CRS](#).

The GeoTIFF v1.0 format has also been used to describe pseudo-3D compound CRSs consisting of a projected CRS and a vertical CRS or a geographic 2D CRS and a vertical CRS, as well as a geographic 3D CRS. In this document, this usage is permitted but not explicitly described through the `GTModelTypeGeoKey`. Recommendations are given in Annex D.

Requirements Class 8.0: <code>GTModelTypeGeoKey</code>	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey</a>	
Requirement 8.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.required">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.required</a> <i>A GeoTIFF file SHALL include a GTModelTypeGeoKey</i>
Requirement 8.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.ID</a> <i>The GTModelTypeGeoKey SHALL have ID = 1024</i>
Requirement 8.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.type</a> <i>The GTModelTypeGeoKey SHALL have type = SHORT</i>



Requirement 8.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.value">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.value</a> <i>The GTModelTypeGeoKey value SHALL be:</i> <ul style="list-style-type: none"> <li>* 0 to indicate that the Model CRS is undefined or unknown; or</li> <li>* 1 to indicate that the Model CRS is a 2D projected coordinate reference system, indicated by the value of the ProjectedCRSGeoKey; or</li> <li>* 2 to indicate that the Model CRS is a geographic 2D coordinate reference system, indicated by the value of the GeodeticCRSGeoKey; or</li> <li>* 3 to indicate that the Model CRS is a geocentric Cartesian 3D coordinate reference system, indicated by the value of the GeodeticCRSGeoKey; or</li> <li>* 32767 to indicate that the Model CRS type is user-defined.</li> </ul>
Requirement 8.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.reserved">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.reserved</a> <i>GTModelTypeGeoKey values in the range 4-32766 SHALL be reserved</i>
Requirement 8.6	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.private">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.private</a> <i>GTModelTypeGeoKey values in the range 32768-65535 SHALL be private</i>
Requirement 8.7	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.projCRS">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.projCRS</a> <i>If the GTModelTypeGeoKey value is 1 (Model CRS is a projected 2D CRS) then the GeoTIFF file SHALL include a ProjectedCRSGeoKey.</i>
Requirement 8.8	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.geogCRS">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.geogCRS</a> <i>If the GTModelTypeGeoKey value is 2 (Model CRS is a geographic 2D CRS) then the GeoTIFF file SHALL include a GeodeticCRSGeoKey.</i>
Requirement 8.9	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.geocenCRS">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.geocenCRS</a> <i>If the GTModelTypeGeoKey value is 3 (Model CRS is a geocentric CRS) then the GeoTIFF file SHALL include a GeodeticCRSGeoKey.</i>
Requirement 8.10	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.userdefined">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey.userdefined</a> <i>If the GTModelTypeGeoKey value is 32767 (user-defined) then the GTCitationGeoKey SHALL be populated.</i>

**NOTE**

The GTCitationGeoKey is also provided to give an ASCII reference to published documentation on the overall configuration of the GeoTIFF file (see [Requirements Class Citation GeoKeys](#)).



## 7.3. Raster to Model Coordinate Transformation Requirements

For most common applications, the transformation between raster space and model space may be defined with a set of raster-to-model tiepoints and scaling parameters. The *ModelTiepointTag* and *ModelPixelScaleTag* may be used for this purpose.

Alternatively, the *ModelTransformationTag* may be used to specify the transformation matrix between the raster space (and its dependent pixel-value space) and the (possibly 3D) model space.

Consult [GeoTIFF Tags for Coordinate Transformations](#) for a description of their semantics.

**NOTE** It should be noted that model space axis order in the following 3 tags *ModelTiepointTag*, *ModelPixelScaleTag* and *ModelTransformationTag* is fixed at (lon,lat,height) in case of geographic 3D and (east,north,height) in case of projected regardless of the model space CRS definition. This convention was implicit in GeoTIFF 1.0 and still is valid in this revision.

### 7.3.1. Requirements Class ModelTiepointTag

Requirements Class 9.0: ModelTiepointTag	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTiepointTag">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTiepointTag</a>	
Requirement 9.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTiepointTag.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTiepointTag.ID</a> The <i>ModelTiepointTag</i> SHALL have ID = 33922
Requirement 9.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTiepointTag.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTiepointTag.type</a> The <i>ModelTiepointTag</i> SHALL have type = DOUBLE
Requirement 9.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTiepointTag.count">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTiepointTag.count</a> The <i>ModelTiepointTag</i> SHALL have 6 values for each of the tiepoints

### 7.3.2. Requirements Class ModelPixelScaleTag

Requirements Class 10.0: ModelPixelScaleTag	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag</a>	
Requirement 10.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.ID</a> The <i>ModelPixelScaleTag</i> SHALL have ID = 33550
Requirement 10.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.type</a> The <i>ModelPixelScaleTag</i> SHALL have type = DOUBLE
Requirement 10.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.count">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.count</a> The <i>ModelPixelScaleTag</i> SHALL have 3 values representing the scale factor in the X, Y, and Z directions

Requirement 10.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.standardConvention">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.standardConvention</a> <i>A positive ScaleX in the ModelPixelScaleTag SHALL indicate that model space X coordinates increase as raster space I indices increase. This is the standard horizontal relationship between raster space and model space. A positive ScaleY in the ModelPixelScaleTag SHALL indicate that model space Y coordinates decrease as raster space J indices increase. This is the standard vertical relationship between raster space and model space. The ScaleZ is primarily used to map the pixel value of a digital elevation model into the correct Z-scale (in other words a <b>Z-Scaling factor</b>).</i>
Requirement 10.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.axisReversal">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.axisReversal</a> <i>Simple reversals of orientation from the standard relationship between raster and model space (e.g., horizontal or vertical flips) SHALL be indicated by reversal of sign in the corresponding component of the ModelPixelScaleTag. GeoTIFF compliant readers shall honor this sign-reversal convention.</i>

### 7.3.3. Requirements Class ModelTransformationTag

Requirements Class 11.0: ModelTransformationTag	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTransformationTag">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTransformationTag</a>	
Requirement 11.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTransformationTag.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTransformationTag.ID</a> <i>The ModelTransformationTag SHALL have ID = 34264</i>
Requirement 11.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTransformationTag.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTransformationTag.type</a> <i>The ModelTransformationTag SHALL have type = DOUBLE</i>
Requirement 11.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTransformationTag.count">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTransformationTag.count</a> <i>The ModelTransformationTag SHALL have 16 values representing the terms of the 4 by 4 transformation matrix. The terms SHALL be in row-major order</i>

## 7.4. Requirements for definition of Model CRS (when Model is from GeoTIFF CRS register)

### 7.4.1. Overview

When the Model CRS is included in the GeoTIFF CRS register (i.e., EPSG register), only its register code is required. For 2D projected CRSs ("map grids") the code is given through the ProjectedCRSGeoKey. For geodetic CRSs (geographic 2D and geocentric CRSs) the code is given through the GeodeticCRSGeoKey. If the Model CRS is a pseudo-3D compound CRS consisting of

either a projected 2D CRS or a geographic 2D CRS together with a vertical CRS, the code of the vertical component is given through the VerticalGeoKey.

**NOTE**

It is a practice in some Communities to indicate a geographic 3D CRS (with ellipsoidal height) by including the code of the geographic 3D CRS in a VerticalGeoKey. See [Geographic 3D CRS](#).

## 7.4.2. Requirements Class ProjectedCRSGeoKey

This key is used to specify the projected coordinate reference system from the GeoTIFF CRS register or to indicate that the Model CRS is a user-defined projected coordinate reference system.

**NOTE**

In GeoTIFF 1.0 this key was called ProjectedCSTypeGeoKey.

Requirements Class 12.0: ProjectedCRSGeoKey	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey</a>	
Requirement 12.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey.ID</a> <i>The ProjectedCRSGeoKey SHALL have ID = 3072</i>
Requirement 12.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey.type</a> <i>The ProjectedCRSGeoKey SHALL have type = SHORT</i>
Requirement 12.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey.reserved">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey.reserved</a> <i>ProjectedCRSGeoKey values in the range 1-1023 SHALL be reserved.</i>
Requirement 12.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey.EPSG">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey.EPSG</a> <i>ProjectedCRSGeoKey values in the range 1024-32766 SHALL be EPSG Projected CRS Codes</i>  NOTE: In GeoTIFF v1.0 the range was 20000-32760. Several values in this range have been deprecated or deleted from the EPSG Dataset and should no longer be used. See <a href="#">Table G.1 - Deprecated and deleted EPSG Projected CRS codes</a>
Requirement 12.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey.userdefined">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey.userdefined</a> <i>A ProjectedCRSGeoKey value of 32767 SHALL be a user-defined projected CRS. If the ProjectedCRSGeoKey value is 32767 (User-Defined) then the ProjectedCitationGeoKey, GeodeticCRSGeoKey and ProjectionGeoKey SHALL be populated.</i>
Requirement 12.6	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey.private">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey.private</a> <i>ProjectedCRSGeoKey values in the range 32768-65535 SHALL be private</i>

### 7.4.3. Requirements Class GeodeticCRSGeoKey

This key is provided to specify the geodetic (geographic or geocentric) coordinate reference system from the GeoTIFF CRS register or to indicate that the Model CRS is a user-defined geodetic coordinate reference system.

#### NOTE

In GeoTIFF 1.0 this key was called GeographicTypeGeoKey. Geodetic CRS is a superset of geographic 2D CRS, geographic 3D CRS and geocentric (earth-centred 3D Cartesian) CRS.

Requirements Class 13.0: GeodeticCRSGeoKey	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey</a>	
Requirement 13.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.ID</a> <i>The GeodeticCRSGeoKey SHALL have ID = 2048</i>
Requirement 13.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.type</a> <i>The GeodeticCRSGeoKey SHALL have type = SHORT</i>
Requirement 13.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.reserved">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.reserved</a> <i>GeodeticCRSGeoKey values in the range 1-1023 SHALL be reserved.</i>  NOTE: In GeoTIFF v1.0 the reserved ranges were 1001-3999 and 5000-32766.
Requirement 13.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.EPSG">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.EPSG</a> <i>GeodeticCRSGeoKey values in the range 1024-32766 SHALL be EPSG geographic 2D or geocentric CRS codes</i>  NOTE: In GeoTIFF v1.0 the range was 4000-4999. Several values in this range have been deprecated or deleted from the EPSG Dataset and should no longer be used. See <a href="#">Table G.2 - Deprecated and deleted EPSG Geodetic CRS codes</a>
Requirement 13.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.user-defined">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.user-defined</a> <i>If the GeodeticCRSGeoKey value is 32767 (User-Defined) then the GeodeticCitationGeoKey, GeodeticDatumGeoKey and at least one of GeogAngularUnitsGeoKey or GeogLinearUnitsGeoKey SHALL be populated.</i>  NOTE: if the user-defined CRS is geographic 2D, GeogAngularUnitsGeoKey should be populated ; if the user-defined CRS is geocentric, GeogLinearUnitsGeoKey should be populated.
Requirement 13.6	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.private">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.private</a> <i>GeodeticCRSGeoKey values in the range 32768-65535 SHALL be private</i>

## 7.4.4. Requirements Class VerticalGeoKey

This key is provided to specify the vertical coordinate reference system from the GeoTIFF CRS register or to indicate that the CRS is a user-defined vertical coordinate reference system. The value for VerticalGeoKey should follow the recommendations for including height in model CRS definitions as provided in Annex D.

**NOTE** In GeoTIFF 1.0 this key was called VerticalCSTypeGeoKey. In GeoTIFF v1.0 vertical coordinate reference systems were described in draft form, with the statement "Vertical coordinate systems are not yet implemented. These sections are provided for future development, and any vertical coordinate systems in the current revision must be defined using the VerticalCitationGeoKey."

Requirements Class 14.0: VerticalGeoKey	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey</a>	
Requirement 14.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey.ID</a> <i>The VerticalGeoKey SHALL have ID = 4096</i>
Requirement 14.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey.type</a> <i>The VerticalGeoKey SHALL have type = SHORT</i>
Requirement 14.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey.reserved">http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey.reserved</a> <i>VerticalGeoKey values in the range 1-1023 SHALL be reserved</i>  NOTE: In GeoTIFF v1.0 the reserved ranges were 0001-4999 and 6000-32766.
Requirement 14.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey.EPSG">http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey.EPSG</a> <i>VerticalGeoKey values in the range 1024-32766 SHALL be <b>either</b> EPSG Vertical CRS Codes <b>or</b> EPSG geographic 3D CRS codes</i>  NOTE: In GeoTIFF v1.0 the ranges were 5000-5099 and 5200-5999. As at 2018-05-29 no EPSG vertical CRSs have been or are in this range. Values in this range have been and are used as EPSG vertical datum codes; in this document their use as codes for vertical CRSs is deprecated.
Requirement 14.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey.userdefined">http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey.userdefined</a> <i>If the VerticalGeoKey value is 32767 (User-Defined) then the VerticalCitationGeoKey, the VerticalUnitsGeoKey and VerticalDatumGeoKey SHALL be populated.</i>
Requirement 14.6	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey.private">http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey.private</a> <i>VerticalGeoKey values in the range 32768-65535 SHALL be private</i>

## 7.4.5. Requirements Class Citation GeoKeys

The *GTCitationGeoKey* is provided to give an ASCII reference to published documentation on the overall configuration of the GeoTIFF file. The *GeodeticCitationGeoKey*, *ProjectedCitationGeoKey* and

*VerticalCitationGeoKey* are used to describe Model CRS elements through ASCII free text. A citation may be included with a CRS identified through the GeoTIFF CRS register ([[Requirements for definition of Model CRS \(when Model CRS is from GeoTIFF CRS register\)](#)]). A citation is mandatory for a user-defined CRSs and CRS objects ([Requirements for definition of user-defined Model CRS](#)). The *GeodeticCitationGeoKey*, *ProjectedCitationGeoKey* and *VerticalCitationGeoKey* are used with CRSs and CRS components.

#### NOTE

In GeoTIFF 1.0 the *GeodeticCitationGeoKey* key was called *GeogCitationGeoKey* and the *ProjectedCitationGeoKey* key was called *PCSCitationGeoKey*.

### Requirements Class 15.0: CitationGeoKeys

<http://www.opengis.net/spec/GeoTIFF/1.1/req/CitationGeoKeys>

Requirement 15.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/CitationGeoKeys.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/CitationGeoKeys.ID</a> <i>The GTCitationGeoKey SHALL have ID = 1026</i>  <i>The GeodeticCitationGeoKey SHALL have ID = 2049</i>  <i>The ProjectedCitationGeoKey SHALL have ID = 3073</i>  <i>The VerticalCitationGeoKey SHALL have ID = 4097</i>
Requirement 15.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/CitationGeoKeys.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/CitationGeoKeys.type</a> <i>The CitationGeoKeys SHALL have type = ASCII</i>

## 7.5. Requirements for definition of user-defined Model CRS

The GeoKeys described in this section are needed only when Model CRSs are not available from the GeoTIFF CRS register and the CRS or one or more of its component objects is user-defined, that is if one or more of *ProjectedCRSGeoKey*, *GeodeticCRSGeoKey*, or *VerticalGeoKey* has a value of 32767.

#### NOTE

Anyone not interested in constructing a user-defined model CRS can ignore this section.

#### NOTE

It should be noted that the implicit axis order of user-defined CRS definitions is fixed at (lon,lat,height) in case of geographic and (east,north,height) in case of projected regardless of the model space CRS definition. This convention was implicit in GeoTIFF 1.0 and still is valid in this revision. As with GeoTIFF 1.0, it is not possible to express a user-defined CRS that deviates from this axis order convention. The intention is to address this limitation in a future revision.

### 7.5.1. Requirements Class Units GeoKeys

These keys are used to specify Units of Measure (UoM) through the identification of a unit from the GeoTIFF CRS register or to indicate that the unit is user-defined.



The **GeogAngularUnitsGeoKey** key is used to specify the angular unit for:

- the axes in user-defined geographic 2D CRSs;
- the horizontal axes in user-defined geographic 3D CRSs;
- the longitude from the reference meridian in user-defined prime meridians; and
- user-defined map projection parameters that are angles.

The **GeogAzimuthUnitsGeoKey** key is used to specify the angular unit for user-defined map projection parameters when these differ from the angular unit described through the **GeogAngularUnitsGeoKey**.

The **GeogLinearUnitsGeoKey** key is used to specify the linear unit for:

- the axes in user-defined geocentric Cartesian CRSs;
- the height axis of a user-defined geographic 3D CRS; and
- for user-defined ellipsoid axes.

The **ProjLinearUnitsGeoKey** key is used to specify the linear units for:

- the axes of a user-defined projected CRS; and
- map projection parameters that are lengths.

The **VerticalUnitsGeoKey** key is used to specify the linear unit for:

- the axis of a user-defined vertical CRS.

#### Requirements Class 16.0: UnitsGeoKey

<http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey>

Requirement 16.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.ID</a> <i>The GeogAngularUnitsGeoKey SHALL have ID = 2054</i>  <i>The GeogAzimuthUnitsGeoKey SHALL have ID = 2060</i>  <i>The GeogLinearUnitsGeoKey SHALL have ID = 2052</i>  <i>The ProjLinearUnitsGeoKey SHALL have ID = 3076</i>  <i>The VerticalUnitsGeoKey SHALL have ID = 4099</i>
Requirement 16.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.type</a> <i>The GeogAngularUnitsGeoKey, the GeogAzimuthUnitsGeoKey, the GeogLinearUnitsGeoKey, the ProjLinearUnitsGeoKey and the VerticalUnitsGeoKey SHALL each have type = SHORT</i>

Requirement 16.3	<p><a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.reserved">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.reserved</a>  <i>GeogAngularUnitsGeoKey, GeogAzimuthUnitsGeoKey, GeogLinearUnitsGeoKey, ProjLinearUnitsGeoKey and VerticalUnitsGeoKey values in the range 1-1023 SHALL be reserved.</i></p> <p>NOTE: In GeoTIFF v1.0 the range 0001-2000 was used for obsolete GeoTIFF codes.</p>
Requirement 16.4	<p><a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.angular">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.angular</a>  <i>GeogAngularUnitsGeoKey and GeogAzimuthUnitsGeoKey values in the range 1024-32766 SHALL be EPSG Unit Of Measure (UOM) codes with type = angle.</i></p> <p>NOTE: In GeoTIFF v1.0 the range was 9100-9199</p>
Requirement 16.5	<p><a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.linear">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.linear</a>  <i>GeogLinearUnitsGeoKey, ProjLinearUnitsGeoKey and VerticalUnitsGeoKey values in the range 1024-32766 SHALL be EPSG Unit Of Measure (UOM) codes with type = length.</i></p> <p>NOTE: In GeoTIFF v1.0 the range was 9000-9099. Several values in this range have been deprecated or deleted from the EPSG Dataset and should no longer be used. See <a href="#">Table G.3 - Deprecated and deleted EPSG Unit of Measure codes</a></p>
Requirement 16.6	<p><a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.userdefinedAngular">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.userdefinedAngular</a>  <i>A GeogAngularUnitsGeoKey or a GeogAzimuthUnitsGeoKey value of 32767 SHALL be a user-defined angular unit. If the value is 32767 (User-Defined) then the GeodeticCitationGeoKey and the GeogAngularUnitSizeGeoKey SHALL be populated</i></p>
Requirement 16.7	<p><a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.userdefinedGeogLinear">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.userdefinedGeogLinear</a>  <i>A GeogLinearUnitsGeoKey value of 32767 SHALL be a user-defined linear unit. If the value is 32767 (User-Defined) then the GeodeticCitationGeoKey and the GeogLinearUnitSizeGeoKey SHALL be populated</i></p>
Requirement 16.8	<p><a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.userdefinedProjLinear">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.userdefinedProjLinear</a>  <i>A ProjLinearUnitsGeoKey value of 32767 SHALL be a user-defined linear unit. If the value is 32767 (User-Defined) then the ProjectedCitationGeoKey and the ProjLinearUnitSizeGeoKey SHALL be populated.</i></p>



Requirement 16.9	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.userdefinedVertical">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.userdefinedVertical</a> <i>A VerticalUnitsGeoKey value of 32767 (user defined) SHALL not be used</i>  NOTE: The rationale for this is that it would require a VerticalUnitSizeGeoKey, which does not exist in GeoTIFF 1.0. For vertical units, this document supports only EPSG linear units.
Requirement 16.10	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.private">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey.private</a> <i>GeogAngularUnitsGeoKey, GeogAzimuthUnitsGeoKey, GeogLinearUnitsGeoKey, ProjLinearUnitsGeoKey and VerticalUnitsGeoKey values in the range 32768-65535 SHALL be private.</i>

### 7.5.2. Requirements Class Unit Size GeoKeys

These keys allow the definition of size of user-defined angular and linear units, given in the SI base unit for that unit type (meters for length, radians for angle).

Note: this specification does not support user-defined units for vertical coordinate reference systems.

Requirements Class 17.0: UnitSizeGeoKey	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitSizeGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitSizeGeoKey</a>	
Requirement 17.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitSizeGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitSizeGeoKey.ID</a> <i>The GeogAngularUnitSizeGeoKey SHALL have ID = 2055</i>  <i>The GeogLinearUnitSizeGeoKey SHALL have ID = 2053</i>  <i>The ProjLinearUnitSizeGeoKey SHALL have ID = 3077</i>
Requirement 17.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitSizeGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitSizeGeoKey.type</a> <i>The GeogAngularUnitSizeGeoKey, GeogLinearUnitSizeGeoKey and ProjLinearUnitSizeGeoKey SHALL each have type = DOUBLE</i>
Requirement 17.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitSizeGeoKey.units">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitSizeGeoKey.units</a> <i>The units of the GeogAngularUnitSizeGeoKey value SHALL be radians.</i>  <i>The units of the GeogLinearUnitSizeGeoKey value SHALL be meters.</i>  <i>The units of the ProjLinearUnitSizeGeoKey value SHALL be meters.</i>

### 7.5.3. Geodetic Datum

#### Requirements Class GeodeticDatumGeoKey

This key is used to specify a geodetic datum from the GeoTIFF CRS register, or to indicate that the geodetic datum or one or both of its component ellipsoid or prime meridian is user-defined.

**NOTE** In GeoTIFF 1.0 this key was called GeogGeodeticDatumGeoKey.

Requirements Class 18.0: GeodeticDatumGeoKey	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey</a>	
Requirement 18.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey.ID</a> <i>The GeodeticDatumGeoKey SHALL have ID = 2050</i>
Requirement 18.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey.type</a> <i>The GeodeticDatumGeoKey SHALL have type = SHORT</i>
Requirement 18.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey.reserved">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey.reserved</a> <i>GeodeticDatumGeoKey values in the range 1-1023 SHALL be reserved.</i>  NOTE: In GeoTIFF v1.0 the reserved ranges were 1001-5999 and 7000-32766.
Requirement 18.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey.EPSG">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey.EPSG</a> <i>GeodeticDatumGeoKey values in the range 1024-32766 SHALL be EPSG geodetic datum codes.</i>  NOTE: In GeoTIFF v1.0 the range was 6000-6999. Several values in this range have been deprecated or deleted from the EPSG Dataset and should no longer be used. See <a href="#">Table G.4 - Deprecated and deleted EPSG geodetic datum codes</a>
Requirement 18.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey.userdefined">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey.userdefined</a> <i>If the GeodeticDatumGeoKey value is 32767 (User-Defined) then the GeodeticCitationGeoKey, PrimeMeridianGeoKey and EllipsoidGeoKey SHALL be populated.</i>
Requirement 18.6	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey.private">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey.private</a> <i>GeodeticDatumGeoKey values in the range 32768-65535 SHALL be private</i>

## Requirements Class PrimeMeridianGeoKey

This key is used to specify a Prime Meridian from the GeoTIFF CRS register or to indicate that the Prime Meridian is user-defined. The default is Greenwich, England.

**NOTE** In GeoTIFF 1.0 this key was called GeogPrimeMeridianGeoKey.

Requirements Class 19.0: PrimeMeridianGeoKey	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey</a>	

Requirement 19.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey.ID</a> <i>The PrimeMeridianGeoKey SHALL have ID = 2051</i>
Requirement 19.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey.type</a> <i>The PrimeMeridianGeoKey SHALL have type = SHORT</i>
Requirement 19.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey.reserved">http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey.reserved</a> <i>PrimeMeridianGeoKey values in the range 1-1023 SHALL be reserved</i>  NOTE: In GeoTIFF v1.0 the range was 101-7999 and 9000-32766
Requirement 19.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey.EPSG">http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey.EPSG</a> <i>PrimeMeridianGeoKey values in the range 1024-32766 SHALL be EPSG Prime Meridian Codes</i>  NOTE: In GeoTIFF v1.0 the range was 8000-8999
Requirement 19.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey.userdefined">http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey.userdefined</a> <i>If the PrimeMeridianGeoKey value is 32767 (User-Defined) then the GeodeticCitationGeoKey, and PrimeMeridianLongGeoKey SHALL be populated</i>
Requirement 19.6	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey.private">http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey.private</a> <i>PrimeMeridianGeoKey values in the range 32768-65535 SHALL be private</i>

## Requirements Class PrimeMeridianLongitudeGeoKey

This key allows definition of a user-defined Prime Meridian, the location of which is defined by its longitude relative to the international reference meridian (for the earth this is Greenwich).

**NOTE** In GeoTIFF 1.0 this key was called GeogPrimeMeridianLongGeoKey.

Requirements Class 20.0: PrimeMeridianLongitudeGeoKey	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianLongitudeGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianLongitudeGeoKey</a>	
Requirement 20.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianLongitudeGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianLongitudeGeoKey.ID</a> <i>The PrimeMeridianLongitudeGeoKey SHALL have ID = 2061</i>
Requirement 20.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianLongitudeGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianLongitudeGeoKey.type</a> <i>The PrimeMeridianLongitudeGeoKey SHALL have type = DOUBLE</i>

Requirement 20.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianLongitudeGeoKey.units">http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianLongitudeGeoKey.units</a> <i>The unit for the PrimeMeridianLongitudeGeoKey value SHALL be GeogAngularUnits</i>
------------------	---

## Requirements Class EllipsoidGeoKey

This key is provided to specify an ellipsoid (or sphere) from the GeoTIFF CRS register or to indicate that the ellipsoid (or sphere) is user-defined.

**NOTE** In GeoTIFF 1.0 this key was called GeogEllipsoidGeoKey.

Requirements Class 21.0: EllipsoidGeoKey	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey</a>	
Requirement 21.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey.ID</a> <i>The EllipsoidGeoKey SHALL have ID = 2056</i>
Requirement 21.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey.type</a> <i>The EllipsoidGeoKey SHALL have type = SHORT</i>
Requirement 21.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey.reserved">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey.reserved</a> <i>EllipsoidGeoKey values in the range 1-1023 SHALL be reserved</i>
Requirement 21.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey.EPSG">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey.EPSG</a> <i>EllipsoidGeoKey values in the range 1024-32766 SHALL be EPSG ellipsoid Codes</i>  NOTE: In GeoTIFF v1.0 the range was 7000-7999. Several values in this range have been deprecated or deleted from the EPSG Dataset and should no longer be used. See <a href="#">Table G.5 - Deprecated and deleted EPSG ellipsoid codes</a>
Requirement 21.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey.user-defined">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey.user-defined</a> <i>If the EllipsoidGeoKey value is 32767 (User-Defined) then the GTCitationGeoKey and the EllipsoidSemiMajorAxisGeoKey SHALL be populated together with the one of either the EllipsoidSemiMinorAxisGeoKey or the EllipsoidInvFlatteningGeoKey.</i>
Requirement 21.6	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey.private">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey.private</a> <i>EllipsoidGeoKey values in the range 32768-65535 SHALL be private</i>

## Requirements Class Ellipsoid parameter GeoKeys

These keys are used to specify the size and shape of a user-defined ellipsoid or sphere used as the model of the earth. Only bi-axial ellipsoids and spheres are catered for. An ellipsoid is defined through two parameters,

its semi-major axis ( $a$ )

and either its semi-minor axis ( $b$ ) or its inverse flattening ( $1/f$ ) where  $1/f = a/(a - b)$ .

If the model is a sphere,  $1/f$  is infinite so  $a$  and  $b$  must be used, with the value of  $b$  set to that of  $a$ .

### Requirements Class EllipsoidSemiMajorAxisGeoKey

This key is provided to specify the first defining parameter of a user-defined bi-axial ellipsoid or a user-defined sphere. It allows the specification of the ellipsoid semi-major axis ( $a$ ) or the sphere's radius.

**NOTE** In GeoTIFF 1.0 this key was called GeogSemiMajorAxisGeoKey.

Requirements Class 22.0: EllipsoidSemiMajorAxisGeoKey	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMajorAxisGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMajorAxisGeoKey</a>	
Requirement 22.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMajorAxisGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMajorAxisGeoKey.ID</a> <i>The EllipsoidSemiMajorAxisGeoKey SHALL have ID = 2057</i>
Requirement 22.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMajorAxisGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMajorAxisGeoKey.type</a> <i>The EllipsoidSemiMajorAxisGeoKey SHALL have type = DOUBLE</i>
Requirement 22.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMajorAxisGeoKey.units">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMajorAxisGeoKey.units</a> <i>The units of the EllipsoidSemiMajorAxisGeoKey SHALL be defined by the value of GeogLinearUnitsGeoKey</i>

### Requirements Class EllipsoidSemiMinorAxisGeoKey

This key is provided to specify the second defining parameter of a user-defined bi-axial ellipsoid or of a user-defined sphere. It allows the specification of the ellipsoid semi-minor axis ( $b$ ) or the sphere's radius.

**NOTE** In GeoTIFF 1.0 this key was called GeogSemiMinorAxisGeoKey.

Requirements Class 23.0: EllipsoidSemiMinorAxisGeoKey	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMinorAxisGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMinorAxisGeoKey</a>	
Requirement 23.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMinorAxisGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMinorAxisGeoKey.ID</a> <i>The EllipsoidSemiMinorAxisGeoKey SHALL have ID = 2058</i>
Requirement 23.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMinorAxisGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMinorAxisGeoKey.type</a> <i>The EllipsoidSemiMinorAxisGeoKey SHALL have type = DOUBLE</i>
Requirement 23.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMinorAxisGeoKey.units">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMinorAxisGeoKey.units</a> <i>The units of the EllipsoidSemiMinorAxisGeoKey SHALL be defined by the value of GeogLinearUnitsGeoKey</i>

## EllipsoidInvFlatteningGeoKey

This key is provided to specify the second defining parameter of a user-defined bi-axial ellipsoid. It allows the specification of the ellipsoid inverse flattening ( $1/f$ ). It is a ratio and does not require a unit.

**NOTE** In GeoTIFF 1.0 this key was called GeogInvFlatteningGeoKey.

### Requirements Class 24.0: EllipsoidInvFlatteningGeoKey

<http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidInvFlatteningGeoKey>

Requirement 24.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidInvFlatteningGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidInvFlatteningGeoKey.ID</a> <i>The EllipsoidInvFlatteningGeoKey SHALL have ID = 2059</i>
Requirement 24.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidInvFlatteningGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidInvFlatteningGeoKey.type</a> <i>The EllipsoidInvFlatteningGeoKey SHALL have type = DOUBLE</i>

## 7.5.4. Requirements Class Vertical Datum

This key may be used to specify the vertical datum for a user-defined vertical coordinate reference system.

### Requirements Class 25.0: VerticalDatumGeoKey

<http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey>

Requirement 25.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey.ID</a> <i>The VerticalDatumGeoKey SHALL have ID = 4098</i>
Requirement 25.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey.type</a> <i>The VerticalDatumGeoKey SHALL have type = SHORT</i>
Requirement 25.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey.reserved">http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey.reserved</a> <i>VerticalDatumGeoKey values in the range 1-1023 SHALL be reserved</i>  NOTE: In GeoTIFF v1.0 the reserved range was 16384-32766.
Requirement 25.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey.EPSG">http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey.EPSG</a> <i>VerticalDatumGeoKey values in the range 1024-32766 SHALL be EPSG vertical datum codes</i>  NOTE: In GeoTIFF v1.0 the range was given as 1-16383 but without reference to EPSG.

Requirement 25.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey.userdefined">http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey.userdefined</a> <i>If the VerticalDatumGeoKey value is 32767 (User-Defined) then the VerticalCitationGeoKey SHALL be populated.</i>
Requirement 25.6	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey.private">http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey.private</a> <i>VerticalDatumGeoKey values in the range 32768-65535 SHALL be private</i>

### 7.5.5. Map Projection GeoKeys

#### Requirements Class ProjectionGeoKey

The *ProjectionGeoKey* key is used to specify a map projection from the GeoTIFF CRS register or to indicate that the map projection is user-defined. In the EPSG Dataset a map projection is a coordinate conversion, a subtype of coordinate operation.

Requirements Class 26.0: ProjectionGeoKey	
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey</a>	
Requirement 26.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.ID</a> <i>The ProjectionGeoKey SHALL have ID = 3074</i>
Requirement 26.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.type</a> <i>The ProjectionGeoKey SHALL have type = SHORT</i>
Requirement 26.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.reserved">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.reserved</a> <i>ProjectionGeoKey values in the range 1-1023 SHALL be reserved</i>
Requirement 26.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.EPSG">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.EPSG</a> <i>ProjectionGeoKey values in the range 1024-32766 SHALL be valid EPSG map projection (coordinate operation) codes</i>  NOTE: In GeoTIFF v1.0 the range was 10000-19999. Several values in this range have been deprecated or deleted from the EPSG Dataset. See <a href="#">Table G.6 - Deprecated and deleted EPSG Map projection codes</a>
Requirement 26.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.userdefined">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.userdefined</a> <i>If the ProjectionGeoKey value is 32767 (User-Defined) then the ProjectedCitationGeoKey, ProjectionMethodGeoKey, and ProjLinearUnitsGeoKey SHALL be populated</i>
Requirement 26.6	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.private">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.private</a> <i>ProjectionGeoKey values in the range 32768-65535 SHALL be private</i>

#### Requirements Class ProjMethodGeoKey (coordinate operation method)

The *ProjMethodGeoKey* key is used to specify a map projection method from the GeoTIFF v1.0 coordinate transformation code list (Annex C) or to indicate that the map projection method is user-



defined.

**NOTE** In GeoTIFF 1.0 this key was called ProjCoordTransGeoKey.

**NOTE** GeoTIFF v1.0 did not make reference to the EPSG coordinate operation methods (a future version of GeoTIFF might do this).

#### Requirements Class 27.0: ProjMethodGeoKey

<http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey>

Requirement 27.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey.ID</a> <i>The ProjMethodGeoKey SHALL have ID = 3075</i>
------------------	---

Requirement 27.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey.type</a> <i>The ProjMethodGeoKey SHALL have type = SHORT</i>
------------------	--

Requirement 27.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey.transform">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey.transform</a> <i>ProjMethodGeoKey values in the range 1-27 SHALL be GeoTIFF map projection method codes</i>  NOTE: See Annex C
------------------	---

Requirement 27.4	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey.reserved">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey.reserved</a> <i>ProjMethodGeoKey values in the range 28-32766 SHALL be reserved</i>
------------------	---

Requirement 27.5	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey.userdefined">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey.userdefined</a> <i>If the ProjectionMethodGeoKey value is 32767 (User-Defined) then the ProjectedCitationGeoKey and keys for each map projection parameter (coordinate operation parameter) appropriate to that method SHALL be populated.</i>
------------------	---

Requirement 27.6	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey.private">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey.private</a> <i>ProjMethodGeoKey values in the range 32768-65535 SHALL be private</i>
------------------	---

#### Map Projection parameters (coordinate operation parameters)

Each map projection method requires several map projection parameters (coordinate operation parameters). GeoTIFF v1.0 did not specify which parameters should be associated with which methods, nor make reference to the EPSG coordinate operation parameters associated with each method (a future version of GeoTIFF might do this).

#### Requirements Class 28.0: ProjAngularParameters

<http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAngularParameters>



Requirement 28.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAngularParameters.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAngularParameters.ID</a> <i>The ProjStdParallel1GeoKey SHALL have ID = 3078</i>  <i>The ProjStdParallel2GeoKey SHALL have ID = 3079</i>  <i>The ProjNatOriginLongGeoKey SHALL have ID = 3080</i>  <i>The ProjNatOriginLatGeoKey SHALL have ID = 3081</i>  <i>The ProjFalseOriginLongGeoKey SHALL have ID = 3084</i>  <i>The ProjFalseOriginLatGeoKey SHALL have ID = 3085</i>  <i>The ProjCenterLongGeoKey SHALL have ID = 3088</i>  <i>The ProjCenterLatGeoKey SHALL have ID = 3089</i>  <i>The ProjStraightVertPoleLongGeoKey SHALL have ID = 3095</i>
Requirement 28.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAngularParameters.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAngularParameters.type</a> <i>The ProjAngularParameters SHALL have type = DOUBLE</i>
Requirement 28.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAngularParameters.units">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAngularParameters.units</a> <i>All parameters in this requirements class SHALL have units as specified by the GeogAngularUnitsGeoKey</i>

#### Requirements Class 29.0: ProjAzimuthAngleGeoKey

<http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAzimuthAngleGeoKey>

Requirement 29.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAzimuthAngleGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAzimuthAngleGeoKey.ID</a> <i>The ProjAzimuthAngleGeoKey SHALL have ID = 3094</i>
Requirement 29.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAzimuthAngleGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAzimuthAngleGeoKey.type</a> <i>The ProjAzimuthAngleGeoKey SHALL have type = DOUBLE</i>
Requirement 29.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAzimuthAngleGeoKey.units">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAzimuthAngleGeoKey.units</a> <i>The ProjAzimuthAngleGeoKey SHALL have units as specified by the GeogAzimuthUnitsGeoKey</i>

#### Requirements Class 30.0: ProjLinearParameters

<http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjLinearParameters>

Requirement 30.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjLinearParameters.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjLinearParameters.ID</a> <i>The ProjFalseEastingGeoKey SHALL have ID = 3082</i>  <i>The ProjFalseNorthingGeoKey SHALL have ID = 3083</i>  <i>The ProjFalseOriginEastingGeoKey SHALL have ID = 3086</i>  <i>The ProjFalseOriginNorthingGeoKey SHALL have ID = 3087</i>  <i>The ProjCenterEastingGeoKey SHALL have ID = 3090</i>  <i>The ProjCenterNorthingGeoKey SHALL have ID = 3091</i>
Requirement 30.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjLinearParameters.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjLinearParameters.type</a> <i>All parameters in this requirements class SHALL have type = DOUBLE</i>
Requirement 30.3	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjLinearParameters.units">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjLinearParameters.units</a> <i>All parameters in this requirements class SHALL have units as specified by the ProjLinearUnitsGeoKey</i>

#### Requirements Class 31.0: ProjScalarParameters

<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjScalarParameters">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjScalarParameters</a>	
Requirement 31.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjScalarParameters.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjScalarParameters.ID</a> <i>The ProjScaleAtNatOriginGeoKey SHALL have ID = 3092</i>  <i>The ProjScaleAtCenterGeoKey SHALL have ID = 3093</i>
Requirement 31.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjScalarParameters.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjScalarParameters.type</a> <i>All parameters in this requirements class SHALL have type = DOUBLE</i>

## 7.6. Requirements for dynamic CRS

In a dynamic CRS, coordinates of a point on the surface of the Earth may change with time. To be unambiguous the coordinates must always be qualified with the epoch at which they are valid.

The date at which coordinates are referenced to a dynamic coordinate reference system is expressed as a decimal year in the Gregorian calendar, and stored in the *CoordinateEpochGeoKey*. Example: 2017-03-25 in the Gregorian calendar is epoch 2017.23.

#### Requirements Class 32.0: CoordinateEpochGeoKey

<a href="http://www.opengis.net/spec/GeoTIFF/1.2/req/CoordinateEpochGeoKey">http://www.opengis.net/spec/GeoTIFF/1.2/req/CoordinateEpochGeoKey</a>	
Requirement 32.1	<a href="http://www.opengis.net/spec/GeoTIFF/1.2/req/CoordinateEpochGeoKey.ID">http://www.opengis.net/spec/GeoTIFF/1.2/req/CoordinateEpochGeoKey.ID</a> <i>The CoordinateEpochGeoKey SHALL have ID = 5120</i>

Requirement 32.2	<a href="http://www.opengis.net/spec/GeoTIFF/1.2/req/CoordinateEpochGeoKey.type">http://www.opengis.net/spec/GeoTIFF/1.2/req/CoordinateEpochGeoKey.type</a> <i>The CoordinateEpochGeoKey SHALL have type = DOUBLE</i>
---------------------	--

# Chapter 8. Media Types for GeoTIFF data encoding

A GeoTIFF file is a TIFF file. It is common to use the tiff MIME type, image/tiff according to [RFC3302] (see also <http://www.iana.org/assignments/media-types/media-types.xhtml#image>).

OGC GMLCOV GeoTIFF extension (OGC 12-100r1) specifies image/tiff as the MIME identifier (cf. Requirement #5 in OGC 12-100r1).

The recommendation for the MIME type is to use the image/tiff application parameter, with the geotiff value, therefore as follows: image/tiff; application=geotiff.

# Annex A: Abstract Test Suite (Normative)

## A.1. General Approach

This GeoTIFF standard specifies an encoding of information for exchange between software components. As such, this Abstract Test Suite can only validate the conformance of a specific GeoTIFF document. In most cases, GeoTIFF conformance will be incorporated into the conformance testing of a software component. These components fall into two categories; GeoTIFF readers and GeoTIFF writers.

Conformance of GeoTIFF readers will be validated by the successful processing of a set of representative samples of validated GeoTIFF files.

Conformance of GeoTIFF writers will be validated by the successful validation of a set of representative samples of GeoTIFF files generated by that software component.

## A.2. Conformance Class TIFF

<http://www.opengis.net/spec/GeoTIFF/1.1/conf/Core>

### A.2.1. TIFF Core Test

**Test id:** <http://www.opengis.net/spec/GeoTIFF/1.1/conf/Core>

**Requirements:**

<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/TIFF">http://www.opengis.net/spec/GeoTIFF/1.1/req/TIFF</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ByteOrder">http://www.opengis.net/spec/GeoTIFF/1.1/req/ByteOrder</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/DataTypes">http://www.opengis.net/spec/GeoTIFF/1.1/req/DataTypes</a>

**Purpose:** Verify that the GeoTIFF file conforms to the TIFF specification.

**Pre-conditions:** None

**Test Variables:** None

**Test Process:**

There is no authoritative conformance test for TIFF 6.0. 2 basic tests may be done on TIFF header (4 first bytes), called TIFF magic: • Bytes 0-1 (byte order within the file) = 0X4949 ("II" = little endian) or 0X4D4D ("MM" = big endian). • Bytes 2-3 = the short integer value 42 interpreted using the byte order specified in bytes 0-1.

The best that can be achieved is to use a TIFF reference implementation to successfully read a GeoTIFF file. The OGC recommends the use of tiffdump based on the open source LibTIFF library (<https://gitlab.com/libtiff/libtiff>) for dumping the content of TIFF tags (displaying error messages if any), or opensource TIFF file validator (such as the JHOVE tool, opensource developed in Java - cf. <http://jhove.openpreservation.org/>).

Once TIFF 6.0 conformance has been validated, execute test <http://www.opengis.net/spec/GeoTIFF/1.1/conf/TIFF.Tags>.

## A.2.2. TIFF Tags Test

**Test id:** <http://www.opengis.net/spec/GeoTIFF/1.1/conf/TIFF.Tags>

**Requirements:**

<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/TIFF">http://www.opengis.net/spec/GeoTIFF/1.1/req/TIFF</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/DataGeoTags">http://www.opengis.net/spec/GeoTIFF/1.1/req/DataGeoTags</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ByteOrder">http://www.opengis.net/spec/GeoTIFF/1.1/req/ByteOrder</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/TagSort">http://www.opengis.net/spec/GeoTIFF/1.1/req/TagSort</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.ID</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.type</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.count">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.count</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag.ID</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag.count">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag.count</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.ID</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.type</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTransformationTag.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTransformationTag.ID</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTransformationTag.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTransformationTag.type</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.ID</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.type</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTiepointTag.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTiepointTag.ID</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTiepointTag.type">http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTiepointTag.type</a>

**Purpose:** Verify the TIFF header and prepare for processing the GeoTIFF tags.

**Pre-conditions:** None

**Test Variables:**

Variable	Scope	Description
IFD_Offset	Local	Location within the TIFF file of an IFD
GeoKeyDirectory	Global	Location of the GeoTIFF GeoKey directory
ASCIIValues	Global	Location of the ASCII values for GeoTIFF ASCII GeoKeys
DoubleValues	Global	Location of the Double values for GeoTIFF Double GeoKeys
TransformTag	Local	Location of the Model Transform Tag

PixelScaleTag	Local	Location of the ModelPixelScale Tag
TiepointTag	Local	Location of the ModelTiepoint Tag
TagLength	Parameter	Length of the value of a TIFF Tag
TagValue	Parameter	Location of the value of a TIFF tag in the GeoTIFF file

### Test Process:

Validate and process the TIFF header

- Verify that Bytes 0-1 = 0X4949 ("II" = little endian) or 0X4D4D ("MM" = big endian).
- Verify that Bytes 2-3 = the short integer value 42 interpreted using the byte order specified in bytes 0-1.
- Bytes 4-7 are the offset to the first Image File Directory. Save this value as IFD\_Offset.

Process each IFD using the following pseudocode:

```

WHILE IFD_Offset is not 0, process this IFD
{
  Bytes 0-1 contain the number of IFD entries in this IFD.
  DO FOR each IFD entry (processed in sequence)
  {
    Bytes 0-1 contain the TIFF tag value.
    Verify that the new tag value is greater than the previous tag value.
    IF value = 34735 THEN
      {
        Validate that Bytes 2-3 = 3 (Short Integer)
        Validate that Bytes 4-7 represent an Integer value greater than or equal to
4      Set GeoKeyDirectory to the value in Bytes 8-11
      }
    IF value = 34736 THEN
      {
        Validate that Bytes 2-3 = 12 (Double)
        Set DoubleValues to the value in Bytes 8-11
      }
    IF value = 34737 THEN
      {
        Validate that Bytes 2-3 = 2 (ASCII)
        Set ASCIIValues to the value in Bytes 8-11
      }
    IF value = 33550 (ModelPixelScaleTag) THEN
      {
        Set PixelScaleTag to the location of this IFD entry in the GeoTIFF file
      }
    IF value = 33922 (ModelTiepointTag) THEN
      {
        Set TiepointTag to the location of this IFD entry in the GeoTIFF file
      }
  }
}

```

```

    IF value = 34264 (ModelTransformationTag) THEN
        {
            Set TransformTag to the location of this IFD entry in the GeoTIFF file
        }
    }
    IF GeoKeyDirectory has been set THEN
        {
            execute test http://www.opengis.net/spec/GeoTIFF/1.1/conf/GeoKeyDirectory
            Validate that there is a GTModelType GeoKey in the GeoKey Directory
        }
        ELSE Throw an error.
    IF PixelScaleTag has been set THEN
        {
            Validate that Bytes 2-3 = 12 (Double)
            Set TagLength to the value in Bytes 4-7
            Set TagValue to the value in Bytes 8-11
            Validate that this IFD contains a ModelTiepointTag
            Execute test
http://www.opengis.net/spec/GeoTIFF/1.1/conf/Raster2Model\_CoordinateTransformation\_GeoKey/ModelPixelScaleTag
        }
        IF TiepointTag has been set THEN
            {
                Validate that Bytes 2-3 = 12 (Double)
                Set TagLength to the value in Bytes 4-7
                Set TagValue to the value in Bytes 8-11
                Execute test
http://www.opengis.net/spec/GeoTIFF/1.1/conf/Raster2Model\_CoordinateTransformation\_GeoKey/ModelTiepointTag
            }
        IF TransformTag has been set THEN
            {
                Validate that Bytes 2-3 = 12 (Double)
                Set TagLength to the value in Bytes 4-7
                Set TagValue to the value in Bytes 8-11
                Validate that this IFD does not contain a ModelPixelScaleTag
                Execute test
http://www.opengis.net/spec/GeoTIFF/1.1/conf/Raster2Model\_CoordinateTransformation\_GeoKey/ModelTransformationTag
            }
            Validate that this IFD contains either a ModelTransformationTag or a
            ModelTiepointTag.
            IFD_Offset = the last four bytes of the current IFD
        }

```

### A.2.3. GeoKey Directory Test

**Test id:** <http://www.opengis.net/spec/GeoTIFF/1.1/conf/GeoKeyDirectory>

**Requirements:**



<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyDirectoryVersion">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyDirectoryVersion</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyDirectoryVersionValue">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyDirectoryVersionValue</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyRevision">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyRevision</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyRevisionValue">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyRevisionValue</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.minorRevision">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.minorRevision</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.minorRevisionValue">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.minorRevisionValue</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.numberOfKeys">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.numberOfKeys</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntrySetCount">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntrySetCount</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntry">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntry</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryKeyID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryKeyID</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryTIFFTagLocation">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryTIFFTagLocation</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeySort">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeySort</a>

**Purpose:** Verify the GeoKey Directory

**Pre-conditions** A GeoKey Directory has been located

**Test Variables:**

Variable	Scope	Description
IFD_Offset	Local	Location within the TIFF file of an IFD
GeoKeyDirectory	Global	Location of the GeoTIFF GeoKey directory
ASCIIValues	Global	Location of the ASCII values for GeoTIFF ASCII GeoKeys
DoubleValues	Global	Location of the Double values for GeoTIFF Double GeoKeys
GeoKeyOffset	Parameter	Location of this GeoKey in the GeoKey directory
KeySetCount	Local	The number of entries in the GeoKey directory

**Test Process:**

1. Validate and process the GeoKey Directory Header
  - Verify that Bytes 0-1 = 1 (Key Directory Version).
  - Verify that Bytes 2-3 = 1 (Key Revision)
  - Verify that Bytes 4-5 = 0 or 1 (Key Minor Revision)
  - Bytes 6-7 contain the number of Key Entry Sets in this directory. Set KeySetCount to this value.
2. Process each Key Entry Set using the following pseudocode:

```

SET GeoKeyOffset = 8
WHILE KeySetCount is not 0
{
    Verify that the GeoKey (first Short integer) is greater than the previous
    GeoKey.
    Process the second Short integer in the Key Entry Set
    {
        IF value = 0 THEN Execute test
http://www.opengis.net/spec/GeoTIFF/1.1/conf/Short\_Param passing GeoKeyOffset as a
        parameter
        IF value = 34735 THEN Execute test
http://www.opengis.net/spec/GeoTIFF/1.1/conf/Short\_Param passing GeoKeyOffset as a
        parameter
        IF value = 34736 THEN Execute test
http://www.opengis.net/spec/GeoTIFF/1.1/conf/Double\_Param passing GeoKeyOffset as a
        parameter
        IF value = 34737 THEN Execute test
http://www.opengis.net/spec/GeoTIFF/1.1/conf/ASCII\_Param passing GeoKeyOffset as a
        parameter
    }
    SET GeoKeyOffset = GeoKeyOffset + 8
    KeySetCount = KeySetCount - 1
}

```

3. Validate that the number of Key Sets processed equal the number specified in the header.

#### A.2.4. Short Parameters Test

**Test id:** <http://www.opengis.net/spec/GeoTIFF/1.1/conf/ShortParameters>

##### Requirements:

<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.KeyEntry.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.KeyEntry.ID</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryTIFFTagLocation">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryTIFFTagLocation</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryKeyCount">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryKeyCount</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryValueOffset">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryValueOffset</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoShortParams.Criteria">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoShortParams.Criteria</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoShortParams.Location">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoShortParams.Location</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTModelTypeGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/GTRasterTypeGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticDatumGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitsGeoKey</a>

<http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidGeoKey>

<http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectedCRSGeoKey>

<http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey>

<http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjMethodGeoKey>

<http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalGeoKey>

<http://www.opengis.net/spec/GeoTIFF/1.1/req/VerticalDatumGeoKey>

**Purpose:** Verify Short parameters

**Pre-conditions** The GeoKeyDirectory and GeoKeyOffset values have been set **Test Variables:**

Variable	Scope	Description
GeoKeyDirectory	Global	Location of the GeoTIFF GeoKey directory
GeoKeyOffset	Parameter	Location of this Key Entry Set in the GeoKey directory
GeoKey	Local	Temporary value of the GeoKey
KeyLength	Local	Temporary value for the length of the value for the GeoKey
KeyValueOffset	Local	The location of the GeoKey value in the file

**Test Process:**

Locate the Key Entry Set using the GeoKeyDirectory and GeoKeyOffset values.

```

Process the second Short integer in the Key Entry Set
{
  IF value != 0 OR 34735 THEN error out
}
Process the first Short integer in the Key Entry Set
{
  SET GeoKey to the value
}
Process the third Short integer in the Key Entry Set
{
  SET KeyLength to the value
}
IF KeyLength = 1 THEN
  SET KeyValueOffset = GeoKeyDirectory + GeoKeyOffset + 6
ELSE
{
  Process the fourth Short integer in the Key Entry Set
  {
    SET KeyValueOffset to the value
  }
  SET KeyValueOffset = GeoKeyDirectory + (KeyValueOffset * 2)
}

```

Read a KeyLength Short values from the GeoTIFF file starting at KeyValueOffset.  
 Validate the value  
   Locate the GeoKey in the following table  
   Verify that the values read satisfy the constraints defined in the associated Requirements Class.  
   Verify that any GeoKeys required by the associated Requirements Class are present in the GeoKey Directory.

GeoKey	Requirements Class
0	ignore
1024	GTModelTypeGeoKey
1025	GTRasterTypeGeoKey
2048	GeodeticCRSGeoKey
2050	GeodeticDatumGeoKey
2051	PrimeMeridianGeoKey
2052	UnitsGeoKey (Linear Units)
2054	UnitsGeoKey (Angular Units)
2056	EllipsoidGeoKey
2060	UnitsGeoKey (Azimuth Units)
3072	ProjectedCRSGeoKey

GeoKey	Requirements Class
3074	ProjectionGeoKey
3075	ProjMethodGeoKey
3076	UnitsGeoKey (Linear Units)
4096	VerticalGeoKey
4098	VerticalDatumGeoKey
4099	UnitsGeoKey (Vertical Units)

### A.2.5. Double Parameters Test

**Test id:** <http://www.opengis.net/spec/GeoTIFF/1.1/conf/DoubleParameters>

**Requirements:**

<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.KeyEntry.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.KeyEntry.ID</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryTIFFTagLocation">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryTIFFTagLocation</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryKeyCount">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryKeyCount</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryValueOffset">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryValueOffset</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag.ID">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag.ID</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag.count">http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoDoubleParamsTag.count</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianLongitudeGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/PrimeMeridianLongitudeGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitSizeGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/UnitSizeGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMajorAxisGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMajorAxisGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMinorAxisGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidSemiMinorAxisGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidInvFlatteningGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/EllipsoidInvFlatteningGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAngularParameterGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAngularParameterGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjLinearParameterGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjLinearParameterGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjScalarParameterGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjScalarParameterGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAzimuthAngleGeoKey">http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjAzimuthAngleGeoKey</a>
<a href="http://www.opengis.net/spec/GeoTIFF/1.2/req/CoordinateEpochGeoKey">http://www.opengis.net/spec/GeoTIFF/1.2/req/CoordinateEpochGeoKey</a>

**Purpose:** Verify Double parameters

**Pre-conditions** The GeoKeyDirectory, DoubleValues and GeoKeyOffset values have been set.

**Test Variables:**

Variable	Scope	Description
GeoKeyDirectory	Global	Location of the GeoTIFF GeoKey directory

DoubleValues	Global	Location of the Double values for GeoTIFF Double GeoKeys
GeoKeyOffset	Parameter	Location of this Key Entry Set in the GeoKey directory
GeoKey	Local	Temporary value of the GeoKey
KeyLength	Local	Temporary value for the length of the value for the GeoKey
KeyValueOffset	Local	The location of the GeoKey value in the file

### Test Process:

Locate the Key Entry Set using the GeoKeyDirectory and GeoKeyOffset values.

```

Process the second Short integer in the Key Entry Set
{
  IF value != 34736 THEN error out
}
Process the first Short integer in the Key Entry Set
{
  Set GeoKey to the value
}
Process the third Short integer in the Key Entry Set
{
  Set KeyLength to the value
}
Process the fourth Short integer in the Key Entry Set
{
  SET KeyValueOffset to the value
}
SET KeyValueOffset = DoubleValues + (KeyValueOffset * 8)

```

Read a KeyLength Double values from the GeoTIFF file starting at KeyValueOffset.  
 Validate the value  
   Locate the GeoKey in the following table  
   Verify that the values read satisfy the constraints defined in the associated Requirements Class.  
   Verify that any GeoKeys required by the associated Requirements Class are present in the GeoKey Directory.

GeoKey	Requirements Class
0	ignore
2053	UnitSizeGeoKey (Geog Linear)
2055	UnitSizeGeoKey (Geog Angular)
2057	EllipsoidSemiMajorAxisGeoKey
2058	EllipsoidSemiMinorAxisGeoKey

GeoKey	Requirements Class
2059	EllipsoidInvFlatteningGeoKey
2061	PrimeMeridianLongitudeGeoKey
3077	UnitSizeGeoKey (Projected Linear)
3078	ProjAngularParameters (Standard Parallel 1)
3079	ProjAngularParameters (Standard Parallel 2)
3080	ProjAngularParameters (Natural Origin Longitude)
3081	ProjAngularParameters (Natural Origin Latitude)
3082	ProjLinearParameters (False Easting)
3083	ProjLinearParameters (False Northing)
3084	ProjAngularParameters (False Origin Longitude)
3085	ProjAngularParameters (False Origin Latitude)
3086	ProjLinearParameters (False Origin Easting)
3087	ProjLinearParameters (False Origin Northing)
3088	ProjAngularParameters (Center Longitude)
3089	ProjAngularParameters (Center Latitude)
3090	ProjLinearParameters (Projection Center Easting)
3091	ProjLinearParameters (Projection Center Northing)
3092	ProjScalarParameters (Scale at Natural Origin)
3093	ProjScalarParameters (Scale at Center)
3094	ProjAzimuthAngleGeoKey
3095	ProjAngularParameters (Straight Vertical Pole)
5120	CoordinateEpochGeoKey

Double GeoKey Tests

## A.2.6. ASCII Parameters Test

**Test id:** <http://www.opengis.net/spec/GeoTIFF/1.1/conf/AsciiParameters>

**Requirements:**

<http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.KeyEntryKeyID>

<http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryTIFFTagLocation>

<http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryKeyCount>

<http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoKeyDirectoryTag.keyEntryValueOffset>

<http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.ID>

<http://www.opengis.net/spec/GeoTIFF/1.1/req/GeoAsciiParamsTag.count>

<http://www.opengis.net/spec/GeoTIFF/1.1/req/CitationGeoKeys>

**Purpose:** Verify ASCII parameters

**Pre-conditions** The GeoKeyDirectory, ASCIIValues and GeoKeyOffset values have been set.

**Test Variables:**

Variable	Scope	Description
GeoKeyDirectory	Global	Location of the GeoTIFF GeoKey directory
ASCIIValues	Global	Location of the ASCII values for GeoTIFF ASCII GeoKeys
GeoKeyOffset	Parameter	Location of this Key Entry Set in the GeoKey directory
GeoKey	Local	Temporary value of the GeoKey
KeyLength	Local	Temporary value for the length of the value for the GeoKey
KeyValueOffset	Local	The location of the GeoKey value in the file

**Test Process:**

Locate the Key Entry Set using the GeoKeyDirectory and GeoKeyOffset values.

```
Process the second Short integer in the Key Entry Set
{
  IF value != 34737 THEN error out
}
Process the first Short integer in the Key Entry Set
{
  Set GeoKey to the value
}
Process the third Short integer in the Key Entry Set
{
  Set KeyLength to the value
}
Process the fourth Short integer in the Key Entry Set
{
  SET KeyValueOffset to the value
}
SET KeyValueOffset = AsciiValues + KeyValueOffset
```



Read a KeyLength ASCII string values from the GeoTIFF file starting at KeyValueOffset.

- The individual strings are delimited by the "|" character.
- The set of ASCII strings is null terminated.

Validate the value

Locate the GeoKey in the following table

Verify that the values read satisfy the constraints defined in the associated Requirements Class.

Verify that any GeoKeys required by the associated Requirements Class are present in the GeoKey Directory.

GeoKey	Requirements Class
1026	CitationGeoKeys (GTCitationGeoKey)
2049	CitationGeoKeys (GeodeticCitationGeoKey)
3073	CitationGeoKeys (ProjectedCitationGeoKey)
4097	CitationGeoKeys (VerticalCitationGeoKey)

## A.3. Conformance Class

### Raster2Model\_CoordinateTransformation\_GeoKey

[http://www.opengis.net/spec/GeoTIFF/1.1/conf/Raster2Model\\_CoordinateTransformation\\_GeoKey](http://www.opengis.net/spec/GeoTIFF/1.1/conf/Raster2Model_CoordinateTransformation_GeoKey)

#### A.3.1. ModelPixelScaleTag Test

**Test** **id:** [http://www.opengis.net/spec/GeoTIFF/1.1/conf/Raster2Model\\_CoordinateTransformation\\_GeoKey/ModelPixelScaleTag](http://www.opengis.net/spec/GeoTIFF/1.1/conf/Raster2Model_CoordinateTransformation_GeoKey/ModelPixelScaleTag)

**Requirements:**

<http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.standardConvention>

<http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelPixelScaleTag.axisReversal>

**Purpose:** Verify the contents of the ModelPixelScaleTag parameter

**Pre-conditions** The TagLength and TagValue values have been set.

**Test Variables:**

Variable	Scope	Description
TagLength	Parameter	Length of the value of a TIFF Tag
TagValue	Parameter	Location of the value of a TIFF tag in the GeoTIFF file

**Test Process:**

Verify that the TagLength is three (3)

Read three double values from the GeoTIFF file starting at TagValue.

### A.3.2. ModelTiepointTag Test

**Test id:** [http://www.opengis.net/spec/GeoTIFF/1.1/conf/Raster2Model\\_CoordinateTransformation\\_GeoKey/ModelTiepointTag](http://www.opengis.net/spec/GeoTIFF/1.1/conf/Raster2Model_CoordinateTransformation_GeoKey/ModelTiepointTag)

**Requirements:**

<http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTiepointTag.count>

**Purpose:** Verify the contents of the ModelTiepointTag parameter

**Pre-conditions** The TagLength and TagValue values have been set.

**Test Variables:**

Variable	Scope	Description
TagLength	Parameter	Length of the value of a TIFF Tag
TagValue	Parameter	Location of the value of a TIFF tag in the GeoTIFF file

**Test Process:**

Verify that the TagLength is six (6)

Read six double values from the GeoTIFF file starting at TagValue.

### A.3.3. ModelTransformationTag Test

**Test id:** [http://www.opengis.net/spec/GeoTIFF/1.1/conf/Raster2Model\\_CoordinateTransformation\\_GeoKey/ModelTransformationTag](http://www.opengis.net/spec/GeoTIFF/1.1/conf/Raster2Model_CoordinateTransformation_GeoKey/ModelTransformationTag)

**Requirements:**

<http://www.opengis.net/spec/GeoTIFF/1.1/req/ModelTransformationTag.count>

**Purpose:** Verify the contents of the ModelTransformationTag parameter

**Pre-conditions** The TagLength and TagValue values have been set.

**Test Variables:**

Variable	Scope	Description
TagLength	Parameter	Length of the value of a TIFF Tag
TagValue	Parameter	Location of the value of a TIFF tag in the GeoTIFF file

#### Test Process:

Verify that the TagLength is sixteen (16)

Read sixteen double values from the GeoTIFF file starting at TagValue.

# Annex B: GeoTIFF File Structure and GeoTIFF CRS and models principles (Informative)

## B.1. The GeoTIFF File Structure

### B.1.1. Introduction

The GeoTIFF 1.0 specification (Ritter and Ruth, 1995) includes a detailed description of the structural approach used in GeoTIFF and the semantics and values of the tags. The tag specifications are included in Clause 7 of this standard as requirements. This Annex provides an informative overview of the structure of a GeoTIFF file and tags. Much of this information is excerpted from Ritter and Ruth, 1995.

GeoTIFF fully complies with the TIFF 6.0 specifications, and its extensions do not in any way go against the TIFF recommendations, nor do they limit the scope of raster data supported by TIFF.

GeoTIFF uses a small set of reserved TIFF tags to store a broad range of georeferencing information, catering to geodetic as well as projected coordinate reference system needs. No information is stored in private structures, IFD's or other mechanisms that would hide information from naive TIFF reading software.

GeoTIFF uses a "MetaTag" (GeoKey) approach to encode dozens of information elements into just 6 tags, taking advantage of TIFF platform-independent data format representation to avoid cross-platform interchange difficulties. These keys are designed in a manner parallel to standard TIFF tags, and closely follow the TIFF discipline in their structure and layout. New keys may be defined as needs arise, within the current framework, and without requiring the allocation of new tags from Aldus/Adobe.

GeoTIFF uses numerical codes to describe coordinate reference systems, datums, ellipsoids, etc. The codes are derived from the EPSG list compiled by the International Association of Oil and Gas Producers, and mechanisms for adding user-defined systems or their components have been established. The GeoTIFF information content is designed to be compatible with the data decomposition approach used by the National Spatial Data Infrastructure (NSDI) of the U.S. Federal Geographic Data Committee (FGDC).

While GeoTIFF provides a robust framework for specifying a broad class of existing coordinate reference systems, it is also fully extensible, permitting internal, private or proprietary information storage. However, since this standard arose from the need to avoid multiple proprietary encoding systems, use of private implementations is to be discouraged.

### B.1.2. GeoTIFF Design Considerations

Every effort has been made to adhere to the philosophy of TIFF data abstraction. The GeoTIFF tags conform to a hierarchical data structure of tags and keys, similar to the tags which have been implemented in the "basic" and "extended" TIFF tags already supported in TIFF Version 6

specification. The following are some points considered in the design of GeoTIFF.

- Private binary structures, while permitted under the TIFF spec, are in general difficult to maintain, and are intrinsically platform- dependent. Whenever possible, information should be sorted into their intrinsic data-types, and placed into appropriately named tags. Also, implementers of TIFF readers would be more willing to honor a new tag specification if it does not require parsing novel binary structures.
- Any Tag value which is to be used as a "keyword" switch or modifier should be a SHORT type, rather than an ASCII string. This avoids common mistakes of mis-spelling a keyword, as well as facilitating an implementation in code using the "switch/case" features of most languages. In general, scanning ASCII strings for keywords (CaseINSensitive?) is a hazardous (not to mention slower and more complex) operation.
- True "Extensibility" strongly suggests that the Tags defined have a sufficiently abstract definition so that the same tag and its values may be used and interpreted in different ways as more complex information spaces are developed. For example, the old SubFileType tag (255) had to be obsoleted and replaced with a NewSubFileType tag, because images began appearing which could not fit into the narrowly defined classes for that Tag. Conversely, the YCbCrSubsampling Tag has taken on new meaning and importance as the JPEG compression standard for TIFF becomes finalized.

### B.1.3. GeoTIFF Software Requirements

GeoTIFF requires support for all documented TIFF 6.0 tag data-types, and in particular requires the IEEE double-precision floating-point "DOUBLE" type tag. Most of the parameters for georeferencing will not have sufficient accuracy with single-precision IEEE, nor with RATIONAL format storage. The only other alternative for storing high-precision values would be to encode as ASCII, but this does not conform to TIFF recommendations for data encoding.

It is worth emphasizing here that the TIFF spec indicates that TIFF-compliant readers shall honor the 'byte-order' indicator, meaning that 4-byte integers from files created on opposite order machines will be swapped in software, and that 8-byte DOUBLE's will be 8-byte swapped.

A GeoTIFF reader/writer, in addition to supporting the standard TIFF tag types, must also have an additional module which can parse the "Geokey" MetaTag information. A public-domain software package for performing this function is available (libgeotiff), see <https://trac.osgeo.org/geotiff#libgeotiff>.

### B.1.4. GeoTIFF File and "Key" Structure

This section describes the abstract file-format and "GeoKey" data storage mechanism used in GeoTIFF. Uses of this mechanism for implementing georeferencing and geocoding is detailed in sections [Coordinate Transformations](#) and [Geocoding Raster Data](#).

A GeoTIFF file is a TIFF 6.0 file, and inherits the file structure as described in the corresponding portion of the TIFF spec. All GeoTIFF specific information is encoded in several additional reserved TIFF tags, and contains no private Image File Directories (IFD's), binary structures or other private information invisible to standard TIFF readers.

The number and type of parameters that would be required to describe most popular projection types would, if implemented as separate TIFF tags, likely require dozens or even hundred of tags, exhausting the limited resources of the TIFF tag-space. On the other hand, a private IFD, while providing thousands of free tags, is limited in that its tag-values are invisible to non-savvy TIFF readers (which don't know that the IFD\_OFFSET tag value points to a private IFD).



To avoid these problems, a GeoTIFF file stores projection parameters in a set of "Keys" which are virtually identical in function to a "Tag", but has one more level of abstraction above TIFF. Effectively, it is a sort of "Meta-Tag". A Key works with formatted tag-values of a TIFF file the way that a TIFF file deals with the raw bytes of a data file. Like a tag, a Key has an ID number ranging from 0 to 65535, but unlike TIFF tags, all key ID's are available for use in GeoTIFF parameter definitions.

The Keys in GeoTIFF (also call "GeoKeys") are all referenced from the GeoKeyDirectoryTag, which defined as follows (Clause 7.1).

```
GeoKeyDirectoryTag:
  Tag = 34735 (87AF.H)
  Type = SHORT (2-byte unsigned short)
  N = variable, >= 4
  Alias: ProjectionInfoTag, CoordSystemInfoTag
```

This tag may be used to store the GeoKey Directory, which defines and references the "GeoKeys", as described below.

The tag is an array of unsigned SHORT values, which are primarily grouped into blocks of 4. The first 4 values are special, and contain GeoKey directory header information. The header values consist of the following information, in order.

Header={KeyDirectoryVersion, KeyRevision, MinorRevision, NumberOfKeys} where

- *KeyDirectoryVersion* indicates the current version of Key implementation, and will only change if this Tag's Key structure is changed. (Similar to the TIFFVersion (42)). The current DirectoryVersion number is 1. This value will most likely never change, and may be used to ensure that this is a valid Key-implementation.
- *KeyRevision* indicates what revision of Key-Sets are used.
- *MinorRevision* indicates what set of Key-codes are used. The complete revision number is denoted <KeyRevision>.<MinorRevision>.
- *NumberOfKeys* indicates how many Keys are defined by the rest of this Tag.

This header is immediately followed by a collection of <NumberOfKeys> KeyEntry sets, each of which is also 4-SHORTS long. Each KeyEntry is modeled on the "TIFFEntry" format of the TIFF directory header, and is of the form:

- KeyEntry = { KeyID, TIFFTagLocation, Count, ValueOffset } where
- *KeyID* gives the key-ID value of the Key (identical in function to TIFF tag ID, but completely independent of TIFF tag-space).
- *TIFFTagLocation* indicates which TIFF tag contains the value(s) of the Key: if TIFFTagLocation is 0, then the value is SHORT, and is contained in the "ValueOffset" entry. Otherwise, the type (format) of the value is implied by the TIFF-Type of the tag containing the value.
- *Count* indicates the number of values in this key.
- *ValueOffset* indicates the index-offset **into** the TagArray indicated by TIFFTagLocation, if it is nonzero. If TIFFTagLocation=0, then ValueOffset contains the actual (SHORT) value of the Key, and Count=1 is implied. **Note that the offset is not a byte-offset, but rather an index based on the natural data type of the specified tag array.**

Following the KeyEntry definitions, the KeyDirectory tag may also contain additional values. For example, if a Key requires multiple SHORT values, they shall be placed at the end of this tag and the KeyEntry will set TIFFTagLocation=GeoKeyDirectoryTag, with the ValueOffset pointing to the location of the value(s).

All key-values which are not of type SHORT are to be stored in one of the following two tags, based on their format:

```
GeoDoubleParamsTag:  
  Tag = 34736 (87B0.H)  
  Type = DOUBLE (IEEE Double precision)  
  N = variable
```

This tag is used to store all of the DOUBLE valued GeoKeys, referenced by the GeoKeyDirectoryTag. The meaning of any value of this double array is determined from the GeoKeyDirectoryTag reference pointing to it. FLOAT values should first be converted to DOUBLE and stored here.

```
GeoAsciiParamsTag:
  Tag = 34737 (87B1.H)
  Type = ASCII
  N = variable
```

This tag is used to store all of the ASCII valued GeoKeys, referenced by the GeoKeyDirectoryTag. Since keys use offsets into tags, any special comments may be placed at the beginning of this tag. For the most part, the only keys that are ASCII valued are "Citation" keys, giving documentation and references for obscure projections, datums, etc.

Note on ASCII Keys.

Special handling is required for ASCII-valued keys. While it is true that TIFF 6.0 permits multiple NULL-delimited strings within a single ASCII tag, the secondary strings might not appear in the output of naive "tiffdump" programs. For this reason, the null delimiter of each ASCII Key value shall be converted to a "|" (pipe) character before being installed back into the ASCII holding tag, so that a dump of the tag will look like this.

```
AsciiTag="first_value|second_value|etc...last_value|"
```

A GeoTIFF-reader must check for and convert the final "|" pipe character of a key back into a NULL before returning it to the client software.

*GeoKey Sort Order:*

In the TIFF spec it is required that TIFF tags be written out to the file in tag-ID sorted order. This is done to avoid forcing software to perform N-squared sort operations when reading and writing tags.

To follow the TIFF philosophy, GeoTIFF-writers shall store the GeoKey entries in key-sorted order within the GeoKeyDirectoryTag.

```
Example:
GeoKeyDirectoryTag=( 1, 1, 2, 6,
                    1024, 0, 1, 2,
                    1026, 34737, 12, 0,
                    2048, 0, 1, 32767,
                    2049, 34737, 14, 12,
                    2050, 0, 1, 6,
                    2051, 34736, 1, 0 )
GeoDoubleParamsTag(34736)=(1.5)
GeoAsciiParamsTag(34737)=("Custom File|My Geographic|")
```

The first line indicates that this is a Version 1 GeoTIFF GeoKey directory, the keys are Rev. 1.2, and there are 6 Keys defined in this tag.

The next line indicates that the first Key (ID=1024 = GTModelTypeGeoKey) has the value 2



(Geographic 2D), explicitly placed in the entry list (since TIFFTagLocation=0). The next line indicates that the Key 1026 (the GTCitationGeoKey) is listed in the GeoAsciiParamsTag (34737) array, starting at offset 0 (the first in array), and running for 12 bytes and so has the value "Custom File" (the "|" is converted to a null delimiter at the end). Going further down the list, the Key 2051 (GeogLinearUnitSizeGeoKey) is located in the GeoDoubleParamsTag (34736), at offset 0 and has the value 1.5; the value of key 2049 (GeogCitationGeoKey) is "My Geographic."

The TIFF layer handles all the problems of data structure, platform independence, format types, etc., by specifying byte-offsets, byte-order format and count, while the Key describes its key values at the TIFF level by specifying Tag number, array-index, and count. Since all TIFF information occurs in TIFF arrays of some sort, we have a robust method for storing anything in a Key that would occur in a Tag.

With this Key-value approach, there are 65536 Keys which have all the flexibility of TIFF tag, with the added advantage that a TIFF dump will provide all the information that exists in the GeoTIFF implementation.

This GeoKey mechanism is used extensively in Clause 7 where the parameters for defining Coordinate Reference Systems and, if necessary, their underlying component elements are specified.

## B.2. Coordinate Reference Systems in GeoTIFF

In the TIFF/GeoTIFF framework, there are essentially three different spaces in which coordinates may be defined. The spaces are:

1. The raster space (Image space) R, used to reference the pixel values in an image,
2. The Device space D, and
3. The Model space, M, used to reference points on the earth.

In the sections that follow we discuss the relevance and use of each of these spaces, and their corresponding coordinate systems, from the standpoint of GeoTIFF.

### B.2.1. Device Space and GeoTIFF

In standard TIFF 6.0 there are tags that relate raster space R with device space D, such as monitor, scanner or printer. The list of such tags consists of the following:

```
ResolutionUnit (296)
XResolution (282)
YResolution (283)
Orientation (274)
XPosition (286)
YPosition (287)
```

In GeoTIFF, provision is made to identify earth-referenced coordinate systems (model space M) and to relate M space with R space. This provision is independent of and can co-exist with the

relationship between raster and device spaces. To emphasize the distinction, this specification shall not refer to "X" and "Y" raster coordinates, but rather to raster space "J" (row) and "I" (column) coordinate variables instead, as defined in section [Raster Space](#).

## B.2.2. Raster Space

### *Raster Data*

Raster data consists of spatially coherent, digitally stored numerical data, collected from sensors, scanners, or in other ways numerically derived. The manner in which this storage is implemented in a TIFF file is described in the standard TIFF specification (see [TIFF Specification Revision 6.0](#) ).

Raster data values, as read in from a file, are organized by software into two-dimensional arrays, the indices of the arrays being used as coordinates. There may also be additional indices for multispectral data, but these indices do not refer to spatial coordinates but spectral, and so are not of concern here.

Many different types of raster data may be georeferenced, and there may be subtle ways in which the nature of the data itself influences how the coordinate system (Raster Space) is defined for raster data. For example, pixel data derived from imaging devices and sensors represent aggregate values collected over a small, finite, geographic area, and so it is natural to define coordinate systems in which the pixel value is thought of as filling an area. On the other hand, digital elevations models may consist of discrete "postings," which may best be considered as point measurements at the vertices of a grid, and not in the interior of a cell.

### *Raster Space*

The choice of origin for raster space is not entirely arbitrary, and depends upon the nature of the data collected. Raster space coordinates shall be referred to by their pixel types, i.e., as "PixelIsArea" or "PixelIsPoint."

Note: For simplicity, both raster spaces documented below use a fixed pixel size and spacing of 1. Information regarding the visual representation of this data, such as pixels with non-unit aspect ratios, scales, orientations, etc., are best communicated with the TIFF 6.0 standard tags.

#### **"PixelIsArea" Raster Space**

The "PixelIsArea" raster grid space R, which is the default, uses coordinates I and J, with (0,0) denoting the upper-left corner of the image, and increasing I to the right, increasing J down. The first pixel-value fills the square grid cell with the bounds:

upper-left = (0,0), bottom-right = (1,1)

and so on; by extension this one-by-one grid cell is also referred to as a pixel. An N by M pixel image covers an area with the mathematically defined bounds (0,0), (N,M).

(0,0) (1,0)

x---x---x-> I

| \* | \* |

x---x---x

| (1,1) (2,1)

v

J

Standard (PixelIsArea) TIFF Raster space R,  
showing the locations (x) and areas (\*) of several pixels.

The location of the area pixel is referenced at the upper left of the pixel  
(pixelCorner convention).

### "PixelIsPoint" Raster Space

The PixelIsPoint raster grid space R uses the same coordinate axis names as used in PixelIsArea Raster space, with increasing I to the right, increasing J down. The first pixel-value however, is realized as a point value located at (0,0). An N by M pixel image consists of points which fill the mathematically defined bounds (0,0), (N-1,M-1).

(0,0) (1,0)

x-----x-----> I

|

|

x-----x

|

v

J

(1,1)

PixelIsPoint TIFF Raster space R,  
showing the location (x) of several pixels.

The location of the pixel is referenced at the point pixel (pixelCenter convention).

If a point-pixel image were to be displayed on a display device with pixel cells having the same size as the raster spacing, then the upper-left corner of the displayed image would be located in raster space at (-0.5, -0.5).

To georeference an image in GeoTIFF, you must specify a Raster Space coordinate system, choose a Model coordinate reference system, and specify a transformation between these two, as described in [Coordinate Transformations](#). Its ModelTiePoint tag may be used to provide the location of pixel (0, 0) with the coordinates of the upper left corner of this pixel (in case of PixelIsArea) or the coordinates of this point pixel (in case of PixelIsPoint).

### B.2.3. Model Coordinate Reference Systems (Model space)

'Real world' coordinate reference systems are imposed on models of the earth, hence the term *model coordinate reference system* used in GeoTIFF.

#### Ellipsoid

The geoid - the earth stripped of all topography - forms a reference surface for the earth. However, because it is related to the earth's gravity field, the geoid is a very complex surface; indeed, at a detailed level its description is not well known. The geoid is therefore not used in practical mapping.

It has been found that an oblate ellipsoid (an ellipse rotated about its minor axis) is a good approximation to the shape of the geoid and therefore a good model of the earth. Many approximations exist: several hundred ellipsoids have been defined for scientific purposes and about 30 are in day-to-day use for Earth mapping. The size and shape of these bi-axial ellipsoids can be defined through two parameters. GeoTIFF requires one of these parameters to be:

- the semi-major axis (a), and
- the second to be either the inverse flattening ( $1/f$ ) or the semi-minor axis (b).

Other ellipsoid parameters needed for cartographic applications, for example the eccentricity, can easily be calculated from the two defining parameters. Note that GeoTIFF uses the modern geodesy convention for the symbol (b) for the semi-minor axis. No provision is made for mapping other planets in which a tri-dimensional (tri-axial) ellipsoid might be required, where (b) would represent the semi-major axis and (c) the semi-minor axis.

Historical models exist which use a spherical approximation; such models are not recommended for modern applications, but if needed the size of a model sphere may be defined by specifying identical values for the semi-major and semi-minor axes; the inverse flattening cannot be used as it becomes infinite for a perfect sphere.

### **Prime Meridian**

The coordinate axes of the system referencing points on an ellipsoid are called latitude and longitude. More precisely, geodetic latitude and longitude are required in this GeoTIFF standard. A discussion of the several other types of latitude and longitude is beyond the scope of this document as they are not required for conventional georeferencing.

Geodetic latitude is defined to be the angle subtended with the ellipsoid's equatorial plane by a perpendicular through the surface of the ellipsoid from a point. Latitude is positive if north of the equator, negative if south.

Geodetic longitude is defined to be the angle measured about the minor (polar) axis of the ellipsoid from a prime meridian to the meridian through a point, positive if east of the prime meridian and negative if west. Unlike latitude, which has a natural origin at the equator, there is no feature on the ellipsoid which forms a natural origin for the measurement of longitude. The zero longitude can be any defined meridian. Historically, nations have used the meridian through their national astronomical observatories, giving rise to several prime meridians. By international convention, the meridian through Greenwich, England is the standard prime meridian. Longitude is only unambiguous if the longitude of its prime meridian relative to Greenwich is given. Prime meridians other than Greenwich that are sometimes used for earth mapping are included in the GeoTIFF reference lists.

### **Geodetic Datum (Geodetic Reference Frame)**

As well as there being several ellipsoids in use to model the earth, any one particular ellipsoid can have its location and orientation relative to the earth defined in different ways. If the relationship between the ellipsoid and the earth is changed, then the coordinates of a point will change. Conversely, for coordinates to uniquely describe a location, the relationship between the earth and the ellipsoid must be defined. This relationship is described by a geodetic datum or geodetic

reference frame. An exact geodetic definition of geodetic datums and reference frames is beyond the scope of GeoTIFF.

## **Geodetic Coordinate Reference Systems**

A geodetic coordinate reference system is created by associating a coordinate system - a set of axes - with a geodetic datum. Subtypes of geodetic CRS supported by GeoTIFF are as follows.

- **Geocentric**, when the coordinate system is a 3-dimensional Cartesian coordinate system with its origin at or near the centre of the earth. The Z-axis is in or parallel to the earth's axis of rotation. The X-axis is in the plane of the equator and passes through its intersection with the prime meridian, and the Y-axis is in the plane of the equator forming a right-handed coordinate system with the X and Z axes.
- **Geographic**, when the coordinate system is ellipsoidal, i.e., latitude and longitude in the 2D case and in the 3D case additionally with ellipsoidal height. GeoTIFF v1.0 did not clearly define whether geographic CRSs are 2D or 3D.

Geocentric coordinates are readily converted to and from geographic 3D coordinates. Geographic 2D coordinates cannot be converted to geocentric coordinates without some assumption regarding height.

## **Projected Coordinate Reference Systems**

Before digital computing capabilities were available, calculation on the surface of an ellipsoid was a non-trivial task. Reduction of the ellipsoid surface to a plane facilitated spatial calculations. A geographical coordinate reference system cannot be represented on a plane surface without distortion. Map projections are conversions of ellipsoidal coordinates (latitude and longitude) to Cartesian coordinates in a plane. A map projection consists of a coordinate operation method (through which the characteristics of the distortions are controlled) and a set of defining parameters specific to the method which are parameters in the method formulas, together with specified values for the set of coordinate operation parameters required by the projection method. A projected coordinate reference system results from the application of a map projection to a geographic coordinate reference system.

## **Vertical Coordinate Reference Systems**

Many uses of GeoTIFF will be limited to a two-dimensional, horizontal, description of location for which geographic 2D coordinate reference systems and projected 2D coordinate reference systems are adequate. If a three-dimensional description of location is required, GeoTIFF allows this either through a geocentric coordinate reference system, or through the use of a geographic 3D coordinate reference system (where the vertical component is height above the ellipsoid), or by defining a 1D vertical coordinate reference system and using this together with a geographic 2D or projected coordinate reference system in an implicit compound CRS structure.

Vertical CRS are referenced to a vertical reference surface (vertical datum) at or close to the geoid, and associated with a 1D vertical coordinate system in which heights or depths are given.

Through increasing use of satellite navigation and positioning systems, the ellipsoid is increasingly being used as a vertical reference surface. Heights above the ellipsoid are expressed as part of a

geographic 3D CRS, but are not referenced to a vertical CRS (See [Geographic 3D CRS](#)). The ellipsoid surface may be offset vertically from the reference surface for a vertical CRS approximating the geoid by up to +/- 100m, and generally the two surfaces will not be exactly parallel to each other.

## B.3. Defining Model Coordinate Reference Systems

The following subtypes of Model coordinate reference system (CRS) are recognized in GeoTIFF:

- Geographic 2D;
- Geocentric;
- Projected ('map grid (2D)'); and
- Vertical.

Projected ('map grid') and geographic 2D CRSs form two-dimensional horizontal coordinate reference systems (i.e., horizontal with respect to the earth's surface). Height is not part of these systems. To describe a position in three dimensions using these 2D systems it is necessary to consider height as a second one-dimensional vertical coordinate reference system in a 2D + 1D pseudo 3D compound CRS structure. Recommendations for describing compound CRSs are given in Annex D.

True spatial 3D CRS subtypes are geocentric and geographic 3D. See Annex D for recommendations for describing geographic 3D CRSs.

Within the GeoTIFF standard a Model coordinate reference system (geocentric, geographic, projected or vertical) can be identified either by

- the code of a standard coordinate reference system

or by

- a user-defined system.

### B.3.1. Standard Model Coordinate Reference Systems

In GeoTIFF, standard CRSs are identified through reference to an EPSG CRS code. This is sufficient to define the CRS component objects. Further information on EPSG codes is given in [\[Requirements for definition of Model CRS \(when Model CRS is from GeoTIFF CRS register\)\]](#).

#### NOTE

This document removes the reference to the specific EPSG codes listed in the 1995 GeoTIFF v1.0 specification and replaces it by **allowing reference to any code in the EPSG Dataset**, including codes for any objects introduced into the EPSG Dataset after publication of this document.

### B.3.2. User-defined Model Coordinate Reference Systems

GeoTIFF attempts to allow Model CRSs that are not described in the standard CRS register to be defined through user-defined keys. However the provisions made are limited in that:

- no provision was made for fully describing coordinate system; although axis units could be described, provision for describing axis order and positive direction was omitted; and
- there is ambiguity in the provision for describing user-defined map projections. Codes for some common map projection methods and map projection parameters were provided, but neither the method nor the parameter were defined. Inferences may be made from the listed map projection method names and map projection parameter names, but ambiguity remains so interoperability is not guaranteed.

In practice, user-defined Model CRS definition is limited to the following cases.

1. A user-defined projected CRS which uses a base geographic CRS and a map projection that are both individually available from the GeoTIFF CRS register but, in the register, not associated together. EPSG geogCRS code needs citing through Requirement <http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.EPSG>, EPSG projection code needs citing through Requirement <http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.EPSG>
2. A user-defined projected CRS which uses a user-defined geographic CRS with a map projection that is available from the GeoTIFF CRS register. GeogCRS needs defining as in Requirement <http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.userdefined>, EPSG projection code needs citing through Requirement <http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.EPSG>
3. A user-defined geographic CRS available from the GeoTIFF CRS register and a map projection not in EPSG register. EPSG geogCRS code needs citing through Requirement <http://www.opengis.net/spec/GeoTIFF/1.1/req/GeodeticCRSGeoKey.EPSG>, projection needs defining through Requirement <http://www.opengis.net/spec/req/GeoTIFF/1.1/ProjectionGeoKey.userdefined> using the v1.0 provisions (use the names in annex C).
4. Neither base GeogCRS or map projection is in EPSG. GeogCRS needs defining, projection needs defining through Requirement <http://www.opengis.net/spec/GeoTIFF/1.1/req/ProjectionGeoKey.userdefined> using the v1.0 provisions (the names in annex C).

For the transformation from raster space to model space, some implicit convention is made about axis positive direction and axis order. It is assumed that:

- projected CRS axes are easting, northing;
- geographic 2D CRS axes are longitude east, latitude north; and
- vertical CRS axis is height up.

#### NOTE

Users must note that this GeoTIFF practice is not in line with ISO TC211 and OGC rules for 2D CRS axis order.

### User-defined geographic 2D CRS

For a user-defined geographic 2D CRS the user is expected to provide:

- geocentric coordinate reference system name (through the *GeodeticCitationGeoKey*);
- geodetic datum through the *GeodeticDatumGeoKey*, either:
  - the geodetic datum code (if available through standard EPSG code), or

- user-defined geodetic datum name and other defining information:
  - the geodetic datum name (through the *GeodeticCitationGeoKey*),
  - the ellipsoid (through the *EllipsoidGeoKey*, see [User-defined ellipsoid](#)), and
  - the prime meridian (through the *PrimeMeridianGeoKey*, see [User-defined prime meridian](#));
- axis unit through the *GeogAngularUnitsGeoKey*, either:
  - angle unit code (if available through standard EPSG code), or
  - user-defined angle unit name (through the *GeodeticCitationGeoKey*) and scaling from SI base unit of radian (through the *GeogAngularUnitSizeGeoKey*); and
- if the CRS uses a user-defined ellipsoid, the ellipsoid axis unit through the *GeogLinearUnitsGeoKey*, either:
  - length unit code (if available through standard EPSG code), or
  - user-defined length unit name (through the *GeodeticCitationGeoKey*) and scaling from SI base unit of meter (through the *GeogLinearUnitSizeGeoKey*).

### User-defined geocentric CRS

For a user-defined geocentric CRS the user is expected to provide:

- geocentric coordinate reference system name (through the *GeodeticCitationGeoKey*);
- geodetic datum through the *GeodeticDatumGeoKey*, either:
  - the geodetic datum code (if available through standard EPSG code), or
  - user-defined geodetic datum name and other defining information:
    - the geodetic datum name (through the *GeodeticCitationGeoKey*),
    - the ellipsoid (through the *EllipsoidGeoKey*, see [User-defined ellipsoid](#)), and
    - the prime meridian (through the *PrimeMeridianGeoKey*, see [User-defined prime meridian](#));
- axis unit through the *GeogLinearUnitsGeoKey*, either:
  - length unit code (if available through standard EPSG code), or
  - user-defined length unit name (through the *GeodeticCitationGeoKey*) and scaling from SI base unit of meter (through the *GeogLinearUnitSizeGeoKey*); and
- if the CRS uses a user-defined prime meridian, prime meridian Greenwich longitude unit through the *GeogAngularUnitsGeoKey*, either:
  - angle unit code (if available through standard EPSG code), or
  - user-defined angle unit name (through the *GeodeticCitationGeoKey*) and scaling from SI base unit of radian (through the *GeogAngularUnitSizeGeoKey*).

### User-defined ellipsoid

For any user-defined geocentric, geographic 3D or geographic 2D CRS an ellipsoid needs to be identified. The user is expected to provide:



- ellipsoid through the *EllipsoidGeoKey*, either:
  - the ellipsoid code (if available through standard EPSG code), or
  - the user-defined ellipsoid name and other defining information:
    - the ellipsoid name (through the *GeodeticCitationGeoKey*),
    - the ellipsoid semi-major axis (through the *EllipsoidSemiMajorAxisGeoKey*),
    - either the ellipsoid semi-minor axis (through the *EllipsoidSemiMinorAxisGeoKey*) or the ellipsoid inverse flattening (through the *EllipsoidInvFlatteningGeoKey*),
    - The units for the ellipsoid axis or axes;
- For geocentric the ellipsoid axis or axes values must given in the length unit defined through the *GeogLinearUnitsGeoKey* already required (see [User-defined geocentric CRS](#)); and
- For geographic 2D CRSs, then a *GeogLinearUnitsGeoKey* is additionally required.

### User-defined prime meridian

For any user-defined geocentric, geographic 3D or geographic 2D CRS a prime meridian needs to be identified whenever it is not Greenwich. (If no prime meridian is identified, it should be assumed to be Greenwich). The user is expected to provide:

- Prime meridian through the *PrimeMeridianGeoKey*, either:
  - the prime meridian code (if available through standard EPSG code), or
  - the user-defined prime meridian name and other defining information:
    - the prime meridian name (through the *GeodeticCitationGeoKey*),
    - the prime meridian longitude (through the *PrimeMeridianLongitudeGeoKey*),
    - the units for the prime meridian longitude;
- For geographic CRSs the prime meridian longitude value must given in the angle unit defined through the *GeogAngularUnitsGeoKey* already required (see [User-defined geographic 2D CRS](#)); and
- For geocentric CRSs, then a *GeogAngularUnitsGeoKey* is additionally required.

### User-defined Projected Coordinate Reference Systems

For a user-defined projected CRS the user is expected to provide:

- projected coordinate reference system name (through *ProjectedCitationGeoKey*);
- base geographic CRS (either standard EPSG code or user-defined, see [User-defined geographic 2D CRS](#));
- map projection through the *ProjectionGeoKey*, either:
  - map projection code (if available through standard EPSG code), or
  - user-defined map projection (see below); and
- axis unit through *ProjLinearUnitsGeoKey*, either:
  - length unit code (if available through standard EPSG code), or

- user-defined length unit name (through the *ProjectedCitationGeoKey*) and scaling from SI base unit of meter (through the *ProjLinearUnitSizeGeoKey*).

### User-defined map projection

For a user-defined map projection the user is expected to provide:

- map projection name (through *ProjectedCitationGeoKey*);
- map projection method (through *ProjMethodGeoKey*);
- map projection parameter values (using a set of keys appropriate to the map projection method):
  - For map projection parameters that are lengths the parameter value needs to be expressed in the units defined through the *ProjLinearUnitsGeoKey*, and
  - For map projection parameters that are angles the parameter value needs to be expressed in the units defined through the *GeogAngularUnitsGeoKey*, which is required in the base geographic CRS description, except for azimuths when the value needs to be expressed in the units defined through a *GeogAzimuthUnitsGeoKey*; and
- if the map projection method requires a parameter that is an azimuth, the azimuth unit through a *GeogAzimuthUnitsGeoKey*.

### User-defined Vertical Coordinate Reference Systems

For a user-defined vertical CRS the user is expected to provide:

- vertical coordinate reference system name (through *VerticalCitationGeoKey*);
- user-defined vertical datum through *VerticalDatumGeoKey*, either:
  - the vertical datum code (if available through standard EPSG code), or
  - the vertical datum name and other defining information (through the *VerticalCitationGeoKey*); and
- vertical axis unit through *VerticalUnitsGeoKey*, either:
  - linear unit code (if available through standard EPSG code), or
  - linear unit name (through *VerticalCitationGeoKey*) and scaling from SI base unit of meter (through *GeogLinearUnitSizeGeoKey*).

## B.4. Model CRS Reference Parameters

Most of the GeoTIFF standard definitions for model ('real world') coordinate reference systems and their component elements are based on the hierarchical system developed for the EPSG Geodetic Parameter Dataset ('EPSG Dataset'). The complete set of EPSG definitions is available at <http://www.epsg-registry.org>.

The EPSG Dataset is maintained by the Geodesy Subcommittee of the International Association of Oil and Gas Producers (IOGP). It follows the ISO 19111 / OGC Abstract Specification Topic 2 data model for describing the definitions of coordinate reference systems (CRSs). CRSs and coordinate

operations are composed of a number of objects and attributes. Some of these objects themselves are composed objects and attributes, in a nested structure. Each release of new or revised data is indicated by the EPSG Dataset version number. Since 1999 (from EPSG Dataset v5.0 and later) EPSG policy has been to never remove any invalid data but instead to leave it in the Dataset with its status set to deprecated. Deprecated data contains a significant error (significant defined as having impact on the result of applying a transformation or conversion) and is invalid. As such, since 1999 reference to the version of the EPSG Dataset to qualify codes of entities within the Dataset has been unnecessary. Using EPSG Dataset versions 5.0 and 9.3 as examples, `urn:ogc:def:crs:EPSG:5.0:4326` and `urn:ogc:def:crs:EPSG:9.3:4326` and `urn:ogc:def:crs:EPSG::4326` reference the same object. The terms of use of the EPSG Dataset are given at <http://www.epsg.org/TermsOfUse.aspx>.

### B.4.1. EPSG coding of objects

Within the EPSG Dataset each object has a code. There have been three generations of coding.

1. In v1.x of the publicly-available EPSG Dataset (1994-1996, published by the Petrotechnical Open Software Corporation, POSC), codes were alphanumeric. The initial letter indicated the object type, and objects within each type were then assigned sequential numbers.
2. With the introduction of GeoTIFF v1.0, EPSG Dataset v2.1 object codes were changed to integer values in the range 1024 through 32766. This overall code range was divided into non-overlapping sub-ranges, with one sub-range range for each object type. At that time, all EPSG object codes were unique. The GeoTIFF v1.0 specification was written at this time, and the EPSG code ranges for object types were written into the GeoTIFF v1.0 specification.
3. However as the number of items in the EPSG Dataset grew, some of the object code sub-ranges became fully assigned. The unique code system broke down. Since 2006, all object types have been separately assigned codes within the range 1024 through 32766. Within each object type codes remain unique, but one code value may be used for several object types. For example, code 4326 is used for both a CRS and for a geographic extent (in EPSG called 'area'). Codes at and just above the lower end of the range 1024 through 32766 may be used by numerous object types: for example by the year 2018 code 1026 has been assigned to 10 different object types. EPSG codes therefore are only unique when the object type is disclosed. `urn:ogc:def:EPSG::4326` is ambiguous, `urn:ogc:def:crs:EPSG::4326` and `urn:ogc:def:area:EPSG::4326` are unambiguous.

The GeoTIFF v1.0 specification refers to "obsolete EPSG/POSC codes." These refer to the numeric part of the alphanumeric coding in (i) above. These values had been used in some GeoTIFF v0.x files and for backward compatibility with those earlier files GeoTIFF v1.0 retained references to them. As all of these alphanumeric codes were changed to the integer coding in (ii) above, reference to these obsolete codes should now be unnecessary. In effect, for model CRS GeoKeys the obsolete code range may be treated as a reserved code range.

Note: 'EPSG/POSC obsolete codes' refers specifically to the coding in generation (i) above, and should not be confused with codes from generations (ii) and (iii) which have been given the status of 'deprecated.'

A reference to an EPSG coordinate reference system code is sufficient for a complete definition: it implies use of the CRS components (datum, ellipsoid, map projection, etc.) that are associated with that CRS in the EPSG Dataset definition. The EPSG codes for coordinate reference system components should only be referenced when describing a user-defined coordinate reference

system.

## B.5. Coordinate Transformations

The purpose of GeoTIFF is to allow the definitive identification of georeferenced locations within a raster dataset. This is generally accomplished through tying raster space coordinates to a model space coordinate system, when no further information is required. In the GeoTIFF nomenclature, "georeferencing" refers to tying raster space to a model space M, while "geocoding" refers to defining how the model space M assigns coordinates to points on the earth.

The three tags defined below may be used for defining the relationship between R and M, and the relationship may be diagrammed as:

```
ModelPixelScaleTag
ModelTiepointTag
R ----- OR -----> M
(I,J,K) ModelTransformationTag (X,Y,Z)
```

The next section describes these georeferencing tags in detail.

## B.6. GeoTIFF Tags for Coordinate Transformations

For most common applications, the transformation between raster and model space may be defined with a set of raster-to-model tiepoints and scaling parameters. The following two tags may be used for this purpose:

```
ModelTiepointTag:
  Tag = 33922 (8482.H)
  Type = DOUBLE (IEEE Double precision)
  N = 6*K, K = number of tiepoints
  Alias: GeoreferenceTag
```

This tag stores raster → model tiepoint pairs in the order

```
ModelTiepointTag = (... , I,J,K, X,Y,Z...),
```

where (I,J,K) is the point at location (I,J) in raster space with pixel-value K, and (X,Y,Z) is a vector in model space. In most cases the model space is only two-dimensional, in which case both K and Z should be set to zero; this third dimension is provided in anticipation of support for 3D digital elevation models and vertical coordinate systems.

A raster image may be georeferenced simply by specifying its location, size and orientation in the model coordinate space M. This may be done by specifying the location of three of the four bounding corner points. However, tiepoints are only to be considered exact at the points specified; thus defining such a set of bounding tiepoints does **not** imply that the model space locations of the

interior of the image may be exactly computed by a linear interpolation of these tiepoints.

However, since the relationship between the Raster space and the model space will often be an exact, affine transformation, this relationship can be defined using one set of tiepoints and the "ModelPixelScaleTag," described below, which gives the vertical and horizontal raster grid cell size, specified in model units.

If possible, the first tiepoint placed in this tag shall be the one establishing the location of the point (0,0) in raster space. However, if this is not possible (for example, if (0,0) maps to a part of model space in which the projection is ill-defined), then there is no particular order in which the tiepoints need be listed.

For orthorectification or mosaicking applications, a large number of tiepoints may be specified on a mesh over the raster image. However, the definition of associated grid interpolation methods is not in the scope of the current GeoTIFF spec.

Remark: all GeoTIFF information is independent of the XPosition, YPosition, and Orientation tags of the standard TIFF 6.0 spec.

The next two tags ModelPixelScaleTag and ModelTransformationTag are optional tags provided for defining exact affine transformations between raster and model space; GeoTIFF files may use either, but **shall never use both** within the same TIFF image directory.

```
ModelPixelScaleTag:  
  Tag = 33550 (830E.H)  
  Type = DOUBLE (IEEE Double precision)  
  N = 3
```

This tag may be used to specify the size of raster pixel spacing in the model space units, when the raster space can be embedded in the model space coordinate reference system without rotation, and consists of the following 3 values:

```
ModelPixelScaleTag = (ScaleX, ScaleY, ScaleZ)
```

where ScaleX and ScaleY give the horizontal spacing of raster pixels in the 2 directions. The ScaleZ is primarily used to map the pixel value of a digital elevation model into the correct Z-scale (in other words a **Z-Scaling factor**) and so for most other purposes this value should be zero (since most model spaces are 2-D, with Z=0).

A single tiepoint in the ModelTiepointTag, together with this tag, completely determine the relationship between raster and model space; thus they comprise the two tags which GeoTIFF files most often will use to place a raster image into a "standard position" in model space.

Like the Tiepoint tag, this tag information is independent of the XPosition, YPosition, Resolution and Orientation tags of the standard TIFF 6.0 spec. However, simple reversals of orientation between raster and model space (e.g., horizontal or vertical flips) may be indicated by reversal of sign in the corresponding component of the ModelPixelScaleTag. GeoTIFF compliant readers must honor this sign-reversal convention.

This ModelPixelScaleTag tag must not be used if the raster image requires rotation or shearing to place it into the standard model space. In such cases the transformation must be defined with the more general ModelTransformationTag, defined below.

```
ModelTransformationTag
  Tag = 34264 (85D8.H)
  Type = DOUBLE
  N = 16
```

This tag may be used to specify the transformation matrix between the raster space (and its dependent pixel-value space) and the (possibly 3D) model space. If specified, the tag has the following organization:

```
ModelTransformationTag = (a,b,c,d,e....m,n,o,p).
```

where

model		image
coords =	matrix *	coords
- -	- -	- -
X	a b c d	I
Y	e f g h	J
Z	i j k l	K
1	m n o p	1
- -	- -	- -

By convention, and without loss of generality, the following parameters are currently hard-coded and will always be the same (but must be specified nonetheless):

```
m = n = o = 0, p = 1.
```

When the model space is 2-D, the matrix will have the more limited form:

$$\begin{bmatrix}
- & - & | & - & & - & | & - & - \\
| & X & | & a & b & 0 & d & | & I \\
| & | & | & | & | & | & | & | & | \\
| & Y & | & e & f & 0 & h & | & J \\
| & | & | & | & | & | & | & | & | \\
| & Z & | & 0 & 0 & 0 & 0 & | & K \\
| & | & | & | & | & | & | & | & | \\
| & 1 & | & 0 & 0 & 0 & 1 & | & 1 \\
| & - & | & - & & - & | & - & -
\end{bmatrix}
=
\begin{bmatrix}
- & - & | & - & & - & | & - & - \\
| & X & | & a & b & 0 & d & | & I \\
| & | & | & | & | & | & | & | & | \\
| & Y & | & e & f & 0 & h & | & J \\
| & | & | & | & | & | & | & | & | \\
| & Z & | & 0 & 0 & 0 & 0 & | & K \\
| & | & | & | & | & | & | & | & | \\
| & 1 & | & 0 & 0 & 0 & 1 & | & 1 \\
| & - & | & - & & - & | & - & -
\end{bmatrix}$$

Values "d" and "h" will often be used to represent translations in X and Y, and so will not necessarily be zero. All 16 values should be specified, in all cases. Only the raster-to-model transformation is defined; if the inverse transformation is required it must be computed by the client, to the desired accuracy.

This matrix tag should not be used if the ModelTiepointTag and the ModelPixelScaleTag are already defined. If only a single tiepoint (I,J,K,X,Y,Z) is specified, and the ModelPixelScale = (Sx, Sy, Sz) is specified, then the corresponding transformation matrix may be computed from them as:

$$\begin{bmatrix}
- & & & - \\
| & S_x & 0.0 & 0.0 & T_x & | \\
| & 0.0 & -S_y & 0.0 & T_y & | \\
| & 0.0 & 0.0 & S_z & T_z & | \\
| & 0.0 & 0.0 & 0.0 & 1.0 & | \\
| & - & & & -
\end{bmatrix}
\begin{matrix}
T_x = X - I/S_x \\
T_y = Y + J/S_y \\
T_z = Z - K/S_z \text{ (if not 0)}
\end{matrix}$$

where the -Sy is due the reversal of direction from J increasing- down in raster space to Y increasing-up in model space.

Like the Tiepoint tag, this tag information is independent of the XPosition, YPosition, and Orientation tags of the standard TIFF 6.0 spec.

## B.7. Cookbook for Defining Transformations

Here is a 4-step guide to producing a set of GeoTIFF tags for defining coordinate transformation information of a raster dataset.

Step 1: Establish the Raster Space coordinate system used: RasterPixelIsArea or RasterPixelIsPoint.

Step 2: Establish/define the model space Type in which the image is to be georeferenced. If you are geocoding this data set, then the model space is defined to be the corresponding geographic, geocentric or projected coordinate reference system. Usually this will be a projected coordinate reference system.

Step 3: Identify the nature of the transformations needed to tie the raster data down to the model space coordinate reference system.

Case 1: The model-location of a raster point (x,y) is known, but not the scale or orientations: Use the ModelTiepointTag to define the (X,Y,Z) coordinates of the known raster point.

Case 2: The location of three non-collinear raster points are known exactly, but the linearity of the transformation is not known.

Use the ModelTiepointTag to define the (X,Y,Z) coordinates of all three known raster points. Do not compute or define the ModelPixelScale or ModelTransformation tag.

Case 3: The position and scale of the data is known exactly, and no rotation or shearing is needed to fit into the model space.

Use the ModelTiepointTag to define the (X,Y,Z) coordinates of the known raster point, and the ModelPixelScaleTag to specify the scale.

Case 4: The raster data requires rotation and/or lateral shearing to fit into the defined model space:

Use the ModelTransformation matrix to define the transformation.

Case 5: The raster data cannot be fit into the model space with a simple affine transformation (rubber-sheeting required). Use only the ModelTiepoint tag, and specify as many tiepoints as your application requires. Note, however, that this is not an interoperable GeoTIFF implementation, and should not be used for interchange; it is recommended that the image be geometrically rectified first, and put into a standard projected coordinate reference system.

Step 4: Install the defined tag values in the TIFF file and close it.

## B.8. Geocoding Raster Data

A geocoded image is a georeferenced image as described in section [Coordinate Transformations](#), which also specifies a model space coordinate reference system (CRS) between the model space M



(to which the raster space has been tied) and the earth. The relationship can be diagrammed, including the associated TIFF tags, as follows:



The geocoding coordinate reference system is defined by the GeoKeyDirectoryTag, while the Georeferencing information (T) is defined by the ModelTiepointTag and the ModelPixelScale, or ModelTransformationTag. Since these two systems are independent of each other, the tags used to store the parameters are separated from each other in the GeoTIFF file to emphasize the orthogonality.

# Annex C: GeoTIFF Map Projection Method codes (Normative)

## C.1. Map Projection methods

GeoTIFF v1.0 lists a number of map projection methods (which it calls 'coordinate transformations'). These are names, without any formulas or clear citation. As such they are an ambiguous identification of method. It is not possible to identify whether the formulas are ellipsoidal or spherical. If it is assumed that they are ellipsoidal formulas, for some the name does not adequately distinguish between method variations where different formulas lead to significantly different results in application. The codes for these listed methods are given in table C.1. These remain valid for this v1.1 revision.

<u>GeoTIFF v1.0 Map Projection Method Name</u>	<u>GeoTIFF v1.0 Map Projection Method Name Alias</u>	<u>GeoTIFF v1.0 Value for ProjMet hodGeo Key</u>
TransverseMercator	GaussBoaga; GaussKruger	1
TransvMercator_Modified_Alaska	AlaskaConformal	2
ObliqueMercator	ObliqueMercator_Hotine	3
ObliqueMercator_Laborde		4
ObliqueMercator_Rosenmund	SwissObliqueCylindrical	5
ObliqueMercator_Spherical		6
Mercator		7
LambertConfConic_2SP		8
LambertConfConic_Helmert		9
LambertAzimEqualArea		10
AlbersEqualArea		11
AzimuthalEquidistant		12
EquidistantConic		13
Stereographic		14
PolarStereographic		15
ObliqueStereographic		16
Equirectangular		17
CassiniSoldner	TransvEquidistCylindrical	18

<b><u>GeoTIFF v1.0 Map Projection Method Name</u></b>	<b><u>GeoTIFF v1.0 Map Projection Method Name Alias</u></b>	<b><u>GeoTIFF v1.0 Value for ProjMet hodGeo Key</u></b>
Gnomonic		19
MillerCylindrical		20
Orthographic		21
Polyconic		22
Robinson		23
Sinusoidal		24
VanDerGrinten		25
NewZealandMapGrid		26
TransvMercator_SouthOriented		27

Table C.1 - Codes for GeoTIFF v1.0 map projection methods

**NOTE** ProjMethodGeoKey was called ProjCoordTransGeoKey in GeoTIFF v1.0

## C.2. Map Projection parameters

GeoTIFF v1.0 lists a number of map projection parameters. These are names, without any definition or clear citation. As such they are ambiguous. It is also not clear which parameters should be used for which methods. The map projection parameter GeoKey codes are listed in table C.2. These remain valid for this v1.1 revision.

<b><u>GeoTIFF v1.0 Map Projection Parameter Name</u></b>	<b><u>GeoTIFF v1.0 Map Projection Parameter Alias</u></b>	<b><u>GeoT IFF v1.0 GeoK ey</u></b>	<b><u>Parameter Value Unit</u></b>
ProjStdParallel1GeoKey	ProjStdParallelGeoKey	3078	GeogAngularUnits
ProjStdParallel2GeoKey		3079	GeogAngularUnits
ProjNatOriginLongGeoKey	ProjOriginLongGeoKey	3080	GeogAngularUnits
ProjNatOriginLatGeoKey	ProjOriginLatGeoKey	3081	GeogAngularUnits
ProjFalseEastingGeoKey		3082	ProjLinearUnits
ProjFalseNorthingGeoKey		3083	ProjLinearUnits
ProjFalseOriginLongGeoKey		3084	GeogAngularUnits

<b><u>GeoTIFF v1.0 Map Projection Parameter Name</u></b>	<b><u>GeoTIFF v1.0 Map Projection Parameter Alias</u></b>	<b><u>GeoT IFF v1.0 GeoK ey</u></b>	<b><u>Parameter Value Unit</u></b>
ProjFalseOriginLatGeoKey		3085	GeogAngularUnits
ProjFalseOriginEastingGeoKey		3086	ProjLinearUnits
ProjFalseOriginNorthingGeoKey		3087	ProjLinearUnits
ProjCenterLongGeoKey		3088	GeogAngularUnits
ProjCenterLatGeoKey		3089	GeogAngularUnits
ProjCenterEastingGeoKey		3090	ProjLinearUnits
ProjCenterNorthingGeoKey		3091	ProjLinearUnits
ProjScaleAtNatOriginGeoKey	ProjScaleAtOriginGeoKey	3092	ratio
ProjScaleAtCenterGeoKey		3093	ratio
ProjAzimuthAngleGeoKey		3094	GeogAzimuthUnits
ProjStraightVertPoleLongGeoKey		3095	GeogAngularUnits

*Table C.2 - GeoKey codes for GeoTIFF v1.0 map projection parameters*

# Annex D: Recommendations for including height in model CRS definitions (Informative)

## D.1. Introduction

GeoTIFF 1.0 presently only handles Geographic 2D CRS or Projected CRS (2D) or geocentric (intrinsically 3D) as indicated by the `GTModelTypeGeoKey`. A `verticalCRS` is a 1D gravity-related CRS. An ellipsoidal height is not a 1D CRS: it can only be used as the height part of a geographic 3D CRS. In both cases, when the GeoTIFF file contains digital elevation models (Terrain or Surface model, or gridded bathymetric data), the vertical reference is provided by the compound CRSs mechanism (Horizontal 2D CRS + `VerticalGeoKey`) documented below.

The value of the `VerticalGeoKey` may:

- be a `verticalCRS` (case of 1D gravity-related CRS); or
- describe a geographic 3D CRS (case of ellipsoidal height).

Therefore this key is named `VerticalGeoKey` (and cannot be called `VerticalCRSGeoKey`).

Note: In GeoTIFF v1.0 it was called `VerticalCSTypeGeoKey`.

This specification supports the use of user-defined Vertical CRSs as part of a compound structure, but does not support the definition of user-defined geographic 3D CRSs.

## D.2. Compound CRSs

A future version of GeoTIFF may expand the values of the `GTModelTypeGeoKey` to explicitly describe the Model CRS being compound. This document does not make such an expansion.

Recommendation: For a 2D+1D compound CRS comprised of projected CRS + vertical CRS, `GTModelTypeGeoKey` value should be 1 and both a `ProjectedCRSGeoKey` and a `VerticalGeoKey` should be given. The `ProjectedCRSGeoKey` should describe a 2D projected CRS, the `VerticalGeoKey` should describe the vertical CRS.

Recommendation: For a 2D+1D compound CRS comprised of geographic 2D CRS + vertical CRS, `GTModelTypeGeoKey` value should be 2 and both a `GeodeticCRSGeoKey` and a `VerticalGeoKey` should be given. The `GeodeticCRSGeoKey` should describe a geographic 2D CRS, the `VerticalGeoKey` should describe the vertical CRS.

## D.3. Temporary provisions for including ellipsoidal height as one of the coordinates in GeoTIFF

A future version of GeoTIFF may expand the values of the `GTModelTypeGeoKey` to explicitly differentiate between geographic 2D and geographic 3D CRSs. This document does not make such

an expansion.

In this document there are three possible means of describing ellipsoidal height as one of the coordinates in a GeoTIFF v1.1 file. All are temporary solutions.

a) Give GTModelTypeGeoKey value of 2 and identify a geographic 2D CRS through the GeodeticCRSGeoKey, giving the ellipsoidal height description by inserting a geographic 3D CRS code in the VerticalGeoKey. The geographic 2D CRS should be the horizontal component of the geographic 3D CRS (this is the **recommended option**).

b) Give GTModelTypeGeoKey value of 1 and identify a projected CRS through the ProjectedCRSGeoKey, giving the ellipsoidal height description by inserting a geographic 3D CRS code in the VerticalGeoKey. The projected CRS should have as its base CRS the geographic 2D CRS which is the horizontal component of the geographic 3D CRS.

**NOTE**

If the geographic 2D CRS (in case a) or the projected CRS (in case b) would not respect this condition, then a transformation would have to be performed to produce the Lat, Lon that represent the horizontal coordinate values that are to be combined with the Z to get the 3D geographic coordinate, thus introducing some error.

c) give GTModelTypeGeoKey value of 2 and use the VerticalGeoKey to describe an ellipsoid from which the ellipsoid height is measured using the GeoTIFF v1.0 codes in Table D.1 below.

None of these are long-term solutions. Until a major revision of this specification is available, recommended practice for producers/writers is to use (a). Readers should be prepared for any of these options.

*Table D.1 - Deprecated codes from GeoTIFF v1.0 indicating Geographic 3D CRS ellipsoid heights (corresponding to option c)*

<u>Ellipsoid Name</u>	<u>GeoTIFF v1.0 Vertical Code</u>
Airy_1830_ellipsoid	5001
Airy_Modified_1849_ellipsoid	5002
ANS_ellipsoid	5003
Bessel_1841_ellipsoid	5004
Bessel_Modified_ellipsoid	5005
Bessel_Namibia_ellipsoid	5006
Clarke_1858_ellipsoid	5007
Clarke_1866_ellipsoid	5008
Clarke_1880_Benoit_ellipsoid	5010
Clarke_1880_IGN_ellipsoid	5011
Clarke_1880_RGS_ellipsoid	5012

<b><u>Ellipsoid Name</u></b>	<b><u>GeoTIFF v1.0 Vertical Code</u></b>
Clarke_1880_Arc_ellipsoid	5013
Clarke_1880_SGA_1922_ellipsoid	5014
Everest_1830_1937_Adjustment_ellipsoid	5015
Everest_1830_1967_Definition_ellipsoid	5016
Everest_1830_1975_Definition_ellipsoid	5017
Everest_1830_Modified_ellipsoid	5018
GRS_1980_ellipsoid	5019
Helmert_1906_ellipsoid	5020
Indonesian_National_Spheroid_ellipsoid	5021
International_1924_ellipsoid	5022
International_1967_ellipsoid	5023
Krassowsky_1940_ellipsoid	5024
NWL_9D_ellipsoid	5025
NWL_10D_ellipsoid	5026
Plessis_1817_ellipsoid	5027
Struve_1860_ellipsoid	5028
War_Office_ellipsoid	5029
WGS_84_ellipsoid	5030
GEM_10C_ellipsoid	5031
OSU86F_ellipsoid	5032
OSU91A_ellipsoid	5033

# Annex E: Summary of GeoKey IDs and names

(Informative)

Table E.1 - Summary of GeoKey IDs and names

<u>Key ID</u>	<u>Type</u>	<u>GeoTIFF v1.0 key name</u>	<u>GeoTIFF v1.0 key alias</u>	<u>This document key name</u>
<u>GeoTIFF Configuration Keys</u>				
1024	Short	GTModelTypeGeoKey		(as GeoTIFF v1.0)
1025	Short	GTRasterTypeGeoKey		(as GeoTIFF v1.0)
1026	Ascii	GTCitationGeoKey		(as GeoTIFF v1.0)
<u>Geodetic CRS Parameter Keys</u>				
2048	Short	GeographicTypeGeoKey		GeodeticCRSGeoKey
2049	Ascii	GeogCitationGeoKey		GeodeticCitationGeoKey
2050	Short	GeogGeodeticDatumGeoKey		GeodeticDatumGeoKey
2051	Short	GeogPrimeMeridianGeoKey		PrimeMeridianGeoKey
2052	Short	GeogLinearUnitsGeoKey		(as GeoTIFF v1.0)
2053	Double	GeogLinearUnitSizeGeoKey		(as GeoTIFF v1.0)
2054	Short	GeogAngularUnitsGeoKey		(as GeoTIFF v1.0)
2055	Double	GeogAngularUnitSizeGeoKey		(as GeoTIFF v1.0)
2056	Short	GeogEllipsoidGeoKey		EllipsoidGeoKey
2057	Double	GeogSemiMajorAxisGeoKey		EllipsoidSemiMajorAxisGeoKey
2058	Double	GeogSemiMinorAxisGeoKey		EllipsoidSemiMinorAxisGeoKey
2059	Double	GeogInvFlatteningGeoKey		EllipsoidInvFlatteningGeoKey



<b><u>Key ID</u></b>	<b><u>Type</u></b>	<b><u>GeoTIFF v1.0 key name</u></b>	<b><u>GeoTIFF v1.0 key alias</u></b>	<b><u>This document key name</u></b>
2061	Double	GeogPrimeMeridianLongGeoKey		PrimeMeridianLongitudeGeoKey
2062	Double (3 or 7 values)	Reserved (GeogTOWGS84GeoKey used by GDAL)		Reserved
<b><u>Projected CRS Parameter Keys</u></b>				
<u>2060</u>	Short	GeogAzimuthUnitsGeoKey		(as GeoTIFF v1.0)
3072	Short	ProjectedCSTypeGeoKey		ProjectedCRSGeoKey
3073	Ascii	PCSCitationGeoKey		ProjectedCitationGeoKey
3074	Short	ProjectionGeoKey		(as GeoTIFF v1.0)
3075	Short	ProjCoordTransGeoKey		ProjMethodGeoKey
3076	Short	ProjLinearUnitsGeoKey		(as GeoTIFF v1.0)
3077	Double	ProjLinearUnitSizeGeoKey		(as GeoTIFF v1.0)
3078	Double	ProjStdParallel1GeoKey	ProjStdParallelGeoKey	(as GeoTIFF v1.0)
3079	Double	ProjStdParallel2GeoKey		(as GeoTIFF v1.0)
3080	Double	ProjNatOriginLongGeoKey	ProjOriginLongGeoKey	(as GeoTIFF v1.0)
3081	Double	ProjNatOriginLatGeoKey	ProjOriginLatGeoKey	(as GeoTIFF v1.0)
3082	Double	ProjFalseEastingGeoKey		(as GeoTIFF v1.0)
3083	Double	ProjFalseNorthingGeoKey		(as GeoTIFF v1.0)
3084	Double	ProjFalseOriginLongGeoKey		(as GeoTIFF v1.0)
3085	Double	ProjFalseOriginLatGeoKey		(as GeoTIFF v1.0)
3086	Double	ProjFalseOriginEastingGeoKey		(as GeoTIFF v1.0)

<b><u>Key ID</u></b>	<b><u>Type</u></b>	<b><u>GeoTIFF v1.0 key name</u></b>	<b><u>GeoTIFF v1.0 key alias</u></b>	<b><u>This document key name</u></b>
3087	Double	ProjFalseOriginNorthingGeoKey		(as GeoTIFF v1.0)
3088	Double	ProjCenterLongGeoKey		(as GeoTIFF v1.0)
3089	Double	ProjCenterLatGeoKey		(as GeoTIFF v1.0)
3090	Double	ProjCenterEastingGeoKey		(as GeoTIFF v1.0)
3091	Double	ProjCenterNorthingGeoKey		(as GeoTIFF v1.0)
3092	Double	ProjScaleAtNatOriginGeoKey	ProjScaleAtOriginGeoKey	(as GeoTIFF v1.0)
3093	Double	ProjScaleAtCenterGeoKey		(as GeoTIFF v1.0)
3094	Double	ProjAzimuthAngleGeoKey		(as GeoTIFF v1.0)
3095	Double	ProjStraightVertPoleLongGeoKey		(as GeoTIFF v1.0)
<b><u>Vertical CRS Parameter Keys (4096-5119)</u></b>				
4096	Short	VerticalCSTypeGeoKey		VerticalGeoKey
4097	Ascii	VerticalCitationGeoKey		(as GeoTIFF v1.0)
4098	Short	VerticalDatumGeoKey		(as GeoTIFF v1.0)
4099	Short	VerticalUnitsGeoKey		(as GeoTIFF v1.0)
<b><u>Dynamic CRS Parameter Keys</u></b>				
5120	Double	CoordinateEpochGeoKey		(as GeoTIFF v1.2)

# Annex F: Examples

## F.1. Introduction

This annex provides examples of how GeoTIFF may be implemented at the Tag and GeoKey level, following the general "Cookbook" approach presented in [Cookbook for Defining Transformations](#): common examples, less common ones, including a Lunar example.

## F.2. Common Examples

### F.2.1. UTM Projected Aerial Photo

We have an aerial photo which has been orthorectified and resampled to a UTM grid, zone 60, using WGS 84 coordinate reference system; the coordinates of the upper-left corner of the image are given in easting/northing, as 350807.4m, 5316081.3m. The scanned map pixel scale is 100 meters/pixels (the actual dpi scanning ratio is irrelevant).

```
ModelTiepointTag = (0, 0, 0, 350807.4, 5316081.3, 0.0)
ModelPixelScaleTag = (100.0, 100.0, 0.0)
GeoKeyDirectoryTag:
    GTModelTypeGeoKey = 1 (ModelTypeProjected 2D)
    GTRasterTypeGeoKey = 1 (RasterPixelIsArea)
    ProjectedCRSGeoKey = 32660 (Projected 2D CRS WGS 84 / UTM zone 60N)
    ProjectedCitationGeoKey = "UTM Zone 60 N with WGS 84"
```

Notes:

1. We did not need to specify CitationGeoKey and indicate the base geographic CRS and the projection, since the 32660 code implies particular geographic CRS, projection and units already (WGS 84 Geographic 2D, UTM in zone 60N and meters). The citation was added just for documentation.
2. The "GeoKeyDirectoryTag" is expressed using the "GeoKey" structure defined above. At the TIFF level the tags look like this:

```
GeoKeyDirectoryTag=( 1,      0,  2,      4,
                    1024,    0,  1,      1,
                    1025,    0,  1,      1,
                    3072,    0,  1, 32660,
                    3073, 34737, 25,      0 )
GeoAsciiParamsTag(34737)=("UTM Zone 60 N with WGS 84|")
```

For the rest of these examples we will only show the GeoKey-level dump, with the understanding that the actual TIFF-level tag representation can be determined from the documentation.

## F.2.2. United States State Plane zone

We have a USGS State Plane Map of Texas, Central Zone, using NAD83, correctly oriented. The map resolution is 1000 meters/pixel, at origin. There is a grid intersection line in the image at pixel location (50,100), and corresponds to the projected coordinate reference system easting/northing of (949465.0, 3070309.1).

```
ModelTiepointTag = ( 50, 100, 0, 949465.0, 3070309.1, 0)
ModelPixelScaleTag = (1000, 1000, 0)
GeoKeyDirectoryTag:
    GTModelTypeGeoKey = 1 (ModelTypeProjected 2D)
    GTRasterTypeGeoKey = 1 (RasterPixelIsArea)
    ProjectedCRSGeoKey = 32139 (Projected 2D CRS NAD83 / Texas Central)
```

Notice that in this case, since the projected CRS is a standard code, we do not need to define the base Geographic CRS, geodetic datum, etc, since those are implied by the projected CRS code. Also, since this is NAD83, meters are used rather than US Survey feet (as in NAD27).

## F.2.3. Lambert Conformal Conic Aeronautical Chart

We have a 500 x 500 scanned aeronautical chart of Seattle, WA, using Lambert Conformal Conic projection, correctly oriented. The central meridian is at 120 degrees west. The map resolution is 1000 meters/pixel, at origin, and uses NAD27 datum. The standard parallels of the projection are at 41°21'N and 48°40'N. The latitude of the origin is at 45 degrees North, and occurs in the image at the raster coordinates (80,100). The origin is given a false easting and northing of 200000m, 1500000m.

```
ModelTiepointTag = ( 80, 100, 0, 200000, 1500000, 0)
ModelPixelScaleTag = (1000, 1000, 0)
GeoKeyDirectoryTag:
    GTModelTypeGeoKey = 1 (ModelTypeProjected 2D)
    GTRasterTypeGeoKey = 1 (RasterPixelIsArea)
    GeodeticCRSGeoKey = 4267 (GCS_NAD27)
    ProjectedCRSGeoKey = 32767 (user-defined)
    ProjectionGeoKey = 32767 (user-defined)
    ProjLinearUnitsGeoKey = 9001 (Linear_Meter)
    ProjMethodGeoKey = 8 (CT_LambertConfConic_2SP)
        ProjStdParallel1GeoKey = 41.333
        ProjStdParallel2GeoKey = 48.666
        ProjCenterLongGeoKey = -120.0
        ProjNatOriginLatGeoKey = 45.0
        ProjFalseEastingGeoKey, = 200000.0
        ProjFalseNorthingGeoKey, = 1500000.0
```

Notice that the Tiepoint takes the false easting and northing into account when tying the raster point (50,100) to the projection origin.

## F.2.4. DMA ADRG Raster Graphic Map

The U.S. Defense Mapping Agency (now NGA) produces ARC digitized raster graphics datasets by scanning maps and geometrically resampling them into an equirectangular projection, so that they may be directly indexed with WGS 84 geographic coordinates. The upper left corner is 120 degrees West, 32 degrees North. The scale for one map is 0.2 degrees per pixel horizontally, 0.1 degrees per pixel vertically. If stored in a GeoTIFF file it contains the following information:

```
ModelTiepointTag=(0.0, 0.0, 0.0, -120.0, 32.0, 0.0)
ModelPixelScale = (0.2, 0.1, 0.0)
GeoKeyDirectoryTag:
    GTModelTypeGeoKey = 2 (ModelTypeGeographic 2D)
    GTRasterTypeGeoKey = 1 (RasterPixelIsArea)
    GeodeticCRSGeoKey = 4326 (Geographic 2D WGS 84)
```

## F.3. Less Common Examples

### F.3.1. Unrectified Aerial photo, known tiepoints, in degrees.

We have an aerial photo, and know only the WGS 84 GPS location of several points in the scene: the upper left corner is 120 degrees West, 32 degrees North, the lower-left corner is at 120 degrees West, 30 degrees 20 minutes North, and the lower-right hand corner of the image is at 116 degrees 40 minutes West, 30 degrees 20 minutes North. The photo is not geometrically corrected, however, and the complete projection is therefore not known.

```
ModelTiepointTag=( 0.0,    0.0, 0.0,    -120.0,    32.0, 0.0,
                  0.0, 1000.0, 0.0,    -120.0, 30.33333, 0.0,
                  1000.0, 1000.0, 0.0, -116.6666667, 30.33333, 0.0)
GeoKeyDirectoryTag:
    GTModelTypeGeoKey = 1 (ModelTypeGeographic 2D)
    GTRasterTypeGeoKey = 1 (RasterPixelIsArea)
    GeodeticCRSGeoKey = 4326 (Geographic 2D WGS 84)
```

Remark: Since we have not specified the ModelPixelScaleTag, clients reading this GeoTIFF file are not permitted to infer that there is a simple linear relationship between the raster data and the geographic model coordinate space. The only points that are known to be exact are the ones specified in the tiepoint tag.

### F.3.2. Rotated Scanned Map

We have a scanned standard British National Grid, covering the 100km grid zone NZ. Consulting documentation for BNG we find that the southwest corner of the NZ zone has an easting, northing of 400000m, 500000m. This scanned map has a resolution of 100 meter pixels, and was rotated 90 degrees to fit onto the scanner, so that the southwest corner is now the northwest corner. In this case we must use the ModelTransformation tag rather than the tiepoint/scale pair to map the raster data into model space:

```

ModelTransformationTag = ( 0, 100.0, 0, 400000.0,
                          100.0,    0, 0, 500000.0,
                          0,    0, 0,    0,
                          0,    0, 0,    1)
GeoKeyDirectoryTag:
  GTModelTypeGeoKey = 1 ( ModelTypeProjected 2D)
  GTRasterTypeGeoKey = 1 (RasterPixelIsArea)
  ProjectedCRSGeoKey = 27700 (ProjectedCRS OSGB 1936 / British National Grid)
  ProjectedCitationGeoKey = "British National Grid, Zone NZ"

```

Remark: the matrix has 100.0 in the off-diagonals due to the 90 degree rotation; increasing I points north, and increasing J points east.

### F.3.3. Digital Elevation Model

#### Example 1 (DMA)

This DMA (Defense Mapping Agency, now NGA) example stores digital elevation models using an equirectangular projection, so that it may be indexed with WGS 84 geographic coordinates. Since elevation postings are point-values, the pixels should not be considered as filling areas, but as point-values at grid vertices. To accommodate the base elevation of the Angeles Crest forest, the pixel value of 0 corresponds to an elevation of 1000 meters relative to WGS 84 reference ellipsoid. The upper left corner is at 120 degrees West, 32 degrees North, and has a pixel scale of 0.2 degrees/pixel longitude, 0.1 degrees/pixel latitude.

```

ModelTiepointTag=(0.0, 0.0, 0.0, -120.0, 32.0, 1000.0)
ModelPixelScale = (0.2, 0.1, 1.0)
GeoKeyDirectoryTag:
  GTModelTypeGeoKey = 2 (ModelTypeGeographic 2D)
  GTRasterTypeGeoKey = 2 (RasterPixelIsPoint)
  GeodeticCRSGeoKey = 4326 (Geographic 2D WGS 84)
  VerticalGeoKey = 4979 (Geographic 3D WGS 84, used here to document use of
ellipsoidal height)
  VerticalCitationGeoKey = "Geographic 3D WGS 84, Ellipsoidal height"
  VerticalUnitsGeoKey = 9001 (Linear_Meter)

```

Remarks:

1. Note the "RasterPixelIsPoint" raster space, indicating that the DEM posting of the first pixel is at the raster point (0,0,0), and therefore corresponds to 120W,32N exactly.
2. The third value of the "PixelScale" is 1.0 to indicate that a single pixel-value unit corresponds to 1 meter, and the last tiepoint value indicates that base value zero indicates 1000m above the reference surface.

#### Example 2: DGED Level 6 example (DGIWG)

The DGIWG (Defense Geographic Information Working Group) has published a Defense Gridded

Elevation Data (DGED) product specification, including levels ranking between 0 (DTED0) to 9 (#12.5 cm). This example is at Level 6 Geographic and stores digital elevation models using an equirectangular projection, using WGS 84 geographic coordinates. Since elevation postings are point-values, the pixels should not be considered as filling areas, but as point-values at grid vertices. Elevation values are absolute values above geoid EGM 2008 (EPSG code 3855), as the Z coordinate of ModelTiepointTag is 0. The upper left corner is at 12.5 degrees East, 55.7 degrees North, and has a pixel scale of 1.25e-05 degrees/pixel longitude, 8.33e-06 degrees/pixel latitude.

```
ModelTiepointTag=(0.0, 0.0, 0.0, 12.5000063, 55.7000042, 0)
ModelPixelScale = (1.25e-05, 8.3333333e-06, 1.0)
GeoKeyDirectoryTag:
    GTModelTypeGeoKey = 2 (ModelTypeGeographic 2D)
    GTRasterTypeGeoKey = 2 (RasterPixelIsPoint)
    GeodeticCRSGeoKey = 4326 (Geographic 2D WGS 84)
    VerticalGeoKey = 3855 (EGM2008)
    VerticalCitationGeoKey = "EGM2008 geoid height"
    VerticalUnitsGeoKey = 9001 (Linear_Meter)
```

### F.3.4. Spherical Moon Example

#### Introduction

The GeoTIFF standard can be used for images from extraterrestrial bodies as well as the Earth. This Annex illustrates a simple example for a spherical Moon. This example also shows how more custom Earth-base examples could also be defined, highlighting the flexibility of the GeoTiff standard.

#### Example

Note this example (using listgeo), is showing the header values as mapped strings instead of the original short Integer. e.g. GTModelTypeGeoKey = ModelTypeProjected (which is really mapped from value 1).

```
$ listgeo Lunar_LRO_LOLA_Global_LDEM_118m_Mar2014.tif
```

```

Geotiff_Information:
  Version: 1
  Key_Revision: 1.0
  Tagged_Information:
    ModelTiepointTag (2,3):
      0          0          0
      -5458203.076608  2729101.538304  0
    ModelPixelScaleTag (1,3):
      118.4505876      118.4505876      0
  End_Of_Tags.
  Keyed_Information:
    GTModelTypeGeoKey (Short,1): ModelTypeProjected
    GTRasterTypeGeoKey (Short,1): RasterPixelIsArea
    GeodeticCRSGeoKey (Short,1): User-Defined
    GeodeticCitationGeoKey (Ascii,124): "GCS Name = Moon 2000|Datum =
D_Moon_2000|Ellipsoid =
      Moon_2000_IAU_IAG|Primem = Reference_Meridian|AUnits = Decimal_Degree|"
    GeodeticDatumGeoKey (Short,1): User-Defined
    GeogAngularUnitSizeGeoKey (Double,1): 0.0174532925199433
    EllipsoidGeoKey (Short,1): User-Defined
    EllipsoidSemiMajorAxisGeoKey (Double,1): 1737400
    EllipsoidSemiMinorAxisGeoKey (Double,1): 1737400
    PrimeMeridianLongitudeGeoKey (Double,1): 0
    ProjectedCRSGeoKey (Short,1): User-Defined
    ProjectedCitationGeoKey (Ascii,30): "SimpleCylindrical Moon|"
    ProjectionGeoKey (Short,1): User-Defined
    ProjMethodGeoKey (Short,1): CT_Equirectangular
    ProjLinearUnitsGeoKey (Short,1): Linear_Meter
    ProjStdParallel1GeoKey (Double,1): 0
    ProjFalseEastingGeoKey (Double,1): 0
    ProjFalseNorthingGeoKey (Double,1): 0
    ProjCenterLongGeoKey (Double,1): 0
    ProjCenterLatGeoKey (Double,1): 0
  End_Of_Keys.
End_Of_Geotiff.

```

## NOTE

as of writing, listgeo outputs older GeoKey names. The above output has been slightly modified to use the new GeoKey names.



# Annex G: Deprecated and deleted EPSG codes

This section is for documenting backward compatibility of the use of CRS or projection codes in GeoTIFF with version 1.0.

Geotiff v1.0 sections 6.3.2, 6.3.3 and 6.3.4 listed codes for EPSG objects available at that time. Most of these remain valid, although there may have been minor changes to names and other non-essential detail. However since the publication of GeoTIFF v1.0 several of these object records have been either deprecated or deleted from the EPSG Dataset. Deprecated records remain in the EPSG Dataset but are no longer valid; they usually have been superseded by a later record, with a cross reference included in the EPSG Dataset. Deleted records have been removed from the EPSG dataset and the code could be (and in some cases has been) reused for a totally different object. Particular care is needed in the treatment of GeoTIFF files that have used these deleted object records, *shown in italics* in tables G.1 through G.6 below. These tables list the EPSG codes listed in GeoTIFF v1.0 that are no longer valid and which should no longer be used. The list was correct at 29th May 2018. For any later deprecation and replacement of records refer to the EPSG Dataset. Note that the names in the GeoTIFF v1.0 specification and given in these tables have prefixes and underscores not found in the EPSG Dataset.

Table G.1 - Deprecated and deleted EPSG Projected CRS codes

Name given in GeoTIFF v1.0	EPSG CRS Code	Comment
PCS_AGD66_AMG_zone_48	20248	Deprecated in EPSG, no replacement.
PCS_AGD84_AMG_zone_48	20348	Deprecated in EPSG, no replacement.
PCS_AGD84_AMG_zone_57	20357	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>
PCS_AGD84_AMG_zone_58	20358	Deprecated in EPSG, no replacement.
PCS_Lisbon_Portugese_Grid	20700	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>
PCS_Arc_1950_Lo13	20973	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>
PCS_Arc_1950_Lo15	20975	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>
PCS_Arc_1950_Lo17	20977	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>
PCS_Arc_1950_Lo19	20979	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>

<b>Name given in GeoTIFF v1.0</b>	<b>EPSG CRS Code</b>	<b>Comment</b>
PCS_Arc_1950_Lo21	20981	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>
PCS_Arc_1950_Lo23	20983	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>
PCS_Arc_1950_Lo25	20985	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>
PCS_Arc_1950_Lo27	20987	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>
PCS_Arc_1950_Lo29	20989	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>
PCS_Arc_1950_Lo31	20991	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>
PCS_Arc_1950_Lo33	20993	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>
PCS_Arc_1950_Lo35	20995	<i>Deleted in EPSG, code not re-used as at 2018-05-29, no replacement.</i>
PCS_Batavia_NEIEZ	21100	Deprecated in EPSG, replaced by 3001 Batavia / NEIEZ.
PCS_Beijing_Gauss_13N	21473	Deprecated in EPSG, replaced by 21453 Beijing 1954 / Gauss-Kruger 13N.
PCS_Beijing_Gauss_14N	21474	Deprecated in EPSG, replaced by 21454 Beijing 1954 / Gauss-Kruger 14N.
PCS_Beijing_Gauss_15N	21475	Deprecated in EPSG, replaced by 21455 Beijing 1954 / Gauss-Kruger 15N.
PCS_Beijing_Gauss_16N	21476	Deprecated in EPSG, replaced by 21456 Beijing 1954 / Gauss-Kruger 16N.
PCS_Beijing_Gauss_17N	21477	Deprecated in EPSG, replaced by 21457 Beijing 1954 / Gauss-Kruger 17N.
PCS_Beijing_Gauss_18N	21478	Deprecated in EPSG, replaced by 21458 Beijing 1954 / Gauss-Kruger 18N.
PCS_Beijing_Gauss_19N	21479	Deprecated in EPSG, replaced by 21459 Beijing 1954 / Gauss-Kruger 19N.
PCS_Beijing_Gauss_20N	21480	Deprecated in EPSG, replaced by 21460 Beijing 1954 / Gauss-Kruger 20N.
PCS_Beijing_Gauss_21N	21481	Deprecated in EPSG, replaced by 21461 Beijing 1954 / Gauss-Kruger 21N.
PCS_Beijing_Gauss_22N	21482	Deprecated in EPSG, replaced by 21462 Beijing 1954 / Gauss-Kruger 22N.

<b>Name given in GeoTIFF v1.0</b>	<b>EPSG CRS Code</b>	<b>Comment</b>
PCS_Beijing_Gauss_23N	21483	Deprecated in EPSG, replaced by 21463 Beijing 1954 / Gauss-Kruger 23N.
PCS_Bern_1898_Swiss_Old	21790	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 21780 Bern 1898 (Bern) / LV03C.</i>
PCS_Bogota_UTM_zone_17N	21817	Deprecated in EPSG, no replacement.
PCS_Bogota_Colombia_3W	21891	Deprecated in EPSG, replaced by 21896 Bogota 1975 / Colombia West zone.<
PCS_Bogota_Colombia_Bogota	21892	Deprecated in EPSG, replaced by 21897 Bogota 1975 / Colombia Bogota zone.
PCS_Bogota_Colombia_3E	21893	Deprecated in EPSG, replaced by 21898 Bogota 1975 / Colombia East Central zone.
PCS_Bogota_Colombia_6E	21894	Deprecated in EPSG, replaced by 21899 Bogota 1975 / Colombia East.
PCS_Douala_UTM_zone_32N	22832	Deprecated in EPSG, replaced by 2214 Douala 1948 / AOF west.
PCS_Garoua_UTM_zone_33N	23433	Deprecated in EPSG, replaced by 2312 Garoua / UTM zone 33N.
PCS_ID74_UTM_zone_53N	23853	Deprecated in EPSG, no replacement.
PCS_ID74_UTM_zone_46S	23886	Deprecated in EPSG, no replacement.
PCS_Kalianpur_India_IVb	24384	<i>Deleted in EPSG, code not re-used as at 2018-05-29.</i>
PCS_La_Canoa_UTM_zone_21N	24721	<i>Deleted in EPSG, code not re-used as at 2018-05-29.</i>
PCS_Mhast_UTM_zone_32S	26432	Deprecated in EPSG, replaced by 3353 Mhast (onshore) / UTM zone 32S and 3354 Mhast (offshore) / UTM zone 32S.
PCS_Monte_Mario_Italy_1	26591	Deprecated in EPSG, replaced by 3003 Monte Mario / Italy zone 1.
PCS_Monte_Mario_Italy_2	26592	Deprecated in EPSG, replaced by 3004 Monte Mario / Italy zone 2.
PCS_NAD27_California_VII	26747	Deprecated in EPSG, replaced by 26799 NAD27 / California zone VII.
PCS_NAD27_Hawaii_zone_1	26761	<i>Deleted in EPSG, code not re-used as at 2018-05-29.</i>

<b>Name given in GeoTIFF v1.0</b>	<b>EPSG CRS Code</b>	<b>Comment</b>
PCS_NAD27_Hawaii_zone_2	26762	<i>Deleted in EPSG, code not re-used as at 2018-05-29.</i>
PCS_NAD27_Hawaii_zone_3	26763	<i>Deleted in EPSG, code not re-used as at 2018-05-29.</i>
PCS_NAD27_Hawaii_zone_4	26764	<i>Deleted in EPSG, code not re-used as at 2018-05-29.</i>
PCS_NAD27_Hawaii_zone_5	26765	<i>Deleted in EPSG, code not re-used as at 2018-05-29.</i>
PCS_NAD27_BLM_14N_feet	26774	<i>This GeoTIFF v1.0 entry is incorrect. 26774 is NAD27 / Indiana West. NAD27 / BLM 14N (feet) is 32074, see below.</i>
PCS_NAD27_BLM_15N_feet	26775	<i>This GeoTIFF v1.0 entry is incorrect. 26775 is NAD27 / Iowa North. NAD27 / BLM 15N (feet) is 32075, see below.</i>
PCS_NAD27_BLM_16N_feet	26776	<i>This GeoTIFF v1.0 entry is incorrect. 26776 is NAD27 / Iowa South. NAD27 / BLM 16N (feet) is 32076, see below.</i>
PCS_NAD27_BLM_17N_feet	26777	<i>This GeoTIFF v1.0 entry is incorrect. 26777 is NAD27 / Kansas North. NAD27 / BLM 17N (feet) is 32077, see below.</i>
PCS_NAD27_Michigan_North	26788	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 6966 NAD27 / Michigan North.</i>
PCS_NAD27_Michigan_Central	26789	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 6201 NAD27 / Michigan Central.</i>
PCS_NAD27_Michigan_South	26790	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 6202 NAD27 / Michigan South.</i>
PCS_NAD_Michigan_Michigan_East	26801	Deprecated in EPSG, replaced by 5623 NAD27 Michigan / Michigan East.
PCS_NAD_Michigan_Michigan_Old_Central	26802	Deprecated in EPSG, replaced by 5624 NAD27 Michigan / Michigan Old Central.
PCS_NAD_Michigan_Michigan_West	26803	Deprecated in EPSG, replaced by 5625 NAD27 Michigan / Michigan West.
PCS_NAD83_Kentucky_North	26979	Deprecated in EPSG, replaced by 2205 NAD83 / Kentucky North.
PCS_Nahrwan_1967_UTM_38N	27038	Deprecated in EPSG, replaced by 7006 Nahrwan 1934 / UTM zone 38N.
PCS_NTF_France_I	27581	Deprecated in EPSG, replaced by 27571 NTF (Paris) / Lambert zone I.

<b>Name given in GeoTIFF v1.0</b>	<b>EPSG CRS Code</b>	<b>Comment</b>
PCS_NTF_France_II	27582	Deprecated in EPSG, replaced by 27572 NTF (Paris) / Lambert zone II.
PCS_NTF_France_III	27583	Deprecated in EPSG, replaced by 27573 NTF (Paris) / Lambert zone III.
PCS_NTF_Nord_France	27591	Deprecated in EPSG, replaced by 27561 NTF (Paris) / Nord France.
PCS_NTF_Centre_France	27592	Deprecated in EPSG, replaced by 27562 NTF (Paris) / Centre France.
PCS_NTF_Sud_France	27593	Deprecated in EPSG, replaced by 27563 NTF (Paris) / Sud France.
PCS_Pulkovo_Gauss_4N	28464	Deprecated in EPSG, replaced by 2494 Pulkovo 1942 / Gauss-Kruger CM 21E.
PCS_Pulkovo_Gauss_5N	28465	Deprecated in EPSG, replaced by 2495 Pulkovo 1942 / Gauss-Kruger CM 27E.
PCS_Pulkovo_Gauss_6N	28466	Deprecated in EPSG, replaced by 2496 Pulkovo 1942 / Gauss-Kruger CM 33E.
PCS_Pulkovo_Gauss_7N	28467	Deprecated in EPSG, replaced by 2497 Pulkovo 1942 / Gauss-Kruger CM 39E.
PCS_Pulkovo_Gauss_8N	28468	Deprecated in EPSG, replaced by 2498 Pulkovo 1942 / Gauss-Kruger CM 45E.
PCS_Pulkovo_Gauss_9N	28469	Deprecated in EPSG, replaced by 2499 Pulkovo 1942 / Gauss-Kruger CM 51E.
PCS_Pulkovo_Gauss_10N	28470	Deprecated in EPSG, replaced by 2500 Pulkovo 1942 / Gauss-Kruger CM 57E.
PCS_Pulkovo_Gauss_11N	28471	Deprecated in EPSG, replaced by 2501 Pulkovo 1942 / Gauss-Kruger CM 63E.
PCS_Pulkovo_Gauss_12N	28472	Deprecated in EPSG, replaced by 2502 Pulkovo 1942 / Gauss-Kruger CM 69E.
PCS_Pulkovo_Gauss_13N	28473	Deprecated in EPSG, replaced by 2503 Pulkovo 1942 / Gauss-Kruger CM 75E.
PCS_Pulkovo_Gauss_14N	28474	Deprecated in EPSG, replaced by 2504 Pulkovo 1942 / Gauss-Kruger CM 81E.
PCS_Pulkovo_Gauss_15N	28475	Deprecated in EPSG, replaced by 2505 Pulkovo 1942 / Gauss-Kruger CM 87E.
PCS_Pulkovo_Gauss_16N	28476	Deprecated in EPSG, replaced by 2506 Pulkovo 1942 / Gauss-Kruger CM 93E.
PCS_Pulkovo_Gauss_17N	28477	Deprecated in EPSG, replaced by 2507 Pulkovo 1942 / Gauss-Kruger CM 99E.

<b>Name given in GeoTIFF v1.0</b>	<b>EPSG CRS Code</b>	<b>Comment</b>
PCS_Pulkovo_Gauss_18N	28478	Deprecated in EPSG, replaced by 2508 Pulkovo 1942 / Gauss-Kruger CM 105E.
PCS_Pulkovo_Gauss_19N	28479	Deprecated in EPSG, replaced by 2509 Pulkovo 1942 / Gauss-Kruger CM 111E.
PCS_Pulkovo_Gauss_20N	28480	Deprecated in EPSG, replaced by 2510 Pulkovo 1942 / Gauss-Kruger CM 117E.
PCS_Pulkovo_Gauss_21N	28481	Deprecated in EPSG, replaced by 2511 Pulkovo 1942 / Gauss-Kruger CM 123E.
PCS_Pulkovo_Gauss_22N	28482	Deprecated in EPSG, replaced by 2512 Pulkovo 1942 / Gauss-Kruger CM 129E.
PCS_Pulkovo_Gauss_23N	28483	Deprecated in EPSG, replaced by 2513 Pulkovo 1942 / Gauss-Kruger CM 135E.
PCS_Pulkovo_Gauss_24N	28484	Deprecated in EPSG, replaced by 2514 Pulkovo 1942 / Gauss-Kruger CM 141E.
PCS_Pulkovo_Gauss_25N	28485	Deprecated in EPSG, replaced by 2515 Pulkovo 1942 / Gauss-Kruger CM 147E.
PCS_Pulkovo_Gauss_26N	28486	Deprecated in EPSG, replaced by 2516 Pulkovo 1942 / Gauss-Kruger CM 153E.
PCS_Pulkovo_Gauss_27N	28487	Deprecated in EPSG, replaced by 2517 Pulkovo 1942 / Gauss-Kruger CM 159E.
PCS_Pulkovo_Gauss_28N	28488	Deprecated in EPSG, replaced by 2518 Pulkovo 1942 / Gauss-Kruger CM 165E.
PCS_Pulkovo_Gauss_29N	28489	Deprecated in EPSG, replaced by 2519 Pulkovo 1942 / Gauss-Kruger CM 171E.
PCS_Pulkovo_Gauss_30N	28490	Deprecated in EPSG, replaced by 2520 Pulkovo 1942 / Gauss-Kruger CM 177E.
PCS_Pulkovo_Gauss_31N	28491	Deprecated in EPSG, replaced by 2521 Pulkovo 1942 / Gauss-Kruger CM 177W.
PCS_Pulkovo_Gauss_32N	28492	Deprecated in EPSG, replaced by 2522 Pulkovo 1942 / Gauss-Kruger CM 171W.
PCS_SAD69_UTM_zone_18N	29118	Deprecated in EPSG, replaced by 29168 SAD69 / UTM zone 18N.
PCS_SAD69_UTM_zone_19N	29119	Deprecated in EPSG, replaced by 29169 SAD69 / UTM zone 19N.
PCS_SAD69_UTM_zone_20N	29120	Deprecated in EPSG, replaced by 29170 SAD69 / UTM zone 20N.
PCS_SAD69_UTM_zone_21N	29121	Deprecated in EPSG, replaced by 29171 SAD69 / UTM zone 21N.

Name given in GeoTIFF v1.0	EPSG CRS Code	Comment
PCS_SAD69_UTM_zone_22N	29122	Deprecated in EPSG, replaced by 29172 SAD69 / UTM zone 22N.
PCS_SAD69_UTM_zone_17S	29177	Deprecated in EPSG, replaced by 29187 SAD69 / UTM zone 17S.
PCS_SAD69_UTM_zone_18S	29178	Deprecated in EPSG, replaced by 29188 SAD69 / UTM zone 18S.
PCS_SAD69_UTM_zone_19S	29179	Deprecated in EPSG, replaced by 29189 SAD69 / UTM zone 19S.
PCS_SAD69_UTM_zone_20S	29180	Deprecated in EPSG, replaced by 29190 SAD69 / UTM zone 20S.
PCS_SAD69_UTM_zone_21S	29181	Deprecated in EPSG, replaced by 29191 SAD69 / UTM zone 21S.
PCS_SAD69_UTM_zone_22S	29182	Deprecated in EPSG, replaced by 29192 SAD69 / UTM zone 22S.
PCS_SAD69_UTM_zone_23S	29183	Deprecated in EPSG, replaced by 29193 SAD69 / UTM zone 23S.
PCS_SAD69_UTM_zone_24S	29184	Deprecated in EPSG, replaced by 29194 SAD69 / UTM zone 24S.
PCS_SAD69_UTM_zone_25S	29185	Deprecated in EPSG, replaced by 29195 SAD69 / UTM zone 25S.
PCS_Sudan_UTM_zone_35N	29635	Deprecated in EPSG, replaced by 20135 Adindan / UTM zone 35N.
PCS_Sudan_UTM_zone_36N	29636	Deprecated in EPSG, replaced by 20136 Adindan / UTM zone 36N.
PCS_Tananarive_Laborde	29700	Deprecated in EPSG, replaced by 20701 Tananarive (Paris) / Laborde Grid and 29702 Tananarive (Paris) / Laborde Grid approximation.
PCS_Timbalai_1948_Borneo	29800	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 29873 Timbalai 1948 / RSO Borneo (m).</i>
PCS_TM65_Irish_Nat_Grid	29900	Deprecated in EPSG, replaced by 29903 TM65 / Irish Grid.
PCS_Voirol_Unifie_N_Algerie	30591	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 30791 Nord Sahara 1959 / Nord Algerie.</i>
PCS_Voirol_Unifie_S_Algerie	30592	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 30792 Nord Sahara 1959 / Sud Algerie.</i>
PCS_Bern_1938_Swiss_New	30600	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 21780 Bern 1898 (Bern) / LV03C.</i>

<b>Name given in GeoTIFF v1.0</b>	<b>EPSG CRS Code</b>	<b>Comment</b>
PCS_MGI_Austria_West	31291	Deprecated in EPSG, replaced by 31281 MGI (Ferro) / Austria West Zone.
PCS_MGI_Austria_Central	31292	Deprecated in EPSG, replaced by 31282 MGI (Ferro) / Austria Central Zone.
PCS_MGI_Austria_East	31293	Deprecated in EPSG, replaced by 31283 MGI (Ferro) / Austria East Zone.
PCS_DHDN_Germany_zone_1	31491	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 5520 DHDN / 3-degree Gauss-Kruger zone 1.</i>
PCS_DHDN_Germany_zone_2	31492	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 31466 DHDN / 3-degree Gauss-Kruger zone 2.</i>
PCS_DHDN_Germany_zone_3	31493	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 31467 DHDN / 3-degree Gauss-Kruger zone 3.</i>
PCS_DHDN_Germany_zone_4	31494	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 31468 DHDN / 3-degree Gauss-Kruger zone 4.</i>
PCS_DHDN_Germany_zone_5	31495	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 31469 DHDN / 3-degree Gauss-Kruger zone 5.</i>
PCS_NAD27_New_York_Long_Is	32018	Deprecated in EPSG, replaced by 4456 NAD27 / New York Long Island.
PCS_NAD27_Pennsylvania_S	32029	Deprecated in EPSG, replaced by 4455 NAD27 / Pennsylvania South.
PCS_NAD27_Tennessee	32036	Deprecated in EPSG, replaced by 2204 NAD27 / Tennessee.
PCS_NAD27_Puerto_Rico	32059	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 3991 Puerto Rico State Plane CS of 1927.</i>
PCS_NAD27_St_Croix	32060	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 3992 Puerto Rico / St. Croix.</i>
PCS_NAD27_BLM_14N_feet	32074	Deprecated in EPSG, replaced by 32064 NAD27 / BLM 14N (ftUS).
PCS_NAD27_BLM_15N_feet	32075	Deprecated in EPSG, replaced by 32065 NAD27 / BLM 15N (ftUS).
PCS_NAD27_BLM_16N_feet	32076	Deprecated in EPSG, replaced by 32066 NAD27 / BLM 16N (ftUS).



<b>Name given in GeoTIFF v1.0</b>	<b>EPSG CRS Code</b>	<b>Comment</b>
PCS_NAD27_BLM_17N_f eet	32077	Deprecated in EPSG, replaced by 32067 NAD27 / BLM 17N (ftUS).

*Table G.2 - Deprecated and deleted EPSG Geodetic CRS codes*

<b>Name given in GeoTIFF v1.0</b>	<b>EPSG CRS Code</b>	<b>Comment</b>
GCS_Bern_1898	4217	<i>Deleted in EPSG, code reassigned to NAD83 / BLM 59N (ftUS) projected CRS, entity not replaced.</i>
GCS_Cote_d_Ivoire	4226	Deprecated in EPSG, replaced by 4142 Locodjo 1965 and 4143 Abidjan 1987.
GCS_Douala	4228	Deprecated in EPSG, replaced by 4192 Douala 1948.
GCS_Gandajika_1970	4233	Deprecated in EPSG, replaced by 4684 Gan 1970 and 4685 Gandajika.
GCS_Garoua	4234	Deprecated in EPSG, replaced by 4197 Garoua.
GCS_Guyane_Francaise	4235	Deprecated in EPSG, replaced by 4623 CSG67.
GCS_Manoca	4260	Deprecated in EPSG, replaced by 4193 Manoca 1962.
GCS_Mhast	4264	Deprecated in EPSG, replaced by 4704 Mhast (onshore) and 4705 Mhast (offshore).
GCS_NAD_Michigan	4268	Deprecated in EPSG, replaced by 4267 NAD27.
GCS_Qornoq	4287	Deprecated in EPSG, replaced by 4194 Qornoq 1927.
GCS_RT38	4290	<i>Deleted in EPSG, code re-used for a coordinate transformation, entity replaced by 4308 RT38.</i>
GCS_SAD69	4291	Deprecated in EPSG, replaced by 4618 SAD69.
GCS_Segora	4294	Deprecated in EPSG, replaced by 4613 Segara.
GCS_Sudan	4296	Deprecated in EPSG, replaced by 4201 Adindan.
GCS_Voirol_Unifie	4305	<i>Deleted in EPSG, code re-used for a map projection, entity replaced by 4307 Nord Sahara 1959.</i>
GCS_Voirol_Unifie_Paris	4812	<i>Deleted in EPSG, code reassigned to New Beijing / 3- degree Gauss-Kruger CM 132E projected CRS, entity replaced by 4819 Nord Sahara 1959 (Paris).</i>
GCS_NDG_Paris	4902	Deprecated in EPSG, replaced by 4901 ATF (Paris)
GCSE_Clarke1866Michig an	4009	Deprecated in EPSG, no replacement.

<b>Name given in GeoTIFF v1.0</b>	<b>EPSG CRS Code</b>	<b>Comment</b>
GCSE_Everest1830_1975 Definition	4017	<i>Deleted in EPSG, code reassigned to MOLDREF99 geographic 3D CRS, entity replaced by 4045 Unknown datum based upon the Everest 1830 (1975 Definition) ellipsoid.</i>
GCSE_International1967	4023	<i>Deleted in EPSG, code reassigned to MOLDREF99 geographic 2D CRS, entity replaced by 4036 Unknown datum based upon the GRS 1967 ellipsoid.</i>
GCSE_NWL10D	4026	<i>Deleted in EPSG, code reassigned to MOLDREF99 / Moldova TM projected CRS, entity not replaced.</i>
GCSE_Sphere	4035	<i>Deprecated in EPSG, replaced by 4047 Unspecified datum based upon the GRS 1980 Authalic Sphere.</i>

*Table G.3 - Deprecated and deleted EPSG Unit of Measure codes*

<b>Name given in GeoTIFF v1.0</b>	<b>EPSG CRS Code</b>	<b>Comment</b>
Linear_Foot_Modified_American	9004	<i>Deleted in EPSG, code not re-used as at 2018-05-29.</i>
Linear_Foot_Indian	9006	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 9080 Indian foot, 9081 Indian foot (1937), 9082 Indian foot (1962) and 9083 Indian foot (1975).</i>
Linear_Link	9007	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 9098 link.</i>
Linear_Link_Benoit	9008	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 9053 British link (Benoit 1895 A) and 9063 British link (Benoit 1895 B).</i>
Linear_Link_Sears	9009	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 9043 British link (Sears 1922).</i>
Linear_Chain_Benoit	9010	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 9052 British chain (Benoit 1895 A) and 9062 British chain (Benoit 1895 B).</i>
Linear_Chain_Sears	9011	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 9042 British chain (Sears 1922).</i>
Linear_Yard_Sears	9012	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 9040 British yard (Sears 1922).</i>

<b>Name given in GeoTIFF v1.0</b>	<b>EPSG CRS Code</b>	<b>Comment</b>
Linear_Yard_Indian	9013	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 9084 Indian yard, 9085 Indian yard (1937), 9086 Indian yard (1962) and 9087 Indian yard (1975).</i>
Linear_Mile_International_Nautical	9015	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 9030 nautical mile.</i>

*Table G.4 - Deprecated and deleted EPSG Geodetic Datum codes*

<b>Name given in GeoTIFF v1.0</b>	<b>EPSG CRS Code</b>	<b>Comment</b>
Datum_Bern_1898	6217	<i>Deleted in EPSG, code not re-used as at 2018-05-29, entity not replaced.</i>
Datum_Cote_d'Ivoire	6226	Deprecated in EPSG, replaced by 6142 Locodjo 1965 and 6143 Abidjan 1987.
Datum_Douala	6228	Deprecated in EPSG, replaced by 6192 Douala 1948.
Datum_Gandajika_1970	6233	Deprecated in EPSG, replaced by 6684 Gan 1970 and 6685 Gandajika.
Datum_Garoua	6234	Deprecated in EPSG, replaced by 6197 Garoua.
Datum_Guyane_Francaise	6235	Deprecated in EPSG, replaced by 6623 CSG67.
Datum_Manoca	6260	Deprecated in EPSG, replaced by 6193 Manoca 1962.
Datum_Mhast	6264	Deprecated in EPSG, replaced by 6704 Mhast (onshore) and 6705 Mhast (offshore).
Datum_NAD_Michigan	6268	Deprecated in EPSG, replaced by 6267 North American Datum 1927.
Datum_Qornoq	6287	Deprecated in EPSG, replaced by 6194 Qornoq 1927.
Datum_RT38	6290	<i>Deleted in EPSG, code not re-used as at 2018-05-29, entity replaced by 6308 Stockholm 1938.</i>
Datum_South_American_Datum_1969	6291	Deprecated in EPSG, replaced by 6618 SAD69.
Datum_Segara	6294	Deprecated in EPSG, replaced by 6613 Gunung Segara.
Datum_Sudan	6296	Deprecated in EPSG, replaced by 6201 Adindan.
Datum_Voirol_Unifie_1960	6305	<i>Deleted in EPSG, code not re-used as at 2018-05-29, entity replaced by 6307 Nord Sahara 1959.</i>

Name given in GeoTIFF v1.0	EPSG CRS Code	Comment
Datum_Nord_de_Guerre	6902	Deprecated in EPSG, replaced by 6901 ATF (Paris)

Table G.5 - Deprecated and deleted EPSG Ellipsoid codes

Name given in GeoTIFF v1.0	EPSG CRS Code	Comment
Ellipse_Bessel_Namibia	7006	Deprecated in EPSG, replaced by 7046 Bessel Namibia (GLM).
Ellipse_Clarke_1866_Michigan	7009	Deprecated in EPSG, replaced by 7008 Clarke 1866.
Ellipse_Everest_1830_1975_Definition	7017	Deleted in EPSG, code not re-used as at 2018-05-29, entity not replaced.
Ellipse_International_1967	7023	Deleted in EPSG, code not re-used as at 2018-05-29, entity replaced by 7036 GRS 1967 and 7050 GRS 1967 Modified.
Ellipse_NWL_10D	7026	Deleted in EPSG, code not re-used as at 2018-05-29, entity not replaced.
Ellipse_Sphere	7035	Deprecated in EPSG, replaced by 7047 GRS 1980 Authalic Sphere.

Table G.6 - Deprecated and deleted EPSG Map projection codes

Name given in GeoTIFF v1.0	EPSG CRS Code	Comment
Proj_California_CS27_VII	10407	Deprecated in EPSG, replaced by 10408 California CS27 zone VII.
Proj_Kentucky_CS83_North	11631	Deprecated in EPSG, replaced by 15303 Kentucky CS83 North zone (metres).
Proj_Michigan_CS27_North	12111	Deprecated in EPSG, replaced by 6965 Michigan CS27 North zone.
Proj_Michigan_CS27_Central	12112	Deprecated in EPSG, replaced by 6198 Michigan CS27 Central zone.
Proj_Michigan_CS27_South	12113	Deprecated in EPSG, replaced by 6199 Michigan CS27 South zone.
Proj_New_York_CS27_Long_Island	13104	Deprecated in EPSG, replaced by 4454 New York CS27 Long Island zone.
Proj_Pennsylvania_CS27_South	13702	Deprecated in EPSG, replaced by 4436 Pennsylvania CS27 South zone.
Proj_BLM_14N_feet	15914	BLM zone 14N (US survey feet) (incorrect unit in GeoTIFF v1.0 specification).

<b>Name given in GeoTIFF v1.0</b>	<b>EPSG CRS Code</b>	<b>Comment</b>
Proj_BLM_15N_feet	15915	<i>BLM zone 15N (US survey feet) (incorrect unit in GeoTIFF v1.0 specification).</i>
Proj_BLM_16N_feet	15916	<i>BLM zone 16N (US survey feet) (incorrect unit in GeoTIFF v1.0 specification).</i>
Proj_BLM_17N_feet	15917	<i>BLM zone 17N (US survey feet) (incorrect unit in GeoTIFF v1.0 specification).</i>
Proj_RSO_Borneo	19912	<i>Deleted in EPSG, code not re-used as at 2018-05-29, replaced by 19956 Rectified Skew Orthomorphic Borneo Grid (chains), 19957 Rectified Skew Orthomorphic Borneo Grid (feet) and 19958 Rectified Skew Orthomorphic Borneo Grid (metres).</i>

# Annex H: Backward compatibility

This revision 1.1 of GeoTIFF is aimed at being backward compatible with the 1.0 version (dated 1995, including last revision dating December 2000, as available at <http://geotiff.maptools.org/spec/geotiffhome.html>), both for coordinate reference systems based on EPSG register codes or user-defined coordinate reference systems.

This annex provides the description of the changes.

- Alignment of Terminology with the ISO TC211 and OGC Abstract Specification Topic 2 - referencing by coordinates. An example of this is the term 'Coordinate System' in GeoTIFF v1.0 (which was in fact a Coordinate Reference System), renamed 'Coordinate Reference System' in this document.
- As a consequence of these terminology changes, some GeoKey names have been changed and clarified (but the corresponding code values have been preserved). See [Table E.1 - Summary of GeoKey IDs and names](#)
- Use of EPSG register codes instead of static codes: this allows a modernization of GeoTIFF and the use of any EPSG coordinate reference systems including those introduced since 1995. This is a significant added value of this revision.
- Clarification of the VerticalGeoKeys (previously named Vertical CS Keys). This is the 2nd significant provision of this revision, which now gives clear GeoTIFF identification of elevation data and their vertical reference.
- Clarification of requirements (which were previously identified by "is" or "shall"), according to OGC rules.
- Addition of Annex A (Abstract test suite).
- Clarification of clauses and descriptive statements on the geodetic sections, including Coordinate Reference Systems, projection, datums, thanks to a full revision from Roger Lott (IOGP) and chair of OGC CRS standards working group.
- Deprecation of EPSG codes that have been either deprecated or deleted from the EPSG Dataset (see [Table G.1 - Deprecated and deleted EPSG Projected CRS codes](#)).
- Deprecation of GeoTIFF v1.0 Ellipsoid Vertical CS Codes, see item b/ in [Geographic 3D CRS](#).
- Suppression of Intergraph tag, which was already deprecated in 1.0, and which is no longer in use (this has been confirmed by "Hexagon Geospatial").

# Annex I: Revision History

Date	Release	Editor	Primary clauses modified	Description
2016-04-28	0.1	T. Habermann	all	initial version
2018-06-07	0.2	C. Heazel	all	AsciiDoc version
2019-01-07	0.3	E. Devys, R. Lott, E. Rouault	update of all geographic requirements & content	revised AsciiDoc version
2019-06-05	0.5	C. Heazel	all	Applied changes recommended by OGC Naming Authority
2019-09-10	1.1	E. Devys, R. Lott	Introduction of chapter 7, 7.4.4 + Annex D.3	update for publishing
2020-10-27	1.1 (this document)	E. Devys, R. Lott	Adjustment of TIFF as publicly available spec. in 1- Scope + clarification of Annex D.3	update for publishing

# Annex J: Bibliography

**GeoTIFF Format Specification**, Ritter, Niles & Ruth, Mike, October 31, 1995, revised December 2000

Note: The GeoTIFF standard, dated 1995, has undergone minor adjustments and was republished in 2000. The resulting specification, referenced as GeoTIFF 1.0, is available at <http://geotiff.maptools.org/spec/geotiffhome.html>

GeoTIFF profile for Georeferenced Imagery, DGIWG 108, 2017-12-08, Retrieved from [https://portal.dgiwg.org/files/?artifact\\_id=68102&format=pdf](https://portal.dgiwg.org/files/?artifact_id=68102&format=pdf)

Ritter, N., & Ruth, M. (1997). The GeoTiff data interchange standard for raster geographic images. *International Journal of Remote Sensing*, 18(7), 1637–1647. doi:10.1080/014311697218340Ritter

Wiggins, R. H., Davidson, H. C., Harnsberger, H. R., Lauman, J. R., & Goede, P. a. (2001). Image file formats: past, present, and future. *Radiographics : a review publication of the Radiological Society of North America, Inc*, 21(3), 789–98. Retrieved from <http://www.ncbi.nlm.nih.gov/pubmed/11353125>