

Different Quantum and Quantum Inspired approaches DNA Pattern Matching: A Comparative Study

1 Introduction

This work presents three distinct approaches to DNA pattern matching: a quantum-inspired Aho-Corasick algorithm, a baseline Grover search implementation, and an optimized Grover algorithm with quantum hashing. We provide theoretical analysis, implementation details, and complexity comparisons for each approach.

DNA pattern matching is a fundamental problem in bioinformatics with applications in genome analysis, sequence alignment, and motif discovery. Classical algorithms like Aho-Corasick achieve linear time complexity but require sequential processing. Quantum algorithms offer potential advantages through superposition and amplitude amplification.

2 Algorithm 1: Quantum-Inspired Aho-Corasick

2.1 Algorithm Overview

The quantum-inspired Aho-Corasick algorithm combines classical automaton construction with quantum measurement simulation:

1. **Classical Preprocessing:** Build traditional Aho-Corasick trie with failure links
2. **Quantum Simulation:** Create quantum circuit simulating automaton traversal
3. **Hybrid Execution:** Use classical state transitions with quantum pattern marking

Basically this is a quantum inspired one with limited quantum elements on the algorithm. However we can run real world example and can be used for educational purposes.

2.2 Code

```
1 def build_classical_trie(self, patterns):
2     root = {'failure': root, 'output': []}
3
4     # Build trie structure
5     for pattern_id, pattern in enumerate(patterns):
6         current = root
7         for symbol in pattern:
8             current = current.setdefault(symbol, {})
9             if 'output' not in current:
10                 current['output'] = []
11             current['output'].append((pattern_id, pattern))
12
13     # Build failure links using BFS
14     queue = deque()
15     for symbol in ['A', 'C', 'G', 'T']:
16         if symbol in root:
17             root[symbol]['failure'] = root
18             queue.append(root[symbol])
19         else:
20             root[symbol] = root
21
22     while queue:
23         current = queue.popleft()
24         for symbol in ['A', 'C', 'G', 'T']:
25             if symbol in current:
26                 child = current[symbol]
27                 failure = current['failure']
28                 while symbol not in failure and failure != root:
29                     failure = failure['failure']
30                 child['failure'] = failure[symbol] if symbol in
failure else root
31                 child['output'].extend(failure[symbol]['output'])
32                 queue.append(child)
```

Listing 1: Trie Construction with Failure Links

```
1 def quantum_simulate_aho_corasick(self, text, patterns):
2     trie = self.build_classical_trie(patterns)
3     states, state_mapping = self._enumerate_states(trie)
4
5     state_qubits = max(1, ceil(np.log2(len(states))))
6     pattern_qubits = len(patterns)
7
8     qr_state = QuantumRegister(state_qubits, 'state')
9     qr_patterns = QuantumRegister(pattern_qubits, 'patterns')
10    qc = QuantumCircuit(qr_state, qr_patterns)
11
12    # Process text with hybrid classical-quantum approach
13    current_state = trie
14    for i, symbol in enumerate(text):
15        # Classical automaton traversal
16        while symbol not in current_state and current_state != trie
:
17            current_state = current_state['failure']
18
```

```

19     if symbol in current_state:
20         current_state = current_state[symbol]
21
22     # Quantum pattern marking
23     if current_state['output']:
24         for pattern_id, pattern in current_state['output']:
25             qc.mcx(qr_state, qr_patterns[pattern_id])

```

Listing 2: Quantum Circuit Simulation

2.3 Complexity Analysis

Phase	Time Complexity	Space Complexity
Trie Construction	$O(\sum P_i)$	$O(\sum P_i)$
Failure Link Building	$O(\sum P_i)$	$O(\sum P_i)$
Pattern Matching	$O(n + \text{matches})$	$O(\log \text{states})$ qubits

Table 1: Quantum-Inspired Aho-Corasick Complexity

3 Algorithm 2: Baseline Grover Search

3.1 Algorithm Overview

The baseline Grover implementation uses amplitude amplification for pattern matching:

1. **Superposition:** Initialize uniform superposition over all positions
2. **Oracle:** Mark positions containing target patterns
3. **Diffusion:** Amplify marked state amplitudes
4. **Measurement:** Extract match positions

Theorem 1 (Grover Speedup). *For M matches in a search space of size N , Grover’s algorithm finds a solution with high probability using $O(\sqrt{N/M})$ oracle queries.*

Proof. The proof follows from the geometry of amplitude amplification:

$$|\psi_0\rangle = \frac{1}{\sqrt{N}} \sum_{x=0}^{N-1} |x\rangle \quad (1)$$

$$G = -H^{\otimes n} X^{\otimes n} H^{\otimes n} \cdot O \quad (2)$$

$$|\psi_k\rangle = G^k |\psi_0\rangle \quad (3)$$

where each iteration rotates the state vector by $\theta = 2 \arcsin(2\sqrt{M(N-M)/N^2})$. $\square$

3.2 Code

```

1 def oracle_multi(text, patterns):
2     L = len(patterns[0])
3     n = len(text)
4     S = n - L + 1
5     n_idx = ceil(log2(S))
6
7     # Quantum registers
8     idx = QuantumRegister(n_idx, 'idx')
9     char = QuantumRegister(2*L, 'char')
10    match = QuantumRegister(1, 'match')
11
12    qc = QuantumCircuit(idx, char, match)
13
14    # Load substring at each position
15    for k in range(L):
16        for pos in range(S):
17            j = pos + k
18            b1, b0 = dna2bits[text[j]]
19            bits = int2bits(pos, n_idx)
20
21            # Controlled loading based on position
22            ctrls = [idx[q] for q, b in enumerate(bits) if b]
23            neg_ctrls = [idx[q] for q, b in enumerate(bits) if not
b]
24
25            for q in neg_ctrls: qc.x(q)
26            if b0: qc.mcx(ctrls + neg_ctrls, char[2*k])
27            if b1: qc.mcx(ctrls + neg_ctrls, char[2*k + 1])
28            for q in neg_ctrls: qc.x(q)
29
30    # Phase kickback for pattern matching
31    qc.x(match)
32    qc.h(match)
33
34    for pat in patterns:
35        # Mark matching patterns
36        for k, base in enumerate(pat):
37            b1, b0 = dna2bits[base]
38            if not b0: qc.x(char[2*k])
39            if not b1: qc.x(char[2*k + 1])
40
41    qc.mct(char, match) # Multi-controlled phase flip
42
43    # Uncompute
44    for k, base in reversed(list(enumerate(pat))):
45        b1, b0 = dna2bits[base]
46        if not b0: qc.x(char[2*k])
47        if not b1: qc.x(char[2*k + 1])

```

Listing 3: Oracle Construction

```

1 def grover_multi_patterns(text, patterns, shots=10000):
2     # Calculate optimal iterations
3     N = 2**n_idx
4     M = len([i for i in range(S) if any(text[i:i+L] == pat for pat
in patterns)])

```

```

5     k = max(1, round((pi/4) * sqrt(N/M))) if M > 0 else 1
6
7     # Apply Grover operator
8     Uf = oracle_multi(text, patterns)
9     D = diffuser(n_idx)
10
11    for _ in range(k):
12        qc.append(Uf, qc.qubits)
13        qc.append(D, idx[:])

```

Listing 4: Grover Iterations

4 Algorithm 3: Optimized Grover with Quantum Hashing

4.1 Algorithm Overview

The optimized implementation introduces several key improvements:

1. **Quantum Hashing:** Convert patterns to hash values for efficient comparison
2. **Optimized QRAM:** Efficient substring loading with multiplexed addressing
3. **Ancilla Management:** Minimize auxiliary qubits through reversible computation
4. **Linear Diffuser:** Reduce gate complexity in amplitude amplification

Definition 1 (Quantum Hash Function). *For a DNA pattern $P = p_1p_2 \dots p_L$, the quantum hash is:*

$$H(P) = \sum_{i=1}^L \text{DNA2BITS}(p_i) \cdot 2^{2(i-1)}$$

where DNA2BITS maps $\{A, C, G, T\} \rightarrow \{00, 01, 10, 11\}$.

4.2 Code

```

1 def quantum_substring_loader(qc, idx_reg, char_reg, text, L, n_idx)
2     :
3     n = len(text)
4     S = n - L + 1
5
6     # Efficient character-by-character loading
7     for k in range(L):
8         for pos in range(S):
9             addr = pos + k
10            base = text[addr]

```

```

10         b0, b1 = DNA2BITS[base]
11
12         # Binary representation of position
13         bit_rep = [(pos >> i) & 1 for i in range(n_idx)]
14         flip_list = [idx_reg[i] for i in range(n_idx) if
bit_rep[i] == 0]
15         controls = list(idx_reg)
16
17         # Controlled character loading
18         if flip_list:
19             qc.x(flip_list)
20
21         if b0: qc.mcx(controls, char_reg[2*k])
22         if b1: qc.mcx(controls, char_reg[2*k+1])
23
24         if flip_list:
25             qc.x(flip_list) # Uncompute

```

Listing 5: Optimized Substring Loading

```

1 def optimized_oracle(text, patterns):
2     # Load substring
3     quantum_substring_loader(qc, idx, char, text, L, n_idx)
4
5     # Compute hash
6     for i in range(2*L):
7         qc.cx(char[i], hash_reg[i])
8
9     # Pattern matching via hash comparison
10    pattern_hashes = pattern_hash(patterns)
11    for hash_val in pattern_hashes:
12        # Prepare hash comparison
13        for bit in range(2*L):
14            if (hash_val >> bit) & 1 == 0:
15                qc.x(hash_reg[bit])
16
17        # Phase kickback
18        qc.h(match)
19        qc.mct(hash_reg, match[0], ancillas, mode='recursion')
20        qc.h(match)
21
22        # Uncompute
23        for bit in range(2*L):
24            if (hash_val >> bit) & 1 == 0:
25                qc.x(hash_reg[bit])
26
27    # Uncompute hash and substring
28    for i in range(2*L):
29        qc.cx(char[i], hash_reg[i])
30    quantum_substring_loader(qc, idx, char, text, L, n_idx)

```

Listing 6: Pattern Hashing Oracle

5 Comparative Analysis

This is a comparative analysis of all separate complexities:

Metric	Quantum Aho-Corasick	Baseline Grover	Optimized Grover
Time Complexity	$O(n + \text{matches})$	$O(\sqrt{N} \cdot 2^L)$	$O(\sqrt{N} \cdot L)$
Space Complexity	$O(\log \text{states})$	$O(\log N + L)$	$O(\log N + L)$
Preprocessing	$O(\sum P_i)$	$O(1)$	$O(P)$
Quantum Advantage	Simulation only	Quadratic speedup	Quadratic + efficiency

Table 2: Algorithm Comparison

6 Practical Considerations

Resource	Aho-Corasick	Baseline Grover	Optimized Grover
Logical Qubits	$\log(\text{states}) + P $	$\log N + 2L + 1$	$\log N + 4L + 3$
Circuit Depth	$O(n)$	$O(\sqrt{N} \cdot L)$	$O(\sqrt{N} \cdot \log L)$
Coherence Time	Linear in n	$O(\sqrt{N})$	$O(\sqrt{N})$
Error Correction	Moderate	High	Moderate

Table 3: Quantum Resource Requirements

6.1 Classical vs. Quantum Advantage

The quantum advantage depends on several factors:

- **Database Size:** Quantum speedup becomes significant for $N > 10^6$
- **Pattern Length:** Classical methods dominate for $L > \log_2 \sqrt{N}$
- **Hardware Constraints:** Current NISQ devices limit practical implementations
- **Error Rates:** Quantum error correction overhead affects real-world performance

7 Implementation Results

7.1 Verification Results

All three implementations were tested on identical DNA sequences:

```

1 text = "ACGTACGTACGTACGT"
2 patterns = ["ACGT", "GTAC"]
3

```




Figure 1: Algorithmic scaling comparison

```

4 # Expected matches:
5 # "ACGT" at positions: [0, 4, 8, 12]
6 # "GTAC" at positions: [2, 6, 10]

```

Listing 7: Test Configuration

Results showed perfect agreement between classical and quantum implementations, validating the correctness of all approaches.

7.2 Performance Metrics

Implementation	Success Rate	Circuit Depth	Execution Time
Quantum Aho-Corasick	100%	45	0.12s
Baseline Grover	95%	128	0.34s
Optimized Grover	98%	67	0.19s

Table 4: Simulation Performance (16-base sequence, 2 patterns)




Figure 2: Gate complexity scaling with pattern length

8 Conclusion

This comparative study demonstrates three distinct approaches to quantum DNA pattern matching:

1. **Quantum Aho-Corasick:** Maintains classical efficiency while enabling quantum simulation
2. **Baseline Grover:** Provides theoretical quadratic speedup with high resource requirements
3. **Optimized Grover:** Achieves practical quantum advantage through algorithmic improvements

The choice of algorithm depends on specific requirements:

- Use **Quantum Aho-Corasick** for near-term applications with classical performance guarantees
- Use **Baseline Grover** for theoretical studies and proof-of-concept implementations
- Use **Optimized Grover** for practical quantum advantage in large-scale pattern matching, when scalable quantum computers will be available.