

Understanding the problem



**University of
Sheffield**

**Implamenting multistage constant-current charging
methods in lithium based batterys to reduce
degredation**

George W. Kirby

200328186

November 18, 2025

Supervisor: Dr. Ross Drummond

Contents

1 Introduction

There are currently over 7 billion people with access to electricity [?], the global consumption of energy is rising by 4.5×10^{16} Joules every year; 77% of which is from utilising non-renewable sources. With the affects of non-renewables on the environment still not fully realised, coupled with the concern of their finite-life nature, poses a constant need to increase usage of renewable sources. However, a large set of renewable generation methods fall under the category of variable renewable energy (VRE) sources [?], thus requiring a robust form of energy storage to solve the intermittent availability - methods of storage do exist and suitable solutions depend on the specifics and locations; as battery technology increases, the use of battery as a storage medium for the energy sector are ever more increasing. There is also the rapid increase in electric vehicle production, with a push to increase the adoption of EV's, 17.3 million cars were produced in 2024 [?] alone with a recent 20% average year-on increase. Lithium Ion batteries (LIB's) are the most common currently used batteries due to their desirable characteristics in energy density, aging properties, cost and more.

EV's and the energy sector account now account for 90% of the total lithium ion battery demand since 2016, the total lithium-ion battery demand is 10-times larger [?] since 2016. Different resources predict different forecasts of total battery growth [?, ?], regardless, it appears the rate of demand will not be decreasing in the near future.

LIB's, like all batteries and decrease in performance and capacity [?] until they are deemed unsuitable for their current use. This means eventually, all current batteries in use today will need to be disposed of, given that over 660,000 tonnes of earth metals were mined in 2023 alone, a strong case for slowing down the need for mining new materials is made, whilst keeping up with the demand (cite the IEA thing). It's noted that battery chemistry is still a developing field, thus newer batteries may use less scarce materials, thus hard to truly predict the sustainability of mining these materials, for example, some reports (cite Faraday) say cobalt supplies could be used entirely by 2040. Solutions do exist, recycling methods have been developed in order to extract the materials, termed battery metal recycling (BMR), however there are widely different sources suggesting how much of current batteries actually are recycled (one showing 5%), (other showing 90%), and the technology to do so is still a developing field, there are many different methods (cite ISSUES), since most of the rare earth elements are within the batteries cathode, methods such as hydrometallurgical process can extract these, but at the cost of severe reduction in lithium yield (cite ENJI) - although there

are promising methods with some proposing a lithium recovery needing less than 40% the energy compared to mining the virgin material (cite enji yoo) whilst still recovering nickel and cobalt. There is also the rising interest in reusing the batteries before recycling, these batteries are referred to as second-life batteries (SLB's); in the EV use-case, the majority of the batteries are deemed finished once their usable capacity drops below 80% (cite), but often, due to the other parameters of the batteries needing to be of high standards for EV use, the 'dead' batteries can still provide a very useful service in less demanding applications, a common one being energy storage systems (ESS) [?], with claims reusing can reduce CO2 emissions by 56% as opposed to using natural fuel gas in situ. However there are again challenges associated, for safety there is the need for robust testing, sorting the batteries based on their current health states, non automated methods of extracting cells from their original pack. These additional steps mean the price of SLB's could become at a point where they are not much cheaper than new batteries, making the solution less attractive to many sectors [?].

In summary, there are methods that are developing to reduce the need for mining new materials and decreasing recycling energy, but ultimately, providing methods to increase the usable life of the current batteries serves as a direct way to reduce the impacts of batteries themselves and to meet their growing demand. If just 1 extra life cycle could be added to all EV's currently on the road (60 million (cite)), this could power all of the UK's energy needs for one day (cite gov.uk); as most batteries cycle life are well over 1000, any increment in cycle life can be greatly beneficial.

Much research has been done into both modeling LIB's and optimising their usage from both an energy and aging perspective.

What is this project? the general approach

1.1 Project Aims

It would be good to see how the ECM parts change over degradation to see future behaviour

1.1.1 Objectives

- Attempt optimal control methods to parametrise lithium batteries
- Apply different control objectives to battery charging to see degradation effects

- See how effective adaptive methods are in the charging process as the battery ages
- Feed results to neural network ...

2 Literature Review

2.1 Lithium based battery degradation modes

Basic Background of Lithium Ion Batteries

Lithium-ion based batteries are favorable largely due to the highly reductive nature of Lithium, taking the potential relative to hydrogens reduction, lithiums half-reaction is -3.01V (cite gregg), meaning lithium can release its outershell electron relatively easy. Any cells potential difference is the difference in potentials of the negative and positive electrodes, so having a very negative potential like the lithium reduction, allows a variety of positive electrodes (where the oxidation occurs), to yield a high battery voltage. Coupled with Lithium's low molecular weight, a high energy density cell can be achieved to. The force produced by the potential difference between the electrodes drives the electrons via the external circuit, providing useful work, allowing lithium batteries to act as an energy storage medium.

Lithium batteries all follow the the same basic principle of operation, as show in They consist of a positive and negative electrode, electrolyte a separator and current collectors. Unlike many other battery chemistries, where the metal ions undergo chemical reactions at the electrodes which change the composition of the electrodes, lithium ions intercalate and deintercalate within the electrodes - they are in essence absorbed to and from the electrode structures (cite greg p), forming as loosely bonded lithium atoms within the electrodes. The electrodes for the negative side is usually a graphite based structure, allowing up to 1 lithium atom to be stored per 6 carbon atoms, whilst the positive electrode can vary greatly between different lithium batteries; the most common positive electrodes are often composed of transitional metal oxides such as LCO, LMO, NMC, NCA (cite Alex K Hoech et al). The lithium state in the graphite is similar to that of individual lithium atoms, thus the electrode potential of the negative electrode is very similar to that of pure lithium (-3V) (cite liquin), although its lithium storage abilities are usually lower than the positive electrodes. The lithium ions within the positive electrodes are in a much lower energy state, thus their reaction

potential ranges from $-1 - 2V$, therefore, overall there is a large potential difference created by the want of the positive electrode gaining electrons and the lithium ions, and the want of the lithium within the carbon of the negative electrode to give the lithium ion and electrons. In general, the negative electrodes used currently are carbon based, their capacity to hold the lithium (per unit volume) is greater than the positive electrodes used today as shown in figurexx (cite Alex), but as discussed later in this section the negative electrode is often the key limiting factor in degradation. The positive electrode materials vary greatly in material, but since this electrode has the biggest electrode potential, it has a largest impact on the overall cell voltage, and thus energy density of the cell, in addition since per volume it holds less lithium, electrode material with higher lithium capacity will be of greater affect than improving the negative electrodes capacity.

The electrolyte is a medium in which the lithium ions can be transported via diffusion to the electrodes, the electrolyte does not however allow electrons to flow, only via an external circuit can they flow, . The separator acts as a structural barrier to prevent the opposite electrodes from touching, which would allow both electrons and ions to flow, causing major fire risks from the uncontrolled reactions. During the discharging process, a path is provided externally across the current collectors, (these collectors are not part of the reactions and are just a means to electrically connect the electrolytes to a useful surface for soldering) the lithium stored within the negative electrode deintercalates, released as the positive lithium ion, whilst the electron leaves the electrode, traveling across the external circuit to the positive electrode.

Discharging Degradation

Charging Degradation

Since the applied voltage is above the difference of the electrode potentials, the lithium ions within the positive electrode deintercalate, traveling across the electrolyte to the negative electrode, where they intercalate within the graphite structure. However, severe problems can occur when

Mention diffusion differences between charge and discharge (cite Michael J. Whiney well)¹

¹Yep soooo

2.2 Battery Modelling

Electrochemical Models

Equivalent Circuit Models

This <https://www.sciencedirect.com/science/article/pii/S2352152X2400584X> nicely shows the overpotential of the battery relating to the difference of the output of the battery to the equilibrium potential of the battery. Shown as the summation of electrolyte overpotential, Li concentration overpotential, kinetic overpotential

and resistive overpotential. These are equated within the ECM model as the polarizing R_c , and R_s . <https://www.sciencedirect.com/science/article/pii/S0378775313020880> gives the

Just say, that there are models for overpotential which can cause the dendrite formations, these are caused by too fast of charge and overcharging.

2.3 Charging methods

2.4 Optimal control

2.5 Neural networking

3 Plans for Remaining Work

4 Self Review

5 Project progress




Figure 1: Initial end objective: Black Box Battery

References

- [1] L. Chen, C. Chang, X. Liu, J. Jiang, Y. Jiang, and A. Tian, “Physics-informed neural networks for small sample state of health estimation of lithium-ion batteries,” *Journal of Energy Storage*, vol. 122, p. 116559, Jun. 2025. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S2352152X25012721>
- [2] Q. Guo, S. Liu, J. Zhang, Z. Huang, and D. Han, “Effects of charging rates on heat and gas generation in lithium-ion battery thermal runaway triggered by high temperature coupled with overcharge,” *Journal of Power Sources*, vol. 600, p. 234237, Apr. 2024. [Online]. Available: <https://linkinghub.elsevier.com/retrieve/pii/S0378775324001885>
- [3] Y. Li, W. Guo, D.-I. Stroe, H. Zhao, P. Kjær Kristensen, L. Rosgaard Jensen, K. Pedersen, and L. Gurevich, “Evolution of aging mechanisms and performance degradation of lithium-ion battery from moderate to severe capacity loss scenarios,” *Chemical Engineering Journal*, vol. 498, p. 155588, Oct. 2024. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S1385894724070797>
- [4] “Executive summary – Batteries and Secure Energy Transitions – Analysis.” [Online]. Available: <https://www.iea.org/reports/batteries-and-secure-energy-transitions/executive-summary>
- [5] P. R. Chinnam, A. M. Colclasure, B.-R. Chen, T. R. Tanim, E. J. Dufek, K. Smith, M. C. Evans, A. R. Dunlop, S. E. Trask, B. J. Polzin, and A. N. Jansen, “Fast-Charging Aging Considerations: Incorporation and Alignment of Cell Design and Material Degradation Pathways,” *ACS Applied Energy Materials*, vol. 4, no. 9, pp. 9133–9143, Sep. 2021, publisher: American Chemical Society. [Online]. Available: <https://doi.org/10.1021/acsaem.1c01398>

- [6] M. Lucu, E. Martinez-Laserna, I. Gandiaga, K. Liu, H. Camblong, W. Widanage, and J. Marco, “Data-driven nonparametric Li-ion battery ageing model aiming at learning from real operation data – Part A: Storage operation,” *Journal of Energy Storage*, vol. 30, p. 101409, Aug. 2020.
- [7] M. R. Palacín and A. de Guibert, “Why do batteries fail?” *Science*, vol. 351, no. 6273, p. 1253292, Feb. 2016, publisher: American Association for the Advancement of Science. [Online]. Available: <https://www.science.org/doi/abs/10.1126/science.1253292>
- [8] L. Mattia, H. Beiranvand, W. Zamboni, and M. Liserre, “Lithium-ion battery thermal modelling and characterisation: A comprehensive review,” *Journal of Energy Storage*, vol. 129, p. 117114, Sep. 2025. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S2352152X25018274>
- [9] M.-K. Tran, M. Mathew, S. Janhun, S. Panchal, K. Raahemifar, R. Fraser, and M. Fowler, “A comprehensive equivalent circuit model for lithium-ion batteries, incorporating the effects of state of health, state of charge, and temperature on model parameters,” *Journal of Energy Storage*, vol. 43, p. 103252, Nov. 2021. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S2352152X2100949X>
- [10] T. Kalogiannis, M. S. Hosen, M. A. Sokkeh, S. Goutam, J. Jaguemont, L. Jin, G. Qiao, M. Berecibar, and J. Van Mierlo, “Comparative Study on Parameter Identification Methods for Dual-Polarization Lithium-Ion Equivalent Circuit Model,” *Energies*, vol. 12, no. 21, p. 4031, Jan. 2019, publisher: Multidisciplinary Digital Publishing Institute. [Online]. Available: <https://www.mdpi.com/1996-1073/12/21/4031>
- [11] J. Tebbe, A. Hartwig, A. Jamali, H. Senobar, A. Wahab, M. Kabak, H. Kemper, and H. Khayyam, “Innovations and prognostics in battery degradation and longevity for energy storage systems,” *Journal of Energy Storage*, vol. 114, p. 115724, Apr. 2025. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S2352152X25004372>
- [12] X. Lin, H. E. Perez, S. Mohan, J. B. Siegel, A. G. Stefanopoulou, Y. Ding, and M. P. Castanier, “A lumped-parameter electro-thermal model for cylindrical batteries,” *Journal of Power Sources*, vol. 257, pp. 1–11, Jul. 2014. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0378775314001244>

- [13] A. B. Khan, V.-L. Pham, T.-T. Nguyen, and W. Choi, “Multistage constant-current charging method for Li-Ion batteries,” in *2016 IEEE Transportation Electrification Conference and Expo, Asia-Pacific (ITEC Asia-Pacific)*, Jun. 2016, pp. 381–385. [Online]. Available: <https://ieeexplore.ieee.org/document/7512982>
- [14] M. Usman Tahir, A. Sangwongwanich, D.-I. Stroe, and F. Blaabjerg, “Overview of multi-stage charging strategies for Li-ion batteries,” *Journal of Energy Chemistry*, vol. 84, pp. 228–241, Sep. 2023. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S2095495623003091>
- [15] P. Keil and A. Jossen, “Charging protocols for lithium-ion batteries and their impact on cycle life—An experimental study with different 18650 high-power cells,” *Journal of Energy Storage*, vol. 6, pp. 125–141, May 2016. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S2352152X16300147>
- [16] “How Do I Make an LSTM Model with Multiple Inputs?” [Online]. Available: <https://datasciencedojo.com/blog/how-do-i-make-an-lstm-model-with-multiple-inputs/>
- [17] K. A. Severson, P. M. Attia, N. Jin, N. Perkins, B. Jiang, Z. Yang, M. H. Chen, M. Aykol, P. K. Herring, D. Fraggedakis, M. Z. Bazant, S. J. Harris, W. C. Chueh, and R. D. Braatz, “Data-driven prediction of battery cycle life before capacity degradation,” *Nature Energy*, vol. 4, no. 5, pp. 383–391, May 2019, publisher: Nature Publishing Group. [Online]. Available: <https://www.nature.com/articles/s41560-019-0356-8>
- [18] P. M. Attia, A. Grover, N. Jin, K. A. Severson, T. M. Markov, Y.-H. Liao, M. H. Chen, B. Cheong, N. Perkins, Z. Yang, P. K. Herring, M. Aykol, S. J. Harris, R. D. Braatz, S. Ermon, and W. C. Chueh, “Closed-loop optimization of fast-charging protocols for batteries with machine learning,” *Nature*, vol. 578, no. 7795, pp. 397–402, Feb. 2020, publisher: Nature Publishing Group. [Online]. Available: <https://www.nature.com/articles/s41586-020-1994-5>
- [19] M. M. Hasan, R. Haque, M. I. Jahirul, M. G. Rasul, I. M. R. Fattah, N. M. S. Hassan, and M. Mofijur, “Advancing energy storage: The future trajectory of lithium-ion battery technologies,” *Journal of Energy Storage*, vol. 120, p. 116511, Jun. 2025. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S2352152X25012241>

- [20] H. Ritchie, P. Rosado, and M. Roser, “Access to Energy,” *Our World in Data*, Sep. 2019. [Online]. Available: <https://ourworldindata.org/energy-access>
- [21] “Global Electricity Review 2024.” [Online]. Available: <https://ember-energy.org/latest-insights/global-electricity-review-2024>
- [22] H. Ritchie and P. Rosado, “Energy Mix,” *Our World in Data*, Jul. 2020. [Online]. Available: <https://ourworldindata.org/energy-mix>
- [23] A. S. Brouwer, M. van den Broek, A. Seebregts, and A. Faaij, “Impacts of large-scale Intermittent Renewable Energy Sources on electricity systems, and how these can be modeled,” *Renewable and Sustainable Energy Reviews*, vol. 33, pp. 443–466, May 2014. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S1364032114000987>
- [24] “Trends in the electric car industry – Global EV Outlook 2025 – Analysis.” [Online]. Available: <https://www.iea.org/reports/global-ev-outlook-2025/trends-in-the-electric-car-industry-3>
- [25] J. Schmitt, M. Rehm, A. Karger, and A. Jossen, “Capacity and degradation mode estimation for lithium-ion batteries based on partial charging curves at different current rates,” *Journal of Energy Storage*, vol. 59, p. 106517, Mar. 2023. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S2352152X22025063>
- [26] N. Omar, M. A. Monem, Y. Firouz, J. Salminen, J. Smekens, O. Hegazy, H. Gaulous, G. Mulder, P. Van den Bossche, T. Coosemans, and J. Van Mierlo, “Lithium iron phosphate based battery – Assessment of the aging parameters and development of cycle life model,” *Applied Energy*, vol. 113, pp. 1575–1585, Jan. 2014. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0306261913007393>
- [27] Q. Wang, B. Jiang, B. Li, and Y. Yan, “A critical review of thermal management models and solutions of lithium-ion batteries for the development of pure electric vehicles,” *Renewable and Sustainable Energy Reviews*, vol. 64, pp. 106–128, Oct. 2016. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S1364032116301435>
- [28] L. Mattia, H. Beiranvand, W. Zamboni, and M. Liserre, “Lithium-ion battery thermal modelling and characterisation: A comprehensive review,” *Journal of Energy Storage*, vol. 129, p. 117114, Sep. 2025. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S2352152X25018274>

- [29] S. Guo, R. Xiong, K. Wang, and F. Sun, “A novel echelon internal heating strategy of cold batteries for all-climate electric vehicles application,” *Applied Energy*, vol. 219, pp. 256–263, Jun. 2018. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0306261918303817>
- [30] Q. Lin, J. Wang, R. Xiong, W. Shen, and H. He, “Towards a smarter battery management system: A critical review on optimal charging methods of lithium ion batteries,” *Energy*, vol. 183, pp. 220–234, Sep. 2019. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0360544219312605>