

Aggregate & Oil		Gulf - Grade	Minimum Ambient Temp. (°C)	Capacity		Change Period
						Tipper (Hrs)
ENGINE OIL	H6 2V Diesel Engine - MDV Truck / MDV Bus	Gulf Super Fleet ULE Duramax	-20 °C	17.5 L W/O Filter 18 L With Filter		Every 1000 Hrs or 12 months, whichever is earlier
	A4 Diesel Engine - MDV Truck / MDV Bus			16 L W/O Filter 16.5 L With Filter		Every 500 Hrs or 12 months, whichever is earlier
COOLANT	Radiator Coolant - MDV Truck	Gulf Eurocool Dura Max 40	-18 °C	<b>H6</b> : 28 ± 1 L <b>A4</b> : 35 ± 1 L		Every 5000 Hrs or 3 years, whichever is earlier
GEAR BOX OIL	ZF 8S-1110 / 9S-1110 Gear Box	Gulf Gear ZX Dura Max 80W90	-20 °C	8.8 L W/O PTO 9.2 L With PTO		Every 3000 Hrs or 18 months, whichever is earlier
	ZF 6S, 5S (OD / DD) Gear Box			6.5 L W/O PTO 7.5 L With PTO		Every 2000 Hrs or 18 months, whichever is earlier
	AL 6MT86 Gear Box			8 L W/O PTO 8.3 L With PTO		Every 1000 Hrs or 18 months, whichever is earlier
	ALGB 940 Gear Box	Gulf Gear TX Dura Max 80W90		9.2 L W/O PTO 9.5 L With PTO		Every 1000 Hrs or 18 months, whichever is earlier
POWER STEERING OIL	Power Steering - MDV Truck	Gulf ATF DX II	-40 °C	Single Steer - 4 L Twin Steer - 6 L		Every 4000 Hrs or 24 months, whichever is earlier
REAR AXLE OIL	Rear Axle - MDV / ICV - Truck & Bus	Gulf Gear ED Dura Max 80W90	-15 °C	-		Every 2000 Hrs or 24 months, whichever is earlier
HUB GREASING	Front Wheel Bearing - Hub greasing	Gulf Crown LX Dura Max NLGI 3	-20 °C	-		Every 1500 Hrs or 12 months, whichever is earlier
	Rear Wheel Bearing - Hub greasing					
TIPPING OIL	Tipping Unit	Gulf Tipper Hydraulic Max 68	-15 °C	<b>Tank Capacity (L)</b>	<b>Filling Quantity (L)</b>	<b>First oil change:</b> Normal & Dusty operation - 6 months <b>Next oil change:</b> Normal operation - 24 Months Dusty operation - 12 Months
				40 (ICV & MDV)	33 ± 2	
				60 (MDV)	52 ± 3	
				90 (MDV)	77 ± 3	
				120 (MDV)	105 ± 5	
CAB TILT OIL	Cabin tilt - MDV Truck	Gulf ATF DX II	-40 °C	600 ml Max		Every 5000Hrs or 5 Years, whichever is earlier
		Gulf Harmony HVI plus 15	-30 to + 60°C			
	Cabin tilt - ICV Truck	Gulf Harmony HVI plus 15	-30 to + 60°C	400 ml Max		
CLUTCH OIL	Clutch Fluid - With Integral Pedal Unit (IPU)	Gulf Clutch Fluid Dura Max	-40 °C	500 ml with bleeding		Every 3000 Hrs or 12 months, whichever is earlier