

● **RUNNING**

● TU-MAIN
200 PRODUCE

● TU-CIP
0 IDLE

● TU-ELYPREP
0 IDLE

1 **ERRORS**
PRESS TO LEARN MORE

FULL HMI
DETAILED VIEW

HYDROVOLTA SPEC PAGE (PERTH)

27 AUG 2026 ● LIVE · UPDATED 1S AGO

WATER INTAKE

CONDUCTIVITY **48,172** $\mu\text{S}/\text{cm}$
NORMAL 40-55k $\mu\text{S}/\text{cm}$

FLOW **908** l/h
NORMAL 850-950 l/h

pH **8.1**
NORMAL pH 7.5-8.5

**HYDRO
VOLTA**

RECOVERY
56.8 %

PRODUCT WATER

CONDUCTIVITY **213** $\mu\text{S}/\text{cm}$
MAX 400 $\mu\text{S}/\text{cm}$

FLOW **516** l/h
NORMAL 480-540 l/h

pH **7.2**
NORMAL pH 6.5-8.5

DISCHARGED WATER

CONDUCTIVITY **71,783** $\mu\text{S}/\text{cm}$
PERMIT max 90k $\mu\text{S}/\text{cm}$

FLOW **392** l/h
NORMAL 340-430 l/h

pH **7.9**
PERMIT pH 6.0-9.0

ENERGY USE

4.5 kW now

38.4 kWh today

8.82 kWh/m³

POWER LED



DC OK



RUN



SIGNAL



ALARM



WARNING



START



STOP



RESET



CIP



US



DC



STOP

EMERGENCY STOP

HOLD 3 S TO HALT ALL