

## My DE1 repository link

[Click here](#)

## De Morgan's laws

---

### Table

c	b	a	f(c,b,a)
0	0	0	1
0	0	1	1
0	1	0	0
0	1	1	0
1	0	0	0
1	0	1	1
1	1	0	0
1	1	1	0

### Code

```
-----  
--  
-- Example of basic OR, AND, XOR gates.  
-- Nexys A7-50T, Vivado v2020.1, EDA Playground  
--  
-- Copyright (c) 2019-2020 Tomas Fryza  
-- Dept. of Radio Electronics, Brno University of Technology, Czechia  
-- This work is licensed under the terms of the MIT license.  
--  
-----  
  
library ieee;           -- Standard library  
use ieee.std_logic_1164.all; -- Package for data types and logic operations  
  
-----  
-- Entity declaration for basic gates  
-----  
entity gates is  
    port(  
        a_i      : in  std_logic;           -- Data input
```

```

        b_i    : in  std_logic;      -- Data input
        c_i    : in  std_logic;      -- Data input
        f_o    : out std_logic;      -- OR output function
        fnand_o: out std_logic;      -- NAND output function
        fnor_o : out std_logic      -- NOR output function
    );
end entity gates;


-----
-- Architecture body for basic gates
-----

architecture dataflow of gates is
begin
    f_o  <= ((not b_i) and a_i) or ((not c_i) and (not b_i));
    fnand_o <= ((b_i nand b_i) nand a_i) nand ((c_i nand c_i) nand (b_i nand
b_i));
    fnor_o <= ((b_i nor (a_i nor a_i)) nor (b_i nor c_i)) nor ((b_i nor (a_i nor
a_i)) nor (b_i nor c_i));

end architecture dataflow;

```

## Result



## Link

[EDA Playground link for De morgan's laws](#)

## Distributive laws

## Code

```

library ieee;
use ieee.std_logic_1164.all;

-----

entity gates is
    port(

```

```
x_i      : in  std_logic;      -- Data input
y_i      : in  std_logic;      -- Data input
z_i      : in  std_logic;      -- Data input

p1_o     : out std_logic;      -- Postulate no.1
p2_o     : out std_logic;      -- Postulate no.2
p3_o     : out std_logic;      -- Postulate no.3
p4_o     : out std_logic;      -- Postulate no.4

f1_o     : out std_logic;      -- Function no.1
f2_o     : out std_logic;      -- Function no.2
f3_o     : out std_logic;      -- Function no.3
f4_o     : out std_logic;      -- Function no.4
);
end entity gates;


-----
-- Architecture body for basic gates
-----

architecture dataflow of gates is
begin
    p1_o  <= x_i and (not x_i);
    p2_o  <= x_i or  (not x_i);
    p3_o  <= x_i or  x_i or x_i;
    p4_o  <= x_i and x_i and x_i;

    f1_o  <= (x_i and y_i) or (x_i and z_i);
    f2_o  <= x_i and (y_i or z_i);
    f3_o  <= (x_i or y_i) and (x_i or z_i);
    f4_o  <= x_i or (y_i and z_i);

end architecture dataflow;
```

Result



Link

[EDA Playground link for Distributive laws](#)