

OPENSEISMOMATLAB

Software for strong ground motion data processing

Contents

- [Files](#)
- [baselineCorr](#)
- [BLKIN](#)
- [CDReSp](#)
- [DRHA](#)
- [example_Constant_ductility_response_spectra](#)
- [example_Fourier_spectra](#)
- [example_Linear_elastic_response_spectra](#)
- [example_Spectra_comparison_1](#)
- [example_Spectra_comparison_2](#)
- [example_Verification](#)
- [FASp](#)
- [HalfStep](#)
- [helpFun](#)
- [Install](#)
- [LReSp](#)
- [LIDA](#)
- [NLIDABLKIN](#)
- [OpenSeismoMatlab](#)

Files

Contents of the OpenSeismoMatlab software

baselineCorr

Baseline correction of acceleration time history

[baselineCorr.m](#)

BLKIN

Bilinear elastoplastic hysteretic model with elastic viscous damping

[BLKIN.m](#)

CDReSp

Constant Ductility Response Spectra (CDReSp)

[CDReSp.m](#)

DRHA

Dynamic Response History Analysis (DRHA) of a SDOF system

[DRHA.m](#)

example_Constant_ductility_response_spectra

Constant ductility response spectra

[example_Constant_ductility_response_spectra.m](#)

example_Fourier_spectra

Fourier spectra

[example_Fourier_spectra.m](#)

example_Linear_elastic_response_spectra

Linear elastic response spectra

[example_Linear_elastic_response_spectra.m](#)

example_Spectra_comparison_1

Comparison of elastic and constant ductility response spectra for $\mu=1$

[example_Spectra_comparison_1.m](#)

example_Spectra_comparison_2

Comparison of constant ductility response spectra of RSN1044 for $\mu=2$

[example_Spectra_comparison_2.m](#)

example_Verification

Verification

[example_Verification.m](#)

FASp

Single sided Fourier amplitude spectrum

[FASp.m](#)

HalfStep

Reproduce a signal with half time step

[HalfStep.m](#)

helpFun

Help for functions in Command Window

Install

Main script for installation of the folder of OpenSeismoMatlab

LEReSp

Fast calculation of Linear Elastic Response Spectra (LEReSp) and

[LEReSp.m](#)

LIDA

Linear Implicit Dynamic Analysis (LIDA)

[LIDA.m](#)

NLIDABLKIN

Non Linear Implicit Dynamic Analysis of a bilinear kinematic hardening

[NLIDABLKIN.m](#)

OpenSeismoMatlab

Seismic parameters of an acceleration time history

[OpenSeismoMatlab.m](#)

baselineCorr

Documentation of the baselineCorr function.

```
helpFun('baselineCorr')
```

Baseline correction of acceleration time history

```
[COR_XG, COR_XGT, COR_XGTT] = BASELINECORR(T,XGTT)
```

Description

Linear baseline correction is performed for an uncorrected acceleration time history. Initially, first order fitting (straight line) is performed on the acceleration time history and the fitting line is subtracted from the acceleration time history, giving thus the first correction. Afterwards, the first correction of the acceleration is integrated to obtain the velocity, and then first order fitting (straight line) is performed on this velocity time history. The gradient of the straight fitting line is then subtracted from the first correction of the acceleration time history, giving thus the second correction of the acceleration time history. The second correction of the acceleration time history is then integrated to give the corrected velocity and displacement time histories.

Input parameters

T [double(1:numsteps x 1)] is the time vector of the input acceleration time history XGTT. numsteps is the length of the input acceleration time history.
XGTT [double(1:nstep x 1)]: column vector of the acceleration history of the excitation imposed at the base. nstep is the number of time steps of the dynamic response.

Output parameters

COR_XG [double(1:nstep x 1)]: time-history of displacement
COR_XGT [double(1:nstep x 1)]: time-history of velocity
COR_XGTT [double(1:nstep x 1)]: time-history of acceleration

Example

```
%
fid=fopen('elcentro.dat','r');
text=textscan(fid,'%f %f');
fclose(fid);
time=text{1,1};
xgttl=9.81*text{1,2};
%
dt=time(2)-time(1);
%
xgt1 = cumtrapz(time,xgttl);
xg1 = cumtrapz(time,xgt1);
%
[xg2, xgt2, xgtt2] = baselineCorr(time,xgttl)
%
figure()
plot(time,xgttl)
hold on
plot(time,xgtt2)
```

```
%  
figure()  
plot(time,xgt1)  
hold on  
plot(time,xgt2)  
%  
figure()  
plot(time,xg1)  
hold on  
plot(time,xg2)
```

Copyright (c) 2018-2022

George Papazafeiropoulos

Major, Infrastructure Engineer, Hellenic Air Force

Civil Engineer, M.Sc., Ph.D.

Email: gpapazafeiropoulos@yahoo.gr

Documentation of the BLKIN function.

```
helpFun('BLKIN')
```

Bilinear elastoplastic hysteretic model with elastic viscous damping

```
[F,K,C,K_STATUS,D] = BLKIN(U,UT,K_HI,K_LO,UY,M,KSI,K_STATUS,D)
```

Description

Define the internal force vector, tangent stiffness matrix and tangent damping matrix of a bilinear elastoplastic hysteretic structure with elastic damping as a function of displacement and velocity.

The MDOF structure modeled with this function consists of lumped masses connected with stiffness and damping elements in series. Each lumped mass has one degree of freedom. The first degree of freedom is at the top of the structure and the last at its fixed base. However, the last degree of freedom is not included in the input arguments of the function, i.e. not contained in `ndof`, as it is always fixed. The nonlinear stiffness is virtually of the bilinear type, where an initial stiffness and a post-yield stiffness are defined. The unloading or reloading curve of this model are parallel to the initial loading curve, and a hysteresis loop is created by continuously loading and unloading the structure above its yield limit. This behavior can be viewed as hardening of the kinematic type.

An appropriate reference for this function definition is Hughes, Pister & Taylor (1979): "Implicit-explicit finite elements in nonlinear transient analysis". This function should be defined in accordance with equations (3.1), (3.2) and (3.3) of this paper. This representation has as special cases nonlinear elasticity and a class of nonlinear "rate-type" viscoelastic materials. Tangent stiffness and tangent damping matrices are the "consistent" linearized operators associated to `f` in the sense of [Hughes & Pister, "Consistent linearization in mechanics of solids", Computers and Structures, 8 (1978) 391-397].

Input parameters

`U` [double(1 x 1)] is the absolute displacement.

`UT` [double(1 x 1)] is the absolute velocity.

`K_HI` [double(1 x 1)] is the initial stiffness of the system before its first yield, i.e. the high stiffness.

`K_LO` [double(1 x 1)] is the post-yield stiffness of the system, i.e. the low stiffness.

`UY` [double(1 x 1)] is the yield limit of the structure. The structure is considered to yield, if the displacement exceeds `uy(i)`.

`M` [double(1 x 1)] is the lumped mass.

`KSI` [double(1 x 1)] is the ratio of critical viscous damping of the system, assumed to be unique for all damping elements of the structure.

`K_STATUS` [double(1 x 1)] is the is the stiffness vector which takes into account any plastic response of the structure. It is used to record the status of the structure so that it is known before the next application of this function at a next (time) step.

Initialize by setting $K_STATUS=K_HI$.

D [double(1 x 1)] is the equilibrium displacement vector which takes into account any plastic response of the structure. It is used to record the status of the structure so that it is known before the next application of this function at a next (time) step. Initialize by setting $D=zeros(ndof,1)$.

Output parameters

F [double(1 x 1)] is the internal force vector of the structure (sum of forces due to stiffness and damping) at displacement u and velocity ut

K [double(1 x 1)] is the tangent stiffness matrix (nonlinear function of displacement u and velocity ut). It is equivalent to the derivative $d(f)/d(u)$

C [double(1 x 1)] is the tangent damping matrix (nonlinear function of displacement u and velocity ut). It is equivalent to the derivative $d(f)/d(u)$

K_STATUS [double(1 x 1)] is the stiffness vector which takes into account any plastic response of the structure. It is used to record the status of the structure so that it is known before the next application of this function at a next (time) step.

D [double(1 x 1)] is the equilibrium displacement vector which takes into account any plastic response of the structure. It is used to record the status of the structure so that it is known before the next application of this function at a next (time) step.

Example

```
%
u=0:0.2:4;
u=[u,u(end:-1:1)];
u=[u,-u];
u=[u u];
%
ut=0.001*ones(1,numel(u));
ut=[ut,-ut];
ut=[ut,ut(end:-1:1)];
ut=[ut ut];
%
k_hi=1000;
%
k_lo=1;
%
uy=2;
%
M=1;
%
ksi=0.05;
%
k=k_hi;
%
d=0;
%
f=zeros(1,numel(u));
for i=1:numel(u)
    [f(i),K,C,k,d] = BLKIN(u(i),ut(i),k_hi,k_lo,uy,M,ksi,k,d);
end
%
figure()
plot(u,f)
```

Copyright (c) 2018-2022

George Papazafeiropoulos

Major, Infrastructure Engineer, Hellenic Air Force

Civil Engineer, M.Sc., Ph.D.

Email: gpapazafeiropoulos@yahoo.gr

Documentation of the CDSp function.

```
helpFun('CDSp')
```

Constant Ductility Response Spectra (CDSp)

```
[PSA,PSV,SD,SV,SA,FYK,MUK,ITERK]=CDRESP(DT,XGTT,T,KSI,MU,N,TOL,PYSF,...  
    DTTOL,ALGID,RINF)
```

Description

The constant ductility response spectra for a given time-history of constant time step, a given eigenperiod range, a given viscous damping ratio and a given ductility are computed. See section 7.5 in Chopra (2012) and the notes "Inelastic Response Spectra" (CEE 541. Structural Dynamics) by Henri P. Gavin.

Input parameters

DT [double(1 x 1)] is the time step of the input acceleration time history XGTT.

XGTT [double(1:numsteps x 1)] is the input acceleration time history. numsteps is the length of the input acceleration time history.

T [double(1:numSDOFs x 1)] contains the values of eigenperiods for which the response spectra are requested. numSDOFs is the number of SDOF oscillators being analysed to produce the spectra.

KSI [double(1 x 1)] is the fraction of critical viscous damping.

MU [double(1 x 1)] is the target ductility for which the response spectra are calculated.

N [double(1 x 1)] is the maximum number of iterations that can be performed until convergence of the calculated ductility to the target ductility is achieved. Default value 30.

TOL [double(1 x 1)] is the tolerance for convergence for the target ductility. Default value 0.01.

PYSF [double(1 x 1)] is the post-yield stiffness factor, i.e. the ratio of the postyield stiffness to the initial stiffness. PYSF=0 is not recommended for simulation of an elastoplastic system. A small positive value is always suggested. PYSF is ignored if MU=1. Default value 0.01.

DTTOL [double(1 x 1)] is the tolerance for resampling of the input acceleration time history. For a given eigenperiod T, resampling takes place if DT/T>dtTol. Default value 0.01.

ALGID [char(1 x :inf)] is the algorithm to be used for the time integration. It can be one of the following strings for superior optimally designed algorithms:

- 'generalized a-method': The generalized a-method (Chung & Hulbert, 1993)
- 'HHT a-method': The Hilber-Hughes-Taylor method (Hilber, Hughes & Taylor, 1977)
- 'WBZ': The Wood-Bossak-Zienkiewicz method (Wood, Bossak & Zienkiewicz, 1980)
- 'U0-V0-Opt': Optimal numerical dissipation and dispersion zero order displacement zero order velocity algorithm
- 'U0-V0-CA': Continuous acceleration (zero spurious root at the low frequency limit) zero order displacement zero order velocity algorithm

'U0-V0-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) zero order displacement zero order velocity algorithm
 'U0-V1-Opt': Optimal numerical dissipation and dispersion zero order displacement first order velocity algorithm
 'U0-V1-CA': Continuous acceleration (zero spurious root at the low frequency limit) zero order displacement first order velocity algorithm
 'U0-V1-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) zero order displacement first order velocity algorithm
 'U1-V0-Opt': Optimal numerical dissipation and dispersion first order displacement zero order velocity algorithm
 'U1-V0-CA': Continuous acceleration (zero spurious root at the low frequency limit) first order displacement zero order velocity algorithm
 'U1-V0-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) first order displacement zero order velocity algorithm
 'Newmark ACA': Newmark Average Constant Acceleration method
 'Newmark LA': Newmark Linear Acceleration method
 'Newmark BA': Newmark Backward Acceleration method
 'Fox-Goodwin': Fox-Goodwin formula

Default value 'U0-V0-CA'.

RINF [double(1 x 1)] is the minimum absolute value of the eigenvalues of the amplification matrix. For the amplification matrix see eq.(61) in Zhou & Tamma (2004). Default value 0.

Output parameters

PSA [double(1:numSDOFs x 1)] is the Pseudo-Spectral Acceleration.
 PSV [double(1:numSDOFs x 1)] is the Pseudo-Spectral Velocity.
 SD [double(1:numSDOFs x 1)] is the Spectral Displacement.
 SV [double(1:numSDOFs x 1)] is the Spectral Velocity.
 SA [double(1:numSDOFs x 1)] is the Spectral Acceleration.
 FYK [double(1:numSDOFs x 1)] is the yield limit that each SDOF must have in order to attain ductility equal to μ_K .
 MUK [double(1:numSDOFs x 1)] is the achieved ductility for each period (each SDOF).
 ITERK [double(1:numSDOFs x 1)] is the number of iterations needed for convergence for each period (each SDOF).

Example

```
%
dt=0.02;
%
N=10;
a=rand(N,1)-0.5;
b=100*pi*rand(N,1);
c=pi*(rand(N,1)-0.5);
t=(0:dt:(100*dt))';
xgtt=zeros(size(t));
for i=1:N
    xgtt=xgtt+a(i)*sin(b(i)*t+c(i));
end
%
T=(0.04:0.04:4)';
%
ksi=0.05;
%
mu=2;
%
```

```

n=50;
%
tol=0.01;
%
pysf=0.1;
%
dtTol=0.02;
%
AlgID='U0-V0-Opt';
%
rinf=1;
%
[CDPSa,CDPSv,CDSd,CDSv,CDSa,fyK,muK,iterK]=CDReSp(dt,xgtt,T,ksi,...
    mu,n,tol,pysf,dtTol,AlgID,rinf);
%
figure()
plot(T,CDSd)
%
figure()
plot(T,fyK)
%
figure()
plot(T,muK)
%
figure()
plot(T,iterK)

```

Copyright (c) 2018-2022

George Papazafeiropoulos

Major, Infrastructure Engineer, Hellenic Air Force

Civil Engineer, M.Sc., Ph.D.

Email: gpapazafeiropoulos@yahoo.gr

Documentation of the DRHA function.

```
helpFun('DRHA')
```

Dynamic Response History Analysis (DRHA) of a SDOF system

```
[U,V,A,F,ES,ED] = DRHA(K,M,DT,XGTT,KSI,U0,UT0,RINF)
```

Description

Determine the time history of structural response of a SDOF system

Input parameters

K [double(1 x 1)] is the stiffness of the system.
M [double(1 x 1)] is the lumped masses of the structure.
DT [double(1 x 1)] is the time step of the response history analysis from which the response spectrum is calculated
XGTT [double(1:nstep x 1)]: column vector of the acceleration history of the excitation imposed at the base. nstep is the number of time steps of the dynamic response.
KSI [double(1 x 1)] is the ratio of critical damping of the SDOF system. Default value 0.05.
U0 [double(1 x 1)] is the initial displacement of the SDOF system. Default value 0.
UT0 [double(1 x 1)] is the initial velocity of the SDOF system. Default value 0.
RINF [double(1 x 1)] is the minimum absolute value of the eigenvalues of the amplification matrix. For the amplification matrix see eq.(61) in Zhou & Tamma (2004). Default value 1.

Output parameters

U [double(1 x 1:nstep)]: displacement time history.
V [double(1 x 1:nstep)]: velocity time history.
A [double(1 x 1:nstep)]: acceleration time history.
F [double(1 x 1:nstep)]: equivalent static force time history.
ES [double(1 x 1:nstep)]: time-history of the recoverable strain energy of the system (total and not incremental).
ED [double(1 x 1:nstep)]: time-history of the energy dissipated by viscoelastic damping during each time step (incremental). cumsum(Ed) gives the time history of the total energy dissipated at dof i from the start of the dynamic analysis.

Copyright (c) 2018-2022

George Papazafeiropoulos
Major, Infrastructure Engineer, Hellenic Air Force
Civil Engineer, M.Sc., Ph.D.
Email: gpapazafeiropoulos@yahoo.gr

Constant ductility response spectra

Generate the constant ductility response spectra and associated results of an earthquake suite using OpenSeismoMatlab.

Contents

- [Input](#)
- [Calculation](#)
- [Output](#)
- [Copyright](#)

Input

earthquake motions

```
eqmotions={'Imperial Valley'; % Imperial valley 1979
           'Kocaeli';
           'Loma Prieta';
           'Northridge';
           'San Fernando';
           'Spitak';
           'Cape Mendocino';
           'ChiChi';
           'El Centro'; % Imperial valley 1940
           'Hollister';
           'Kobe'};
```

Set the eigenperiod range for which the response spectra will be calculated.

```
Tspectra=(0.08:0.08:4)';
```

Set critical damping ratio of the response spectra to be calculated.

```
ksi=0.05;
```

Set the target ductility (not used here)

```
mu=2;
```

Set the postyield stiffness factor for each earthquake

```
p=[0.02;0.01;0.02;0.01;0.01;0.01;0.02;0.01;0.01;0.01;0.01];
```

Extract nonlinear response spectra

```
sw='cgs';
```

Calculation


Initialize CDRS

```
CDRS=cell(numel(eqmotions),1);
% Calculation of peak values
for i=1:numel(eqmotions)
    % earthquake
    data=load([eqmotions{i},'.dat']);
    t=data(:,1);
    dt=t(2)-t(1);
    xgtt=data(:,2);
    S=OpenSeismoMatlab(dt,xgtt,sw,[],[],ksi,Tspectra,mu,p(i));
    CDRS{i}=[S.Period,S.CDSd,S.CDSv,S.CDPSa,S.fyK,S.muK,S.iterK];
end
```

Output

Plot constant ductility spectral displacement

```
Fig1 = figure('units', 'centimeters', 'Position', [0,0, 20/sqrt(2), 20]);
% Scan all subplots
for i=1:numel(eqmotions)
    subplot(4,3,i)
    plot(CDRS{i}(:,1),CDRS{i}(:,2),'k','LineWidth',1);
    set(gca,'FontName','Times New Roman')
    title(eqmotions{i},'FontName','Times New Roman')
    ylabel('Sd','FontName','Times New Roman')
    xlabel('Period (s)','FontName','Times New Roman')
    axis tight
end
```




Plot constant ductility spectral velocity

```
Fig2 = figure('units', 'centimeters', 'Position', [0,0, 20/sqrt(2), 20]);
% Scan all subplots
for i=1:numel(eqmotions)
    subplot(4,3,i)
    plot(CDRS{i}(:,1),CDRS{i}(:,3),'k','LineWidth',1);
    set(gca,'FontName','Times New Roman')
    title(eqmotions{i},'FontName','Times New Roman')
    ylabel('Sv','FontName','Times New Roman')
    xlabel('Period (s)','FontName','Times New Roman')
```



```
axis tight
end
```




Plot constant ductility spectral acceleration

```
Fig3 = figure('units', 'centimeters', 'Position', [0,0, 20/sqrt(2), 20]);
% Scan all subplots
for i=1:numel(eqmotions)
    subplot(4,3,i)
    plot(CDRS{i}(:,1),CDRS{i}(:,4),'k','LineWidth',1);
```

```

set(gca,'FontName','Times New Roman')
title(egmotions{i},'FontName','Times New Roman')
ylabel('PSa','FontName','Times New Roman')
xlabel('Period (s)','FontName','Times New Roman')
axis tight
end

```



Plot constant ductility spectral yield limit

```


Fig4 = figure('units', 'centimeters', 'Position', [0,0, 20/sqrt(2), 20]);

```

```


% Scan all subplots
for i=1:numel(eqmotions)
    subplot(4,3,i)
    plot(CDRS{i}(:,1),CDRS{i}(:,5),'k','LineWidth',1);
    set(gca,'FontName','Times New Roman')
    title(eqmotions{i},'FontName','Times New Roman')
    ylabel('fy','FontName','Times New Roman')
    xlabel('Period (s)','FontName','Times New Roman')
    axis tight
end

```



Plot constant ductility spectral achieved ductility


```
Fig5 = figure('units', 'centimeters', 'Position', [0,0, 20/sqrt(2), 20]);  
% Scan all subplots  
for i=1:numel(eqmotions)  
    subplot(4,3,i)  
    plot(CDRS{i}(:,1),CDRS{i}(:,6),'k','LineWidth',1);  
    set(gca,'FontName','Times New Roman')  
    title(eqmotions{i},'FontName','Times New Roman')  
    ylabel('mu','FontName','Times New Roman')  
    xlabel('Period (s)','FontName','Times New Roman')  
    axis tight  
end
```



Plot constant ductility spectral number of iterations needed for convergence

```
Fig6 = figure('units', 'centimeters', 'Position', [0,0, 20/sqrt(2), 20]);
% Scan all subplots
for i=1:numel(eqmotions)
    subplot(4,3,i)
    plot(CDRS{i}(:,1),CDRS{i}(:,7),'k','LineWidth',1);
    set(gca,'FontName','Times New Roman')
    title(eqmotions{i},'FontName','Times New Roman')
    ylabel('iter','FontName','Times New Roman')
    xlabel('Period (s)','FontName','Times New Roman')
```

```
axis tight
end
```



Copyright

Copyright (c) 2018-2022 by George Papazafeiropoulos

- Major, Infrastructure Engineer, Hellenic Air Force
- Civil Engineer, M.Sc., Ph.D.
- Email: gpapazafeiropoulos@yahoo.gr

Fourier spectra

Generate the Fourier spectra of an earthquake suite using OpenSeismoMatlab.

Contents

- [Input](#)
- [Calculation](#)
- [Output](#)
- [Copyright](#)

Input

earthquake motions

```
eqmotions={'Imperial Valley'; % Imperial valley 1979
           'Kocaeli';
           'Loma Prieta';
           'Northridge';
           'San Fernando';
           'Spitak';
           'Cape Mendocino';
           'ChiChi';
           'El Centro'; % Imperial valley 1940
           'Hollister';
           'Kobe'};
```

Set the eigenperiod range for which the response spectra will be calculated.

```
Tspectra=(0.02:0.01:4)';
```

Set critical damping ratio of the response spectra to be calculated.

```
ksi=0.05;
```

Set the target ductility (not used here)

```
mu=2;
```

Extract fourier spectra

```
sw='fas' ;
```

Calculation

Initialize Fourier


```

Fourier=cell(numel(eqmotions),1);
% Calculation of peak values
for i=1:numel(eqmotions)
    % earthquake
    data=load([eqmotions{i},'.dat']);
    t=data(:,1);
    dt=t(2)-t(1);
    xgtt=data(:,2);
    S=OpenSeismoMatlab(dt,xgtt,sw);
    Fourier{i}=[S.freq,S.FAS];
end

```


Output

Plot Fourier amplitude

```

Fig1 = figure('units', 'centimeters', 'Position', [0,0, 20/sqrt(2), 20]);
% Scan all subplots
for i=1:numel(eqmotions)
    subplot(4,3,i)
    plot(Fourier{i}(:,1),Fourier{i}(:,2),'k','LineWidth',1);
    set(gca,'FontName','Times New Roman')
    title(eqmotions{i},'FontName','Times New Roman')
    ylabel('FAS','FontName','Times New Roman')
    xlabel('Frequency (Hz)','FontName','Times New Roman')
    axis tight
end

```



Copyright

Copyright (c) 2018-2022 by George Papazafeiropoulos

- Major, Infrastructure Engineer, Hellenic Air Force
- Civil Engineer, M.Sc., Ph.D.
- Email: gpapazafeiropoulos@yahoo.gr

Linear elastic response spectra

Generate the linear elastic response spectra of an earthquake suite using OpenSeismoMatlab.

Contents

- [Input](#)
- [Calculation](#)
- [Output](#)
- [Copyright](#)

Input

Earthquake motions

```
eqmotions={'Imperial Valley'; % Imperial valley 1979
           'Kocaeli';
           'Loma Prieta';
           'Northridge';
           'San Fernando';
           'Spitak';
           'Cape Mendocino';
           'ChiChi';
           'El Centro'; % Imperial valley 1940
           'Hollister';
           'Kobe'};
```

Set the eigenperiod range for which the response spectra will be calculated.

```
Tspectra=(0.01:0.01:4)';
```

Set critical damping ratio of the response spectra to be calculated.

```
ksi=0.05;
```

Set the target ductility (not used here)

```
mu=2;
```

Extract linear elastic response spectra

```
sw='es' ;
```

Calculation

Initialize LERS

```
LERS=cell(numel(eqmotions),1);
```


Calculation of peak values

```
for i=1:numel(eqmotions)
    % earthquake
    data=load([eqmotions{i},'.dat']);
    t=data(:,1);
    dt=t(2)-t(1);
    xgtt=data(:,2);
    S=OpenSeismoMatlab(dt,xgtt,sw,[],[],ksi,Tspectra,mu);
    LERS{i}=[S.Period,S.Sd,S.PSv,S.PSa];
end
```

Output

Plot displacement response spectra


```
Fig1 = figure('units', 'centimeters', 'Position', [0,0, 20/sqrt(2), 20]);
% Scan all subplots
for i=1:numel(eqmotions)
    subplot(4,3,i)
    plot(LERS{i}(:,1),LERS{i}(:,2),'k','LineWidth',1);
    set(gca,'FontName','Times New Roman')
    title(eqmotions{i},'FontName','Times New Roman')
    ylabel('Sd','FontName','Times New Roman')
    xlabel('Period (s)','FontName','Times New Roman')
    axis tight
end
```



Plot pseudo-velocity response spectra

```
Fig2 = figure('units', 'centimeters', 'Position', [0,0, 20/sqrt(2), 20]);
% Scan all subplots
for i=1:numel(eqmotions)
    subplot(4,3,i)
    plot(LEERS{i}(:,1),LEERS{i}(:,3),'k','LineWidth',1);
    set(gca,'FontName','Times New Roman')
    title(eqmotions{i},'FontName','Times New Roman')
    ylabel('PSv','FontName','Times New Roman')
    xlabel('Period (s)','FontName','Times New Roman')
```

```
axis tight
end
```




Plot pseudo-acceleration response spectra

```
Fig3 = figure('units', 'centimeters', 'Position', [0,0, 20/sqrt(2), 20]);
% Scan all subplots
for i=1:numel(eqmotions)
    subplot(4,3,i)
    plot(LERS{i}(:,1),LERS{i}(:,4),'k','LineWidth',1);
end
```

```

set(gca,'FontName','Times New Roman')
title(egmotions{i},'FontName','Times New Roman')
ylabel('PSa','FontName','Times New Roman')
xlabel('Period (s)','FontName','Times New Roman')
axis tight
end

```



Copyright

Copyright (c) 2018-2022 by George Papazafeiropoulos

- Major, Infrastructure Engineer, Hellenic Air Force
 - Civil Engineer, M.Sc., Ph.D.
 - Email: gpapazafeiropoulos@yahoo.gr
-

Comparison of elastic and constant ductility response spectra for $\mu=1$

Compare the linear elastic acceleration response spectrum and the constant ductility response spectrum for $\mu=1$ (degenerates to linear elastic). Also, compare with corresponding results of SeismoSignal software

Contents

- [Input](#)
- [First we use the CDS to calculate linear response](#)
- [Next we use ES to calculate linear response](#)
- [Results from SeismoSignal](#)
- [Output](#)

Input

Earthquake motion

```
eqmotions={'Imperial Valley'}; % Imperial valley 1979
data=load([eqmotions{1},'.dat']);
t=data(:,1);
dt=t(2)-t(1);
xgtd=data(:,2);
```

Set the eigenperiod range for which the response spectra will be calculated.

```
Tspectra=(0.05:0.05:4)';
```

Set critical damping ratio of the response spectra to be calculated.

```
ksi=0.05;
```

First we use the CDS to calculate linear response

Set the target ductility

```
mu=1; % mu=1 equivalent to a linear SDoF
```

Extract constant ductility response spectra

```
sw='cds';
```

Calculation CDRS{i}=[S.Period,S.CDSd,S.CDSv,S.CDPSa,S.fyK,S.muK,S.iterK];

```
S1=OpenSeismoMatlab(dt,xgtd,sw,[],[],ksi,Tspectra,mu);
```

Next we use ES to calculate linear response

Extract linear elastic response spectra

```
sw='es';
```

Initialize LERS

```
LERS=cell(numel(eqmotions),1);
```

Calculation LERS{i}=[S.Period,S.Sd,S.PSv,S.PSa];

```
S2=OpenSeismoMatlab(dt,xgtd,sw,[],[],ksi,Tspectra,mu);
```


Results from SeismoSignal

```
fileID = fopen('SeismoSignal_Imperial Valley.txt');  
for idx = 1:5  
    fgetl(fileID);  
end  
C = textscan(fileID, repmat('%f',1,12));  
fclose(fileID);
```

Output

Plot spectral acceleration response spectra

```
plot(S1.Period,S1.CDSa,'k','LineWidth',1);  
hold on  
plot(S2.Period,S2.Sa,'r','LineWidth',1);  
plot(C{1},C{2})  
legend('CDS with mu=1','LinearSpectrum','SeismoSignal');  
xlabel('Period');  
ylabel('Spectra Acc.')
```



Comparison of constant ductility response spectra of RSN1044 for $\mu=2$

Contents

- [Input](#)
- [Results from OpenSeismoMatlab](#)
- [Results from SeismoSignal](#)
- [Output](#)

Input

Earthquake motions

```
GMFileLoc = 'input\';
```

A text file containing the lists of GM names

```
RecordList = ['input\Record_List.txt'];
```

Read E.Q. records name from the specifid list

```
fid = fopen (RecordList,'r');  
records = textscan(fid, '%s'); % length = num of records*1, cell  
fclose (fid);
```

Read E.Q. records name from the specifid list Return variables include record names, dt, num of points, PGA, Acc TH, Spectral Acc The accelration-related variables (PGA, Sa, Acc TH) are in unit of g; disp-related in m If you do not specify scaling factors at this step, the default value = 1 for each GM

```
[RecordName_all, dt, numPoint_all, PGA_all, xgtd] =...  
    fn_ParseAT2File2(GMFileLoc, records);
```

Set the eigenperiod range for which the response spectra will be calculated.

```
Tspectra=(0.05:0.05:4)';
```

Set critical damping ratio of the response spectra to be calculated.

```
ksi=0.02;
```

Results from OpenSeismoMatlab

Set the target ductility

```
mu=2; % mu=1 equivalent to a linear SDoF
```

Extract constant ductility response spectra

```
sw='cds' ;
```

Calculation CDRS{i}=[S.Period,S.CDSd,S.CDSv,S.CDPSa,S.fyK,S.muK,S.iterK];

```
S1=OpenSeismoMatlab(dt,xgtt{1},sw,[],[],ksi,Tspectra,mu);
```

Results from SeismoSignal


```
fileID = fopen('input/RSN1044_Damping2.txt');  
for idx = 1:5  
    fgetl(fileID);  
end  
C = textscan(fileID, repmat('%f',1,15));  
fclose(fileID);
```

Output

Plot spectral acceleration response spectra


```
figure()  
plot(S1.Period,S1.CDSa/9.8,'k','LineWidth',1);  
hold on  
%plot(S2.Period,S2.Sa,'r','LineWidth',1);  
plot(C{1},C{3})  
legend('CDS with mu=2','SeismoSignal');  
xlabel('Period');  
ylabel('Spectra Acc.')
```

```
hold off
```




Plot spectral velocity response spectra

```
figure()
plot(S1.Period,S1.CDSv,'k','LineWidth',1);
hold on
%plot(S2.Period,S2.Sa,'r','LineWidth',1);
plot(C{1},C{7}/100)
legend('CDS with mu=2','SeismoSignal');
xlabel('Period');
ylabel('Spectra Vel.')
hold off
```




Plot spectral displacement response spectra

```
figure()
plot(S1.Period,S1.CDSd,'k','LineWidth',1);
hold on
%plot(S2.Period,S2.Sa,'r','LineWidth',1);
plot(C{1},C{11}/100)
legend('CDS with mu=2','SeismoSignal');
xlabel('Period');
ylabel('Spectra Disp.')
hold off
```

Plot the achieved ductility for each eigenperiod. It should be equal or close to the target ductility $\mu=2$

```
figure()
plot(S1.Period,S1.muK,'k','LineWidth',1);
xlabel('Period');
ylabel('Real mu values after iterations')
```



Verification

This is to verify that OpenSeismoMatlab works properly for all of its possible options and types of application

Contents

- [Load earthquake data](#)
- [Time histories without baseline correction](#)
- [Time histories with baseline correction](#)
- [Resample acceleration time history from 0.02 sec to 0.01 sec.](#)
- [PGA](#)
- [PGV](#)
- [PGD](#)
- [Arias intensity and significant duration](#)
- [Linear elastic response spectra and pseudospectra](#)
- [Constant ductility response spectra and pseudospectra](#)
- [Fourier amplitude spectrum and mean period](#)
- [Copyright](#)

Load earthquake data


Earthquake acceleration time history of the El Centro earthquake will be used (El Centro, 1940, El Centro Terminal Substation Building)

```
fid=fopen('elcentro.dat','r');
text=textscan(fid,'%f %f');
fclose(fid);
t=text{1,1};
dt=t(2)-t(1);
xgtt=9.81*text{1,2};
```


Time histories without baseline correction

```
sw='timehist';
baselineSw=false;
S1=OpenSeismoMatlab(dt,xgtt,sw,baselineSw);
```


```
figure(1)
plot(S1.time,S1.disp,'k','LineWidth',1)
```



```
figure(2)  
plot(S1.time,S1.vel,'k','LineWidth',1)
```




```
figure(3)
plot(S1.time,S1.acc,'k','LineWidth',1)
```




Time histories with baseline correction

```
sw='timehist';
baselineSw=true;
S2=OpenSeismoMatlab(dt,xgtt,sw,baselineSw);
```


```
figure(4)
plot(S2.time,S2.disp,'k','LineWidth',1)
```



```
figure(5)
plot(S2.time,S2.vel,'k','LineWidth',1)
```




```
figure(6)
plot(S2.time,S2.acc,'k','LineWidth',1)
```



Resample acceleration time history from 0.02 sec to 0.01 sec.

```
sw='resample';
dti=0.01;
S3=OpenSeismoMatlab(dt,xgtd,sw,[],dti);
```

```
figure(7)
plot(S3.time,S3.acc,'k','LineWidth',1)
```



PGA

```
sw='pga' ;  
S4=OpenSeismoMatlab(dt,xgtt,sw);
```

```
S4.PGA
```

```
ans =  
  
3.127624200000000
```

PGV

```
sw='pgv' ;  
S5=OpenSeismoMatlab(dt,xgtt,sw);
```

```
S5.PGV
```

```
ans =  
  
0.360920691000000
```


PGD

```
sw='pgd';  
S6=OpenSeismoMatlab(dt,xgtt,sw);
```

```
S6.PGD
```

```
ans =  
  
    0.211893410160001
```


Arias intensity and significant duration

```
sw='arias';  
S7=OpenSeismoMatlab(dt,xgtt,sw);
```

```
S7.Ecum
```

```
ans =  
  
    11.251388628141965
```

```
figure(8)  
plot(S7.time,S7.EcumTH,'k','LineWidth',1)
```



S7.t_5_95

ans =

1.6800000000000000 25.500000000000000

S7.Td

ans =

23.840000000000000

S7.arias


ans =

1.645606908074047


Linear elastic response spectra and pseudospectra

```
sw='es';  
ksi=0.05;  
T=0.04:0.02:1;  
S8=OpenSeismoMatlab(dt,xgtd,sw,[],[],ksi,T);
```


```
figure(9)  
plot(S8.Period,S8.PSa,'k','LineWidth',1)
```




```
figure(10)  
plot(S8.Period,S8.PSv,'k','LineWidth',1)
```




```
figure(11)  
plot(S8.Period,S8.Sd,'k','LineWidth',1)
```




```
figure(12)
plot(S8.Period,S8.Sv,'k','LineWidth',1)
```



```
figure(13)
plot(S8.Period,S8.Sa,'k','LineWidth',1)
```




```
figure(14)
plot(S8.Period,S8.SievABS,'k','LineWidth',1)
```



```
figure(15)
plot(S8.Period,S8.SievREL,'k','LineWidth',1)
```

Warning: Imaginary parts of complex X
and/or Y arguments ignored



```
S8.PredPSa
```

```
ans =  
  
8.990993548805100
```

```
S8.PredPeriod
```


```
ans =  
  
0.5000000000000000
```

Constant ductility response spectra and pseudospectra


```
sw='c ds';  
ksi=0.05;
```

```
T=0.04:0.02:1;  
mu=2;  
S9=OpenSeismoMatlab(dt,xgtt,sw,[],[],ksi,T,mu);
```


```
figure(15)  
plot(S9.Period,S9.CDPSa,'k','LineWidth',1)
```




```
figure(16)  
plot(S9.Period,S9.CDPSv,'k','LineWidth',1)
```


```
figure(17)
plot(S9.Period,S9.CDSd,'k','LineWidth',1)
```




```
figure(18)
plot(S9.Period,S9.CDSv,'k','LineWidth',1)
```




```
figure(19)
plot(S9.Period,S9.CDSa,'k','LineWidth',1)
```




```
figure(20)
plot(S9.Period,S9.fyK,'k','LineWidth',1)
```



```
figure(21)
plot(S9.Period,S9.muK,'k','LineWidth',1)
```




```
figure(22)
plot(S9.Period,S9.iterK,'k','LineWidth',1)
```



Fourier amplitude spectrum and mean period

```
sw='fas';  
S10=OpenSeismoMatlab(dt,xgtt,sw);
```

```
figure(23)  
plot(S10.freq,S10.FAS,'k','LineWidth',1)
```



```
S10.Tm
```

```
ans =  
  
0.533389590787339
```

```
S10.Fm
```

```
ans =  
  
3.293755163661824
```

Copyright

Copyright (c) 2018-2022 by George Papazafeiropoulos

- Major, Infrastructure Engineer, Hellenic Air Force
- Civil Engineer, M.Sc., Ph.D.
- Email: gpapazafeiropoulos@yahoo.gr

FASp

Documentation of the FASp function.

```
helpFun('FASp')
```

Single sided Fourier amplitude spectrum

```
[F,U] = FASP(DT,XGTT)
```

Description

Fourier amplitude spectrum of an earthquake.

Input parameters

DT [double(1 x 1)] is the time step of the input acceleration time history XGTT.

XGTT [double(1:numsteps x 1)] is the input acceleration time history.
numsteps is the length of the input acceleration time history.

Output parameters

F [double(1:2^(nextpow2(length(XGTT))-1) x 1)] is the frequency range in which the Fourier amplitudes are calculated.

U [double(1:2^(nextpow2(length(XGTT))-1) x 1)] contains the Fourier amplitudes

Copyright (c) 2018-2022

George Papazafeiropoulos

Major, Infrastructure Engineer, Hellenic Air Force

Civil Engineer, M.Sc., Ph.D.

Email: gpapazafeiropoulos@yahoo.gr

HalfStep

Documentation of the HalfStep function.

```
helpFun('HalfStep')
```

Reproduce signal with half time step

```
UNEW = HALFSTEP(U)
```

Input parameters

U [double(1:n x 1)] is the input signal with time step dt.

Output parameters

UNEW [double(1:n x 1)] is the output signal with time step dt/2.

Verification:

```
%  
u=0.2:0.2:4;  
%  
uNew=HalfStep(u);  
%  
figure()  
plot((1:numel(u)),u)  
hold on  
plot((1:0.5:numel(u)),uNew)
```

Copyright (c) 2018-2022

George Papazafeiropoulos

Major, Infrastructure Engineer, Hellenic Air Force

Civil Engineer, M.Sc., Ph.D.

Email: gpapazafeiropoulos@yahoo.gr

```
helpFun('LEReSp')
```

Fast calculation of Linear Elastic Response Spectra (LEReSp) and pseudospectra.

```
[PSA,PSV,SD,SV,SA,SIEVABS,SIEVREL]=LERESP(DT,XGTT,T,KSI)
```

Description

The linear elastic response spectra for a given time-history of constant time step, a given eigenperiod range and a given viscous damping ratio are computed.

Input parameters

DT [double(1 x 1)] is the time step of the input acceleration time history XGTT.

XGTT [double(1:numsteps x 1)] is the input acceleration time history. numsteps is the length of the input acceleration time history.

T [double(1:numSDOFs x 1)] contains the values of eigenperiods for which the response spectra are requested. numSDOFs is the number of SDOF oscillators being analysed to produce the spectra.

KSI [double(1 x 1)] is the fraction of critical viscous damping.

DTTOL [double(1 x 1)] is the maximum ratio of the integration time step to the eigenperiod. Default value 0.01.

ALGID [char(1 x :inf)] is the algorithm to be used for the time integration. It can be one of the following strings for superior optimally designed algorithms:

'generalized a-method': The generalized a-method (Chung & Hulbert, 1993)

'HHT a-method': The Hilber-Hughes-Taylor method (Hilber, Hughes & Taylor, 1977)

'WBZ': The Wood-Bossak-Zienkiewicz method (Wood, Bossak & Zienkiewicz, 1980)

'U0-V0-Opt': Optimal numerical dissipation and dispersion zero order displacement zero order velocity algorithm

'U0-V0-CA': Continuous acceleration (zero spurious root at the low frequency limit) zero order displacement zero order velocity algorithm

'U0-V0-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) zero order displacement zero order velocity algorithm

'U0-V1-Opt': Optimal numerical dissipation and dispersion zero order displacement first order velocity algorithm

'U0-V1-CA': Continuous acceleration (zero spurious root at the low frequency limit) zero order displacement first order velocity algorithm

'U0-V1-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) zero order displacement first order velocity algorithm

'U1-V0-Opt': Optimal numerical dissipation and dispersion first order displacement zero order velocity algorithm

'U1-V0-CA': Continuous acceleration (zero spurious root at the low frequency limit) first order displacement zero order

```

velocity algorithm
'U1-V0-DA': Discontinuous acceleration (zero spurious root at
the high frequency limit) first order displacement zero order
velocity algorithm
'Newmark ACA': Newmark Average Constant Acceleration method
'Newmark LA': Newmark Linear Acceleration method
'Newmark BA': Newmark Backward Acceleration method
'Fox-Goodwin': Fox-Goodwin formula
RINF [double(1 x 1)] is the minimum absolute value of the eigenvalues
of the amplification matrix. For the amplification matrix see
eq.(61) in Zhou & Tamma (2004).

```

Output parameters

```

PSA [double(1:numSDOFs x 1)] is the Pseudo Acceleration Spectrum.
PSV [double(1:numSDOFs x 1)] is the Pseudo Velocity Spectrum.
SD [double(1:numSDOFs x 1)] is the Spectral Displacement.
SV [double(1:numSDOFs x 1)] is the Spectral Velocity.
SA [double(1:numSDOFs x 1)] is the Spectral Acceleration.
SIEVABS [double(1:numSDOFs x 1)] is the equivalent absolute input
energy velocity.
SIEVREL [double(1:numSDOFs x 1)] is the equivalent relative input
energy velocity.

```

Example

```

%
dt=0.02;
%
N=10;
a=rand(N,1)-0.5;
b=100*pi*rand(N,1);
c=pi*(rand(N,1)-0.5);
t=(0:dt:(100*dt))';
xgtt=zeros(size(t));
for i=1:N
    xgtt=xgtt+a(i)*sin(b(i)*t+c(i));
end
%
T=logspace(log10(0.02),log10(50),1000)';
%
ksi=0.05;
%
[PSa,PSv,Sd,Sv,Sa,SievABS,SievREL]=LEResp(dt,xgtt,T,ksi);

```

Copyright (c) 2018-2022

George Papazafeiropoulos
Major, Infrastructure Engineer, Hellenic Air Force
Civil Engineer, M.Sc., Ph.D.
Email: gpapazafeiropoulos@yahoo.gr

Documentation of the LIDA function.

```
helpFun('LIDA')
```

Linear Implicit Dynamic Analysis (LIDA)

```
[U,UT,UTT] = LIDA(DT,XGTT,OMEGA,KSI,U0,UT0,RINF)
```

Description

Linear implicit direct time integration of second order differential equation of motion of dynamic response of linear elastic SDOF systems. The General Single Step Single Solve (GSSSS) family of algorithms published by X.Zhou & K.K.Tamma (2004) is employed for direct time integration of the general linear or nonlinear structural Single Degree of Freedom (SDOF) dynamic problem. The optimal numerical dissipation and dispersion zero order displacement zero order velocity algorithm designed according to the above journal article, is used in this routine. This algorithm encompasses the scope of Linear Multi-Step (LMS) methods and is limited by the Dahlquist barrier theorem (Dahlquist,1963). The force - displacement - velocity relation of the SDOF structure is linear.

Input parameters

DT [double(1 x 1)] is the time step

XGTT [double(1:nstep x 1)] is the column vector of the acceleration history of the excitation imposed at the base. nstep is the number of time steps of the dynamic response.

OMEGA [double(1 x 1)] is the eigenfrequency of the structure in rad/sec.

KSI [double(1 x 1)] is the ratio of critical damping of the SDOF system. Default value 0.05.

U0 [double(1 x 1)] is the initial displacement of the SDOF system. Default value 0.

UT0 [double(1 x 1)] is the initial velocity of the SDOF system. Default value 0.

ALGID [char(1 x :inf)] is the algorithm to be used for the time integration. It can be one of the following strings for superior optimally designed algorithms:

'generalized a-method': The generalized a-method (Chung & Hulbert, 1993)

'HHT a-method': The Hilber-Hughes-Taylor method (Hilber, Hughes & Taylor, 1977)

'WBZ': The Wood-Bossak-Zienkiewicz method (Wood, Bossak & Zienkiewicz, 1980)

'U0-V0-Opt': Optimal numerical dissipation and dispersion zero order displacement zero order velocity algorithm

'U0-V0-CA': Continuous acceleration (zero spurious root at the low frequency limit) zero order displacement zero order velocity algorithm

'U0-V0-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) zero order displacement zero order velocity algorithm

'U0-V1-Opt': Optimal numerical dissipation and dispersion zero order displacement first order velocity algorithm

'U0-V1-CA': Continuous acceleration (zero spurious root at the low frequency limit) zero order displacement first order velocity algorithm
 'U0-V1-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) zero order displacement first order velocity algorithm
 'U1-V0-Opt': Optimal numerical dissipation and dispersion first order displacement zero order velocity algorithm
 'U1-V0-CA': Continuous acceleration (zero spurious root at the low frequency limit) first order displacement zero order velocity algorithm
 'U1-V0-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) first order displacement zero order velocity algorithm
 'Newmark ACA': Newmark Average Constant Acceleration method
 'Newmark LA': Newmark Linear Acceleration method
 'Newmark BA': Newmark Backward Acceleration method
 'Fox-Goodwin': Fox-Goodwin formula
 RINF [double(1 x 1)] is the minimum absolute value of the eigenvalues of the amplification matrix. For the amplification matrix see eq.(61) in Zhou & Tamma (2004). Default value 1.

Output parameters

U [double(1:nstep x 1)] is the time-history of displacement
 UT [double(1:nstep x 1)] is the time-history of velocity
 UTT [double(1:nstep x 1)] is the time-history of acceleration

Example (Figure 6.6.1 in Chopra, $T_n=1\text{sec}$)

```

dt=0.02;
fid=fopen('elcentro.dat','r');
text=textscan(fid,'%f %f');
fclose(fid);
xgtd=9.81*text{1,2};
Tn=1;
omega=2*pi/Tn;
ksi=0.02;
u0=0;
ut0=0;
rinf=1;
[u,ut,utt] = LIDA(dt,xgtd,omega,ksi,u0,ut0,rinf);
D=max(abs(u))/0.0254
  
```

Copyright (c) 2018-2022

George Papazafeiropoulos
 Major, Infrastructure Engineer, Hellenic Air Force
 Civil Engineer, M.Sc., Ph.D.
 Email: gpapazafeiropoulos@yahoo.gr

NLIDABLKIN

Documentation of the NLIDABLKIN function.

```
helpFun('NLIDABLKIN')
```

Non Linear Implicit Dynamic Analysis of a bilinear kinematic hardening hysteretic structure with elastic damping

```
[U,UT,UTT,FS,EY,ES,ED,JITER] = NLIDABLKIN(DT,XGTT,M,K_HI,K_LO,UY,KSI,...  
    ALGID,U0,UT0,RINF,MAXTOL,JMAX,DAK)
```

Description

General linear implicit direct time integration of second order differential equations of a bilinear elastoplastic hysteretic SDOF dynamic system with elastic damping, with lumped mass. The General Single Step Single Solve (GSSSS) family of algorithms published by X.Zhou & K.K.Tamma (2004) is employed for direct time integration of the general linear or nonlinear structural Single Degree of Freedom (SDOF) dynamic problem. Selection among 9 algorithms, all designed according to the above journal article, can be made in this routine. These algorithms encompass the scope of Linear Multi-Step (LMS) methods and are limited by the Dahlquist barrier theorem (Dahlquist,1963).

Input parameters

DT [double(1 x 1)] is the time step of the integration
XGTT [double(1:NumSteps x 1)] is the acceleration time history which is imposed at the lumped mass of the SDOF structure.
M [double(1 x 1)] is the lumped masses of the structure. Define the lumped masses from the top to the bottom, excluding the fixed dof at the base
K_HI [double(1 x 1)] is the initial stiffness of the system before its first yield, i.e. the high stiffness. Give the stiffness of each storey from top to bottom.
K_LO [double(1 x 1)] is the post-yield stiffness of the system, i.e. the low stiffness. Give the stiffness of each storey from top to bottom.
UY [double(1 x 1)] is the yield limit of the stiffness elements of the structure. The element is considered to yield, if the interstorey drift between degrees of freedom i and i+1 exceeds UY(i). Give the yield limit of each storey from top to bottom.
KSI [double(1 x 1)] is the ratio of critical viscous damping of the system, assumed to be unique for all damping elements of the structure.
ALGID [char(1 x :inf)] is the algorithm to be used for the time integration. It can be one of the following strings for superior optimally designed algorithms:
 'generalized a-method': The generalized a-method (Chung & Hulbert, 1993)
 'HHT a-method': The Hilber-Hughes-Taylor method (Hilber, Hughes & Taylor, 1977)
 'WBZ': The Wood-Bossak-Zienkiewicz method (Wood, Bossak & Zienkiewicz, 1980)
 'U0-V0-Opt': Optimal numerical dissipation and dispersion zero order displacement zero order velocity algorithm

'U0-V0-CA': Continuous acceleration (zero spurious root at the low frequency limit) zero order displacement zero order velocity algorithm
 'U0-V0-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) zero order displacement zero order velocity algorithm
 'U0-V1-Opt': Optimal numerical dissipation and dispersion zero order displacement first order velocity algorithm
 'U0-V1-CA': Continuous acceleration (zero spurious root at the low frequency limit) zero order displacement first order velocity algorithm
 'U0-V1-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) zero order displacement first order velocity algorithm
 'U1-V0-Opt': Optimal numerical dissipation and dispersion first order displacement zero order velocity algorithm
 'U1-V0-CA': Continuous acceleration (zero spurious root at the low frequency limit) first order displacement zero order velocity algorithm
 'U1-V0-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) first order displacement zero order velocity algorithm
 'Newmark ACA': Newmark Average Constant Acceleration method
 'Newmark LA': Newmark Linear Acceleration method
 'Newmark BA': Newmark Backward Acceleration method
 'Fox-Goodwin': Fox-Goodwin formula
 U0 [double(1 x 1)] is the initial displacement.
 UT0 [double(1 x 1)] is the initial velocity.
 RINF [double(1 x 1)] is the minimum absolute value of the eigenvalues of the amplification matrix. For the amplification matrix see eq.(61) in Zhou & Tamma (2004).
 MAXTOL [double(1 x 1)] is the maximum tolerance of convergence of the Full Newton Raphson method for numerical computation of acceleration.
 JMAX [double(1 x 1)] is the maximum number of iterations per increment. If JMAX=0 then iterations are not performed and the MAXTOL parameter is not taken into account.
 DAK [double(1 x 1)] is the infinitesimal acceleration for the calculation of the derivative required for the convergence of the Newton-Raphson iteration.

Output parameters

U [double(1 x 1:NumSteps)] is the time-history of displacement
 UT [double(1 x 1:NumSteps)] is the time-history of velocity
 UTT [double(1 x 1:NumSteps)] is the time-history of acceleration
 FS [double(1 x 1:NumSteps)] is the time-history of the internal force of the structure analysed.
 EY [double(1 x 1:NumSteps)] is the time history of the sum of the energy dissipated by yielding during each time step and the recoverable strain energy of the system (incremental). cumsum(EY)-Es gives the time history of the total energy dissipated by yielding from the start of the dynamic analysis.
 ES [double(1 x 1:NumSteps)] is the time-history of the recoverable strain energy of the system (total and not incremental).
 ED [double(1 x 1:NumSteps)] is the time-history of the energy dissipated by viscoelastic damping during each time step (incremental). cumsum(ED) gives the time history of the total energy dissipated from the start of the dynamic analysis.
 JITER [double(1 x 1:NumSteps)] is the iterations per increment

Notation in the code

u=displacement
un=displacement after increment n
ut=velocity
utn=velocity after increment n
utt=acceleration
uttn=acceleration after increment n

Copyright (c) 2018-2022

George Papazafeiropoulos

Major, Infrastructure Engineer, Hellenic Air Force

Civil Engineer, M.Sc., Ph.D.

Email: gpapazafeiropoulos@yahoo.gr

```
helpFun('OpenSeismoMatlab')
```

Seismic parameters of an acceleration time history

```
PARAM=OPENSEISMOMATLAB(DT,XGTT,SW,BASELINE,DTI,KSI,T,MU,PYSF,ALGID)
```

Description

This function calculates the seismic parameters from an acceleration time history. More specifically, it calculates the following:

- 1) Velocity vs time
- 2) Displacement vs time
- 3) Resampled acceleration time history (i.e. the input acceleration time history with modified time step size)
- 4) Peak ground acceleration
- 5) Peak ground velocity
- 6) Peak ground displacement
- 7) Total cumulative energy and normalized cumulative energy vs time
- 8) Significant duration according to Trifunac & Brady (1975)
- 9) Total Arias intensity (Ia)
- 10) Linear elastic pseudo-acceleration response spectrum
- 11) Linear elastic pseudo-velocity response spectrum
- 12) Linear elastic displacement response spectrum
- 13) Linear elastic velocity response spectrum
- 14) Linear elastic acceleration response spectrum
- 15) Constant ductility displacement response spectrum
- 16) Constant ductility velocity response spectrum
- 17) Constant ductility acceleration response spectrum
- 18) Fourier amplitude spectrum
- 19) Mean period (Tm)

Input parameters

DT [double(1 x 1)] is the size of the time step of the input acceleration time history xgtt.

XGTT [double(1:numsteps x 1)] is the input acceleration time history.

SW [char(1 x :inf)] is a string which determines which parameters of the input acceleration time history will be calculated. sw can take one of the following values (strings are case insensitive):

- 'TIMEHIST': the displacement, velocity and acceleration time histories are calculated.
- 'RESAMPLE': the acceleration time history with modified time step size is calculated.
- 'PGA': The peak ground acceleration is calculated.
- 'PGV': The peak ground velocity is calculated.
- 'PGD': The peak ground displacement is calculated.
- 'ARIAS': The total cumulative energy, significant duration according to Trifunac & Brady (1975) and Arias intensity are calculated.
- 'ES': The linear elastic response spectra and pseudospectra are calculated.
- 'CDS': The constant ductility response spectra are calculated.
- 'FAS': The Fourier amplitude spectrum and the mean period are calculated.

BASELINE\$W [logical(1 x 1)] determines if baseline correction will be applied for the calculation of the various output quantities.
 DTI [double(1 x 1)] is the new time step size for resampling of the input acceleration time history.
 KSI [double(1 x 1)] is the fraction of critical viscous damping.
 T [double(1:numSDOFs x 1)] contains the values of eigenperiods for which the response spectra are requested. numSDOFs is the number of SDOF oscillators being analysed to produce the spectra.
 MU [double(1 x 1)] is the specified ductility for which the response spectra are calculated.
 PYSF [double(1 x 1)] is the post-yield stiffness factor, i.e. the ratio of the postyield stiffness to the initial stiffness. PYSF=0 is not recommended for simulation of an elastoplastic system. A small positive value is always suggested. PYSF is ignored if MU=1. Default value 0.01.
 ALGID [char(1 x :inf)] is the algorithm to be used for the time integration, if applicable. It can be one of the following strings for superior optimally designed algorithms (strings are case sensitive):
 'generalized a-method': The generalized a-method (Chung & Hulbert, 1993)
 'HHT a-method': The Hilber-Hughes-Taylor method (Hilber, Hughes & Taylor, 1977)
 'WBZ': The Wood-Bossak-Zienkiewicz method (Wood, Bossak & Zienkiewicz, 1980)
 'U0-V0-Opt': Optimal numerical dissipation and dispersion zero order displacement zero order velocity algorithm
 'U0-V0-CA': Continuous acceleration (zero spurious root at the low frequency limit) zero order displacement zero order velocity algorithm
 'U0-V0-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) zero order displacement zero order velocity algorithm
 'U0-V1-Opt': Optimal numerical dissipation and dispersion zero order displacement first order velocity algorithm
 'U0-V1-CA': Continuous acceleration (zero spurious root at the low frequency limit) zero order displacement first order velocity algorithm
 'U0-V1-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) zero order displacement first order velocity algorithm
 'U1-V0-Opt': Optimal numerical dissipation and dispersion first order displacement zero order velocity algorithm
 'U1-V0-CA': Continuous acceleration (zero spurious root at the low frequency limit) first order displacement zero order velocity algorithm
 'U1-V0-DA': Discontinuous acceleration (zero spurious root at the high frequency limit) first order displacement zero order velocity algorithm
 'Newmark ACA': Newmark Average Constant Acceleration method
 'Newmark LA': Newmark Linear Acceleration method
 'Newmark BA': Newmark Backward Acceleration method
 'Fox-Goodwin': Fox-Goodwin formula

Output parameters

PARAM (structure) has the following fields:

PARAM.vel [double(1:numsteps x 1)] Velocity vs time
 PARAM.disp [double(1:numsteps x 1)] Displacement vs time
 PARAM.PGA [double(1 x 1)] Peak ground acceleration
 PARAM.PGV [double(1 x 1)] Peak ground velocity
 PARAM.PGD [double(1 x 1)] Peak ground displacement

PARAM.Ecum [double(1 x 1)] Total cumulative energy
 PARAM.EcumTH [double(1:numsteps x 1)] normalized cumulative energy vs time
 PARAM.t_5_95 [double(1 x 2)] Time instants at which 5% and 95% of cumulative energy have occurred
 PARAM.Td [double(1 x 1)] Time between when 5% and 95% of cumulative energy has occurred (significant duration according to Trifunac-Brady (1975))
 PARAM.arias [double(1 x 1)] Total Arias intensity (Ia)
 PARAM.PSa [double(:inf x 1)] Linear elastic pseudo-acceleration response spectrum
 PARAM.PSv [double(:inf x 1)] Linear elastic pseudo-velocity response spectrum
 PARAM.Sd [double(:inf x 1)] Linear elastic displacement response spectrum
 PARAM.Sv [double(:inf x 1)] Linear elastic velocity response spectrum
 PARAM.Sa [double(:inf x 1)] Linear elastic acceleration response spectrum
 PARAM.SievABS [double(:inf x 1)] Linear elastic absolute input energy equivalent velocity spectrum
 PARAM.SievREL [double(:inf x 1)] Linear elastic relative input energy equivalent velocity spectrum
 PARAM.PredPSa [double(1 x 1)] Predominant acceleration of the PSa spectrum
 PARAM.PredPeriod [double(1 x 1)] Predominant period of the PSa spectrum
 PARAM.CDPSa [double(:inf x 1)] Constant ductility pseudo-acceleration response spectrum
 PARAM.CDPSv [double(:inf x 1)] Constant ductility pseudo-velocity response spectrum
 PARAM.CDSd [double(:inf x 1)] Constant ductility displacement response spectrum
 PARAM.CDSv [double(:inf x 1)] Constant ductility velocity response spectrum
 PARAM.CDSa [double(:inf x 1)] Constant ductility acceleration response spectrum
 PARAM.fyK [double(:inf x 1)] yield limit that each SDOF must have in order to attain ductility equal to PARAM.muK.
 PARAM.muK [double(:inf x 1)] achieved ductility for each period (each SDOF).
 PARAM.iterK [double(:inf x 1)] number of iterations needed for convergence for each period (each SDOF).
 PARAM.FAS [double(1:2^(nextpow2(length(xgtt))-1) x 1)] Fourier amplitude spectrum
 PARAM.Tm [double(1 x 1)] Mean period (Tm)
 PARAM.Fm [double(1 x 1)] Mean frequency (Fm)

Copyright (c) 2018-2022

George Papazafeiropoulos
 Major, Infrastructure Engineer, Hellenic Air Force
 Civil Engineer, M.Sc., Ph.D.
 Email: gpapazafeiropoulos@yahoo.gr
