

INDMO - Interface para dispositivos móveis - Aula 01

Iniciando um projeto mobile com React Native com Expo

Requisitos:

- Node JS Versão LTS
- VSCode

1. Criar uma pasta para o projeto:

- Criar uma pasta para o projeto com o nome aula01;
- Abrir a pasta criada com o VSCode;

2. Abrir o terminal na pasta:

npm install --global expo (ignorar os avisos sobre os pacotes obsoletos)

```
PS H:\SENAI\3semestre\IDMO\aulas\aula01> npm install
    WARN deprecated @npmcli/move-file@1.1.2: This functionality has been moved to @npmcli/fs
    MARN deprecated @babel/plugin-proposal-export-namespace-from@7.18.9: This proposal has been merged to the E
CMAScript standard and thus this plugin is no longer maintained. Please use @babel/plugin-transform-export-name
space-from instead.
npm NARN deprecated @babel/plugin-proposal-optional-catch-binding@7.18.6: This proposal has been merged to the ECMAScript standard and thus this plugin is no longer maintained. Please use @babel/plugin-transform-optional-c
atch-binding instead.
npm WARN deprecated @babel/plugin-proposal-nullish-coalescing-operator@7.18.6: This proposal has been merged to
 the ECMAScript standard and thus this plugin is no longer maintained. Please use @babel/plugin-transform-nulli
sh-coalescing-operator instead.
npm NARN deprecated @babel/plugin-proposal-class-properties@7.18.6: This proposal has been merged to the ECMASc
ript standard and thus this plugin is no longer maintained. Please use @babel/plugin-transform-class-properties
 instead.
npm WARN deprecated @babel/plugin-proposal-numeric-separator@7.18.6: This proposal has been merged to the ECMAS
cript standard and thus this plugin is no longer maintained. Please use @babel/plugin-transform-numeric-separat
or instead.
npm WARN deprecated @babel/plugin-proposal-optional-chaining@7.21.0: This proposal has been merged to the ECMAS
cript standard and thus this plugin is no longer maintained. Please use @babel/plugin-transform-optional-chaini
ng instead.
npm MARN deprecated @babel/plugin-proposal-object-rest-spread@7.20.7: This proposal has been merged to the ECMA
Script standard and thus this plugin is no longer maintained. Please use @babel/plugin-transform-object-rest-sp
read instead.
npm WARN deprecated @babel/plugin-proposal-async-generator-functions@7.20.7: This proposal has been merged to t
he ECMAScript standard and thus this plugin is no longer maintained. Please use @babel/plugin-transform-async-g
enerator-functions instead.
npm WARN deprecated uuid@3.4.0: Please upgrade to version 7 or higher. Older versions may use Math.random() i
n certain circumstances, which is known to be problematic. See https://v8.dev/blog/math-random for details.
changed 715 packages in 35s
70 packages are looking for funding
 run `npm fund` for details
PS H:\SENAI\3semestre\IDMO\aulas\aula01> [
```

3. Criar aplicação Expo:

npx create-expo-app aloMundo

```
PS H:\SENAI\3semestre\IDMO\aulas\aula01> npx create-expo-app aloMundo

✓ Downloaded and extracted project files.

> npm install
```



4. Instalar dependências

Para rodar o projeto na web (navegador), precisamos instalar as seguintes dependências que ajudarão a rodar o projeto:

npx expo install react-dom react-native-web @expo/webpack-config

5. Iniciar o projeto:

npx expo start



6. Executando seu aplicativo React Native:

Instale o aplicativo **Expo Go** em seu telefone iOS ou Android e conecte-se à mesma rede sem fio do seu computador. No Android, use o aplicativo **Expo Go** para escanear o código QR do seu terminal para abrir seu projeto. No iOS, use o leitor de código QR integrado do aplicativo iOS Câmera padrão.

Para executar no navegador pressione a tecla w



Opção para executar o aplicativo utilizando Hotspot móvel:

Nas configurações do Windows,

- Navegue até Rede e Internet,
- Localize a opção Hotspot móvel,
- Habilite-a e conecte seu dispositivo mobile,

No VSCode:

Execute normalmente o app com o código:

- npx expo start
- Escaneie o QR code.

Opção para executar o aplicativo em redes diferentes:

Para executar sem estar conectado na mesma rede é necessário instalar um pacote para criação de um túnel:

```
PS H:\SENAI\3semestre\IDMO\aulas\aula01\aloMundo> npx expo start --tunnel
Starting project at H:\SENAI\3semestre\IDMO\aulas\aula01\aloMundo
Starting Metro Bundler

\forall The package @expo/ngrok@^4.1.0 is required to use tunnels, would you like to install it globally? ... yes
Installing @expo/ngrok@^4.1.0...

> npm install --global @expo/ngrok@^4.1.0
Installed @expo/ngrok@^4.1.0
Tunnel connected.
Tunnel ready.
```



```
PS H:\SENAI\3semestre\IDMO\aulas\aula01\aloMundo> npx expo start
Starting project at H:\SENAI\3semestre\IDMO\aulas\aula01\aloMundo
Starting Metro Bundler
Tunnel connected.
Tunnel ready.

    Metro waiting on <a href="mailto:exp://mkrwmxq.anonymous.8081.exp.direct">exp://mkrwmxq.anonymous.8081.exp.direct</a>
    Scan the QR code above with Expo Go (Android) or the Camera app (iOS)

  Using Expo Go
  Press s | switch to development build
  Press a open Android
  Press w open web
> Press j | open debugger
> Press r
               reload app
              toggle menu
  Press m
  Press o open project code in your editor
> Press ? | show all commands
Logs for your project will appear below. Press Ctrl+C to exit.
```

No aplicativo do seu celular, conectar digitando manualmente a URL:

exp://mkrwmxq.anonymous.8081.exp.direct



```
PS H:\SENAI\3semestre\IDMO\aulas\aula01\aloMundo> npx expo start --tunnel
Starting project at H:\SENAI\3semestre\IDMO\aulas\aula01\aloMundo
Starting Metro Bundler
Tunnel connected.
Tunnel ready.
> Metro waiting on exp://mkrwmxq.anonymous.8081.exp.direct
> Scan the QR code above with Expo Go (Android) or the Camera app (iOS)
> Using Expo Go
> Press s | switch to development build
> Press a open Android
> Press w | open web
› Press j
           open debugger
 Press r
           reload app
 Press m
           toggle menu
 Press o open project code in your editor
> Press ? | show all commands
Logs for your project will appear below. Press Ctrl+C to exit.
Android Bundling complete 4236ms
Android Bundling complete 61ms
```

Mensagem exibida se o carregamento se a conexão e carregamento do app forem realizadas com sucesso.