M-Sized Clusters

The Riemann Hypothesis as Subconscious Substructures Applied Through Second-Order Logic

A conceptual framework separating mathematical truth, logical representation, and empirical psychological hypotheses

Central idea. Treat clusters as sets of latent features, and use second-order variables to quantify over sets and relations. Then formulate a testable bridge between a zeta-derived mathematical pattern and measured data—without asserting that the Riemann Hypothesis is a theory of mind.

Prepared 17 October 2026

1. What does “m-sized” mean?

“M-sized” is not a uniquely standard technical term. Here, m is a positive integer and an m-sized cluster is a set containing exactly m distinct members.

$$C_m = \{x_1, x_2, \ldots, x_m\}$$

A fully explicit cardinality condition is: there exist m pairwise-distinct objects $x_1,\ldots,x_m$, and every y belongs to C if and only if y equals one of those objects. For m = 5, the cluster has exactly five members.

Other interpretations are possible: m could be a window length, scale parameter, or index. This document consistently uses exact cluster size.

2. What second-order logic adds

First-order logic quantifies over individual objects. Second-order logic can also quantify over predicates, sets, and/or relations. That lets the model state that there exists a property whose members form a cluster, or that a relation connects members of that cluster.

$$\text{First-order: } \forall x\,(\text{Feature}(x) \rightarrow \ldots)$$
$$\text{Second-order: } \exists F\,\forall x\,(F(x) \leftrightarrow \ldots)$$

F is a predicate variable. The second statement says there is a property F whose extension is exactly the set of objects satisfying the condition. Under full second-order semantics, predicate variables range over all subsets of the domain; under Henkin semantics, they range over a designated collection. This distinction matters for formal results.

3. A typed domain for the model

Let U be a domain of candidate latent features inferred from observations such as word associations, response patterns, or reaction times. Feature(x) says x is an admissible feature. R(x,y) is a defined similarity relation. C(x) means x belongs to a candidate cluster.

$$\text{Cluster}(C) \wedge \forall x\,[C(x) \rightarrow \text{Feature}(x)] \wedge \text{ExactSize}(C,m)$$

ExactSize(C,m) means C contains precisely m distinct elements. If C is represented by a second-order predicate, the cluster itself is a set-like variable rather than an ordinary individual.

A strict all-pairs cohesion condition could be:

$$\forall x \forall y\,[(C(x) \wedge C(y) \wedge x \neq y) \rightarrow R(x,y)]$$

This is suitable only if R is meant to hold between every pair of distinct members. Other clustering methods use average similarity, graph connectivity, or a distance threshold.

4. The Riemann Hypothesis in logical form

The Riemann Hypothesis states that every non-trivial zero ρ of the analytically continued Riemann zeta function has real part 1/2:

$$\forall \rho\,[\text{NonTrivialZero}(\rho) \rightarrow \text{Re}(\rho) = 1/2]$$

This is a logical rendering in a language that already defines complex numbers, ζ(s), and non-trivial zeros; it is not a full foundational formalization of complex analysis. RH remains an unsolved mathematical conjecture.

Second-order logic can quantify over sets or relations built from zero ordinates. It does not prove RH and does not establish a psychological connection. Any link to observed mental processes must be stated as a separate, testable hypothesis.

5. A second-order bridge hypothesis

Let Z be a pre-defined reference structure derived from a specified list of non-trivial zeta-zero ordinates or a published statistic. Let Latent(x) identify features inferred by a fixed procedure. Let S(C,Z) be a pre-registered similarity statistic.

$$\exists C\,[\mathrm{Cluster}(C) \wedge \mathrm{ExactSize}(C,m) \wedge \forall x(C(x) \rightarrow \mathrm{Latent}(x)) \wedge S(C,Z) \geq \tau]$$

Interpretation: there exists a cluster of exactly m latent features whose similarity to reference Z meets threshold τ. This is a hypothesis schema, not a claim that such a cluster has been observed. The statistic S, its normalization, and the threshold τ must be defined in advance.

A statistical test might ask whether the observed score is unusual under a justified null model:

$$P_{\mathrm{null}}(S \geq S_{\mathrm{obs}}) < \alpha$$

This probability statement requires data, a sampling model, and a defensible null hypothesis. If many m values, metrics, or reference sequences are searched, account for multiple comparisons.

6. Interpreting “subconscious substructures” carefully

For research purposes, use “subconscious substructure” as an operational label for latent organization inferred from observable behaviour. It is not a directly inspected object or a single universally agreed mechanism of mind.

Formal object	Possible modelling role	Limit
Zeta-derived reference Z	A mathematical pattern used for comparison.	Not a mental state.
Second-order predicate C	A set of related latent features.	Membership needs a defined rule.
ExactSize(C,m)	A cluster with m members.	m must be fixed or selected by a stated rule.
Similarity S(C,Z)	A quantitative comparison.	Similarity does not establish causation.

This is a proposed analogy and research design. It is not established that cognition follows zeta-zero statistics, that prime numbers encode unconscious thought, or that RH explains consciousness.

7. A falsifiable research protocol

1 — Define observations. Choose a transparent dataset. Treat latent features as model outputs, not direct access to the subconscious.

2 — Fix m. Pre-specify cluster size or use a principled evaluation procedure. Searching many values without correction inflates false-positive risk.

3 — Define predicates. State the domain U and meanings of Feature(x), Latent(x), R(x,y), Cluster(C), and ExactSize(C,m). Map each to a measurement or implementation.

4 — Define Z and S. Specify the zeta-derived quantities, normalization, and similarity statistic before inspecting results.

5 — Compare with nulls. Use shuffled labels, matched random reference sequences, and alternative clustering methods. Report uncertainty and multiple-testing corrections.

6 — Replicate. Test the fixed method on held-out data or an independent sample; report null results as well as positive ones.

7 — Limit the conclusion. A robust association would support only that association under tested conditions. It would not prove RH or show that RH is a mechanism of subconscious processing.

8. Compact second-order specification

$$\exists C\,[\mathrm{Cluster}(C) \wedge \mathrm{ExactSize}(C,m) \wedge \forall x(C(x) \rightarrow \mathrm{Latent}(x)) \wedge \mathrm{Cohesive}(C,R) \wedge \mathrm{RelatedTo}(C,Z)]$$

There exists a set C of exactly m latent features; it meets a pre-defined cohesion criterion R and a separately defined relation to zeta-derived reference Z. Cohesive and RelatedTo must be operationally defined. This is a second-order modelling schema, not a theorem, a proof of RH, or a validated theory of mind.

Glossary

Second-order logic: a logic that allows quantification over predicates, sets, or relations as well as individual objects.

Full semantics: second-order variables range over all subsets or relations on the domain. **Henkin semantics:** they range over a designated collection.

Latent feature: a representation inferred from measured observations. **Null model:** a baseline for estimating how often a pattern might arise under specified assumptions.

Further reading

• Tarski, A. (1956), Logic, Semantics, Metamathematics.
• Shapiro, S. (1991), Foundations without Foundationalism: A Case for Second-Order Logic.
• Edwards, H. M. (1974), Riemann’s Zeta Function.

Scope note: This document proposes a formal analogy and a possible empirical test. It does not report experimental results or imply that the subconscious has been shown to instantiate the Riemann zeta function.