How the RP-Style Decision Circuit Works

A complete walkthrough of the parallel-driver, single-trial optoelectronic circuit featuring an IR optical bench, NPN IF/THEN transistor stage, dual OR/AND logic gating, 10 µF integration node, time code Y, and 74HC74 flip-flop.




Figure 1: Full schematic of the optoelectronic RP decision circuit, showing the optical bench (IR laser, reflector, IR detectors A & B), randomized Driver A, deterministic Driver B with NPN IF/THEN link, dual logic gates, 10 µF timing node, time code Y, and 74HC74 flip-flop.

1. The Big Idea

The circuit is a physical hardware realization of a **Randomized Polynomial-time (RP)** decision procedure. RP is the complexity class of decision problems for which a probabilistic algorithm yields one-sided error:

- If the instance answer is NO ($x \notin L$), the algorithm never outputs 1 (zero false-accept probability).
- If the instance answer is YES ($x \in L$), the algorithm outputs 1 with probability $P \geq ½$ per trial.

The circuit executes one such trial. It receives the problem instance x, routes it in parallel through two electronic drivers connected to an IR optical bench, merges their signals using an NPN transistor threshold link and dual logic gates, and latches the verdict into a D flip-flop on a clock edge. The stored output bit, $\mathrm{SELECT} = Q$, is the verdict.

2. Core Functional Blocks

Block Name	System Role	Physical & Logical Behavior
Optical Bench	Physical entropy source	IR laser beams hit a reflector; differential optical intensity (Δ intensity) feeds IR Detector A (randomized) and IR Detector B (deterministic).
Driver A	Randomized witness test $w(x, r)$	Uses Detector A optical noise as seed r. Outputs $A = 1$ with $P \geq ½$ if $x \in L$, and $A = 0$ always if $x \notin L$.

Block Name	System Role	Physical & Logical Behavior
Driver B	Deterministic logic check $c(x)$	Fixed logic check with no randomness. Controls the NPN transistor IF/THEN stage, driving output $B = \text{HIGH}$ when active.

2. Core Functional Blocks (Continued)

Block Name	System Role	Physical & Logical Behavior
IF/THEN Link (Capacitor C & NPN)	Voltage threshold switch	Integrates charge on capacitor C. When base voltage exceeds $V(C) > 0.7\ V$, the NPN transistor turns ON (+5 V rail), asserting line B.
OR & AND Gates	Coincidence validator	Evaluates lines A and B. The combined structure requires both intermediate conditions ($A \text{ OR } B$ and $A \text{ AND } B$) to be satisfied, which simplifies to $A \text{ AND } B$.
10 µF Node	Low-pass integrator	Smooths transient logic spikes from the gate outputs to establish a clean DC voltage level prior to sampling.
Time Code Y	Deterministic forcing	Applies a fixed timing code sequence to force a HIGH state into the D input of the flip-flop under valid conditions.
Clock / Timer	Sampling clock	Generates a 10 Hz square wave ($T = 100\ ms$) defining precise sampling edges without altering data.
74HC74 D Flip-Flop	Decision memory	Latches D to Q on rising CLK edge. Output Q represents **SELECT**; $\bar{Q}$ represents the complementary **Observation**.

3. Step-by-Step Signal Flow

1. **Input fan-out:** Problem instance x is distributed simultaneously to Driver A and Driver B.
2. **Parallel processing:** Driver A samples IR Detector A noise to execute witness test $w(x, r)$. Driver B executes deterministic precondition check $c(x)$.
3. **Transistor thresholding:** Driver B charges base capacitor C. When $V(C) > 0.7\ V$, the NPN transistor connects line B to +5 V.
4. **Logic gate evaluation:** Signal lines A and B enter both OR and AND gates. Agreement produces a active output.
5. **Capacitive integration & Time coding:** Output pulses charge the 10 µF capacitor and pass through Time Code Y to present a stable HIGH on input D.
6. **Latch evaluation:** At $T = 100\ ms$, the CLK rising edge latches D to output Q ($\text{SELECT} = 1 \implies x \in L$).

4. One-Sided Error Proof

The decision output $Q = 1$ occurs only when both intermediate conditions $(A \text{ OR } B)$ and $(A \text{ AND } B)$ hold. Because $(A \text{ AND } B) \implies (A \text{ OR } B)$, the logic reduces to requiring $A \text{ AND } B = 1$.

Instance Condition	Driver A Output	Driver B Output	SELECT (Q) Output	Algorithmic Interpretation
$x \notin L$ (NO instance)	Always 0	0 or 1	**0**	Never false-accepts. Zero error.
$x \in L$, witness found	1 (prob $P \geq ½$)	1	**1**	Correct acceptance.
$x \in L$, witness missed	0 (prob $P \leq ½$)	1	**0**	False rejection (only error type).

5. Multi-Trial Error Reduction

Because trials are statistically independent and false accepts are impossible, running k repeated trials pushes the false rejection probability down to $(½)^k$.

Trials (k)	Worst-Case Rejection Error $(½)^k$	Total Execution Time at 10 Hz ($T = 100$ ms)
1	0.50000000	0.1 s
2	0.25000000	0.2 s
5	0.03125000	0.5 s
10	0.00097656	1.0 s
20	0.00000095 (9.54×10^{-7})	2.0 s

6. Practical Circuit Considerations

- **Logic Gate Merging:** Direct wire-ANDing of CMOS gate outputs requires pull-up/pull-down isolation or open-drain outputs to avoid bus contention.
- **NPN Bias Parameters:** Base capacitor C must be chosen alongside base resistor R_B such that time constant $\tau = R_B C < 100$ ms to allow switching within one clock cycle.
- **74HC74 Pin Requirements:** Unused active-low pins ($\overline{\text{PRE}}$ and $\overline{\text{CLR}}$) must be tied to +5 V to prevent random resetting.

From Electrons to Photon Statistics

Re-reading the optoelectronic RP-style decision circuit as a physical model of how electron handling shapes photon emission statistics.

1. The Physical Mapping Claim

In optoelectronics, the statistical distribution of emitted or detected photons is directly governed by how charge carriers (electrons) are manipulated prior to radiative recombination. Random, uncorrelated electron injection produces Poissonian light, whereas metered, single-electron injection yields sub-Poissonian light.

2. Three Metrics for Photon Statistics

Metric Parameter	Mathematical Definition	Physical Interpretation
Fano Factor (F)	$F = \text{Var}(n) / \langle n \rangle$	$F = 1$: Poissonian (laser, shot noise). $F > 1$: Super-Poissonian (thermal light). $F < 1$: Sub-Poissonian (squeezed / regulated light).
Mandel Q Parameter	$Q = F - 1$	$Q = 0$: Standard Poissonian source. $Q < 0$: Quantum non-classical photon stream.

Metric Parameter	Mathematical Definition	Physical Interpretation
Second-Order Coherence $g^{(2)}(0)$	$g^{(2)}(0) = \langle n(n-1) \rangle / \langle n \rangle^2$	$g^{(2)}(0) = 2$: Thermal bunched light. $g^{(2)}(0) = 1$: Coherent laser light. $g^{(2)}(0) = 0$: Ideal single-photon antibunched source.

3. Circuit-to-Physics Relabeling Table

Circuit Element	Optoelectronic Counterpart	Statistical Effect
Input x	Drive current / Pump power	Sets mean photon number $\langle n \rangle$
Driver A (Random)	Shot noise / Thermal excitation	Drives photon statistics toward Poissonian ($F = 1$)
Driver B + NPN Link	Coulomb blockade / Regulated injection	Forces regular carrier delivery, yielding sub-Poissonian photons ($F < 1$)

3. Circuit-to-Physics Relabeling Table (Continued)

Circuit Element	Optoelectronic Counterpart	Statistical Effect
OR & AND Gates	Carrier coincidence gate	Requires electron-hole pair coincidence before emission can occur.
10 µF Node & Cap C	RC junction capacitance	Filters high-frequency carrier fluctuations; sets noise-suppression bandwidth.
Time Code Y	Gated pump pulse pattern	Defines active optical emission time bins (e.g., pump in bins 1, 3, 4; skip bin 2).
Clock / Timer	Detector gate window	Establishes counting interval T (symbolically 100 ms; GHz in real systems).
74HC74 Flip-Flop	SPAD Discriminator & Latch	Converts optical photon detection events into binary bit records ($Q = 1$ click).

4. Mathematical Carrier-to-Photon Thinning Relation

If each injected charge carrier converts into a detected photon with overall quantum efficiency η (combining internal efficiency, extraction, and detector efficiency), the photon Fano factor F_{ph} relates to the electron Fano factor F_e via:

$$\mathbf{F_{ph} = 1 - \eta\,(1 - F_e)}$$

- **Random Carriers (Driver A, $F_e = 1$):** Yields $F_{ph} = 1$ regardless of efficiency η (Poissonian light).
- **Regulated Carriers (Driver B, $F_e = 0$):** Yields $F_{ph} = 1 - \eta$. At $\eta = 0.8$, $F_{ph} = 0.2$ (strongly sub-Poissonian).
- **Bunched Carriers ($F_e > 1$):** Yields super-Poissonian photon noise ($F_{ph} > 1$).

5. Physical Detector Analogy & Limitations

The RP decision guarantee (zero false accepts when $x \notin L$) maps directly onto single-photon counting detectors:

- **Zero False Accepts:** In the absence of photons, ideal photodetectors register zero clicks, maintaining one-sided error.
- **False Rejection via Efficiency Loss:** A photon present may be missed with probability $1 - \eta$, playing the role of false rejection error in RP algorithms.
- **Multi-Window Integration:** Counting across k clock windows reduces false rejection probability to $(1 - \eta)^k$.

> **Breakdown Point - Dark Counts:** Detector dark counts (thermal noise clicks in the dark) act as false accepts, which do not exist in pure RP algorithms. Dark counts accumulate linearly with added clock windows k.

6. Comprehensive Integrated Processing Chain

1. **Excitation:** Input bias x drives parallel random (A) and regulated (B) carrier pathways.
2. **Injection:** Driver A injects Poisson noise ($F_e = 1$); Driver B uses NPN thresholding to meter regular carriers ($F_e = 0$).
3. **Gating & Integration:** OR/AND logic gates enforce pair coincidence; the 10 µF RC node filters high-frequency noise.
4. **Time Binning:** Time Code Y modulates the carrier stream into defined time bins.
5. **Detection & Histogramming:** SPAD discriminator and 74HC74 flip-flop record binary clicks ($Q = 1$), building photon count histogram $P(n)$ over time.

Energy-Level Switching, Measurement, & CTCs

Physical protocol breakdown, quantum state transitions, measurement collapse, and closed timelike curve (CTC) feedback equivalence.

1. The 5-Step Physical Protocol

Step	Circuit Element	Physical Event	Physical Outcome
1. Prepare	Input x, Timer, Time Code Y	Set excitation bias and pump time bins (bins 1, 3, 4 active; bin 2 skipped).	Defines carrier drive envelope.
2. Switch	Drivers A & B, NPN link	Carrier transitions from ground state E_1 to excited state E_2.	Emits photon of energy $h\nu = E_2 - E_1$.
3. Gate	OR / AND Gates	Coincidence condition evaluated across lines A and B.	Gated recombination condition ($A \text{ AND } B$).
4. Measure	10 µF Node, 74HC74, CLK	Photon detection triggers discriminator; flip-flop latches output.	Latches verdict $Q = \text{SELECT} \in \{0, 1\}$.
5. Repeat	Clock windows k	Execute k independent sampling cycles.	Reduces false rejection error to $(1/2)^k$.

2. Energy-Level Switching Physics

Radiative recombination emits a photon when an electron drops between discrete quantum levels $E_2 \rightarrow E_1$. The nature of excitation controls the temporal statistics:

- **Random Thermal Excitation (Driver A):** Independent emitters yield Poissonian counts ($F = 1$). Thermal fluctuations induce photon bunching ($g^{(2)}(0) > 1$).
- **Coherent Inversion (Driver B):** Resonant π-pulses invert the two-level system with excited-state probability $P_e = \sin^2(\theta/2) = 1$. Emitter decay guarantees single-photon antibunching ($g^{(2)}(0) \rightarrow 0$).

3. Quantum Measurement Physics

The photon number measurement obeys Born's rule: $P(n) = |\langle n|\psi\rangle|^2$. Prior to detection, the emitted photon and charge carrier may exist in an entangled quantum state. Measurement by the SPAD discriminator collapses the state, yielding a discrete click.

4. Closed Timelike Curves (CTCs) & Circuit Feedback

The schematic note *"Swap A or B (error correction) with Q while adding time codes"* describes feeding output Q back into the excitation drivers. In theoretical physics, a closed loop where an output state conditions its past input is mathematically equivalent to a **Closed Timelike Curve (CTC)** in general relativity.

5. Deutsch CTC Model & Fixed-Point Consistency

In David Deutsch's 1991 quantum CTC formulation, a quantum system traveling along a closed timelike curve must satisfy the self-consistency condition:

$$\rho_{CTC} = \mathrm{Tr}_{other}\left[U \left(\rho_{other} \otimes \rho_{CTC} \right) U^{\dagger} \right]$$

If the feedback loop introduces a logical contradiction (e.g., bit inversion $x = \text{NOT } x$), Deutsch's model resolves the paradox by selecting the maximum-entropy fixed point $\rho_{CTC} = \frac{1}{2} I$ (a 50/50 statistical mixture). This fixed point provides a physical analogy to the $P = \frac{1}{2}$ success threshold of Driver A in RP algorithms.

6. Computational Complexity Implications

Aaronson and Watrous (2009) demonstrated that polynomial-time computers equipped with Deutschian CTCs (**BQP_{CTC}** or **P_{CTC}**) can solve all problems in complexity class **PSPACE**. Thus, closed timelike feedback loops drastically expand computing power beyond standard RP complexity.

7. Comprehensive System Parameter Matrix

Physical Parameter	Circuit Realization	Physical / Algorithmic Function
$E_2 - E_1$	IR Laser Wavelength	Determines photon energy $h\nu$ and detector bandgap matching.
τ (Lifetime)	RC node decay time	Sets recovery time between emission events and $g^{(2)}(\tau)$ dip width.
Pulse Area θ	Driver B pulse amplitude	Controls excitation determinism ($\theta = \pi \implies$ inversion).
F_e & η	Detector A/B Noise & Transistor efficiency	Dictates final photon Fano factor $F_{ph} = 1 - \eta(1 - F_e)$.
Dark-Count Rate	Transistor leakage current	Establishes non-zero false accept baseline in physical systems.
Clock Period T	10 Hz Timer ($T = 100$ ms)	Defines integration window width for decision sampling.
Time Code Y	Pattern register (1011)	Modulates allowed pumping time bins.
Trial Count k	Clock cycle counter	Reduces false rejection error exponentially via $(\frac{1}{2})^k$.

8. Established Physics vs. Theoretical Models

Classification	Domain Topics & Phenomenon
Established Physics	Energy level switching; Poissonian, thermal, and antibunched photon statistics; carrier thinning equation; RP one-sided error reduction via $(½)^k$ repetition.
Theoretical Models	Deutsch fixed-point CTC density matrix formulation; complexity equivalence ($\text{P}_{\text{CTC}} = \text{PSPACE}$); optical feedback loop analogies.
Speculative / Conceptual	Physical existence of closed timelike curves in spacetime; exact physical implementation of CTC time-travel loops via circuit feedback.

9. Standard Academic References

- D. Deutsch, "Quantum mechanics near closed timelike lines," *Physical Review D*, vol. 44, no. 10, pp. 3197–3217, 1991.
- S. Aaronson and J. Watrous, "Closed timelike curves make quantum and classical computing equivalent," *Proceedings of the Royal Society A: Mathematical, Physical and Engineering Sciences*, vol. 465, no. 2107, pp. 2071–2095, 2009.
- M. Ringbauer, C. R. Giarmatzi, R. Chaves, A. G. White, and A. Fedrizzi, "Experimental simulation of closed timelike curves," *Nature Communications*, vol. 5, p. 4145, 2014.
- S. W. Hawking, "Chronology protection conjecture," *Physical Review D*, vol. 46, no. 2, pp. 603–611, 1992.
- R. Loudon, *The Quantum Theory of Light*, 3rd ed. Oxford: Oxford University Press, 2000.

10. Document Executive Summary

Summary of Findings:
1. **Hardware Logic:** The circuit implements an RP decision procedure using an optical bench entropy source, an NPN transistor IF/THEN threshold switch ($V(C) > 0.7\ V$), dual OR/AND logic gates, a 10 µF low-pass node, and a 10 Hz clocked 74HC74 flip-flop.
2. **One-Sided Error:** Zero false accepts occur when $x \notin L$. False rejections ($P \le ½$) decay exponentially to $(½)^k$ over k repeated trials.
3. **Optoelectronic Statistics:** Carrier control dictates photon statistics through $F_{ph} = 1 - \eta(1 - F_e)$, transforming deterministic single-electron injection into antibunched sub-Poissonian light.
4. **Feedback Modeling:** Feeding output bit Q back into driver parameters maps onto Deutsch's fixed-point CTC equation $\rho_{CTC} = \text{Tr}_{other}[U(\rho_{other} \otimes \rho_{CTC})U^{\dagger}]$, providing a foundational bridge between complexity theory, optoelectronics, and theoretical spacetime physics.