Федеральное государственное бюджетное образовательное учреждение высшего образования «Сибирский государственный университет телекоммуникаций и информатики» (СибГУТИ)

Кафедра Вычислительных систем(ВС)

Лабораторная работа №4 по дисциплине «Облачные технологии»

Выполнил:

студент гр.ИВ-622

Тимофеев Д.А.

Работу проверил:

Доцент кафедры ВС, к.т.н.

Ефимов А.В.

СОДЕРЖАНИЕ:

C	ОДЕРЖАНИЕ:	2
	. Выполнение настройки доступа к системе хранения данных	
	1.1. Подключился по ssh	3
	1.2. Сопоставление с картой сети на рисунке 6	4
	1.3. Содержимое папки /etc/sysconfig/network-scripts	5
	1.4. Проверил доступность интерфейсов СХД	5
	1.5. Отправили iSCSI Discovery запрос на один из интерфейсов СХД	5
	1.6. Посмотрел на каких устройствах я авторизирован	6
	1.7. Посмотрел набор устройств	6
	1.8. Добавил multipath	7
	1.9. Restart multipaths	8
	1.10. Показания команды multipath -ll - ✓ успешно	8
	1.11. Показаний команды lsblk	8
	1.12. Монтирую раздел и добавляют файл с текстом	9
	1.13. Смотрим как все смонтировалось	10
	1.14. Увеличил число маршрутов	11

1. Выполнение настройки доступа к системе хранения данных

1.1. Подключился по ssh

```
gfs@gfs-VirtualBox:/etc/nginx$ ssh timofeev@csc.sibsutis.ru -p 7701
ssh: connect to host csc.sibsutis.ru port 7701: No route to host
gfs@gfs-VirtualBox:/etc/nginx$ ssh timofeev@csc.sibsutis.ru -p 7701
The authenticity of host '[linux.csc.sibsutis.ru]:7701 ([91.196.245.194]:7701)' can't be established.
ECDSA key fingerprint is SHA256:dCdh360xMQ+ca8MULZ5fFjB381CxnNfq9mGX+wL7fzE.
Are you sure you want to continue connecting (yes/no)? y
Please type 'yes' or 'no': yes
Warning: Permanently added '[linux.csc.sibsutis.ru]:7701,[91.196.245.194]:7701' (ECDSA) to the list of known hosts.
timofeev@linux.csc.sibsutis.ru's password:
Connection closed by 91.196.245.194 port 7701
gfs@gfs-VirtualBox:/etc/nginx$ ssh timofeev@linux.csc.sibsutis.ru -p 7701
timofeev@linux.csc.sibsutis.ru's password:
[timofeev@linux.csc.sibsutis.ru's password:
[timofeev@linux.csc.sibsutis.ru's password:
```

1.2. Сопоставление с картой сети на рисунке 6

```
timofee
File Edit View Search Terminal Help
         TX packets 0 bytes 0 (0.0 B)
         TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
[timofeev@prod-01 ~]$ ifconfig
br0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
         inet 192.168.1.145 netmask 255.255.255.0 broadcast 192.168.1.255
        inet6 fe80::f292:lcff:fe10:c63b prefixlen 64 scopeid 0x20<link>
ether f0:92:lc:10:c6:3b txqueuelen 1000 (Ethernet)
         RX packets 3434939 bytes 158712936 (151.3 MiB)
         RX errors 0 dropped 0 overruns 0 frame 0
         TX packets 20 bytes 1592 (1.5 KiB)
         TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
enol: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
         inet 10.1.2.18 netmask 255.255.255.0 broadcast 10.1.2.255
         inet6 fe80::f292:1cff:fe10:c638 prefixlen 64 scopeid 0x20<link>
ether f0:92:1c:10:c6:38 txqueuelen 1000 (Ethernet)
         RX packets 5382648 bytes 3066921599 (2.8 GiB)
         RX errors 0 dropped 0 overruns 0 frame 0
TX packets 6584586 bytes 731659196 (697.7 MiB)
         TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
         device memory 0xf7e00000-f7efffff
eno2: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
         inet 10.1.2.19 netmask 255.255.255.0 broadcast 10.1.2.255
         inet6 fe80::f292:1cff:fe10:c639 prefixlen 64 scopeid 0x20<link>
         ether f0:92:1c:10:c6:39 txqueuelen 1000 (Ethernet)
         RX packets 10 bytes 600 (600.0 B)
         RX errors 0 dropped 0 overruns 0 frame 0
         TX packets 20 bytes 1592 (1.5 KiB)
         TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0 device memory 0xf7c00000-f7cfffff
eno3: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
inet 192.168.1.45 netmask 255.255.255.0 broadcast 192.168.1.255
         inet6 fe80::f292:1cff:fe10:c63a prefixlen 64 scopeid 0x20<link>
        ether f0:92:1c:10:c6:3a txqueuelen 1000 (Ethernet)
RX packets 4386215 bytes 1306047437 (1.2 GiB)
         RX errors 0 dropped 0 overruns 0 frame 0
         TX packets 605391 bytes 72574332 (69.2 MiB)
TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
         device memory 0xf7a00000-f7afffff
eno4: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500
         inet6 fe80::f292:1cff:fe10:c63b prefixlen 64 scopeid 0x20<link>
         ether f0:92:1c:10:c6:3b txqueuelen 1000 (Ethernet)
RX packets 3494993 bytes 213690035 (203.7 MiB)
         RX errors 0 dropped 58829 overruns 0 frame 0
         TX packets 37 bytes 3058 (2.9 KiB)
         TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
         device memory 0xf7800000-f78fffff
lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536
         inet 127.0.0.1 netmask 255.0.0.0
         inet6 ::1 prefixlen 128 scopeid 0x10<host>
         loop txqueuelen 1000 (Local Loopback)
         RX packets 24 bytes 1922 (1.8 KiB)
         RX errors 0 dropped 0 overruns 0 frame 0
                             timofeev@prod-01:~
```

1.3. Содержимое папки /etc/sysconfig/network-scripts

1.4. Проверил доступность интерфейсов СХД

```
[timofeev@prod-01 network-scripts]$ ping 10.1.2.11
PING 10.1.2.11 (10.1.2.11) 56(84) bytes of data.
64 bytes from 10.1.2.11: icmp_seq=1 ttl=64 time=0.277 ms
64 bytes from 10.1.2.11: icmp_seq=2 ttl=64 time=0.279 ms
64 bytes from 10.1.2.11: icmp_seq=3 ttl=64 time=0.286 ms
64 bytes from 10.1.2.11: icmp_seq=4 ttl=64 time=0.293 ms
64 bytes from 10.1.2.11: icmp_seq=5 ttl=64 time=0.292 ms
64 bytes from 10.1.2.11: icmp_seq=5 ttl=64 time=0.296 ms
^C
--- 10.1.2.11 ping statistics ---
6 packets transmitted, 6 received, 0% packet loss, time 5000ms
rtt min/avg/max/mdev = 0.277/0.287/0.296/0.012 ms
[timofeev@prod-01 network-scripts]$
```

1.5. Отправили iSCSI Discovery запрос на один из интерфейсов СХД

```
'Csudo: 2 incorrect password attempts
[timofeev@prod-01 network-scripts]$ sudo iscsiadm -m discovery -t st -p 10.1.2.11 -t st
[sudo] password for timofeev:
Sorry, try again.
[sudo] password for timofeev:
iscsiadm: This command will remove the record [iface: default, target: iqn.1986-03.com.hp:storage.p2000g3.13421aff31,
portal: 10.1.2.11,3260], but a session is using it. Logout session then rerun command to remove record.
iscsiadm: This command will remove the record [iface: default, target: iqn.1986-03.com.hp:storage.p2000g3.13421aff31,
portal: 10.1.2.15,3260], but a session is using it. Logout session then rerun command to remove record.
10.1.5.10:3260,1 iqn.1986-03.com.hp:storage.p2000g3.13421aff31
10.1.2.15:3260,4 iqn.1986-03.com.hp:storage.p2000g3.13421aff31
10.1.5.13:3260,7 iqn.1986-03.com.hp:storage.p2000g3.13421aff31
10.1.2.15:3260,4 iqn.1986-03.com.hp:storage.p2000g3.13421aff31
timofeev@prod-01 network-scripts]$
```

1.6. Посмотрел на каких устройствах я авторизирован

```
[timofeev@prod-01 network-scripts]$ sudo iscsiadm -m session
[sudo] password for timofeev:
tcp: [81] 10.1.2.11:3260,3 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)
tcp: [82] 10.1.2.11:3260,3 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)
tcp: [83] 10.1.2.11:3260,3 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)
tcp: [84] 10.1.2.12:3260,5 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)
tcp: [85] 10.1.2.12:3260,5 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)
tcp: [86] 10.1.2.15:3260,4 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)
tcp: [87] 10.1.2.15:3260,4 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)
tcp: [88] 10.1.2.15:3260,4 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)
tcp: [88] 10.1.2.15:3260,4 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)
[timofeev@prod-01 network-scripts]$
```

1.7. Посмотрел набор устройств

```
timofeev@prod-01:/etc/sysconfig/network-scripts
 File Edit View Search Terminal Help
tcp: [85] 10.1.2.12:3260,5 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)
tcp: [86] 10.1.2.15:3260,4 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)
tcp: [87] 10.1.2.15:3260,4 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)
88:0:0:105 sdp 8:208 active ready running
89:0:0:105 sdp 8:240 active ready running
90:0:0:105 sdo 8:224 active ready running
       91:0:0:105 sdat 66:208 active ready running
       92:0:0:105 sdau 66:224 active ready running
       policy='service-time 0' prio=10 status=enabled
       93:0:0:105 sdbv 68:144 active ready running
       94:0:0:105 sdbw 68:160 active ready running
       95:0:0:105 sdbx 68:176 active ready running
 npathd (3600c0ff0001b192745379f5e01000000) dm-5 HP
                                                                                      ,P2000 G3 iSCSI
size=954M features='1 queue_if_no_path' hwhandler='0' wp=rw
       policy='service-time 0' prio=50 status=active
       90:0:0:104 sdl 8:176 active ready running
88:0:0:104 sdk 8:160 active ready running
89:0:0:104 sdm 8:192 active ready running
     - 91:0:0:104 sdar 66:176 active ready running
   - 92:0:0:104 sdas 66:192 active ready running
+- policy='service-time 0' prio=10 status=enabled
|- 93:0:0:104 sdbs 68:96 active ready running
|- 94:0:0:104 sdbt 68:112 active ready running
       95:0:0:104 sdbu 68:128 active ready running
                                                                                      ,P2000 G3 iSCSI
mpathc (3600c0ff0001b192719379f5e01000000) dm-4 HP
- 92:0:0:103 sdag 66:160 active ready running
       91:0:0:103 sdap 66:144 active ready running
       policy='service-time 0' prio=10 status=enabled
       95:0:6:103 sdbq 68:64 active ready running
93:0:0:103 sdbp 68:48 active ready running
94:0:0:103 sdbr 68:80 active ready running
mpathb (3600c0ff0001b19279b369f5e01000000) dm-3 HP
                                                                                      ,P2000 G3 iSCSI
size=954M features='l queue_if_no_path' hwhandler='0' wp=rw
|-+- policy='service-time 0' prio=50 status=active
       90:0:0:102 sde 8:64 active ready running
89:0:0:102 sdf 8:80 active ready running
88:0:0:102 sdg 8:96 active ready running
     - 91:0:0:102 sdao 66:128 active ready running
     - 92:0:0:102 sdan 66:112 active ready running
       policy='service-time 0' prio=10 status=enabled
       94:0:0:102 sdbn 68:16 active ready running
93:0:0:102 sdbm 68:0 active ready running
95:0:0:102 sdbo 68:32 active ready running
- 95:0:0:102 sdb0 68:32 active ready running mpatha (3600c0ff0001b192752369f5e01000000) dm-2 HP ,P20 size=954M features='1 queue if_no_path' hwhandler='0' wp=rw |-+- policy='service-time 0' prio=50 status=active | - 90:0:0:101 sdd 8:48 active ready running | - 88:0:0:101 sda 8:0 active ready running
                                                                                      ,P2000 G3 iSCSI
```

1.8. Добавил multipath

```
timofeev@prod-01:/etc/sysconfig/network-scripts
 File Edit View Search Terminal Help
  GNU nano 2.3.1
                                             File: /etc/multipath.conf
## not change names on reboot (from /dev/sda to /dev/sdb for example)
## devnode lines are not recommended for blacklisting specific devices.
#blacklist {
         wwid 26353900f02796769
         devnode "^(ram|raw|loop|fd|md|dm-|sr|scd|st)[0-9]*"
devnode "^hd[a-z]"
#}
multipaths {
         multipath {
                  wwid
                                              3600c0ff0001b19277e379f5e01000000
                  alias
                                              shavrin
                                              multibus
                  path_grouping_policy
                  path selector
                                              "round-robin 0"
                  failback
                                              manual
                  rr_weight
                  no path retry
                  rr min io
                                              10
         multipath {
                  wwid
                                              3600c0ff0001b1927d1379f5e01000000
                  alias
                                              petruk
                                              multibus
                  path_grouping_policy
                  path_selector
                                              "round-robin 0"
                  failback
                                              manual
                                              priorities
                  rr weight
                  no_path_retry
                  rr min io
                                              10
         multipath {
                                              3600c0ff0001b192720389f5e01000000
                  wwid
                  alias
                                              timofeev
                  path_grouping_policy
path_selector
                                              multibus
                                              "round-robin 0"
                  failback
                                              manual
                                              priorities
                  rr weight
                  no_path_retry
                                              10
                  rr min io
         multipath {
                  wwid
                                              1DEC
                                                        321816758474
                  alias
                                              red
#devices {
         device {
                                              "COMPAQ "
                  vendor
                  product
                                              "HSV110 (C)COMPAQ"
                  path_grouping_policy
                                              multibus
                  path checker
                                              readsector0
                                                         [ Read 116 lines ]
                      ^0 WriteOut
^J Justify
                                                                                        ^K Cut Text
^U UnCut Tex
   Get Help
                                             R Read File
                                                                     Prev Page
                                                                                                              C Cur Pos
                         Justify
                                                                     Next Page
                                                                                           UnCut Text
                                                                                                                 To Spell
   Exit
                                               Where Is
```

1.9. Restart multipaths

```
[timofeev@prod-01 network-scripts]$ sudo nano /etc/multipath.conf
[timofeev@prod-01 network-scripts]$ sudo systemctl restart multipathd.service
[timofeev@prod-01 network-scripts]$ sudo multipath -ll
mpathe (3600c0ff0001b192760379f5e01000000) dm-6 HP ,P2000 G3 iSCSI
```

1.10. Показания команды multipath -ll - **√** успешно

```
- 95:0:0:101 sdbl 67:240 active ready running
timofeev (3600c0ff000lb192720389f5e01000000) dm-13 HP ,P2000 G3 iSCSI
size=954M features='1 queue_if_no_path' hwhandler='0' wp=rw
'-+- policy='round-robin 0' prio=35 status=active
|- 88:0:0:112 sdai 66:32 active ready running
|- 89:0:0:112 sdak 66:64 active ready running
|- 90:0:0:112 sdaj 66:48 active ready running
|- 91:0:0:112 sdbi 67:192 active ready running
|- 92:0:0:112 sdbh 67:176 active ready running
|- 93:0:0:112 sdcr 69:240 active ready running
|- 94:0:0:112 sdcs 70:0 active ready running
|- 95:0:0:112 sdcq 69:224 active ready running
```

1.11. Показаний команды lsblk

```
sdco
                69:192 0 953,6M
                                 0 disk
∟mpathk
                        0 953,6M
               253:12
                                 0 mpath
sdbz
                68:208 0 953,6M
                                 0 disk
∟shavrin
                        0 953,6M
                                 0 mpath
               69:208 0 953,6M
sdcp
                                 0 disk
                       0 953,6M
                                 0 mpath
∟mpathk
sdcq
                69:224 0 953,6M
                                 0 disk
└-timofeev
               253:13 0 953,6M
                                 0 mpath
               69:240 0 953,6M
sdcr
                                 0 disk
\vdashtimofeev
               253:13 0 953,6M
                                 0 mpath
sdcs
               70:0
                        0 953,6M 0 disk
                       0 953,6M 0 mpath
└-timofeev
               253:13
[timofeev@prod-01 network-scripts]$
```

1.12. Монтирую раздел и добавляют файл с текстом

```
253:13 0 953,6M 0 mpath
[timofeev@prod-01 network-scripts]$ sudo mke2fs -j -v /dev/mapper/timofeev
[sudo] password for timofeev:
mke2fs 1.42.9 (28-Dec-2013)
fs types for mke2fs.conf resolution: 'ext3'
Filesystem label=
OS type: Linux
Block size=4096 (log=2)
Fragment size=4096 (log=2)
Stride=0 blocks, Stripe width=256 blocks
61056 inodes, 244128 blocks
12206 blocks (5.00%) reserved for the super user
First data block=0
Maximum filesystem blocks=251658240
8 block groups
32768 blocks per group, 32768 fragments per group
7632 inodes per group
Superblock backups stored on blocks:
         32768, 98304, 163840, 229376
Allocating group tables: done
Writing inode tables: done
Creating journal (4096 blocks): done
Writing superblocks and filesystem accounting information: done
[timofeev@prod-01 network-scripts]$ ls /mnt/
[timofeev@prod-01 network-scripts]$ sudo mkdir /mnt/timofeev
[timofeev@prod-01 network-scripts]$ ls /mnt/
[timofeev@prod-01 network-scripts]$ sudo mount /dev/mapper/timofeev /mnt/timofeev/
[timofeev@prod-01 network-scripts]$ cd /mnt/timofeev/
[timofeev@prod-01 timofeev]$ ls
[timofeev@prod-01 timofeev]$ sudo touch MY_LAB4_DONE.txt
[timofeev@prod-01 timofeev]$ sudo nano MY_LAB4_DONE.txt
[timofeev@prod-01 timofeev]$ sudo nano MY LAB4 DONE.txt
[timofeev@prod-01 timofeev]$
```

1.13. Смотрим как все смонтировалось

		timofeev@prod-01:/mnt/timofeev -
e E <mark>d</mark> it Viev	v Search Terminal Help	
mpathb	253:3 0 953,6M 0	ith
cd co	69:16 0 953,6M 0	
npathg	253:8 0 953,6M 0	
az	67:48 0 953,6M 0	
npathh ce	253:9 0 953,6M 0 69:32 0 953,6M 0	
pathh	253:9 0 953,6M 0	
p	68:48 0 953,6M 0	
pathc	253:4 0 953,6M 0	
f	69:48 0 953,6M 0	
pathh	253:9 0 953,6M 0	
q nathc	68:64 0 953,6M 0	
pathc g	253:4 0 953,6M 0 69:64 0 953,6M 0	
pathh	253:9 0 953,6M 0	
r	68:80 0 953,6M 0	
pathc	253:4 0 953,6M 0	
h	69:80 0 953,6M 0	
etruk		oth /mnt/petruk
s pathd	68:96 0 953,6M 0 253:5 0 953,6M 0	
i	69:96 0 953,6M 0	
- etruk		ith /mnt/petruk
t	68:112 0 953,6M 0	sk .
pathd	253:5 0 953,6M 0	
j	69:112 0 953,6M 0	
etruk u	253:10 0 953,6M 0 68:128 0 953,6M 0	th /mnt/petruk יי
pathd	253:5 0 953,6M 0	
k	69:128 0 953,6M 0	
pathj	253:11 0 953,6M 0	ith
V	68:144 0 953,6M 0	
pathe	253:6 0 953,6M 0	
l pathj	69:144 0 953,6M 0 253:11 0 953,6M 0	
W	68:160 0 953,6M 0	
pathe	253:6 0 953,6M 0	
m	69:160 0 953,6M 0	sk
pathj	253:11 0 953,6M 0	
X natha	68:176 0 953,6M 0	
pathe n	253:6 0 953,6M 0 69:176 0 953,6M 0	
pathk	253:12 0 953,6M 0	
у	68:192 0 953,6M 0	
havrin	253:7 0 953,6M 0	
0	69:192 0 953,6M 0	
pathk	253:12 0 953,6M 0	
z havrin	68:208 0 953,6M 0 253:7 0 953,6M 0	
D D	69:208 0 953,6M 0	
pathk	253:12 0 953,6M 0	
q	69:224 0 953,6M 0	sk
imofeev		th /mnt/timofeev
r	69:240 0 953,6M 0	
imofeev s	253:13 0 953,6M 0 70:0 0 953,6M 0	rth /mnt/timofeev
imofeev		ok hth /mnt/timofeev
	od-01 timofeev]\$	

1.14. Увеличил число маршрутов

```
[timofeev@prod-01 timofeev]$ sudo iscsiadm -m node -T iqn.1986-03.com.hp:storage.p2000g3.13421aff31 -l -p 10.1.2.16:32 60  
[timofeev@prod-01 timofeev]$ sudo iscsiadm -m session  
tcp: [81] 10.1.2.11:3260,3 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)  
tcp: [82] 10.1.2.11:3260,3 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)  
tcp: [83] 10.1.2.11:3260,3 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)  
tcp: [84] 10.1.2.12:3260,5 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)  
tcp: [85] 10.1.2.15:3260,5 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)  
tcp: [86] 10.1.2.15:3260,4 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)  
tcp: [87] 10.1.2.15:3260,4 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)  
tcp: [88] 10.1.2.15:3260,6 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)  
tcp: [89] 10.1.2.16:3260,6 iqn.1986-03.com.hp:storage.p2000g3.13421aff31 (non-flash)  
tcp: [90] 10.1.2.16:3260,6 iqn.1986-03.
```