



# The Main Loop



**Zhivko Petrov**

**A guy that knows C++**



**SoftUni**



**Software University**

<https://about.softuni.bg>

**sli.do**

**#app-dev-cpp**

- Imagine a program, which task is to process string commands

```
while (true) {  
    char *command = readCommand();  
    handleCommand(command);  
}
```

- Pretty straight-forward
- Only problem is the user **can not interact** with the program

- Any graphical application (being a game or not) is designed to handle user requests

```
while (true) {  
    Event *event = waitForEvent();  
    dispatchEvent(event);  
}
```

- Main difference is that program no longer executes only string command
- It is **waiting** for a **user input** – mouse click, keyboard click, touch screen press, etc ...
- The problem is that **nothing is displayed**
- The user can't tell what is happening

- Imagine the context of games
- Your character is sitting still

```
while (true) {  
    Event *event = waitForEvent();  
    dispatchEvent(event);  
}
```

- Now imagine there is a monster hitting you since you are AFK
- Something should happen – your health should deteriorate
- This means **we can't block** on the “waitForEvent()”


- What needs to be done?

```
while (true) {  
    handleInput();  
    update();  
    render();  
  
    //sleep  
}
```

1 spin = 1 frame

- This loop is running as fast as possible
- Your CPU/GPU will be at 100% and the game will run with XXX Frames Per Second (FPS)
- $\text{FPS} = 1\text{s} / \text{time for one frame}$

# The Main Loop



```
while (true) {  
    handleInput();  
    update();  
    render();
```

```
    //sleep
```

```
}
```

How much to sleep depends on  
what FPS are you aiming for


# The Main Loop

- The problem in this approach is the **update** method
- A render call could be **expensive** (taking a lot of time)
- There might be multiple events/updates happening in the meantime
- This results to “**lag**”

```
while (true) {  
    handleInput();  
    update();  
    render();
```

```
    //sleep
```


```
}
```






# The Main Loop

- In order to fix the issue – **all available updates** should be made in **the same frame** before rendering




# The Main Loop

- The timeline of the main loop should look like this



```
while (true) {  
    handleInput();  
    update();  
    render();  
  
    //sleep  
}
```

# Questions?



# Diamond Partners

**SUPER  
HOSTING  
.BG**

**INDEAVR**  
Serving the high achievers

 **SmartIT**

  
SOFTWARE

**zühlke**  
empowering ideas

 **INFRAGISTICS®**



**Coca-Cola HBC**  
Bulgaria



**Postbank**

*Решения за твоето утре*



 **DRAFT  
KINGS**



**SOFTWARE  
GROUP**

# Educational Partners



- This course (slides, examples, demos, exercises, homework, documents, videos and other assets) is **copyrighted content**
- Unauthorized copy, reproduction or use is illegal
- © SoftUni – <https://about.softuni.bg/>
- © Software University – <https://softuni.bg>



- Software University – High-Quality Education, Profession and Job for Software Developers
  - [softuni.bg](http://softuni.bg), [about.softuni.bg](http://about.softuni.bg)
- Software University Foundation
  - [softuni.foundation](http://softuni.foundation)
- Software University @ Facebook
  - [facebook.com/SoftwareUniversity](https://facebook.com/SoftwareUniversity)
- Software University Forums
  - [forum.softuni.bg](http://forum.softuni.bg)

