



FORECASTING USING R

# Welcome to Forecasting Using R

**Rob Hyndman**  
Author, forecast


# What you will learn

- Exploring and visualizing time series
- Simple benchmark methods for forecasting
- Exponential smoothing and ARIMA models
- Advanced forecasting methods
- Measuring forecast accuracy
- Choosing the best method

# Course textbook

Hyndman, R. J. & Athanasopoulos, G. (2017)


*Forecasting: principles and practice*, 2nd edition



- Free and online at [OTexts.org/fpp2/](https://otexts.org/fpp2/)
- Data sets in associated R package fpp2
- R code for all examples

# Time series data


- Series of data observed over time
- Eg.: Daily IBM stock prices, monthly rainfall in London,...



Forecasting is estimating how the sequence of observations will continue into the future.



# Forecasts of monthly Australian expenditure on eating out



- What forecasting methods are available that take account of trend, seasonality and other features of the data?
- How to measure the accuracy of your forecasts?
- How to choose a good forecasting model?



FORECASTING USING R

**Let's practice!**



FORECASTING USING R


# **Trends, seasonality, and cyclicity**

# Time series patterns


Pattern	Description
Trend	A pattern exists involving a long-term increase OR decrease in the data
Seasonal	A periodic pattern exists due to the calendar (e.g. the quarter, month, or day of the week)
Cyclic	A pattern exists where the data exhibits rises and falls that are <i>not of fixed period</i> (duration usually of at least 2 years)




# Examples of time series patterns




# Examples of time series patterns



# Examples of time series patterns



# Examples of time series patterns



# Seasonal or cyclic?

Differences between seasonal and cyclic patterns:

- Seasonal pattern constant length vs. cyclic pattern variable length
- Average length of cycle longer than length of seasonal pattern
- Magnitude of cycle more variable than magnitude of seasonal pattern

The timing of peaks and troughs is predictable with seasonal data, but unpredictable in the long term with cyclic data.



FORECASTING USING R

**Let's practice!**






FORECASTING USING R

# White noise

# White noise

```
> set.seed(3)           # Reproducibility  
> wn <- ts(rnorm(36))   # White noise  
> autoplot(wn)          # Plot!
```




"White noise" is just a time series of iid data

# White noise ACF

```
> ggAcf(wn) +  
  ggtitle("Sample ACF for white noise")
```

Sample ACF for white noise



# Example: Pigs slaughtered


```
> autoplot(pigs/1000) +  
>   xlab("Year") +  
>   ylab("thousands") +  
>   ggtitle("Monthly number of pigs  
slaughtered in Victoria")
```



# Example: Pigs slaughtered

```
> ggAcf(pigs) +  
> ggtitle("ACF of monthly pigs slaughtered  
in Victoria")
```

ACF of monthly pigs slaughtered in Victoria



# Ljung-Box test

The Ljung-Box test considers the first  $h$  autocorrelation values together.

A significant test (small p-value) indicates the data are probably not white noise.

```
> Box.test(pigs, lag = 24, fitdf = 0, type = "Lj")
```

Box-Ljung test

data: pigs

X-squared = 634.15, df = 24, p-value < 2.2e-16



# White noise summary

- White noise is a time series that is purely random
- We can test for white noise by looking at an ACF plot or by doing a Ljung-Box test



FORECASTING USING R

**Let's practice!**