



MACHINE LEARNING TOOLBOX

Welcome to the Machine Learning Toolbox!

Supervised learning

- caret R package
- Automates *supervised learning* (a.k.a. *predictive modeling*)
- Target variable



Supervised learning

- Two types of predictive models
 - Classification → Qualitative
 - Regression → Quantitative
- Use *metrics* to evaluate models
 - Quantifiable
 - Objective
- *Root Mean Squared Error* (RMSE) for regression (e.g. `lm()`)

Evaluating model performance

- Common to calculate in-sample RMSE
 - Too optimistic
 - Leads to overfitting
- Better to calculate out-of-sample error (a la caret)
 - Simulates real-world usage
 - Helps avoid overfitting

In-sample error

```
> # Fit a model to the mtcars data
> data(mtcars)
> model <- lm(mpg ~ hp, mtcars[1:20, ])

> # Predict in-sample
> predicted <- predict(model, mtcars[1:20, ], type = "response")

> # Calculate RMSE
> actual <- mtcars[1:20, "mpg"]
> sqrt(mean((predicted - actual)^2))
[1] 3.172132
```



The Machine Learning Toolbox

Let's practice!



MACHINE LEARNING TOOLBOX

Out-of-sample error measures

Out-of-sample error

- Want models that don't overfit and generalize well
- Do the models perform well on new data?
- Test models on new data, or a *test set*
 - Key insight of machine learning
 - In-sample validation almost guarantees overfitting
- Primary goal of `caret` and this course: don't overfit

Example: out-of-sample RMSE

```
> # Fit a model to the mtcars data
> data(mtcars)
> model <- lm(mpg ~ hp, mtcars[1:20, ])

> # Predict out-of-sample
> predicted <- predict(model, mtcars[21:32, ], type = "response")

> # Evaluate error
> actual <- mtcars[21:32, "mpg"]
> sqrt(mean((predicted - actual)^2))
[1] 5.507236
```

Alternatives:

```
createResamples()
createFolds()
```

Compare to in-sample RMSE

```
> # Fit a model to the full dataset
> model2 <- lm(mpg ~ hp, mtcars)

> # Predict in-sample
> predicted2 <- predict(model, mtcars, type = "response")

> # Evaluate error
> actual2 <- mtcars[, "mpg"]
> sqrt(mean((predicted2 - actual2)^2))
[1] 3.74
```

Compare to out-of-sample RMSE of 5.5



MACHINE LEARNING TOOLBOX

Let's practice!



MACHINE LEARNING TOOLBOX

Cross-validation

Cross-validation

Full dataset

Rows are
randomly
assigned



Fold 1

Fold 2

Fold 3

Fold 4

Fold 5

Fold 6


Fold 7

Fold 8

Fold 9

Fold 10

Fit final model on full dataset



Cross-validation

```
> # Set seed for reproducibility
> library(caret)
> data(mtcars)
> set.seed(42)

> # Fit linear regression model
> model <- train(mpg ~ hp, mtcars,
  method = "lm",
  trControl = trainControl(
    method = "cv", number = 10,
    verboseIter = TRUE
  )
)
+ Fold01: parameter=none
+ Fold02: parameter=none
...
- Fold10: parameter=none
Aggregating results
Fitting final model on full training set
```




MACHINE LEARNING TOOLBOX

Let's practice!