



Welcome to the course



About me

- Author and/or maintainer of several packages
 - TTR, xts, quantmod, quantstrat, blotter
- R/Finance Conference Organizing Committee
- St Louis R User Group



What is getSymbols()?

- Provides access to multiple data sources
- Returns xts object by default
- Can import data two ways:
 - Return data like an ordinary function
 - Create an object like load () does in base R



getSymbols()example

```
> getSymbols(Symbols = "AAPL", src = "yahoo")
[1] "AAPL"
> getSymbols("AAPL")
[1] "AAPL"
```

```
> head(AAPL)
           AAPL.Open AAPL.High AAPL.Low AAPL.Close AAPL.Volume AAPL.Adjusted
               86.29
                         86.58
                                   81.90
                                              83.80
                                                       309579900
                                                                      10.85709
2007-01-03
2007-01-04
               84.05
                         85.95
                                   83.82
                                              85.66
                                                       211815100
                                                                      11.09807
2007-01-05
               85.77
                         86.20
                                              85.05
                                   84.40
                                                       208685400
                                                                      11.01904
               85.96
                                                       199276700
2007-01-08
                         86.53
                                   85.28
                                              85.47
                                                                      11.07345
2007-01-09
               86.45
                                                                      11.99333
                         92.98
                                   85.15
                                              92.57
                                                       837324600
2007-01-10
               94.75
                         97.80
                                              97.00
                                                       738220000
                                   93.45
                                                                      12.56728
```





getSymbols()data sources

Yahoo! Finance



Google Finance



FRED



Oanda



CSV





Other getSymbols() data sources

- Yahoo! Finance Japan
- MySQL
- SQLite
- RData
- rds (created by saveRDS ())



getSymbols()example

```
Default
> # Load data like load()
> getSymbols("AAPL", auto.assign = TRUE)
[1] "AAPL"
> head(AAPL, n = 3)
         AAPL.Open AAPL.High AAPL.Low AAPL.Close AAPL.Volume AAPL.Adjusted
                                                309579900
2007-01-03
             86.29
                      86.58
                              81.90
                                         83.80
                                                             10.85709
2007-01-04 84.05
                   85.95 83.82
                                        85.66
                                                211815100
                                                             11.09807
                                                208685400
2007-01-05 85.77
                   86.20
                             84.40
                                                              11.01904
                                        85.05
```

```
> # Return data like a normal function
> aapl <- getSymbols("AAPL", auto.assign = FALSE)</pre>
> head(aapl, n = 3)
          AAPL.Open AAPL.High AAPL.Low AAPL.Close AAPL.Volume AAPL.Adjusted
               86.29
                         86.58
                                  81.90
                                                                     10.85709
2007-01-03
                                             83.80
                                                     309579900
2007-01-04
              84.05 85.95
                                 83.82
                                             85.66
                                                     211815100
                                                                     11.09807
2007-01-05
               85.77
                         86.20
                                  84.40
                                             85.05
                                                      208685400
                                                                     11.01904
```





Let's practice!





Introduction to Quandl



What is Quandl?

- Data service:
 - https://www.quandl.com/
- R package:
 - https://CRAN.R-project.org/package=Quandl
- Function:
 - Quandl::Quandl()



Quandl() versus getSymbols()

- Both provide access to multiple data sources
- Quandl() always returns data (i.e. does not behave like load())

```
> # Instrument and source specified by Symbols and src arguments
> quantmod::getSymbols(Symbols = "AAPL", src = "yahoo")
> # Instrument and source specified by code argument
> aapl <- Quandl::Quandl(code = "YAHOO/AAPL")</pre>
```



Quandl() versus getSymbols()

- type argument controls class of return object:
 - "raw" (data.frame), "ts", "zoo", "xts", "timeSeries"

```
> # Return ts object instead of data.frame
> aapl <- Quandl::Quandl(code = "YAHOO/AAPL", type = "ts")</pre>
```

- Defaults:
 - getSymbols()returns xts
 - Quandl() returns data.frame





Let's practice!






Finding data from internet sources




Yahoo Finance








Google Finance








Oanda







FRED







Let's practice!