

Adapted to TKT4140 Numerical Methods with Computer Laboratory

Hans Petter Langtangen^{1,2} Leif Rune Hellevik³

Simula Research Laboratory¹

University of Oslo²

Biomechanics Group, Department of Structural Engineering NTNU³

Jan 13, 2015

This is a very quick intro to Python programming

- variables for numbers, lists, and arrays
- while loops and for loops
- functions
- if tests
- plotting

Method: show program code through math examples

Variables, loops, lists, and arrays



Most examples will involve this formula:

$$s = v_0 t + \frac{1}{2} a t^2$$

A program for evaluating a formula

Task

Compute s for $t = 0.5$, $v_0 = 2$, and $a = 0.2$.

Code

```
t = 0.5
v0 = 2
a = 0.2
s = v0*t + 0.5*a*t**2
print s
```

Execution

```
Terminal> python distance.py
1.025
```

Assignment statements assign a name to an object

```
t = 0.5           # real number makes float object
v0 = 2            # integer makes int object
a = 0.2           # float object
s = v0*t + 0.5*a*t**2 # float object
```

Rule: evaluate right-hand side object, left-hand side is a name for that object

Formatted output with text and numbers

- Task: write out $s=1.025$
- Method: printf syntax

```
print 's=%g' % s      # g: compact notation
print 's=%.2f' % s     # f: decimal notation, .2f: 2 decimals
```

Modern alternative: format string syntax

```
print 's={s:.2f}'.format(s=s)
```

Programming with a while loop

- Task: write out a table of t and $s(t)$ values (two columns), for $t \in [0, 2]$ in steps of 0.1
- Method: while loop

```
v0 = 2
a = 0.2
dt = 0.1 # Increment
t = 0 # Start value
while t <= 2:
    s = v0*t + 0.5*a*t**2
    print t, s
    t = t + dt
```

Output of the previous program

```
Terminal> python while.py
0 0.0
0.1 0.201
0.2 0.404
0.3 0.609
0.4 0.816
0.5 1.025
0.6 1.236
0.7 1.449
0.8 1.664
0.9 1.881
1.0 2.1
1.1 2.321
1.2 2.544
1.3 2.769
1.4 2.996
1.5 3.225
1.6 3.456
1.7 3.689
1.8 3.924
1.9 4.161
```

Structure of a while loop

```
while condition:
    <intented statement>
    <intented statement>
    <intented statement>
```

Note:

- the colon in the first line
- all statements in the loop must be indented
- condition is a boolean expression (e.g., $t \leq 2$)

The Python Online Tutor can help you understand the program flow

Python Online Tutor lets you step through the program and examine variables.

```
a = 1
da = 0.5
while a <= 3:
    print a
    a = a + da
```

(Visualize execution)

Lists

A list collects several variables (objects) in a given sequence:

```
L = [-1, 1, 8.0]
```

A list can contain any type of objects, e.g.,

```
L = ['mydata.txt', 3.14, 10]
```

Some basic list operations:

```
>>> L = ['mydata.txt', 3.14, 10]
>>> print L[0]
mydata.txt
>>> print L[1]
3.14
>>> del L[0] # delete the first element
>>> print L
[3.14, 10]
>>> print len(L) # length of L
2
>>> L.append(-1) # add -1 at the end of the list
>>> print L
[3.14, 10, -1]
```

Store our table in two lists, one for each column

```
v0 = 2
a = 0.2
dt = 0.1 # Increment
t = 0
t_values = []
s_values = []
while t <= 2:
    s = v0*t + 0.5*a*t**2
    t_values.append(t)
    s_values.append(s)
    t = t + dt
print s_values # Just take a look at a created list

# Print a nicely formatted table
i = 0
while i <= len(t_values)-1:
    print '%.2f' % t_values[i], '%.4f' % (t_values[i], s_values[i])
    i += 1 # Same as i = i + 1
```

For loops

A for loop is used for visiting elements in a list, one by one:

```
>>> L = [1, 4, 8, 9]
>>> for e in L:
...     print e
...
1
4
8
9
```

Demo in the Python Online Tutor:

```
list1 = [0, 0.1, 0.2]
list2 = []
for element in list1:
    p = element + 2
    list2.append(p)
print list2
```

(Visualize execution)

For loops used traditionally an integer counter over list/array indices

```
for i in range(len(somelist)):
    # Work with somelist[i]
```

Note:

- range returns a list of integers
- range(a, b, s) returns the integers a, a+s, a+2*s, ... up to *but not including* (!) b
- range(b) implies a=0 and s=1
- range(len(somelist)) returns [0, 1, 2]

Let's replace our while loop by a for loop

```
v0 = 2
a = 0.2
dt = 0.1 # Increment
t_values = []
s_values = []
n = int(round(2/dt)) + 1 # No of t values
for i in range(n):
    t = i*dt
    s = v0*t + 0.5*a*t**2
    t_values.append(t)
    s_values.append(s)
print s_values # Just take a look at a created list

# Make nicely formatted table
for t, s in zip(t_values, s_values):
    print '%.2f %.4f' % (t, s)

# Alternative
for i in range(len(t_values)):
    print '%.2f %.4f' % (t_values[i], s_values[i])
```

Traversal of multiple lists at the same time with zip

```
for e1, e2, e3, ... in zip(list1, list2, list3, ...):
```

Alternative: loop over a common index for the lists

```
for i in range(len(list1)):
    e1 = list1[i]
    e2 = list2[i]
    ...
```

Arrays

- List: collect a set of numbers or other objects in a single variable
- Lists are very flexible (can grow, can contain "anything")
- Array: computationally efficient and convenient list
- Arrays must have fixed length and can only contain numbers of the same type (integers, real numbers, complex numbers)
- Arrays require the numpy module

```
>>> import numpy
>>> L = [1, 4, 10.0] # List of numbers
>>> a = numpy.array(L) # Make corresponding array
>>> print a
[ 1.  4. 10.]
>>> print a[i]
4.0
>>> print a.dtype # Data type of an element
float64
>>> b = 2*a + 1
>>> print b
[ 3.  9. 21.]
```

numpy functions creates entire arrays at once

```
>>> c = numpy.log(a) # Take ln of all elements in a
>>> print c
[ 0.         1.38629436  2.30258509]
```

Create $n+1$ uniformly distributed coordinates in $[a, b]$:

```
t = numpy.linspace(a, b, n+1)
```

Let's use arrays in our previous program

```
import numpy
v0 = 2
a = 0.2
dt = 0.1 # Increment
n = int(round(2/dt)) + 1 # No of t values

t_values = numpy.linspace(0, 2, n+1)
s_values = v0*t + 0.5*a*t**2

# Make nicely formatted table
for t, s in zip(t_values, s_values):
    print '%.2f %.4f' % (t, s)
```

Standard mathematical functions are found in the math module

```
>>> import math
>>> print math.sin(math.pi)
1.2246467991473532e-16 # Note: only approximate value
```

Get rid of the math prefix:

```
from math import sin, pi
print sin(pi)

# Or import everything from math
from math import *
print sin(pi), log(e), tanh(0.5)
```

Use the numpy module for standard mathematical functions applied to arrays

Matlab users can do

```
from numpy import *
```

The Python community likes

```
import numpy as np
print np.sin(np.pi)
```

Our convention: use np prefix, but not in formulas involving math functions

```
import numpy as np
from numpy import sin, exp
t = np.linspace(0, 4, 1001)
p = exp(-t)*sin(2*t)
```

Plotting

Plotting is done with matplotlib:


```
import numpy as np
import matplotlib.pyplot as plt

v0 = 0.2
a = 2
n = 21 # No of t values for plotting

t = np.linspace(0, 2, n+1)
s = v0*t + 0.5*a*t**2

plt.plot(t, s)
plt.savefig('myplot.png')
plt.show()
```

The plotfile myplot.png looks like




Plotting of multiple curves

```
import numpy as np
import matplotlib.pyplot as plt


v0 = 0.2
a = 2
n = 21 # No of t values for plotting

t = np.linspace(0, 2, n+1)
s = v0*t + 0.5*a*t**2

plt.plot(t, s)
plt.savefig('myplot.png')
plt.show()
```



Functions and branching



Functions

- $s(t) = v_0 t + \frac{1}{2} a t^2$ is a mathematical function
- Can implement $s(t)$ as a Python function $s(t)$

```
def s(t):  
    return v0*t + 0.5*a*t**2  
  
v0 = 0.2  
a = 4  
value = s(3)  # Call the function
```

Note:

- functions start with the keyword `def`
- statements belonging to the function must be indented
- function input is represented by arguments (separated by comma if more than one)
- function output is returned to the calling code
- `v0` and `a` are *global variables*
- `v0` and `a` must be initialized before `s` is called

Functions can have multiple arguments

`v0` and `a` as function arguments instead of global variables:

```
def s(t, v0, a):  
    return v0*t + 0.5*a*t**2  
  
value = s(3, 0.2, 4)  # Call the function  
  
# More readable call  
value = s(t=3, v0=0.2, a=4)
```

Keyword arguments are arguments with default values

```
def s(t, v0=1, a=1):  
    return v0*t + 0.5*a*t**2  
  
value = s(3, 0.2, 4)  # specify new v0 and a  
value = s(3)          # rely on v0=1 and a=1  
value = s(3, a=2)     # rely on v0=1  
value = s(3, v0=2)     # rely on a=1  
value = s(t=3, v0=2, a=2) # specify everything  
value = s(a=2, t=3, v0=2) # any sequence allowed
```

- Arguments without the argument name are called *positional arguments*
- Positional arguments must always be listed before the keyword arguments in the function and in any call
- The sequence of the keyword arguments can be arbitrary

Vectorization speeds up the code

Scalar code (work with one number at a time):

```
def s(t, v0, a):  
    return v0*t + 0.5*a*t**2  
  
for i in range(len(t)):  
    s_values[i] = s(t_values[i], v0, a)
```

Vectorized code: apply `s` to the entire array

```
s_values = s(t_values, v0, a)
```

How can this work?

- Array: `t`
- Expression: `v0*t + 0.5*a*t**2`
- `r1 = v0*t` (scalar times array)
- `r2 = t**2` (square each element)
- `r3 = 0.5*a*r2` (scalar times array)
- `r1 + r3` (add each element)

Python functions written for scalars normally work for arrays too!

True if computations involve arithmetic operations and math functions:

```
from math import exp, sin  
  
def f(x):  
    return 2*x + x**2*exp(-x)*sin(x)  
  
v = f(4)  # f(x) works with scalar x  
  
# Redefine exp and sin with their vectorized versions  
from numpy import exp, sin, linspace  
x = linspace(0, 4, 100001)  
v = f(x)  # f(x) works with array x
```

However, if tests are not allowed:

```
def f(x):  
    return -1 if x < 0 else x**4*exp(-x)*sin(x)  
  
x = linspace(0, 4, 100001)  
v = f(x)  # will not work
```

Python functions can return multiple values

Return $s(t) = v_0 t + \frac{1}{2} a t^2$ and $s'(t) = v_0 + at$:

```
def movement(t, v0, a):  
    s = v0*t + 0.5*a*t**2  
    v = v0 + a*t  
    return s, v  
  
s_value, v_value = movement(t=0.2, v0=2, a=4)
```

`return s, v` means that we return a *tuple* (\approx list):

```
>>> def f(x):  
...     return x+1, x+2, x+3  
...  
>>> r = f(3)  # Store all three return values in one object r  
>>> print r  
(4, 5, 6)  
>>> type(r)  # What type of object is r?  
<type 'tuple'>  
>>> print r[1]  
5
```

Tuples are constant lists (cannot be changed)

Basic if-else tests

An if test has the structure

```
if condition:
    <statements when condition is True>
else:
    <statements when condition is False>
```

Here,

- condition is a boolean expression with value True or False.

```
if t <= t1:
    s = v0*t + 0.5*a0*t**2
else:
    s = v0*t + 0.5*a0*t1**2 + a0*t1*(t-t1)
```

Multi-branch if tests

```
if condition1:
    <statements when condition1 is True>
elif condition2:
    <statements when condition1 is False and condition2 is True>
elif condition3:
    <statements when condition1 and condition 2 are False
    and condition3 is True>
else:
    <statements when condition1/2/3 all are False>
```

Just if, no else:

```
if condition:
    <statements when condition is True>
```

Implementation of a piecewisely defined function with if

A Python function implementing the mathematical function $s = v_0 t + \frac{1}{2} a t^2$ reads

$$s(t) = \begin{cases} s_0 + v_0 t + \frac{1}{2} a_0 t^2, & t \leq t_1 \\ s_0 + v_0 t_1 + \frac{1}{2} a_0 t_1^2 + a_0 t_1 (t - t_1), & t > t_1 \end{cases}$$

```
def s_func(t, v0, a0, t1):
    if t <= t1:
        s = v0*t + 0.5*a0*t**2
    else:
        s = v0*t + 0.5*a0*t1**2 + a0*t1*(t-t1)
    return s
```

Python functions containing if will not accept array arguments

```
>>> def f(x): return x if x < 1 else 2*x
>>> import numpy as np
>>> x = np.linspace(0, 2, 5)
>>> f(x)
Traceback (most recent call last):
...
ValueError: The truth value of an array with more than one
element is ambiguous. Use a.any() or a.all()
```

Problem: $x < 1$ evaluates to a boolean array, not just a boolean

Remedy 1: Call the function with scalar arguments

```
n = 201 # No of t values for plotting
t1 = 1.5

t = np.linspace(0, 2, n+1)
s = np.zeros(n+1)
for i in range(len(t)):
    s[i] = s_func(t=t[i], v0=0.2, a0=20, t1=t1)
```

Can now easily plot:

```
plt.plot(t, s, 'b-')
plt.plot([t1, t1], [0, s_func(t=t1, v0=0.2, a0=20, t1=t1)], 'r--')
plt.xlabel('t')
plt.ylabel('s')
plt.savefig('myplot.png')
plt.show()
```

Remedy 2: Vectorize the if test with where

Functions with if tests require a complete rewrite to work with arrays.

```
s = np.where(condition, s1, s2)
```

Explanation:

- condition: array of boolean values
- $s[i] = s1[i]$ if condition $[i]$ is True
- $s[i] = s2[i]$ if condition $[i]$ is False

Our example then becomes

```
s = np.where(t <= t1,
             v0*t + 0.5*a0*t**2,
             v0*t + 0.5*a0*t1**2 + a0*t1*(t-t1))
```

Note that $t <= t1$ with array t and scalar $t1$ results in a boolean array b where $b[i] = t[i] <= t1$.

Remedy 3: Vectorize the if test with array indexing

- Let `b` be a boolean array (e.g., `b = t <= t1`)
- `s[b]` selects all elements `s[i]` where `b[i]` is True
- Can assign some array expression `expr` of length `len(s[b])` to `s[b]`: `s[b] = (expr)[b]`

Our example can utilize this technique with `b` as `t <= t1` and `t > t1`:

```
s = np.zeros_like(t)  # Make s as zeros, same size & type as t
s[t <= t1] = (v0*t + 0.5*a0*t**2)[t <= t1]
s[t > t1] = (v0*t + 0.5*a0*t1**2 + a0*t1*(t-t1))[t > t1]
```