

# Junicode VF

Peter S. Baker

January 1, 2024

## 1. Introduction

This package supports Junicode VF, the variable version of Junicode (2.204 or higher) for Lua<sup>A</sup>TeX. Junicode VF is not yet in CTAN, so you must install the font in your system in order to use it. Place the files `junicodevf.sty` and `junicodevf.lua` somewhere your TeX installation can find them (perhaps in the directory with the document you're currently working on). This package loads `fontspec`, so it is not necessary to load that package separately, even if you are using other fonts alongside Junicode VF.

## 2. Loading Junicode VF

Load the package in the usual way, with `\usepackage{junicodevf}`, to set Junicode VF as the main font. By default, the main font is not a set of static outlines whose proportions remain the same though they can be scaled, but rather a set of *variable* outlines that become relatively narrower and lighter as the text size decreases. You can see the difference if we scale a line of footnote text and a line of header text to the same `\large` size:

Here is some sample text for footnotes (usually about 8pt).  
Here is some sample text for headers (18pt or larger).

The letter-shapes are markedly different, but on the page they look pretty much the same, because the purpose of these changes in shape, in addition to promoting legibility, is to allow blocks of text in different sizes (headers, main text, block quotations, footnotes) to coexist on a page without any of them looking too dark or too light.<sup>1</sup> Evenness of texture makes text in different point sizes *look* the same.

Unicode VF's package options give you a number of ways to fine-tune the look of your text:

**light** The weight of the type for the main text is Light. As with the default weight, and all weights selectable by options, "Light" is a range of weights that varies with the size of the type.

**medium** The weight of the type for the main text is Medium—that is, darker than Regular but lighter than Semibold.

**semibold** The weight of bold type is somewhat lighter than the usual bold. This may be a good choice if you have selected the **light** option.

**weightadjustment** Adjusts the weight of the type by adding this number. For example, if you choose **medium** for your document (weight averaging about 500) and **bold** (weight around 700), and also include the option `weightadjustment=-25`, then the weights of medium and bold text will be lightened by 25 (475, 675).

**condensed** The width of the type is narrow—about 85% of the width of the Regular style. As with the default width, and all widths selectable by options, "Condensed" is a range of widths that varies with the size of the type.

**semicondensed** The width of the type is wider than condensed but narrower than the default.

**expanded** The width of the type is wide—about 125% of the width of the Regular style.

---

<sup>1</sup>For example, on a typical LaTeX page a footnote like this, looked at as a block of gray, is usually a little lighter than the main text. But on this page, the "color" of the footnote matches that of the main text. The variation in glyph shape responsible for this effect approximates the way letters in metal type were typically wider and heavier at small sizes.

**semiexpanded** The width of the type is wider than Regular but narrower than Expanded.

**widthadjustment** Adjusts the width of the type by adding this number. For example, if you choose **semicondensed** for your document (width averaging 87.5), and you also include the option **widthadjustment=5**, then the average width will be 92.5, between **semicondensed** and **regular**.

**proportional** Numbers in the document will be proportionally spaced. This is the default.

**tabular** Numbers will be tabular (monospaced).

**oldstyle** Numbers will be old-style, harmonizing with lowercase letters. This is the default.

**lining** Numbers will be lining, harmonizing with uppercase letters.

### 3. Customizing the Main Font

If the options listed in the previous section don't give you the effect you're looking for, this package's more advanced options allow you to choose from an effectively infinite number of styles. Do this by passing OpenType features for your document's main text or for one or more of the four main styles (Regular, Italic, Bold, Bold Italic), and also by supplying custom values for the font's four axes.

For example, if you want your document to use the conventions observed by early English typesetters for the distribution of **s** and **f**, load the package this way:

```
\usepackage[MainFeatures={  
  Language=English,  
  StylisticSet=8  
}]{junicodevf}
```

If you want to use these conventions only for italic text, use **MainItalicFeatures** instead of **MainFeatures**. All of the features you pass via these options must be valid for fontspec: in fact, they are passed straight through to fontspec.

If you want to customize the four basic styles of the main text, use **MainRegularSizeFeatures**, **MainItalicSizeFeatures**, and so on. Each of these defines a list of associative arrays, in which each array in the list prescribes axis coordinates for a range of sizes. For example, here are the **SizeFeatures** for the *Junicode Manual*:

```
\usepackage[
  MainRegularSizeFeatures={
    {size=8.6,wght=550,width=120},
    {size=10.99,wght=475,width=115},
    {size=21.59,wght=400,width=112.5},
    {size=21.59,wght=351,width=100}
  },
  MainItalicSizeFeatures={
    {size=8.6,wght=550,width=118},
    {size=10.99,wght=475,width=114},
    {size=21.59,wght=450,width=111},
    {size=21.59,wght=372,width=98}
  },
  MainBoldSizeFeatures={
    {size=8.6,wght=700,width=120},
    {size=10.99,wght=700,width=115},
    {size=21.59,wght=650,width=112.5},
    {size=21.59,wght=600,width=100}
  },
  MainBoldItalicSizeFeatures={
    {size=8.6,wght=700,width=118},
    {size=10.99,wght=700,width=114},
    {size=21.59,wght=650,width=111},
    {size=21.59,wght=600,width=98}
  }
]{}junicodevf}
```

For each array, a **size** key is mandatory: any array without one is ignored. The arrays should be in order of point size. The first array prescribes axis coordinates for all sizes up to **size**, the last array for all sizes greater than **size**, and any intermediate items a range from the previous to the current **size**.<sup>2</sup> So the ranges

---

<sup>2</sup>If you want only one size array, make **size** improbably low (e.g. 5) and place a comma after the closing brace of the array.

covered in each list above are -8.6, 8.6-10.99, 10.99-21.59, and 21.59-.<sup>3</sup>

The keys other than `size` are the four-letter tags for the font’s axes: `wght` (Weight), `wdth` (Width), and `ENLA` (Enlarge).<sup>4</sup> When a key is omitted, the default value for that axis is used. It is up to the user to make sure the values given for each axis are valid—the package does no checking (but `fontspec` will do a good bit of checking for you). When SizeFeatures are given in this way, they override any other options that set or change axis coordinates (e.g. `weightadjustment`).

## 4. Selecting Alternate Styles

In addition to the document’s main font, you can choose from fifty predefined styles. These match the thirty-eight styles supplied by the static version of Junicode, plus twelve more. The commands for shifting to these styles are as follows (of the italic styles, only the base “jItalic” is listed; append “Italic” to any of the others, except “jRegular”):

<code>\jRegular</code>	<code>\jSmExpLight</code>	<code>\jSmCondSmbold</code>
<code>\jItalic</code>	<code>\jExpLight</code>	<code>\jSmExpSmbold</code>
<code>\jCond</code>	<code>\jMedium</code>	<code>\jExpSmbold</code>
<code>\jSmCond</code>	<code>\jCondMedium</code>	<code>\jBold</code>
<code>\jSmExp</code>	<code>\jSmCondMedium</code>	<code>\jCondBold</code>
<code>\jExp</code>	<code>\jSmExpMedium</code>	<code>\jSmCondBold</code>
<code>\jLight</code>	<code>\jExpMedium</code>	<code>\jSmExpBold</code>
<code>\jCondLight</code>	<code>\jSmbold</code>	<code>\jExpBold</code>
<code>\jSmCondLight</code>	<code>\jCondSmbold</code>	

These commands will be self-explanatory if you bear in mind Junicode’s abbreviations for style names: Cond=Condensed, Exp=Expanded, Sm=Semi.<sup>5</sup> Use them

---

<sup>3</sup>Any modification of the default text size (e.g. in the `\documentclass` command) can affect the size definitions in these arrays, with the result that (for example) `10` no longer means exactly “ten points.” You may have to experiment to get these numbers right.

<sup>4</sup>By convention, tags for axes defined in the OpenType standard are lowercase; custom axes are uppercase. Junicode’s `ENLA` is a custom axis.

<sup>5</sup>The purpose of these abbreviations is to keep font names under the character-limit imposed by some systems.

to shift temporarily to a style other than that of the main text. For example, to shift to the Condensed Light style for a short phrase, use this code:

```
{\jCondLight a short phrase}.
```

The result: a short phrase.

To add features to any of these styles, use the style name (without the prefixed “j” and with **Features** appended) as a package option. To change the size features for the style, do the same, but with **SizeFeatures** instead of **Features** appended:

```
\usepackage[
  CondLightFeatures={
    Language=English,
    StylisticSet=2
  },
  CondLightSizeFeatures={{size=5,wght=325,wdth=80}},
]{junicodevf}
```

This will shift text in the Condensed Light style from default to insular letter-shapes and slightly increase the weight and width of all glyphs in that style. Here the **SizeFeatures** section is very simple (as in the package file itself), but you can have as many size ranges as you want, just as you can for the main font.

## 5. The Enlarge Axis

Unicode’s Enlarge axis is for a special purpose: to represent the enlarged minuscule letters that often begin sentences and other textual units in medieval manuscripts. Thus it should normally be applied only to single letters, not to runs of text.

This package defines four different styles for the Enlarge axis, in four sizes:

Not Enlarged	abc	<i>abc</i>
\EnlargedOne	abc	<i>abc</i>
\EnlargedTwo	abc	<i>abc</i>
\EnlargedThree	abc	<i>abc</i>
\EnlargedFour	abc	<i>abc</i>

You can produce an italic version of the enlarged minuscule by appending “Italic” to the style name. You can also customize these styles with **SizeFeatures**:

```
\usepackage[
  ENLATHreeSizeFeatures={{size=5,ENLA=85}},
]{junicodevf}
```

This example will set all axes except for **ENLA** to their default coordinates. You can, of course, define other axes, and, as with Junicode’s other **SizeFeatures** options, as many size arrays as you like. **Features** options are not available for the Enlarged styles.

## 6. Other Commands

This package’s other commands are offered as conveniences—shorter and more mnemonic than the fontspec commands they invoke (though of course all fontspec commands remain available). Each of these commands also has a corresponding “text” command that works like `\textit{}`—that is, it takes as its sole argument the text to which the command will be applied. Each “text” command consists of the main command with “text” prefixed—for example, `\textInsularLetterForms{}` corresponding to `\InsularLetterForms`. For a fuller account of the OpenType features applied by these commands, see Chapter 4 of the *Junicode Manual*, “Feature Reference.”

<code>\AltThornEth</code>	Applies sso1, Alternate thorn and eth.
<code>\InsularLetterForms</code>	Applies sso2, Insular letter-forms.
<code>\IPAAlternates</code>	Applies sso3, IPA alternates.
<code>\HighOverline</code>	Applies sso4, High Overline.
<code>\MediumHighOverline</code>	Applies sso5, Medium-high Overline.
<code>\EnlargedMinuscules</code>	Applies sso6, Enlarged minuscules.
<code>\Underdotted</code>	Applies sso7, Underdotted.
<code>\ContextualLongS</code>	Applies sso8, Contextual long s.

<code>\AlternateFigures</code>	Applies ss09, Alternate Figures.
<code>\EntitiesAndTags</code>	Applies ss10, Entities and Tags.
<code>\EarlyEnglishFuthorc</code>	Applies ss12, Early English Futhorc.
<code>\ElderFuthark</code>	Applies ss13, Elder Futhark.
<code>\YoungerFuthark</code>	Applies ss14, Younger Futhark.
<code>\LongBranchToShortTwig</code>	Applies ss15, Long Branch to Short Twig.
<code>\ContextualRRotunda</code>	Applies ss16, Contextual r rotunda.
<code>\RareDigraphs</code>	Applies ss17, Rare Digraphs.
<code>\OldStylePunctuation</code>	Applies ss18, Old-style Punctuation.
<code>\LatinToGothic</code>	Applies ss19, Latin to Gothic.
<code>\LowDiacritics</code>	Applies ss20, Low Diacritics.
<code>\jcv, \textcv</code>	Applies any Character Variant feature (see below).

The syntax of `\jcv` is `\jcv[num]{num}`, where the second (required) argument is the number of the Character Variant feature, and the first (optional) argument is an index into the variants provided by that feature (starting with zero, the default). `\textcv` takes an additional required argument (`\textcv[num]{num}{text}`)—the text to which the feature should be applied.

Character Variant features can also be selected with mnemonics, listed below. For example, a feature for lowercase **a** can be expressed as `\textcv[2]{\jcva}{a}`, yielding **ɑ**.

<code>\jcvA</code>	<code>\jcvG</code>	<code>\jcvM</code>
<code>\jcva</code>	<code>\jcvg</code>	<code>\jcvm</code>
<code>\jcvB</code>	<code>\jcvH</code>	<code>\jcvN</code>
<code>\jcvb</code>	<code>\jcvh</code>	<code>\jcvn</code>
<code>\jcvC</code>	<code>\jcvI</code>	<code>\jcvO</code>
<code>\jcvc</code>	<code>\jcvi</code>	<code>\jcvo</code>
<code>\jcvD</code>	<code>\jcvJ</code>	<code>\jcvP</code>
<code>\jcvd</code>	<code>\jcvj</code>	<code>\jcvp</code>
<code>\jcvE</code>	<code>\jcvK</code>	<code>\jcvQ</code>
<code>\jcve</code>	<code>\jcvk</code>	<code>\jcvq</code>
<code>\jcvF</code>	<code>\jcvL</code>	<code>\jcvR</code>
<code>\jcvf</code>	<code>\jcvl</code>	<code>\jcvr</code>



\jcvS	\jcvAogonek	\jcvflorin
\jcvs	\jcvaogonek	\jcvGermanpenny
\jcvT	\jcvASCIItilde	\jcvglottal
\jcvt	\jcvasterisk	\jcvlb
\jcvU	\jcvav	\jcvlhighstroke
\jcvu	\jcvbrevebelow	\jcvmacron
\jcvV	\jcvcombiningdieresis	\jcvmiddot
\jcvv	\jcvcombiningdoublemacron	\jcvoPolish
\jcvW	\jcvcombininginsular	\jcvounce
\jcvw	\jcvcombiningopena	\jcvperiod
\jcvX	\jcvcombiningoverline	\jcvpunctuselevatus
\jcvx	\jcvcombiningrrotunda	\jcvquestion
\jcvY	\jcvcombiningzigzag	\jcvrum
\jcvy	\jcvcomma	\jcvsemicolon
\jcvZ	\jvcurrency	\jcvslash
\jcvz	\jcvdbar	\jcvspacingusabbrev
\jcvaa	\jcvdcroat	\jcvspacingzigzag
\jcvAE	\jcvEng	\jcvsterling
\jcvae	\jcvEogonek	\jcvthorncrossed
\jcvAO	\jcvetabbrev	\jcvTironianEt
\jcvao	\jcvexclam	\jcvYogh

*This document is set in Junicode VF with Weight 435 and Width 107.5.*

*The font for code is Fira Mono,  
and the sans serif font is Fira Sans.*