



The **FHZSS** Pintle Hitch Hotshot Flatdeck Trailer delivers pro-level performance and is built for confident hauling, featuring lengths from 20' to 44', a 102" deck width, and a low 34" deck height. Engineered with a 12" I-Beam frame, super single 10k-12k axles, and GVWR up to 25,900 lbs, it's equipped with 8' heavy-duty slide-in ramps, a winch-ready plate, and robust side steps—perfect for serious hotshot hauling.

## STANDARD FEATURES

### TRAILER SPECS:

#### DIMENSIONS:

AVAILABLE LENGTHS: 20', 22', 24', 26', 28', 30', 32', 34', 36', 38', 40', 42', 44'

DECK WIDTH: 102"

DECK HEIGHT: 34"

#### WEIGHT RATING:

AXLE COUNT: 2

GAWR: 10,000 lbs, 12,000 lbs

GVWR: 25,000 lbs, 25,900 lbs

#### FINISH:

PAINT TYPE: Powdercoat

PREP: Steel Grit Blasted

COLORS: Military Green, Desert Tan, Flame Orange, Midnight Black, Spectra Yellow, Blue Horizon, Lime Green, Ash Grey, True Red, Pearl White, Cloud Grey, Navy Blue, Sunset Orange

#### WARRANTY:

AXLE WARRANTY: 6 Year Lippert Spring Axle Warranty

TRAILER WARRANTY: Three (3) Year Frame

One (1) Year Parts Warranty

**NECK**  
**BOSS**  
ENGINEERED  
I-BEAM



## FLATDECK HOT SHOT TRAILER HORIZON SUPER SINGLE

### PINTLE HITCH

LENGTHS:	20' - 44'
DECK WIDTH:	102"
DECK HEIGHT:	34"
AXLE COUNT:	2
AXLE RATING:	10k, 12k SUPER SINGLES
GVWR:	25,000 - 25,900 lbs

20'-44'

LENGTHS

25K-25.9K

GVWR RANGE OPTIONS

12"

I-BEAM FRAME

NOTE: Image shown may include optional features not standard to the model.

EVERY. DETAIL. MATTERS.

## TONGUE:

### TONGUE:

TYPE:	Neckboss 12" Engineered I-Beam
LENGTH:	83"
SPARE:	Weld On Spare Tire Mount
WINCH PLATE:	Winch Plate Behind Neck

### COUPLER:

STANDARD COUPLER:	Pintle Ring (42,000 lbs)
-------------------	--------------------------

### JACKS:

FRONT JACK:	2 Side Wind Spring Loaded Drop Jack Legs (12,000 lbs)
-------------	---

### TOOLBOX:

TOOLBOX:	Diamond Mesh Wire Floor Storage
----------	---------------------------------

### SAFETY:

SAFETY CHAINS:	3/8" Grade 70 Safety Chain w/Clevis Hook (2 each)
----------------	---

## CHASSIS:

### FRAME:

25K- 25.9K GVWR MAIN FRAME:	12" I-Beam (19 lbs/ft)
TORQUE TUBE 30' & UP ONLY:	4,1/2" Tube

## DECK:

### BED:

REAR OF DECK:	Straight Deck
DECK FRAME:	2" x 6" x 11ga. Tubing Bed Frame
FLOORING:	Pine Lumber Floor
CROSSMEMBERS:	3" Channel (3.50 lbs/ft) 16" Spacing
DECK HEIGHT:	34"
DECK WIDTH:	102"

### SIDES:

RUB RAIL:	2" x 3/8" Rub Rail
STAKE POCKETS:	1,5/8" x 3,5/8" (ID) Stake Pockets (Spaced At 24")
SPOOLS:	2" x 10ga. Pipe Spools (Spaced At 24")
SIDES:	Slide In Side Step On Both Sides

### REAR:

RAMPS:	Ramp Pockets w/ 8' Long Heavy Duty Slide In 4" Channel Ramps (5,000 LBS WHEEL RATING EACH ONLY OVER AREA OF 12" OR MORE)
--------	--

## RUNNING GEAR:

### TIRES:

10K - 12K AXLES:	ST235/75R17.5, Super Single 18PR 6005 lbs
RIMS:	17.5" Black Mod Wheels

### AXLES:

10K AXLE TYPE:	10k Lippert Electric Brake Auto Adjust S/Single Oil Bath Spring Axles 8 On 6.5"
12K AXLE TYPE:	12k Lippert Electric Brake Auto Adjust S/Single Oil Bath Spring Axles 8 On 6.5"
AXLE COUNT:	2 Axles
AXLE WARRANTY:	6 Year Lippert Spring Axle Warranty

### SUSPENSION:

10K - 12K AXLE SUSPENSION TYPE:	Universal Slipper Spring Hangers
---------------------------------	----------------------------------

## ELECTRICAL AND LIGHTING:

### BATTERY AND CHARGING:

BREAKAWAY SYSTEM:	2382 Brightway Group Electric Breakaway Kit
WIRING HARNESS:	All-Weather Wiring Harness (7-Way RV)
FRAME WIRING:	Double Insulated Wiring Harness

### LIGHTING:

LIGHTS:	DOT Approved Tecniq LED Lights
---------	--------------------------------

### SAFETY:


REFLECTIVE TAPE:	3M Dot Compliant Reflective Tape
------------------	----------------------------------

## COLORS:

ACTUAL COLOR MAY VARY, CHECK SPECIFIC MODEL PAGE FOR AVAILABLE COLORS



SCAN ME



EVERY. DETAIL. MATTERS.