

The FFH Gooseneck Full Tilt Flatdeck Trailer delivers maximum heavy-duty performance with a full tilt deck (14°–19°) and 20,000 lbs lifting capacity. Designed for heavy-duty applications, it features a 12" I-beam frame, 2" x 6" x 7ga. tubing bed, and comes in 24′–40' lengths with a 38" deck height. Equipped with tandem 10k–16k axles, a KTI hydraulic system, and wireless remote, it's built for serious hauling power.

STANDARD FEATURES

TRAILER SPECS:		
DIMENSIONS:		
AVAILABLE LENGTHS:	24', 26', 28', 30', 32', 34', 36', 38', 40'	
DECK WIDTH:	102"	
DECK HEIGHT:	38"	
WEIGHT RATING:		
AXLE COUNT:	2	
GAWR:	10,000 lbs, 12,000 lbs, 16,000 lbs	
GVWR:	25,000 lbs, 25,900 lbs, 30,000 lbs	
FINISH:		
PAINT TYPE:	Powdercoat	
PREP:	Steel Grit Blasted	
COLORS:	Military Green, Desert Tan, Flame Orange,	
	Midnight Black, Spectra Yellow, Blue Horizon,	
	Lime Green, Ash Grey, True Red, Pearl White,	
	Cloud Grey, Navy Blue, Sunset Orange	
WARRANTY:		
AXLE WARRANTY:	6 Year Lippert Spring Axle Warranty	
TRAILER WARRANTY:	Three (3) Year Frame	
	One (1) Year Parts Warrantv	





SLIDE IN SIDE STEP ON BOTH SIDES



Neckboss 12" Engineered I-Beam
98" (From Behind Riser)
70" (From Underneath Neck)
Weld On Spare Tire Mount
K: Storage Box
Adjustable 2-5/16" Gn Coupler (30,000 lbs)
2 Side Wind Spring Loaded Drop Jack Legs (12,000 lbs)
Mega Lockable Toolbox
3/8" Grade 70 Safety Chain w/Clevis Hook (2 each)
FRAME: 12" I-Beam (19 lbs/ft)
E: 12" I-Beam (22 lbs/ft)
E: 12" I-Beam (22 lbs/ft)
Lockable Toolbox (Houses Batteries And Pump)
Lockable Toolbox (Houses Batteries And Pump)
Lockable Toolbox (Houses Batteries And Pump)
Lockable Toolbox (Houses Batteries And Pump) K:
Lockable Toolbox (Houses Batteries And Pump) 2" x 6" x 7ga. Tubing Bed Frame
Lockable Toolbox (Houses Batteries And Pump) 2" x 6" x 7ga. Tubing Bed Frame Pine Lumber Floor
Lockable Toolbox (Houses Batteries And Pump) 2" x 6" x 7ga. Tubing Bed Frame Pine Lumber Floor 3" Channel (3.50 lbs/ft) 16" Spacing 38" 102"
Lockable Toolbox (Houses Batteries And Pump) C: 2" x 6" x 7ga. Tubing Bed Frame Pine Lumber Floor 3" Channel (3.50 lbs/ft) 16" Spacing 38"
Lockable Toolbox (Houses Batteries And Pump) 2" x 6" x 7ga. Tubing Bed Frame Pine Lumber Floor 3" Channel (3.50 lbs/ft) 16" Spacing 38" 102" ONLY: 4,1/2" Tube Winch Plate On Deck
Lockable Toolbox (Houses Batteries And Pump) 2" x 6" x 7ga. Tubing Bed Frame Pine Lumber Floor 3" Channel (3.50 lbs/ft) 16" Spacing 38" 102" O NLY: 4,1/2" Tube
Lockable Toolbox (Houses Batteries And Pump) 2" x 6" x 7ga. Tubing Bed Frame Pine Lumber Floor 3" Channel (3.50 lbs/ft) 16" Spacing 38" 102" ONLY: 4,1/2" Tube Winch Plate On Deck
Lockable Toolbox (Houses Batteries And Pump) 2" x 6" x 7ga. Tubing Bed Frame Pine Lumber Floor 3" Channel (3.50 lbs/ft) 16" Spacing 38" 102" ONLY: 4,1/2" Tube Winch Plate On Deck 14° - 19° (Degrees Vary, Depending On Deck Length) 2" x 3/8" Rub Rail
Lockable Toolbox (Houses Batteries And Pump) 2" x 6" x 7ga. Tubing Bed Frame Pine Lumber Floor 3" Channel (3.50 lbs/ft) 16" Spacing 38" 102" ONLY: 4,1/2" Tube Winch Plate On Deck 14° - 19° (Degrees Vary, Depending On Deck Length) 2" x 3/8" Rub Rail 1,5/8" x 3,5/8" (ID) Stake Pockets (Spaced At 24")
Lockable Toolbox (Houses Batteries And Pump) 2" x 6" x 7ga. Tubing Bed Frame Pine Lumber Floor 3" Channel (3.50 lbs/ft) 16" Spacing 38" 102" ONLY: 4,1/2" Tube Winch Plate On Deck 14° - 19° (Degrees Vary, Depending On Deck Length) 2" x 3/8" Rub Rail

LIFT SYSTEM:	
HYDRAULICS:	
	2 Button Hydraulic - Power Up / Power Down
SYSTEM:	
PUMP:	KTI 12V Hydraulic Pump 14' Control Cable
CONTROLLER:	
	LLER: Tuff Wireless 2 Button Wireless Remote
DECK LIFT:	11-i-t/CII27II CirI Durch Coding-law (20,000 lb)
24'-38' DECK LIFT:	Hoist w/ 6" x 21" Single Push Cylinder (20,000 lbs)
40' DECK LIFT:	Hoist w/ 6" x 30" Single Push Cylinder (20,000 lbs)
LIFT CAPACITY:	20,000 lbs When Weight Distributed Across Length Of De
RUNNING GE	AR:
TIRES:	
10K - 12K AXLES:	ST235/80R16, Dual 10PR 3,080 lbs
RIMS:	16" Black Mod Wheels
16K AXLES:	ST235/75R17.5, Dual 18PR 5,675 lbs
RIMS:	17.5" Black Mod Wheels
AXLES:	
10K AXLE TYPE:	10k Lippert Electric Brake Auto Adjust Dual Oil Bath
	Spring Axles 8 On 6.5"
12K AXLE TYPE:	12k Lippert Electric Brake Auto Adjust Dual Oil Bath
	Spring Axles 8 On 6.5"
16K AXLE TYPE:	16k Lippert Electric Brake Auto Adjust Dual Oil Bath
	Spring Axles 8 On 10.83"
AXLE COUNT:	2 Axles
AXLE WARRANTY:	6 Year Lippert Spring Axle Warranty
SUSPENSION:	
10K - 12K AXLE SUSP	ENSION TYPE: Universal Slipper Spring Hangers
16K AXLE SUSPENSION	ON TYPE: Heavy Duty Double Slipper Mechanical Suspension
ELECTRICAL	AND LIGHTING:
BATTERY AND CHA	ARGING:
BATTERY:	2 - Interstate 27 Deep Cycle Batteries
WIRING HARNESS:	All-Weather Wiring Harness (7-Way RV)
FRAME WIRING:	Double Insulated Wiring Harness
LIGHTING:	
LIGHTS:	DOT Approved Tecniq LED Lights
SAFETY:	· · · · · ·
REFLECTIVE TAPE:	3M Dot Compliant Reflective Tape
	• •



COLORS:

COLORS

PAGE FOR AVAILABLE

ACTUAL COLOR MAY VARY, CHECK SPECIFIC MODEL

MILITARY GREEN

DESERT TAN

FLAME ORANGE

MIDNIGHT BLACK

SPECTRA YELLOW

BLUE HORIZON

> LIME GREEN

ASH GREY

TRUE RED

PEARL WHITE

CLOUD GREY

NAVY BLUE

NEW

SUNSET ORANGE