


The FFT Bumper Pull Flatdeck Full Tilt Trailer Horizon is a reliable and versatile solution for transporting heavy equipment, combining strength and functionality. Built on a rugged 12" I-Beam frame with tandem Lippert axles (7K–10K) and GVWR ratings up to 21,000 lbs, it's designed for consistent performance under demanding conditions. A hydraulic tilt system with a wireless remote makes loading and unloading more efficient, while standard features like a powder-coated finish, LED lighting, deep cycle batteries, and a diamond mesh toolbox contribute to its lasting durability. The FFT is built for dependable, everyday use in a variety of work environments.

STANDARD FEATURES

TRAILER SPECS:		
DIMENSIONS:		
AVAILABLE LENGTHS:	22', 24', 26', 28'	
DECK WIDTH:	102"	
DECK HEIGHT:	36"	
WEIGHT RATING:		
AXLE COUNT:	2	
GAWR:	7,000 lbs, 8,000 lbs, 10,000 lbs	
GVWR:	15,200 lbs, 17,000 lbs, 21,000 lbs	
FINISH:		
PAINT TYPE:	Powdercoat	
PREP:	Steel Grit Blasted	
COLORS:	Military Green, Desert Tan, Flame Orange,	
	Midnight Black, Spectra Yellow, Blue Horizon,	
	Lime Green, Ash Grey, True Red, Pearl White,	
	Cloud Grey, Navy Blue, Sunset Orange	
WARRANTY:		
AXLE WARRANTY:	6 Year Lippert Spring Axle Warranty	
TRAILER WARRANTY:	Three (3) Year Frame/One (1) Year Parts Warranty	



SLIDE IN SIDE STEP ON BOTH SIDES







TONCLIE

TONGUE:	
TONGUE:	
15.2K - 17K GVWR TOI	NGUE: Neckboss 10" Engineered I-Beam
21K GVWR TONGUE:	Neckboss 12" Engineered I-Beam
LENGTH:	83"
SPARE:	Weld On Spare Tire Mount
COUPLER:	
15.2K - 17K GVWR	
STANDARD COUPLE	R: Adjustable Auto Latch 2-5/16" Bp Coupler (17,000 lbs)
21K GVWR STANDAR	RD.
COUPLER:	Adjustable Auto Latch 2-5/16" Bp Coupler (21,000 lbs)
JACKS:	
FRONT JACK:	2 Side Wind Spring Loaded Drop Jack Legs (12,000 lbs
TOOLBOX:	
TOOLBOX:	Diamond Mesh Wire Floor Storage
SAFETY:	
SAFETY CHAINS:	3/8" Grade 70 Safety Chain w/Clevis Hook (2 each)
CHASSIS:	
FRAME:	
15.2K GVWR MAIN FF	RAME: 12" I-Beam (14 lbs/ft)
17K GVWR MAIN FRA	AME: 12" I-Beam (16 lbs/ft)
21K GVWR MAIN FRA	AME: 12" I-Beam (19 lbs/ft)
FULL TILT DE	CK:
BED:	
DECK FRAME:	2" x 5" x 11ga. Tubing Bed Frame
FLOORING:	Pine Lumber Floor
CROSSMEMBERS:	3" Channel (3.50 lbs/ft) 16" Spacing
DECK HEIGHT:	36"
DECK WIDTH:	102"
WINCH PLATE:	Winch Plate On Deck
TILT:	18°
SIDES:	
RUB RAIL:	2" x 3/8" Rub Rail
STAKE POCKETS:	1,5/8" x 3,5/8" (ID) Stake Pockets (Spaced At 24")
SPOOLS:	2" x 10ga. Pipe Spools (Spaced At 24")
SIDES:	Slide In Side Step On Both Sides

LIFT SYSTEM:	
HYDRAULICS:	
SYSTEM:	2 Button Hydraulic - Power Up / Power Down
PUMP:	KTI 12V Hydraulic Pump
CONTROLLER:	14' Control Cable
WIRELESS CONTROI	LER: Tuff Wireless 2 Button Wireless Remote
DECK LIFT:	
LIFT CYLINDER:	Hoist w/6" x 21" Single Push Cylinder (20,000 lbs)
LIFT CAPACITY:	20,000 lbs When Weight Distributed Across Length Of De
RUNNING GEA	AR:
TIRES:	
7K AXLES:	Radial Tires ST235/80R16 10PR 3,520 lbs
8K AXLES:	Radial Tires ST235/85R16 14PR 4,400 lbs
RIMS:	16" Black Mod Wheels
10K AXLES:	ST235/75R17.5, Super Single 18PR 6005 lbs
RIMS:	17.5" Black Mod Wheels
AXLES:	
7K AXLE TYPE:	7k Lippert Electric Brake Auto Adjust EZ Lube Spring
	Axles 8 On 6.5"
8K AXLE TYPE:	8k Lippert Electric Brake Auto Adjust Oil Bath Spring
	Axles 8 On 6.5"
10K AXLE TYPE:	10k Lippert Electric Brake Auto Adjust Oil Bath Spring
	Axles 8 On 6.5"
AXLE COUNT:	2 Axles
AXLE WARRANTY:	6 Year Lippert Spring Axle Warranty
SUSPENSION:	
SUSPENSION TYPE:	Spring
ELECTRICAL /	AND LIGHTING:
BATTERY AND CHA	RGING:
BATTERY:	2 - Interstate 27 Deep Cycle Batteries
WIRING HARNESS:	All-Weather Wiring Harness (7-Way RV)
FRAME WIRING:	Double Insulated Wiring Harness
LIGHTING:	
LIGHTS:	DOT Approved Tecniq LED Lights
SAFETY:	
REFLECTIVE TAPE:	3M Dot Compliant Reflective Tape



COLORS:

COLORS

PAGE FOR AVAILABLE

ACTUAL COLOR MAY VARY, CHECK SPECIFIC MODEL

MILITARY GREEN

DESERT TAN

FLAME ORANGE

MIDNIGHT BLACK

SPECTRA YELLOW

BLUE HORIZON

> LIME GREEN

> > ASH GREY

TRUE RED

PEARL WHITE

CLOUD GREY

NAVY BLUE

SUNSET ORANGE