

Preferential Attachment (BA Model)

Social Networks Analysis and Graph Algorithms

Prof. Carlos “ChaTo” Castillo — <https://chato.cl/teach>



**Universitat
Pompeu Fabra**
Barcelona



Contents

- The BA or preferential attachment model
- Degree distribution under the BA model
- Distance distribution under the BA model
- Clustering coefficient under the BA model

Sources

- A. L. Barabási (2016). Network Science – Chapter 05
- R. Srinivasan (2013). Complex Networks – Chapter 12
- D. Easley and J. Kleinberg (2010): Networks, Crowds, and Markets – Chapter 18
- Data-Driven Social Analytics course by Vicenç Gómez and Andreas Kaltenbrunner

The number of nodes N increases: we need models of network growth



Growth of an Open Source Project: Python



<https://www.youtube.com/watch?v=cNBtDstOTmA>


We have seen *what* but not *how*, or *why*

- Power-law degree distributions are prevalent
- We will give a possible answer to *how*
- For now, we will not answer *why*

Preferential Attachment


Growth

- Suppose there are two web pages on a topic, one with many inlinks the other with few, **which one am I most likely to link to?**
- Which **scientific papers are read?**
- Which **book authors sell more?**
- Which **actors are more sought after?**



Our motto: *Ut uberiores divites.*

Preferential attachment simulation



<https://www.youtube.com/watch?v=4GDqJVtPEGg>



Exercise

Slope of degree distribution

Go to netlogoweb.org/launch and select:
“Sample Models / Networks / Preferential Attachment”

- Execute in Netlogo Web the “Preferential Attachment” program:

- Click “setup”
- Click “go”
- Let it run to ~500 nodes



- Guess the slope of the degree distribution in log-log scale

Pin board: <https://upfbarcelona.padlet.org/chato/y8kw9jcjllu02p8c>




The Barabási-Albert (BA) model

- Network starts with m_0 nodes connected arbitrarily as long as their degree is ≥ 1
- At every time step we add 1 node
- This node will have $m \leq m_0$ outlinks
- The probability of an existing node of degree k_i to gain one such link is


In an ER network, $\Pi(k_i) = \frac{1}{N-1}$

$$\Pi(k_i) = \frac{k_i}{\sum_{j=1}^{N-1} k_j}$$

Example ($m_0 = 2; m=2$)



Network growth with $m=2$



<https://www.youtube.com/watch?v=wocaGeNKn7Y>

The Barabási-Albert (BA) model

- Network starts with m_0 nodes connected arbitrarily as long as their degree is ≥ 1
- At every time step we add 1 node
- This node will have m outlinks ($m \leq m_0$)
- The probability of an existing node of degree k_i to gain one such link is

$$\Pi(k_i) = \frac{k_i}{\sum_{j=1}^{N-1} k_j}$$

Write the formula for $N(t)$ and $L(t)$: at $t=0$ the network has m_0 nodes and $L(0)$ links

Summary

Things to remember

- Preferential attachment
- How to create a BA network step by step


Practice on your own

- Describe step by step in pseudocode how to create a Barabási-Albert graph with N nodes having m_0 starting nodes and m outlinks per node.
- For your pseudocode to be valid, if at any point there is a randomized step, you must indicate **what is the probability of each possible outcome**

Additional contents

EXTRA

Video of degree distribution



<https://www.youtube.com/watch?v=5RIQweqPT6A>