




9 8 7 6 ◇ 4 3 2 |

# BILL OF MATERIAL

Item No.	Part No.	Description	Quantity
1	M101030-007	CLIP, LEVER FULCRUM	1
2	M108914-000	FULCRUM, LEVER	1
3	M108916-000	GUSSET, LEVER FULCRUM	1



Level	Date	Approved	Description
<b>REVISIONS</b>			
<b>FreightCar America</b>			

THIS DRAWING IS THE EXCLUSIVE PROPERTY OF FREIGHTCAR AMERICA AND CONTAINS CONFIDENTIAL AND PROPRIETARY INFORMATION. BY ACCEPTING THIS DRAWING, THE RECIPIENT AGREES (A) TO USE THIS DRAWING ONLY FOR THOSE PURPOSES APPROVED IN WRITING BY FREIGHTCAR AMERICA, (B) NOT TO REPRODUCE OR MODIFY THIS DRAWING, IN WHOLE OR IN PART, AND (C) NOT TO DISCLOSE THIS DRAWING TO ANY PERSON OR ENTITY, NOR USE THE DRAWING FOR THE DESIGN OR MANUFACTURE OF ANY ITEM, PART, OBJECT OR APPARATUS THEREOF, EXCEPT UPON THE PRIOR WRITTEN PERMISSION OF FREIGHTCAR AMERICA.

Standard Tolerances (Unless Noted)			
Decimal Dimensions $\pm 0.063$	Hole Diameters $\pm 0.031$		
Diagonals 0.125 Max. Variation	Angles $\pm 1^\circ$		
Radii will be thickness of material	Tolerances are not accumulative		
Made By: MHK/JML	Date: 09-20-12	Ref Dwg:	-
Approved: CSW	Do Not Scale Drawing	Est. Wt:	24.72 lbs

Size	Drawing / Part Number	Rev.
B	A108915-000	-

**SC** HOLES MUST BE ALIGNED

**SC** SPECIAL CHARACTERISTIC - FEATURE THAT IS "KEY" TO FORM, FIT, AND FUNCTION OF THE PART/ASS'Y

**NOTE:**

- ALL WELDING TO BE IN ACCORDANCE WITH RAILROAD WELDING SPECIFICATION AWS D15.1, LATEST REVISION, AND TO BE CLASS 2 UNLESS OTHERWISE SPECIFIED.
- UNLESS OTHERWISE NOTED, ALL WELD LENGTHS SHOWN ARE MINIMUM LENGTHS, WELD TERMINATIONS FOR FILLET WELDS MUST HAVE A MINIMUM EDGE DISTANCE OF 0.25.