yalo

AI Friday

How to build your own Replit Dashboard

on Yalo via Claude Code!

ENG. GERARDO COLLANTE [CBA, ARG]

The Problem

The Problem

Manual access

Ping Mario on #ask-mario every time someone needs Replit access

The Problem

Manual access

Ping Mario on #ask-mario every time someone needs Replit access

No onboarding

No guide, no tutorial — people don't know where to start

The Problem

Manual access

Ping Mario on #ask-mario every time someone needs Replit access

No onboarding

No guide, no tutorial — people don't know where to start

Lost developers

The Problem

Manual access

Ping Mario on #ask-mario every time someone needs Replit access

No onboarding

No guide, no tutorial — people don't know where to start

Lost developers

Low adoption

💡 The Idea

What if an agent could do the whole thing for you?

💡 The Idea

What if an agent could do the whole thing for you?

`/yalo-replit:wizard`

💡 The Idea

What if an agent could do the whole thing for you?

```
/yalo-replit:wizard
```

One command. Access check → project setup → deploy → live URL.

What We Built

ONBOARDING

/yalo-replit:wizard

7-phase flow from access check to live deployment. Handles GitHub, Replit config, and guides the user through every step.

DEPLOY

/yalo-replit:deploy

Triggered by "ready" or "deploy". Commits, pushes, tells you to click Redeploy. One command to go live.

What We Built

ONBOARDING

/yalo-replit:wizard

7-phase flow from access check to live deployment. Handles GitHub, Replit config, and guides the user through every step.

DEPLOY

/yalo-replit:deploy

Triggered by "ready" or "deploy". Commits, pushes, tells you to click Redeploy. One command to go live.

Stack: SKILL.md — natively supports dropdowns, Slack MCP, Bash. No Python runtime needed.

The 7 Phases

The 7 Phases

1. Access check → Slack to Mario if needed — AUTO

The 7 Phases

1. Access check → Slack to Mario if needed — AUTO
2. Project setup — template or from scratch — AUTO

The 7 Phases

1. Access check → Slack to Mario if needed — AUTO
2. Project setup — template or from scratch — AUTO
3. Iterate until you're happy — AUTO

The 7 Phases

1. Access check → Slack to Mario if needed — AUTO
2. Project setup — template or from scratch — AUTO
3. Iterate until you're happy — AUTO

PATH A: WITH GITHUB

The 7 Phases

1. Access check → Slack to Mario if needed — AUTO
2. Project setup — template or from scratch — AUTO
3. Iterate until you're happy — AUTO

PATH A: WITH GITHUB

4. Create GitHub Repo

The 7 Phases

1. Access check → Slack to Mario if needed — AUTO
2. Project setup — template or from scratch — AUTO
3. Iterate until you're happy — AUTO

PATH A: WITH GITHUB

4. Create GitHub Repo
5. Inject config (.replit + nix)

The 7 Phases

1. Access check → Slack to Mario if needed — AUTO
2. Project setup — template or from scratch — AUTO
3. Iterate until you're happy — AUTO

PATH A: WITH GITHUB

4. Create GitHub Repo
5. Inject config (.replit + nix)
6. Import to Replit — MANUAL

The 7 Phases

1. Access check → Slack to Mario if needed — AUTO
2. Project setup — template or from scratch — AUTO
3. Iterate until you're happy — AUTO

PATH A: WITH GITHUB

4. Create GitHub Repo
5. Inject config (.replit + nix)
6. Import to Replit — MANUAL

PATH B: WITHOUT GITHUB

The 7 Phases

1. Access check → Slack to Mario if needed — AUTO
2. Project setup — template or from scratch — AUTO
3. Iterate until you're happy — AUTO

PATH A: WITH GITHUB

4. Create GitHub Repo
5. Inject config (.replit + nix)
6. Import to Replit — MANUAL

PATH B: WITHOUT GITHUB

4. Generate local ZIP

The 7 Phases

1. Access check → Slack to Mario if needed — AUTO
2. Project setup — template or from scratch — AUTO
3. Iterate until you're happy — AUTO

PATH A: WITH GITHUB

4. Create GitHub Repo
5. Inject config (.replit + nix)
6. Import to Replit — MANUAL

PATH B: WITHOUT GITHUB

4. Generate local ZIP
5. Inject config (.replit + nix)

The 7 Phases

1. Access check → Slack to Mario if needed — AUTO
2. Project setup — template or from scratch — AUTO
3. Iterate until you're happy — AUTO

PATH A: WITH GITHUB

4. Create GitHub Repo
5. Inject config (.replit + nix)
6. Import to Replit — MANUAL

PATH B: WITHOUT GITHUB

4. Generate local ZIP
5. Inject config (.replit + nix)
6. Upload at replit.com — MANUAL

The 7 Phases

1. Access check → Slack to Mario if needed — AUTO
2. Project setup — template or from scratch — AUTO
3. Iterate until you're happy — AUTO

PATH A: WITH GITHUB

4. Create GitHub Repo
5. Inject config (.replit + nix)
6. Import to Replit — MANUAL

PATH B: WITHOUT GITHUB

4. Generate local ZIP
5. Inject config (.replit + nix)
6. Upload at replit.com — MANUAL

7. **CLICK DEPLOY!**

Build Together

The wizard doesn't just set up a pipeline. It helps you build your app.

Build Together

The wizard doesn't just set up a pipeline. It helps you build your app.

Dashboard

Charts, metrics, filters

Build Together

The wizard doesn't just set up a pipeline. It helps you build your app.

Dashboard

Charts, metrics, filters

AI Tool

LLM-powered apps

Build Together

The wizard doesn't just set up a pipeline. It helps you build your app.

Dashboard

Charts, metrics, filters

AI Tool

LLM-powered apps

Internal Tool

Forms & workflows

Build Together

The wizard doesn't just set up a pipeline. It helps you build your app.

Dashboard

Charts, metrics, filters

AI Tool

LLM-powered apps

Internal Tool

Forms & workflows

Your Idea

Anything you want

Build Together

The wizard doesn't just set up a pipeline. It helps you build your app.

Dashboard

Charts, metrics, filters

AI Tool

LLM-powered apps

Internal Tool

Forms & workflows

Your Idea

Anything you want

Iteration Loop: `write code → preview → tweak → repeat → "looks great"`

Data via Looker MCP

Your dashboard needs data — but Replit is a public runtime. Credentials can't live there.

Data via Looker MCP

Your dashboard needs data — but Replit is a public runtime. Credentials can't live there.

🚫

Direct BigQuery — NO

Service account keys in a Repl. Raw SQL without governance. Every dashboard re-inventing joins.

Data via Looker MCP

Your dashboard needs data — but Replit is a public runtime. Credentials can't live there.

Direct BigQuery — NO

Service account keys in a Repl. Raw SQL without governance. Every dashboard re-inventing joins.

Looker MCP — YES

Governed semantic layer. Auth handled once. The `looker-analytics` skill queries Explores for you.

Data via Looker MCP

Your dashboard needs data — but Replit is a public runtime. Credentials can't live there.

Direct BigQuery — NO

Service account keys in a Repl. Raw SQL without governance. Every dashboard re-inventing joins.

Looker MCP — YES

Governed semantic layer. Auth handled once. The `looker-analytics` skill queries Explores for you.

Phase 2c of the wizard walks you through this — the setup guide is in Notion.

Looker MCP Setup

One-time setup — the wizard runs you through all of this in Phase 2c.

Looker MCP Setup

One-time setup — the wizard runs you through all of this in Phase 2c.

1

Download the MCP bundle

`looker-mcp-connector.mcpb` — drag into Claude Code to install the connector

Looker MCP Setup

One-time setup — the wizard runs you through all of this in Phase 2c.

1

Download the MCP bundle

`looker-mcp-connector.mcpb` — drag into Claude Code to install the connector

2

Install the governance skill

`looker-analytics-0.5.2.skill` — teaches Claude how to query Looker properly

Looker MCP Setup

One-time setup — the wizard runs you through all of this in Phase 2c.

1

Download the MCP bundle

`looker-mcp-connector.mcpb` — drag into Claude Code to install the connector

2

Install the governance skill

`looker-analytics-0.5.2.skill` — teaches Claude how to query Looker properly

3

Get Looker API credentials

Client ID + Secret — request in `#ask-mario` if you don't have them yet

Looker MCP Setup

One-time setup — the wizard runs you through all of this in Phase 2c.

1

Download the MCP bundle

`looker-mcp-connector.mcpb` — drag into Claude Code to install the connector

2

Install the governance skill

`looker-analytics-0.5.2.skill` — teaches Claude how to query Looker properly

3

Get Looker API credentials

Client ID + Secret — request in `#ask-mario` if you don't have them yet

Two Paths to Replit

Two Paths to Replit

With GitHub

→ Agent creates repo, pushes code

→ User imports repo in Replit

→ `git push` → Redeploy for updates

BEST FOR ONGOING PROJECTS

Two Paths to Replit

With GitHub

- → Agent creates repo, pushes code
- → User imports repo in Replit
- → `git push` → Redeploy for updates

BEST FOR ONGOING PROJECTS

Without GitHub

- → Agent creates ZIP file locally
- → User uploads at replit.com/import
- → Drag & drop for updates

BEST FOR QUICK ONE-OFFS

🎬 Live Demo

Time to start the Live Demo.

```
❯/yalo-replit:wizard
```

ACCESS CHECK → TEMPLATE → DASHBOARD → ITERATE → PUBLISH

The Deploy Cycle

After the one-time initial setup, the daily flow is incredibly simple:

The Deploy Cycle

After the one-time initial setup, the daily flow is incredibly simple:

Edit `app.py` → say "ready" → agent pushes → click **Redeploy** → **Live**

The Deploy Cycle

After the one-time initial setup, the daily flow is incredibly simple:

Edit `app.py` → say "ready" → agent pushes → click **Redeploy** → **Live**

5

PHASES AUTOMATED

The Deploy Cycle

After the one-time initial setup, the daily flow is incredibly simple:

Edit `app.py` → say "ready" → agent pushes → click **Redeploy** → **Live**

5

PHASES AUTOMATED

2

BROWSER STEPS

The Deploy Cycle

After the one-time initial setup, the daily flow is incredibly simple:

Edit `app.py` → say "ready" → agent pushes → click **Redeploy** → **Live**

5	2	1
PHASES AUTOMATED	BROWSER STEPS	CLICK PER DEPLOY

How to Install

How to Install

One-time setup

```
# Inside Claude Code

/plugin marketplace add GerardoYalo/replit-yalo-wizard
/plugin                  ← select and enable yalo-replit
/reload-plugins
```

How to Install

One-time setup

```
# Inside Claude Code

/plugin marketplace add GerardoYalo/replit-yalo-wizard
/plugin                  ← select and enable yalo-replit
/reload-plugins
```

Usage

```
# Start building something

/yalo-replit:wizard
```

How to Install

One-time setup

```
# Inside Claude Code

/plugin marketplace add GerardoYalo/replit-yalo-wizard
/plugin                  ← select and enable yalo-replit
/reload-plugins
```

Usage

```
# Start building something

/yalo-replit:wizard
```

Key Takeaways

Key Takeaways

1. **SKILL.md > Agent SDK** for wizard-style sequential flows in Claude Code

Key Takeaways

1. **SKILL.md > Agent SDK** for wizard-style sequential flows in Claude Code

2. **Plugins are easy to distribute** — marketplace + 2 install commands

Key Takeaways

1. **SKILL.md > Agent SDK** for wizard-style sequential flows in Claude Code
2. **Plugins are easy to distribute** — marketplace + 2 install commands
3. **The wizard should own the flow** — do the active work, don't just instruct

Key Takeaways

1. **SKILL.md > Agent SDK** for wizard-style sequential flows in Claude Code
2. **Plugins are easy to distribute** — marketplace + 2 install commands
3. **The wizard should own the flow** — do the active work, don't just instruct
4. **Governed data via MCP** — no credentials on Replit, no raw SQL

Key Takeaways

1. **SKILL.md > Agent SDK** for wizard-style sequential flows in Claude Code
2. **Plugins are easy to distribute** — marketplace + 2 install commands
3. **The wizard should own the flow** — do the active work, don't just instruct
4. **Governed data via MCP** — no credentials on Replit, no raw SQL

Questions? 🤔