
Optimization of Optical Dosimetry in a Water Phantom by Exploiting Cherenkov Radiation Polarization Imaging

G  r  my Michaud^{1,2},   mily Cloutier^{1,2}, Anastasiia Pusenkova⁴, Tigran Galstian^{3,4},
Louis Archambault^{1,2} et Luc Beaulieu^{1,2}

¹D  partement de physique, g  nie physique et d'optique et Centre de recherche sur le cancer, Universit   Laval, Qu  bec, Canada

²Service de physique m  dicale et de radioprotection, Centre int  gr   de canc  rologie, CHU de Qu  bec-Universit   Laval et Centre de recherche du CHU de Qu  bec, Qu  bec, Qu  bec, Canada

³D  partement de physique, g  nie physique et d'optique et Centre d'optique, photonique et lasers, Universit   Laval, Qu  bec, Canada

⁴Patqer Photonique Inc., Qu  bec, Canada

Introduction: Cherenkov radiation occurs when a charged particle travels through a dielectric medium at a speed greater than that of light [1]. This phenomenon generates polarized light, which can be utilized to detect and quantify radiation dose distributions in medical applications such as radiotherapy [2]. By using Cherenkov light emitted from the irradiated medium, this promising method allows real-time assessment of dose distribution [3]. Building upon previous research by my research group [4, 5], this study aims to validate optical dosimetry methods in a water phantom through polarization of Cherenkov radiation while enhancing their precision.

Methods: The Cherenkov emission signal is captured using a camera equipped with a charge-coupled device (CCD) image sensor during the irradiation of a water tank with dimensions of $15 \times 15 \times 20 \text{ cm}^3$ by photon and electron beams of varying energies, namely 6 MV, 18 MV, 6 MeV, and 18 MeV. Analysis of Cherenkov radiation polarization is performed using a rotating linear polarizer and an innovative polarization modulator developed by PATQER Photonique. This approach allows extraction of the polarized component of the signal, the average polarization angle, and the non-polarized portion of the signal. Radiochromic films and data from a treatment planning system are used for reference.

Results: The measurements yield the normalized dose profile relative to the maximum irradiation dose (d_{max}) and the depth dose profiles (PDD) of the ionizing beam. These results confirm the feasibility and relevance of this approach for accurate real-time assessment of dose distribution in radiotherapy.

Conclusion: Further studies could explore the application of this dosimetric method in clinical scenarios, including evaluating the FLASH effect [2]. Moreover, a hybrid approach, combining the advantages of optical dosimetry with other dose measurement modalities, could be developed for comprehensive and precise dose distribution assessment in radiotherapy. These prospects pave the way for continuous improvement in treatment techniques and better personalization of cancer treatments for patients.

Références

- ¹P. A. ČERENKOV, « Visible Radiation Produced by Electrons Moving in a Medium with Velocities Exceeding that of Light », *Physical Review* **52**, 378-379 (1937).
- ²M. R. ASHRAF, M. RAHMAN, R. ZHANG, B. B. WILLIAMS, D. J. GLADSTONE, B. W. POGUE et P. BRUZA, « Dosimetry for FLASH Radiotherapy : A Review of Tools and the Role of Radioluminescence and Cherenkov Emission », *Frontiers in Physics* **8**, 328 (2020).
- ³L. A. JARVIS, R. ZHANG, D. J. GLADSTONE, S. JIANG, W. HITCHCOCK, O. D. FRIEDMAN, A. K. GLASER, M. JERMYN et B. W. POGUE, « Cherenkov Video Imaging Allows for the First Visualization of Radiation Therapy in Real Time », *International Journal of Radiation Oncology*Biology*Physics* **89**, 615-622 (2014).
- ⁴É. CLOUTIER, L. ARCHAMBAULT et L. BEAULIEU, « Accurate dose measurements using Cherenkov emission polarization imaging », *Medical Physics* **49**, 5417-5422 (2022).
- ⁵É. CLOUTIER, L. BEAULIEU et L. ARCHAMBAULT, « Direct in-water radiation dose measurements using Cherenkov emission corrected signals from polarization imaging for a clinical radiotherapy application », *Scientific Reports* **12**, 9608 (2022).