

6.3 Reflog- git reflog

quarta-feira, 28 de junho de 2023 17:14

- Parecido com o log mostra todas as alterações feitas, desde a criação de branches quanto todas os commits feitos no projeto
- Deve-se usar o comando **git reflog**
- Com isso podemos usar o reflog com o reset para ir para uma modificação específica com o **git reset --hard numerolog**

Usando o git reflog com o git reset --hard

```
PS D:\github_teste\repo_teste2\pasta1> git reflog
5affb97 (HEAD -> main, origin/main, origin/HEAD) HEAD@{0}: checkout: moving from novabranh to mai
7ed6c22 (origin/novabranh, novabranh) HEAD@{1}: commit: Enviando arquivos
e5314a4 HEAD@{2}: merge main: Merge made by the 'ort' strategy.
c78acbb HEAD@{3}: commit: adicionadno arquivo
95300ab HEAD@{4}: checkout: moving from main to novabranh
5affb97 (HEAD -> main, origin/main, origin/HEAD) HEAD@{5}: checkout: moving from BRanch to main
ad00063 (origin/BRanch, BRanch) HEAD@{6}: commit: Criando projeto no submodulo
082e88d HEAD@{7}: checkout: moving from main to BRanch
5affb97 (HEAD -> main, origin/main, origin/HEAD) HEAD@{8}: commit: Criando arquivo no teste
082e88d HEAD@{9}: merge BRanch: Fast-forward
95300ab HEAD@{10}: checkout: moving from BRanch to main
082e88d HEAD@{11}: commit: Enviando
95300ab HEAD@{12}: checkout: moving from novabranh to BRanch
95300ab HEAD@{13}: checkout: moving from main to novabranh
95300ab HEAD@{14}: checkout: moving from novabranh to main
95300ab HEAD@{15}: checkout: moving from main to novabranh
95300ab HEAD@{16}: clone: from https://github.com/Geronimonetto/repo_teste.git
PS D:\github_teste\repo_teste2\pasta1> git reset --hard 95300ab
warning: unable to rmdir 'submodulo': Directory not empty
HEAD is now at 95300ab Criando pasta2
```