

CSC 211: Computer Programming

Header Files and Constructors

Michael Conti

Department of Computer Science and Statistics
University of Rhode Island

Fall 2024



Original design and development by Dr. Marco Alvarez


Header Files

Separate compilation

- Source code can be divided into multiple files
 - ✓ source files can be compiled separately
 - ✓ enterprise code files can take hours to compile
 - Source code separation eliminates the need to compile everything, all the time
- Classes can be implemented in their own files
 - ✓ allows reusing codes in multiple programs
 - ✓ source files including class methods and function definitions
 - ✓ header files including declarations and global constants

3

Compiling multiple files



```
g++ v3.cpp particle.cpp main.cpp -o executable
```

<https://devblogs.nvidia.com/separate-compilation-linking-cuda-device-code/>

4

#include

- Used for including header files
 - ✓ usually contains class declarations, function prototypes, or global constants
- When used with < >
 - ✓ The preprocessor searches in an implementation dependent manner, normally in search directories pre-designated by the compiler/IDE. This method is normally used to include standard library header files
- When used with " "
 - ✓ The preprocessor searches first in the same directory as the file containing the directive, and then follows the search path used for the #include <filename> form. This method is normally used to include programmer-defined header files.
- Cannot compile header files directly!

5

Multiple declarations of classes

- With large projects, multiple declaration of classes must be prevented

- Use #ifndef

```
#ifndef DATE_H  
#define DATE_H
```

```
class Date {  
    // ...  
};
```

```
#endif
```

6

Multiple declarations of classes

- Do header guards need to be capital or use an underscore instead of a dot?
- Preprocessor definitions have to use valid identifiers.
- Dots are not valid in identifiers. There is also a convention that preprocessor definitions (especially preprocessor macros) use all-uppercase names, to distinguish them from non-preprocessor identifiers.
- Not a hard and fast rule, just convention

7

Constructors

Constructors

- Special `methods` used to initialize data members when objects are created
- A constructor ...
 - ✓ ... is a member function (usually **public**)
 - ✓ ... must have the same name as its class
 - ✓ ... is automatically called when an object is created
 - ✓ ... does not have a return type (not even **void**)

constructors cannot be called as other methods

9

Example

```
class Date {  
    private:  
        int month;  
        int year;  
        int day;  
  
    public:  
        Date();  
        // ...  
};
```

No return
value

10

Example: Date

```
#ifndef DATE_H  
#def DATE_H  
class Date {  
    private:  
        int month;  
        int year;  
        int day;  
  
    public:  
        Date();  
        void print();  
};  
#endif
```

```
#include "date.h"  
  
int main() {  
    Date mydate;  
  
    mydate.print();  
}
```

```
#include "date.h"  
#include <iostream>  
  
Date::Date() {  
    month = 1;  
    day = 1;  
    year = 1970;  
}  
  
void Date::print() {  
    std::cout << month << '-' <<  
    day << '-' << year << '\n';  
}
```

g++ date.cpp main.cpp -o exec

11

Overloading constructors

- A constructor with no parameters is also known as the **default constructor**
- Classes may have multiple constructors
 - ✓ constructors are **overloaded** by defining constructors with different parameter lists

```
Date();  
Date(int m, int d, int y);
```

12

Synthesized default constructor

- If you don't define any constructor, C++ will define one default constructor for you
- If you define at least one constructor, C++ will not add any other (not even the default constructor)

13

Initialization lists

- C++ allows for optional initialization lists as part of the constructor definition

```
Date::Date(int _d, int _m, int _y) {  
    day = _d;  
    month = _m;  
    year = _y;  
    // more statements  
}
```

Same as...

```
Date::Date(int _d, int _m, int _y) : day(_d), month(_m), year(_y) {  
    // more statements  
}
```

14

Lets Try it

- Modify Point2D.cpp (on GitHub at ~/code) so it includes the following:
 - ✓ Default Constructor
 - ✓ Parameterized Constructor
- Once working, break it up into:
 - ✓ Class file (Point2D.cpp)
 - ✓ Header/Interface file (Point2D.h)
 - ✓ Driver (main.cpp)

15