


## Problem Set 2 Solution

Jun Wang

[Jwang3316@gatech.edu](mailto:Jwang3316@gatech.edu)

1. Probability: A is 50%, B and C is 25%. So, I set 1 bit for A and set 2 bits for each B and C.  
The entropy of the coding is  $1 \times P(A) + 2 \times (P(B) + P(C)) = 1.5 \text{ bits}$
2. K means can be seen as an EM algorithm that require the Gaussian densities to be spherical for all features, and in the maximization step a mean of data points was used to update the centroid parameter. The centroid location is the only parameter to be estimated, no covariance or slope for any features.
- 3.



4. a.  
I think the most likely method for this dataset is Hierarchical clustering. Because the distances between points in two clusters have a very sparse distribution. Hierarchical clustering can identify the two classes perfectly since there will always be a very close point pair within the two classes.
  - b.  
EM and K means. Because it looks like we only need to estimate two centroid locations for both methods. Given the complexity of Gaussian distribution and posterior probability, I think K means will converge faster than EM. All the hierarchical clustering methods will have problem distinguishing the point that are very close but comes from two classes.
  - c.  
GMM. Because the two clusters are overlapping and only GMM can work well on this.
6.  
Total exploration:  $Q(s, a1)=2.5$   
 $Q(s, a2)=2.25$   
Greedy exploitation:  $Q(s, a1)=2.5$   
 $Q(s, a2)=3$

7.

MDP

Iteration 0:

0	0	0
0	0	0
0	0	G

Iteration 1

0	0	0
0	0	10
0	10	G

Iteration2

0	0	8
0	8	10
8	10	G

Iteration3

0	6.4	8
6.4	8	10
8	10	G