

LAB 2 – BASIC OSPF CONFIGURATION AND VERIFICATION

Part 1: OSPF CONFIGURATION

Install and configure your lab test environment according to the [network drawing](#) and predefined IP-plan. This lab must be executed on hardware.

Scope definition:

- **Part 1a: OSPF using Network statements**

OSPF configuration details;

- Use process ID 10 for OSPF activation on all routers
- Area 0
- Activate OSPF using network statements and inverse masks on the router:
 - Advertise Management, Data-Users subnet via OSPF
- Configure router IDs on the multiaccess network router as follows:
 - Router ID = 10.199.66.* (* = IP 4th octet - see IP-PLAN WAN-Connect-OSPF)
- Disable that LSA updates are send over LAN interfaces

- **Part 1b: OSPF by configuring the interfaces of the router**

OSPF configuration details;

- Use process ID 10 for OSPF activation on all routers
- Area 0
- Activate OSPF by configuring the interfaces of the router:
 - Advertise Management, Data-Users subnet via OSPF
- Configure router IDs on the multiaccess network router as follows:
 - Router ID = 10.199.66.* (* = IP 4th octet - see IP-PLAN WAN-Connect-OSPF)
- Disable that LSA updates are send over LAN interfaces

Part 2: OSPF VERIFICATION

Scope definition:

Verify OSPF;

- Verify with three output commands OSPF operation and neighboring
- Verify the hello and dead timer values on the WAN interfaces that connect to ISP.
- Verify DHCP and routing to internet for the Data-Users subnet