

LAB 3 – CONFIGURATION ACL, NAT AND PAT

Install and configure your lab test environment according to the previous network drawing of lab 2b and predefined IP-plan. This lab must be executed on hardware.

Scope definition:

- **Part 1: Configure extended ACL**

Before starting this task:

- Add an username 'admin' with secure password 'cisco' and privilege 15.

Configure an extended ACL with multiple ACE statements to achieve the following conditions:

- Create an ACE statement to allow SSH-traffic from source IP address **10.199.64.137** to access your management subnet
- Create an ACE statement to allow SSH-traffic from the source management subnet of your colleagues to access your management subnet
- Apply the ACL on the virtual teletype (VTY) and determine the direction

Test your configuration:

- Your colleague should be able to connect to your router and switch when SSH is sourced from his Management-subnet (VLAN 10).
- Your colleague should not be able to connect to your router and switch when SSH is sourced from his User-subnet (VLAN 40).
- Try to connect to your Management devices via SSH via the **LAB-HA-A-PC02** PC in the lab.

- **Part 2: Configure NAT**

- Configure a dynamic NAT for your User-Subnet to hide against the WAN interface of your router

Test your configuration:

- Verify with a show command that your NAT is working

- **Part 3: Configure PAT**

- Configure a PAT for your User-Subnet to hide against the WAN interface of your router

Test your configuration:

- Verify with a show command that your PAT is working