

Vlan 10 – Management
Vlan 20 - VM-Hosts
Vlan 30 - Appliance-Servers
Vlan 40 – Data-Users
Vlan 99 – Native-Vlan

RA0X-L
Vlan 10 – 172.16.x.0/28
Vlan 20 – 172.16.x.16/28
Vlan 30 – 172.16.x.32/28
Vlan 40 – 172.16.x.48/28

Vlan 10 – 172.16.x.128/28
Vlan 20 – 172.16.x.144/28
Vlan 30 – 172.16.x.160/28
Vlan 40 – 172.16.x.176/28

1st client address - HRSP/VRRP default-gateway
2nd client address - LAB-RA0X-C01(02)-R01
3rd client address - LAB-RA0X-C01(02)-R02
4th client address - LAB-RA0X-C01(02)-R03
5th client address - LAB-RA0X-A01(02)-SW01 (mgmt subnet only)
6th client address - LAB-RA0X-A01(02)-SW02 (mgmt subnet only)
7th client address - LAB-RA0X-A01(02)-SW03 (mgmt subnet only)

C01 – core student RA0X-L
A01 – access student RA0X-L
C02 – core student RA0X-R
A02 – access student RA0X-R



LAB 2 - Basic Single OSPF Configuration and Verification

Wim Leppens

Version: V1.0

2SNE

26-11-24