

Formularium MongoDB

```
use test
show dbs
db.dropDatabase()
db.createCollection(Name, options)
show collections
db.collectionName.drop()
db.collectionName.insertOne(); db.collectionName.insertMany()
db.collectionName.updateOne(); db.collectionName.updateMany()
db.collectionName.updateOne( {SELECTION_CRITERIA},
                             {UPDATE_SPECIFICATION})
db.collectionName.deleteOne({}); db.collectionName.deleteMany({})
db.collectionName.deleteOne({SELECTION_CRITERIA})
db.collectionName.findOne(); db.collectionName.find()
db.collectionName.find().sort({key:1})
db.collectionName.find().skip(n)
db.collectionName.find().limit(n)
db.collectionName.find().count()
db.collectionName.countDocuments()
db.collectionName.find({SELECTION_CRITERIA}, {PROJECTION})
```

UPDATE_SPECIFICATION

```
$set:{field1:value1}
$unset:{field1:value1}
$push:{field1:value1}
$push:{field1:{$each:[value1,value2, ...]}}
$pull:{field1:value1}
$addToSet:{field1:{$each:[value1,value2, ...]}}
```

```
switch to DB test; if it does not exist, create DB test
show all databases
drop the current database
create a collection
show all collections in the current database
drop collectionName
add one or multiple documents to a collection
update one or multiple documents in a collection
```

```
delete one or more documents from the collection
delete the first document that matches the criteria
display one or multiple documents
sort in ascending order (1) or descending order (-1) by key
skip a number of documents
limit the output to a number of documents
count the number of items
display the number of documents
```

```
assign a new value to an existing key or create a new key
removes a field
adds value1 to array field1; the array MUST EXIST
adds value1, value2, ... to array field1; the array MUST EXIST
removes value1 from array field1
same as push, but without duplicates
```

SELECTION_CRITERIA:

field: value

field:{\$lt:value}

\$lte

\$gt

\$gte

\$ne

\$in:[value1, value2, ...]

\$nin:[value1, value2, ...]

\$exists

/value/

^ at the beginning

\$ at the end

i

doc_field.subdoc_field: ...

field:[value1,value2]

field:{\$all:[value1,value2]}

field.n: value

\$size

field equals a specific value

field is less than value

less than or equal to

greater than

greater than or equal to

not equal to

equal to value1 or equal to value2, ...

not equal to value1 and not equal to value2, ...

is present

value occurs

must start with

must end with

case-insensitive

restriction on a field of a subdocument

field has exactly these two values

field contains both values, regardless of order or other elements

value is located at position n of the field

number of values in an array