

TypeScript & Dependent Typing

Ruben Pieters

TypeScript



TypeScript

TypeScript
type annotations

JavaScript

TypeScript

Goals:

Static error detection as minimal layer on top of JavaScript

(Disclaimer: my personal summary from

<https://github.com/Microsoft/TypeScript/wiki/TypeScript-Design-Goals>)

TypeScript

Goals:

Static error detection as minimal layer on top of JavaScript

Non-Goals:

Do not alter the way JavaScript code is organized due to addition of type system

(Disclaimer: my personal summary from











<https://github.com/Microsoft/TypeScript/wiki/TypeScript-Design-Goals>)

TypeScript

Type-level features:


- Literal Types
- Union/Intersection Types
- Indexed Access Types (2.1, December 2016)
- Conditional Types (2.8, March 2018)
- ...

TypeScript

Rank	Language	Monthly Active Users	Trend
1	JavaScript	22.63%	
2	Python	14.75%	
3	Java	14.01%	
4	C++	8.45%	
5	C	6.03%	
6	PHP	5.85%	
7	C#	5.03%	
8	Shell	4.85%	
9	Go	4.10%	
10	TypeScript	3.89%	

<http://www.benfrederickson.com/ranking-programming-languages-by-github-users>

TypeScript



<https://insights.stackoverflow.com/survey/2018>

TypeScript

Type-level features:

- Literal Types
- Union/Intersection Types
- Indexed Access Types (2.1, December 2016)
- Conditional Types (2.8, March 2018)
- ...

Illustrate some shortcomings

Improve consistently with TS (non-)goals?

Simple Function

Simple Function

```
function add(  
  x,  
  y,  
) {  
  return x + y  
}
```

Simple Function

```
add("1", 2)
```

Simple Function

```
function add(  
  x: number,  
  y: number,  
): number {  
  return x + y  
}
```

Simple Function

```
add("1", 2)
```

"1" is not a 'number'

Generics

```
function id<A>(
  a: A,
): A {
  return a
}
```

Generics

```
function id<A>(
  a: A,
): A {
  return a
}
```

```
id(1)
// id<number>(a: number): number
```


More Complex

More Complex

```
doAction("parseNumber", string): number
```

```
doAction("toString", number): string
```

More Complex

```
doAction("parseNumber", "2")
```

```
// 2
```

```
doAction("toString", 2)
```

```
// "2"
```

More Complex

```
doAction("parseNumber", "2")
```

```
// 2
```


```
doAction("toString", 2)
```

```
// "2"
```

```
e1.addEventListener("click", yourFunction)
```

```
function doAction(  
  action,  
  input,  
) {  
  switch (action) {  
    case "parseNumber": ...  
    case "toString": ...  
  }  
}
```

```
function doAction(  
  action: "parseNumber" | "toString",  
  input,  
) {  
  switch (action) {  
    case "parseNumber": ...  
    case "toString": ...  
  }  
}
```

```
function doAction(  
  action: "parseNumber" | "toString",  
  input: ,  
) {  
  switch (action) {  
    case "parseNumber": ...  
    case "toString": ...  
  }  
}
```


```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input,
) {
  switch (action) {
    case "parseNumber": ...
    case "toString": ...
  }
}
```



```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input,
) {
  switch (action) {
    case "parseNumber": ...
    case "toString": ...
    default: throw "impossible" // default case needed :(
  }
}
```

```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input: InputMap[K],
) {
  switch (action) {
    case "parseNumber": ...
    case "toString": ...
  }
}
```

```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input: InputMap[K],
) {
  switch (action) {
    case "parseNumber": ...
    case "toString": ...
  }
}
```



```
type InputMap = {
  "parseNumber": string,
  "toString": number,
}
```

```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input: InputMap[K],
): OutputMap[K] {
  switch (action) {
    case "parseNumber": ...
    case "toString": ...
  }
}
```

More Complex

```
doAction("parseNumber", "2") // number
```

```
doAction("parseNumber", 2)
```

```
// doAction<"parseNumber">(action: "parseNumber", input: string):  
number
```

```
doAction("toString", 2) // string
```

```
doAction("toString", "2")
```

```
// doAction<"toString">(action: "toString", input: number): string
```

More Complex

```
addEventListener<K extends keyof WindowEventMap>(
  type: K,
  listener: (this: Window, ev: WindowEventMap[K]) => any,
  options?: boolean | AddEventListenerOptions
): void
```

<https://github.com/Microsoft/TypeScript/blob/master/lib/lib.dom.d.ts>

More Complex

```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input: InputMap[K],
): OutputMap[K] {
  switch (action) {
    case "parseNumber": ...
    case "toString": ...
  }
}
```

Finished?

```
let x: "parseNumber" | "toString"
```

```
doAction(x, "2")
```

```
doAction(x, 2)
```

```
// doAction<"parseNumber" | "toString">(action: "parseNumber" |  
"toString", input: string | number): string | number
```



```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input: InputMap[K],
): OutputMap[K] {
  switch (action) {
    case "parseNumber": ...
    case "toString": ...
  }
}
```

```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input: InputMap[K],
): OutputMap[K] {
  switch (action) {
    case "parseNumber": ...
    case "toString": ...
  }
}
```

InputMap["parseNumber" | "toString"]
= number | string


```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input: InputMap[K],
): OutputMap[K] {
  switch (action) {
    case "parseNumber": return Number.parseInt(input);
    case "toString": ...
  }
}
```

input : number | string

```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input: InputMap[K],
): OutputMap[K] {
  switch (action) {
    case "parseNumber": ...
    case "toString": return 2; // typechecks :(
  }
}
```

```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input: InputMap[K],
): OutputMap[K] {
  switch (action) {
    case "parseNumber": ...
      // result type : string | number
    case "toString": return 2;
      // result type : string | number
  }
}
```

```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input: InputMap[K],
): OutputMap[K] {
  switch (action) {
    case "parseNumber": ...
    case "toString": ...
  }
}
```



Can we fix it?

```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input: UnionToIntersection<InputMap[K]>,
): OutputMap[K] {
  switch (action) {
    case "parseNumber": ...
    case "toString": ...
  }
}
```

`UnionToIntersection<string | number> = string & number`

```
type UnionToIntersection<U> =  
  (U extends any ? (k: U)=>void : never)  
  extends ((k: infer I)=>void) ? I : never
```

<https://stackoverflow.com/questions/50374908/transform-union-type-to-intersection-type>


```
type UnionToIntersection<U> =  
  (U extends any ? (k: U)=>void : never)  
  extends ((k: infer I)=>void) ? I : never
```

```
UnionToIntersection<bool> = true & false
```


<https://stackoverflow.com/questions/50374908/transform-union-type-to-intersection-type>

```
let x: "parseNumber" | "toString";
```

```
doAction(x, "2")
```

```
// doAction<"parseNumber" | "toString">(action: "parseNumber" |  
"toString", input: string & number): string | number
```

```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input: UnionToIntersection<InputMap[K]>,
): OutputMap[K] {
  switch (action) {
    case "parseNumber": return Number.parseInt(input);
    case "toString": ...
  }
}
```



input : UnionToIntersection<InputMap[K]>

```
function doAction<K extends "parseNumber" | "toString">(
  action: K,
  input: UnionToIntersection<InputMap[K]>,
): OutputMap[K] {
  switch (action) {
    case "parseNumber": return Number.parseInt(<any>input);
    case "toString": ...
  }
}
```

... (Don't) Exactly mimic the design of existing languages ...

... (Don't) Exactly mimic the design of existing languages ...

Dependent Types?

... (Don't) Exactly mimic the design of existing languages ...

Dependent Types?

... Produce a language that is composable and easy to reason about ...

Type-level Computation

Type-level Computation

```
type Nat = Z | S
```

```
type Z = { tag: "Z", }
```

```
type S = { tag: "S", pred: Nat, }
```

Type-level Computation

```
type Nat = Z | S
```

```
type Z = { tag: "Z", }
```

```
type S = { tag: "S", pred: Nat, }
```

```
const one: Nat = { tag: "S", pred: { tag: "Z", }, }
```

Type-level Computation

```
type Nat = Z | S
```

```
type Z = { tag: "Z", }
```

```
type S = { tag: "S", pred: Nat, }
```

```
const one: Nat = { tag: "S", pred: { tag: "Z", }, }
```

```
type One = { tag: "S", pred: Z, }
```

Type-level Computation

```
function add(n: Nat, m: Nat): Nat {  
  switch (n.tag) {  
    case "Z": return m;  
    case "S": return { tag: "S", pred: add(n.pred, m), };  
  }  
}
```

```
const two = add(one, one)  
// { tag: "S", pred: { tag: "S", pred: { tag: "Z", }, }, }
```

Type-level Computation

```
type Add<N extends Nat, M extends Nat> =  
  N extends Z ? M :  
  { tag: "S", pred: Add<N["pred"], M> }
```

Type-level Computation

```
type Add<N extends Nat, M extends Nat> =  
  N extends Z ? M :  
  { tag: "S", pred: Add<N["pred"], M> }
```

```
1 extends 1 | 2 ? true : false
```

```
// true
```

```
{ tag: "S" } extends { tag: "Z" } ? true : false
```

```
// false
```

Type-level Computation

```
type Add<N extends Nat, M extends Nat> =  
  N extends Z ? M :  
  { tag: "S", pred: Add<N["pred"], M> }
```

Type-level Computation

```
type Add<N extends Nat, M extends Nat> =  
  N extends Z ? M :  
  { tag: "S", pred: Add<N["pred"], M> }
```

```
type Two = Add<One, One>  
// { tag: "S", pred: { tag: "S", pred: Z } }
```


Type-level Computation

```
type VNil = {  
  tag: "VNil",  
}
```

```
type VCons<A, N extends Nat> = {  
  tag: "VCons",  
  a: A,  
  tail: Vec<A, N>,  
}
```

```
type Vec<A, N extends Nat> = VNil | VCons<A, N>
```

Type-level Computation

```
function vnil<A>(): Vec<A, Z> {  
  return { tag: "VNil", }  
}
```

```
function vcons<A, N extends Nat>(  
  a: A,  
  tail: Vec<A, N>,  
>: Vec<A, { tag: "S", pred: N }> {  
  return { tag: "VCons", a, tail, }  
}
```

Type-level Computation

```
function concat<A, N extends Nat, M extends Nat>(
  v1: Vec<A, N>,
  v2: Vec<A, M>,
): Vec<A, Add<N, M>> { ... }
```

Type-level Computation

```
function concat<A, N extends Nat, M extends Nat>(
  v1: Vec<A, N>,
  v2: Vec<A, M>,
): Vec<A, Add<N, M>> { ... }
```

```
const vec1 = vcons(1, vnil())
// Vec<number, One>
const vec2 = concat(vec1, vec1)
// Vec<number, Two>
```

Type-level Computation

```
function concat<A, N extends Nat, M extends Nat>(
  v1: Vec<A, N>,
  v2: Vec<A, M>,
): Vec<A, Add<N, M>> {
  switch (v1.tag) {
    case "VNil": return v2
    case "VCons": ...
  }
}
```

Type-level Computation

```
function concat<A, N extends Nat, M extends Nat>(
  v1: Vec<A, N>,
  v2: Vec<A, M>,
): Vec<A, Add<N, M>> {
  switch (v1.tag) {
    case "VNil": return v1 // typechecks :(
    case "VCons": ...
  }
}
```

Type-level Computation

```
function head<A, N extends { tag: "S", pred: Nat }>(
  v1: Vec<A, N>,
): A {
  switch (v1.tag) {
    case "VNil": throw "impossible" // still necessary :(
    case "VCons": return v1.a
  }
}
```

Type-level Computation

```
function head<A, N extends { tag: "S", pred: Nat }>(
  v1: Vec<A, N>,
): A { ... }
```

```
const x = head(vnil())
// typechecks :(
```


Type-level Computation

```
function head<A, N extends { tag: "S", pred: Nat }>(
  v1: Vec<A, N>,
): A { ... }
```

```
const x = head(vnil())
// typechecks :(
```

Where is the problem?

Type-level Computation


```
function vnil<A>(): Vec<A, Z> {  
  return { tag: "VNil", }  
}
```

```
type Vec<A, N extends Nat>  
  = VNil | VCons<A, N>
```

```
data Vect : (len : Nat)  
  -> (elem : Type)  
  -> Type where  
  Nil    : Vect Z elem  
  (:::)   : (x : elem)  
    -> (xs : Vect len elem)  
    -> Vect (S len) elem
```

Type-level Computation

```
function add(n: Nat, m: Nat): Nat {  
  switch (n.tag) {  
    case "Z": return m;  
    case "S": return { tag: "S", pred: add(n.pred, m), };  
  }  
}
```



```
type Add<N extends Nat, M extends Nat> =  
  N extends Z ? M :  
  { tag: "S", pred: Add<N["pred"], M> }
```