

The Native Factor-67 Compiler

A Conditional Proof Proposal and Adversarial Audit
for the Riemann Hypothesis

ChatGPT Pro¹ Gideon Freund² Agentic Polymath Project³

¹Principal synthesis, reconstruction, and adversarial audit

²Research harness, prompter, and project steward

³Distributed mathematical collaboration and repository provenance

Proof status

This manuscript is a *proof proposal*, not an announcement that the Riemann hypothesis has been proved. It gives the strongest end-to-end composition recovered from the repository, proves the algebraic and analytic compiler around it, and isolates two load-bearing certification obligations that are definitely not presently discharged: a genuinely outward-rounded Target–Lorenz tail certificate and an unambiguous native-normalization/benchmark identity. The main theorem is conditional on those obligations. The current repository therefore does not establish RH; the remaining imported finite clauses also require independent replay.

Version 1.0 – 16 August 2026

Frozen research base: active proposal line through pull request #524, head
079a80308a218e924d86030c4df40410df960592.

Abstract

We reconstruct the strongest presently composable Riemann-hypothesis proposal in the Agentic Polymath repository. Its central device is a native factor-67 compiler that converts an exact signed arithmetic source into a nonnegative feasible source while preserving the required target marginal and paying only bounded dual cost. Three type firewalls are essential: complete target-bearing sources, current-row-only positive bonuses, and signed observations must never be promoted into one another; the outer Volterra fibre must remain unsplit; and the rough-prime lift must not be identified with the native marginal. With these corrections, the finite and continuum pieces fit into a single same-row identity. A common thinning factor

$$\tau_K = \frac{\sqrt{K}}{\sqrt{K} + 130}, \quad K = \lfloor X/67 \rfloor + 1,$$

repairs every fourth-order column, and the sparse Y_4 dual yields the explicit cost

$$0 \leq J_{\text{nat}}(X) - H(d_X) < 60989 \quad (X \geq 10^{12}).$$

Combined with a frozen prime-square moat and a Mellin–Landau converse, this would imply RH.

The implication is conditional on a compact certification package Cert_{67} . One clause requires rigorous positivity for the Target–Lorenz tail beyond 166000; the available program uses singleton values returned by standard `sqrt` and `log` calls inside an interval wrapper and therefore does not prove outward enclosure. A second clause resolves an inherited notation and normalization collision: one dependency uses J_Λ for the smoothed prime sum, while the endpoint consumer uses P_Λ for that sum and reserves J for the native benchmark. We formulate the exact identity and growth bound that a valid certificate must establish. Thus the manuscript supplies a dependency-closed conditional proof, an explicit failure ledger, and a reproducible route to a machine-checkable closure, but it does not claim an unconditional proof of RH.

Contents

1	Introduction	4
1.1	What is new in this synthesis	4
1.2	The headline theorem	5
2	Notation and the three-sorted proof system	5
2.1	Arithmetic notation	5
2.2	The notation firewall	6
2.3	Three source sorts	6
2.4	Ownership	7
3	The native source and its finite–continuum split	7
3.1	Native normalization	7
3.2	Outer Volterra atoms	8
3.3	Cell decomposition	8

4	The inner two-sorted compiler	9
4.1	A generic Hall residual lemma	9
4.2	Why one-sorted Hall is impossible	9
4.3	Compact and deep leaves	10
5	The unsplit outer rank-one compiler	11
6	Localization, all-column repair, and terminal reserve	12
6.1	The unthinned positive block	12
6.2	Fourth-order responses	12
6.3	Common thinning	13
6.4	Terminal columns	13
7	The sparse Y_4 dual and the constant 60989	13
7.1	Dual identity	13
7.2	The benchmark-growth clause	14
8	Endpoint transport and the Mellin–Landau converse	15
8.1	From feasibility to an endpoint inequality	15
8.2	The prime-square moat	15
8.3	Mellin transform	15
9	The conditional composition theorem	16
10	Adversarial stress test	16
10.1	Failure ledger	16
10.2	The invalid interval implementation	17
10.3	Stress test of the constant 60989	18
11	A rigorous replacement certificate	18
11.1	Certificate architecture	18
11.2	Algebraic–transcendental firewall	18
11.3	Normalization certificate	19
11.4	Recommended machine-readable manifest	19
12	Dependency-closed theorem ledger	20
13	What an independent reviewer should check first	21
14	Discussion	21

15 Conclusion	22
A Algebraic replay of the two-sorted identity	22
B Prime-square constant	22
C Reproducibility and provenance	23

1 Introduction

The Riemann hypothesis asserts that every nontrivial zero of the Riemann zeta function has real part $1/2$. The repository studied here contains several long proof architectures. By August 2026 the most advanced positive endpoint route had concentrated around a factor-67 arithmetic compiler. The attractive feature of that route is not a single spectacular inequality, but a modular implication:

$$\begin{aligned} \text{exact native source} &\implies \text{positive feasible source of bounded dual defect} \\ &\implies \text{eventual one-sided explicit-formula remainder} \\ &\implies \text{RH.} \end{aligned}$$

The danger is precisely the modularity. A source that is positive in one row is not automatically a complete source; a signed identity is not a positive decomposition; a continuum fibre cannot be split merely because its integrated coefficient is positive; and two objects with the same total mass need not have the same native marginal. Several earlier proposals failed at one of these interfaces.

This paper has four goals.

First, it places the live factor-67 proposal in one notation and proves its compositional algebra without referring the reader to a graph of repository files. Second, it enforces a three-sorted type system that rules out the known illegal promotions. Third, it carries the construction through localization, thinning, the sparse fourth-order dual, and the Mellin–Landau endpoint. Fourth, it performs a hostile audit of every non-symbolic input and states the exact certification package still required.

The result is intentionally stronger than a survey and weaker than an accepted proof. It is a complete conditional argument with named, finite verification obligations. Those obligations are sufficiently sharp that an independent reviewer can reject or certify the proposal without reverse-engineering the repository.

1.1 What is new in this synthesis

The main synthesis is the simultaneous use of the following corrections.

1. **Three-sorted source calculus.** Complete sources P , current-row bonuses B , and signed observations O have disjoint interfaces. Only P objects can be recursively compiled.
2. **Native parent initialization.** The finite tree starts directly from the native occurrence atoms, not from a rough-prime lift or a synthetic endpoint parent.
3. **Unsplit outer coupling.** The Volterra fibre p_s is transported only by a rank-one coupling at fixed s ; it is never causally subdivided.
4. **Same-row accounting.** The residual source and the current-only bonus are inserted in the same physical row. This makes the exact row identity visible before any positivity conclusion is drawn.
5. **One common thinning.** The factor τ_K is applied after the positive block has been assembled. The all-column and terminal estimates are then charged in the sparse Y_4 dual.
6. **Notation firewall.** The smoothed prime sum is denoted P_Λ , while the native benchmark is denoted J_{nat} . Their relation is a theorem obligation, not a typographical convention.

7. **Certificate firewall.** A numerical interval computation counts as proof only when every elementary function is outward-enclosed and the event partition is independently replayable.

1.2 The headline theorem

Let

$$P_\Lambda(X) := \sum_{n \leq X} \frac{\Lambda(n)}{\sqrt{n}} \log \frac{X}{n} \quad (1)$$

be the smoothed von Mangoldt sum. Let c_X be the exact native source, H the native benchmark functional, and

$$J_{\text{nat}}(X) := H(c_X), \quad F_\Lambda(X) := J_{\text{nat}}(X) - P_\Lambda(X).$$

The definitions of the response maps and the certification package are given in sections 2 and 11.

Main conditional result

Assume Cert_{67} . For every $X \geq 10^{12}$ there is a nonnegative native-feasible source d_X satisfying

$$0 \leq \Delta_X := J_{\text{nat}}(X) - H(d_X) < 60989.$$

Consequently $F_\Lambda(X) \leq \Delta_X = o(\log^2 X)$. Under the prime-square occupancy identity proved in section 8, the associated explicit-formula remainder is eventually negative. Landau's one-sign theorem then excludes a nontrivial zeta zero off the critical line, and the functional equation gives RH.

The theorem is proved in section 9. Its present logical status is summarized by the following equally important statement.

Theorem 1.1 (Current proof status). *The repository state audited for this manuscript does not establish Cert_{67} . In particular:*

1. *the published Target–Lorenz tail computation does not outward-enclose its calls to `sqrt` and `log`; and*
2. *the inherited sources use the symbol J_Λ for two different quantities, leaving the normalization and the $O(\sqrt{X})$ benchmark bound formally ambiguous until an explicit identity is supplied.*

Therefore this manuscript does not establish the Riemann hypothesis unconditionally.

2 Notation and the three-sorted proof system

2.1 Arithmetic notation

Throughout, μ is the Möbius function, Λ the von Mangoldt function, and $X \geq 10^{12}$ unless otherwise stated. Put

$$K := \lfloor X/67 \rfloor + 1, \quad W := 10000, \quad \tau_K := \frac{\sqrt{K}}{\sqrt{K} + 130}. \quad (2)$$

For $x \geq 1$ and $k \leq x$, define the positive factor-67 coefficient

$$\ell_x(k) := \frac{1}{\sqrt{k}} \left(2\sqrt{\frac{x}{k}} - 1 \right). \quad (3)$$

The outer signed coefficient is $\mu(k)\ell_x(k)$, and its total is

$$L(x) := \sum_{k \leq x} \mu(k)\ell_x(k). \quad (4)$$

The exact continuum density used to initialize the native source is

$$d_X^*(t) := \sum_{k \leq X/t} \frac{\mu(k)}{\sqrt{kt}} \log \frac{X}{kt}, \quad 1 \leq t \leq X. \quad (5)$$

Its discrete tail profile is

$$b_X^*(n) := \sum_{m=n}^{\lfloor X \rfloor} d_X^*(m). \quad (6)$$

The native realization operator R sends the profile to the source $c_X := Rb_X^*$. Rather than rely on a coordinate convention for R , we specify the source by its complete response tuple

$$\mathcal{R}(c) := (C_c, \Xi_c, H(c), (v_q(c))_{q \geq 1}, (R_j(c))_{j \geq 2}). \quad (7)$$

Every equality involving sources below is an equality in this tuple. This is the most economical standalone definition: the proof uses no property of an internal coordinate vector that is not visible in $\mathcal{R}$.

2.2 The notation firewall

The project inherited two incompatible uses of J_Λ . One family of files used it for the prime sum (1); another endpoint theorem denoted that sum by P_Λ and used J for the exact native benchmark. We adopt the latter semantic distinction:

$$\boxed{P_\Lambda(X) = \sum_{n \leq X} \frac{\Lambda(n)}{\sqrt{n}} \log \frac{X}{n}, \quad J_{\text{nat}}(X) = H(c_X), \quad F_\Lambda = J_{\text{nat}} - P_\Lambda.} \quad (8)$$

No step in this paper identifies P_Λ and J_{nat} merely because an imported file used the same letter for both.

Adversarial audit finding

The elementary Chebyshev argument proves

$$P_\Lambda(X) < 8(\log 2)\sqrt{X} \quad (X \geq 2),$$

whereas the thinning charge requires a bound for $J_{\text{nat}}(X)$. A valid proof must derive the required $O(\sqrt{X})$ bound for J_{nat} from the native definitions; a proved comparison such as $J_{\text{nat}} \leq 2P_\Lambda$ would suffice. This is clause N₆₇ of Cert₆₇.

2.3 Three source sorts

Definition 2.1 (Complete source, current bonus, observation). A *complete source* $u \in \mathbf{P}$ carries target, score, row, response, and provenance data. It may be recursively decomposed or inserted into the positive physical block. A *current-row bonus* $B \in \mathbf{B}$ is a nonnegative row vector attached to the current occurrence only; it has no target, no inherited score, no descendant mass, and no fourth-order response. A *signed observation* $E \in \mathbf{O}$ may be paired against a dual or bounded in response norm, but it is not a positive source.

The legal operations are

$$P + P \rightarrow P, \quad B + B \rightarrow B, \quad O + O \rightarrow O, \quad (P, B) \rightarrow \text{same-row block}.$$

There are deliberately no coercions $B \rightarrow P$, $O \rightarrow P$, or $O \rightarrow B$.

Interface contract

A row identity of the form

$$R(\nu) + B = R(E) - R(O), \quad \nu \in P, B \in B,$$

does not imply that $\nu + B$ is a complete source. The bonus may be used only in that row. This rule is the repair for the exact $q = 2$ Hall obstruction.

2.4 Ownership

Every literal native occurrence is assigned the label

$$\lambda = (m, k, d, h, i, \epsilon, c), \tag{9}$$

recording its cell, Möbius index, stopping-line divisor, depth, local occurrence, sign, and coefficient. A deterministic first-owner map sends each label to exactly one leaf of the finite tree. Outer continuum fibres are labelled by (s, k) and remain outside that tree.

Definition 2.2 (One-use invariant). A construction satisfies the one-use invariant when every native literal label has exactly one of the following statuses: retained residual source, absorbed negative source, current-only row bonus, retained outer fibre, top omission, or signed localization error. No label may have two statuses and no label may disappear without entering the signed-error ledger.

This invariant is the combinatorial backbone of the exact coefficient identity in theorem 6.1.

3 The native source and its finite–continuum split

3.1 Native normalization

The exact source has three distinguished responses:

$$C_{c_X} = w_X, \quad \Xi(c_X) = \Omega_X, \quad H(c_X) = J_{\text{nat}}(X). \tag{10}$$

Here C is the target marginal, Ξ the ordinary complement response, and H the native benchmark functional. The first two equalities encode the source-to-endpoint normalization; the third defines the benchmark once the normalization is fixed. Clause N₆₇ of Cert₆₇ requires these equalities in a single coordinate convention and supplies the growth estimate needed in section 7.

At the occurrence level, the inner native coefficient is

$$a_{m,k} := \frac{|\mu(k)|}{\sqrt{km}} \log \frac{X}{km}, \quad km \leq X. \tag{11}$$

The sign is $\text{sgn } \mu(k)$. Starting the finite compiler from these atoms avoids the false identification of a rough-prime lift with the native marginal.

3.2 Outer Volterra atoms

For $1 \leq m \leq s$, set

$$g_s(m) := \left(\sqrt{m} - \frac{m}{\sqrt{s}} \right) \mathbf{1}_{m \leq s}, \quad p_s := Rg_s. \quad (12)$$

Clause N₆₇ requires the native source calculus to give $p_s \geq 0$. Its outer integral is

$$\bar{c}_{\text{out}} = \int_{K+2}^X \frac{2}{s} \sum_{k \leq X/s} \mu(k) \ell_{X/s}(k) p_s \, ds. \quad (13)$$

For fixed s , the factor p_s is one indivisible physical fibre. A proposal may couple its arithmetic coefficients, but may not split the vector p_s according to a causal stopping line.

The need for this rule is not philosophical. At $(p, y, s, j) = (67, 15, 1005, 14)$, direct evaluation gives

$$-\frac{184291}{10^9} < p_{1005}(14) - 67^{-1/2} p_{15}(14) < -\frac{184290}{10^9} < 0. \quad (14)$$

Thus an apparently natural branchwise positive split is false.

3.3 Cell decomposition

Write the adjacent-cell error as

$$\epsilon_X(m) := d_X^*(m) - \int_m^{m+1} d_X^*(t) \, dt, \quad E_{\text{out}}(n) := \sum_{\substack{m \geq K+2 \\ m \geq n}} \epsilon_X(m). \quad (15)$$

Split the outer cells into the retained region

$$K + 2 \leq m \leq X - W - 3$$

and the top collar

$$X - W - 2 \leq m \leq X - 1.$$

Then the exact source identity is

$$\boxed{c_X = c_{\text{in}} + \bar{c}_{\text{ret}} + \bar{c}_{\text{top}} + RE_{\text{out}}.} \quad (16)$$

The inner term contains whole native cells $m \leq K + 1$; the outer retained and top terms are unsplit Volterra integrals. Equation (16) is an equality of complete response tuples.

Lemma 3.1 (Exact split from adjacent-cell summation). *Assume (5)–(15) and the linearity of R . Then (16) holds, and every contribution to the right-hand side has a unique cell owner.*

Proof. On each outer cell $[m, m + 1]$, add and subtract the constant value $d_X^*(m)$. The integral pieces assemble into $\bar{c}_{\text{ret}} + \bar{c}_{\text{top}}$, while the differences telescope in the discrete tail E_{out} . The cells $m \leq K + 1$, retained outer cells, and top cells are disjoint. Linearity of R gives the source identity, and the partition gives unique ownership. $\square$

4 The inner two-sorted compiler

4.1 A generic Hall residual lemma

We first isolate the exact algebra used at both compact and deep leaves.

Lemma 4.1 (Two-sorted Hall residual). *Let E and O be finite sets of positive and negative source atoms. Each atom a has a positive target $T(a) > 0$, a score $S(a)$, and row values $R_j(a)$. Suppose there is a nonnegative transport $t(o, e)$ such that*

$$\sum_{e \in E} t(o, e) = T(o) \quad (o \in O), \quad (17)$$

$$\sum_{o \in O} t(o, e) \leq T(e) \quad (e \in E), \quad (18)$$

and on every used edge

$$\frac{S(e)}{T(e)} \leq \frac{S(o)}{T(o)}, \quad (19)$$

$$\frac{R_j(e)}{T(e)} \geq \frac{R_j(o)}{T(o)} \quad \text{for every current row } j. \quad (20)$$

Define

$$c_e := 1 - \frac{1}{T(e)} \sum_o t(o, e) \geq 0, \quad (21)$$

$$\nu := \sum_{e \in E} c_e e \in \mathbf{P}, \quad (22)$$

$$\sigma := \sum_{o, e} t(o, e) \left(\frac{S(o)}{T(o)} - \frac{S(e)}{T(e)} \right) \geq 0, \quad (23)$$

$$B_j := \sum_{o, e} t(o, e) \left(\frac{R_j(e)}{T(e)} - \frac{R_j(o)}{T(o)} \right) \geq 0. \quad (24)$$

Then

$$T(\nu) = T(E) - T(O), \quad (25)$$

$$S(\nu) = S(E) - S(O) + \sigma, \quad (26)$$

$$R_j(\nu) + B_j = R_j(E) - R_j(O). \quad (27)$$

Moreover $B = (B_j)_j$ is a current-only bonus and cannot be promoted to a complete source.

Proof. Equation (18) gives $c_e \geq 0$. Multiplying (21) by $T(e)$, summing in e , and using (17) gives (25). The score identity follows by expanding $S(\nu)$, inserting $\sum_o t(o, e)$, and grouping the transported terms. The row identity is identical. The signs of σ and B_j follow from (19) and (20). Only the residual coefficients c_e multiply complete source atoms; the differences in (24) are row coordinates without target or score data, so they have sort $\mathbf{B}$, not $\mathbf{P}$. $\square$

4.2 Why one-sorted Hall is impossible

At the $q = 2$ root, the score ordering and row ordering cannot simultaneously be encoded as a complete target-null positive packet. In the language of theorem 4.1, the residual ν , score slack σ , and row bonus B are all nonnegative, but only ν is a complete source. Any proof that recursively splits B has silently added target and score coordinates that the Hall construction never supplied.

Proposition 4.2 (Type firewall at the root). *The valid output of the factor-67 root Hall step is the pair $(\nu, B) \in \mathbf{P} \times \mathbf{B}$ satisfying (25)–(27). There is in general no complete source $u \geq 0$ having target zero, exact score, and row vector B .*

Proof. The first assertion is theorem 4.1. The second is witnessed by the exact $q = 2$ separator in the native model: the target and score constraints determine a cone face on which the required row coordinate has the wrong sign. Clause F_{67} records the finite rational certificate. The proposition is used only negatively: it forbids the illegal promotion $\mathbf{B} \rightarrow \mathbf{P}$. $\square$

4.3 Compact and deep leaves

For compact leaves, the transport is obtained from a finite Hall table. The root coefficients may be represented by

$$T_x(k) := \frac{4\sqrt{x/k} - 3}{\sqrt{k}}, \quad (28)$$

$$S_x(k) := \frac{5\sqrt{x/k} - 3}{\sqrt{k}}, \quad (29)$$

$$R_{x,j}(k) := \frac{Q_{x/k}(j)}{\sqrt{k}}, \quad (30)$$

where $Q_y(j)$ is the native row kernel fixed by the response tuple. The finite table covers $67 \leq x \leq 166000$ and rows $2 \leq j \leq 66$.

For the tail, the arithmetic part is compressed into the Target–Lorenz functions

$$\chi_2(s) = 1 - 2^{-s}, \quad (31)$$

$$\chi_3(s) = 1 + 2^{-s} - 2 \cdot 3^{-s}, \quad (32)$$

$$\chi_4(s) = 1 + 2^{-s} + 3^{-s} - 2 \cdot 4^{-s}. \quad (33)$$

A finite event partition in x reduces all target, score, derivative, and causal inequalities to interval evaluations on boxes. The claimed worst row is 66. The algebraic consequences of those inequalities are correct; the current floating-point proof of the inequalities is not.

Certification clause 4.3 (Finite and tail typed-leaf certificate F_{67}). For every native inner occurrence, the compact table and the rigorous tail certificate produce a transport satisfying (17)–(20), with exact occurrence ownership. The compact range is $67 \leq x \leq 166000$; the tail is $x \geq 166000$. The certificate must include exact or outward-rounded lower bounds for target Hall slack, score-ratio slack, and every row-ratio slack.

Lemma 4.4 (Inner same-row realization). *Assume F_{67} . The entire inner native source admits an exact decomposition*

$$c_{\text{in}} = d_{\text{src}}^0 \dot{+} B_{\text{in}} \quad (34)$$

in the same-row sense: $d_{\text{src}}^0 \in \mathbf{P}$ is nonnegative and complete, $B_{\text{in}} \in \mathbf{B}$ is current-only and rowwise nonnegative, the target marginal is exact, the score is superordinate, and every row satisfies

$$R_j(d_{\text{src}}^0) + B_{\text{in},j} = R_j(c_{\text{in}}). \quad (35)$$

Every native inner occurrence is used exactly once.

Proof. Apply theorem 4.1 independently at each first-owned leaf supplied by F_{67} . Add all residual complete sources and all current-only bonuses within their respective sorts. Target identities telescope through the finite tree; nonnegative score slacks accumulate; row identities add in the same physical row. The first-owner labelling prevents duplication, and the finite tree exhausts the inner labels. No bonus is recursed or assigned a response coordinate. $\square$

5 The unsplit outer rank-one compiler

The outer range has $x = X/s < 67$. At fixed s , abbreviate $a_k = \ell_x(k) > 0$, and split the arithmetic coefficients by Möbius sign:

$$P_+(x) := \sum_{\substack{k \leq x \\ \mu(k)=1}} a_k, \quad P_-(x) := \sum_{\substack{k \leq x \\ \mu(k)=-1}} a_k. \quad (36)$$

Then $L(x) = P_+(x) - P_-(x)$.

Certification clause 5.1 (Factor-67 outer margin O_{67}). For $1 \leq x < 67$,

$$L(x) > \frac{159}{500}. \quad (37)$$

The lower bound is certified on the finitely many floor-pattern intervals of x .

Lemma 5.2 (Rank-one cancellation without fibre splitting). *Assume O_{67} . At fixed s , define*

$$t_x(o, e) := \frac{a_o a_e}{P_+(x)} \quad (\mu(o) = -1, \mu(e) = 1). \quad (38)$$

Then every negative coefficient is exhausted, the positive residual is

$$r_x(e) = a_e \frac{P_+(x) - P_-(x)}{P_+(x)} \geq 0, \quad (39)$$

and the physical row contribution is exactly

$$\sum_e r_x(e) p_s = L(x) p_s \geq 0. \quad (40)$$

No subvector of p_s is introduced.

Proof. For a negative index o ,

$$\sum_e t_x(o, e) = a_o \frac{\sum_e a_e}{P_+} = a_o.$$

For a positive index e , the absorbed amount is

$$\sum_o t_x(o, e) = a_e \frac{P_-}{P_+},$$

which gives (39). The strict margin makes the residual nonnegative. All coefficients multiply the same vector p_s , so their sum is $L(x)p_s$. The calculation modifies only the scalar coefficient of the intact fibre. $\square$

Integrating theorem 5.2 gives a nonnegative retained outer source $\bar{c}_{\text{ret}}$. The top collar is deliberately omitted and later paid by a terminal reserve.

6 Localization, all-column repair, and terminal reserve

6.1 The unthinned positive block

Let I_{src} and I_{bonus} insert the inner residual and bonus into the same physical row, and let Q_{bulk} realize retained outer cells. The block operator is

$$Q_{\text{hyb}} := I_{\text{src}} \oplus I_{\text{bonus}} \oplus Q_{\text{bulk}}. \quad (41)$$

With C_{ret} denoting the localized correction selected from E_{out} , define

$$d_X^0 := I_{\text{src}} d_{\text{src}}^0 + I_{\text{bonus}} B_{\text{in}} + \bar{c}_{\text{ret}} + R C_{\text{ret}}. \quad (42)$$

The type system is internal to the construction: after insertion, d_X^0 is a physical nonnegative source, but the bonus was never independently treated as target-bearing.

Lemma 6.1 (Global exact identity). *Under F_{67} and O_{67} ,*

$$\boxed{c_X - d_X^0 = \bar{c}_{\text{top}} + R(E_{\text{out}} - C_{\text{ret}})}. \quad (43)$$

Moreover $d_X^0 \geq 0$ and satisfies the exact target and score conditions before thinning.

Proof. Subtract (42) from the exact split (16). The inner difference vanishes row by row by (35); the retained outer term is exact by theorem 5.2; and the localization term leaves $R(E_{\text{out}} - C_{\text{ret}})$. The top collar was never inserted and remains as $\bar{c}_{\text{top}}$. Positivity follows from the inner residual and current-row bonus, the outer margin, and the positive realization of C_{ret} . One-use ownership prevents an additional term. $\square$

6.2 Fourth-order responses

For a source u , let $v_q(u)$ be its q -column response and let $D_4 v_q(u)$ be the fourth-order difference paired with the sparse Y_4 dual. Its normalization is fixed by the adjoint identity

$$\langle Y_4, D_4 v(u) \rangle = \langle \mathcal{Y}_4, u \rangle, \quad (44)$$

where $Y_4(q)$ obeys

$$Y_4(q) = \frac{1}{2q^2} + 2Y_4(4q), \quad |Y_4(q)| < \frac{8}{3q^2}. \quad (45)$$

This formulation removes any ambiguity about whether D_4 acts forward or backward on a chosen coordinate convention.

The localization estimates needed below are

$$|v_q(E_{\text{out}})| < \frac{57}{2q\sqrt{K}}, \quad (46)$$

$$|D_4 v_q(E_{\text{out}} - C_{\text{ret}})| < \frac{971}{4q\sqrt{K}}, \quad (47)$$

$$\frac{|D_4 v_q(E_{\text{out}} - C_{\text{ret}})|}{\Omega_X(q)} < \frac{129}{\sqrt{K}} \quad (q \leq X/4). \quad (48)$$

The last inequality is the all-column relative bound.

Certification clause 6.2 (Localization certificate L_{67}). There is a first-owner localization C_{ret} for which (46)–(48) hold simultaneously, with no artificial cutoff atom and with exact carry accounting.

6.3 Common thinning

Define

$$d_X := \tau_K d_X^0. \quad (49)$$

Then

$$c_X - d_X = (1 - \tau_K)c_X + \tau_K [\bar{c}_{\text{top}} + R(E_{\text{out}} - C_{\text{ret}})]. \quad (50)$$

Consequently the fourth-order endpoint defect is

$$e_X^{(4)} = (1 - \tau_K)\Omega_X + \tau_K [\Xi(\bar{c}_{\text{top}}) + D_4 v(E_{\text{out}} - C_{\text{ret}})]. \quad (51)$$

Since

$$1 - \tau_K = \frac{130}{\sqrt{K} + 130}, \quad (52)$$

the relative reserve is larger than $129/\sqrt{K}$. Thus (48) repairs every nonterminal column $q \leq X/4$.

6.4 Terminal columns

For the top omission, the fourth-order response has a one-sided derivative lower bound. Summing the top collar of width $W = 10000$ gives

$$\text{top response removed} > 5033X^{-3/2}. \quad (53)$$

The worst all-column overfill is

$$\text{localized overfill} < 4452X^{-3/2}. \quad (54)$$

Hence the terminal margin is at least

$$(5033 - 4452)X^{-3/2} = 581X^{-3/2} > 0. \quad (55)$$

Proposition 6.3 (All-column nonnegativity). *Assume L_{67} and the terminal bounds (53)–(54). Then $e_X^{(4)}(q) \geq 0$ for every fourth-order column. The ordinary complement*

$$e_X^{\text{ord}}(q) := \sum_{h \geq 0} 2^h e_X^{(4)}(4^h q) \quad (56)$$

is also nonnegative.

Proof. For $q \leq X/4$, combine the thinning reserve in the first term of (51) with (48); the constant 130 strictly dominates 129. The terminal columns are covered by (55). Every summand in (56) is therefore nonnegative. $\square$

7 The sparse Y_4 dual and the constant 60989

7.1 Dual identity

Let Y_4 be the sparse dual generated by (45). Native feasibility and adjunction give

$$\Delta_X := J_{\text{nat}}(X) - H(d_X) = \langle Y_4, e_X^{(4)} \rangle \geq 0. \quad (57)$$

The nonnegativity follows from theorem 6.3 and the sign of the dual weights in the native cone.

The cost is divided according to the exact error ledger. The conservative bounds inherited by the live proposal are shown in table 1.

Table 1: Dual-cost ledger. Strict inequalities add to 60989.

Contribution	Upper bound
Common thinning, $(1 - \tau_K)J_{\text{nat}}(X)$	12012
Nonterminal signed localization error	4
Terminal signed localization and top collar	48972
Endpoint omissions and rounding collars	1
Exact coefficient and same-row identities	0
Total	60989

7.2 The benchmark-growth clause

The thinning charge is

$$(1 - \tau_K)J_{\text{nat}}(X) = \frac{130}{\sqrt{K} + 130} J_{\text{nat}}(X). \quad (58)$$

Because $K > X/67$, the conservative estimate

$$J_{\text{nat}}(X) \leq 16(\log 2)\sqrt{X} \quad (59)$$

gives a uniform value below 12012. The elementary Chebyshev proof establishes (59) with J_{nat} replaced by P_Λ . The proposal therefore requires the following explicit clause.

Certification clause 7.1 (Native normalization and benchmark clause N_{67}). In one fixed coordinate convention, the native source satisfies (10), the endpoint gap is $F_\Lambda = J_{\text{nat}} - P_\Lambda$, the Volterra atoms satisfy $p_s = Rg_s \geq 0$, and

$$J_{\text{nat}}(X) \leq 16(\log 2)\sqrt{X}. \quad (60)$$

The estimate must be proved from the native source definitions. It may follow from a separately proved comparison with P_Λ , but never from a shared symbol.

Lemma 7.2 (Elementary prime-sum estimate). *For $X \geq 2$,*

$$P_\Lambda(X) < 8(\log 2)\sqrt{X}. \quad (61)$$

Proof. Let $\psi(t) = \sum_{n \leq t} \Lambda(n)$. The elementary Chebyshev bound $\psi(t) \leq 2(\log 2)t$ is sufficient. Partial summation in (1) gives an integral against the decreasing derivative of $t^{-1/2} \log(X/t)$. Bounding $\psi(t)$ by $2(\log 2)t$ and evaluating the resulting elementary integral yields a constant at most $8 \log 2$. The estimate is intentionally conservative. $\square$

Proposition 7.3 (Bounded native defect). *Assume N_{67} , L_{67} , and the terminal estimates. Then*

$$0 \leq \Delta_X < 60989. \quad (62)$$

Proof. The lower bound is (57). Clause N_{67} and (58) give the first line of table 1. The localization bounds (46)–(47), the dual decay (45), and the terminal collar give the next three lines. Exact identities cost zero. Adding the strict upper bounds gives $12012 + 4 + 48972 + 1 = 60989$. $\square$

8 Endpoint transport and the Mellin–Landau converse

8.1 From feasibility to an endpoint inequality

Native feasibility means that $d_X \geq 0$, its target marginal does not exceed w_X , its ordinary complement is nonnegative, and its benchmark satisfies

$$H(d_X) \leq P_\Lambda(X). \quad (63)$$

Therefore

$$F_\Lambda(X) = J_{\text{nat}}(X) - P_\Lambda(X) \leq J_{\text{nat}}(X) - H(d_X) = \Delta_X. \quad (64)$$

By theorem 7.3, $F_\Lambda(X) = o(\log^2 X)$ from above.

8.2 The prime-square moat

Let $A(X)$ be the explicit-formula remainder obtained after separating prime squares from the endpoint functional. The frozen occupancy calculation gives

$$A(X) = F_\Lambda(X) - \frac{C_{\text{pp}}}{4} \log^2 X + o(\log^2 X), \quad (65)$$

where

$$C_{\text{pp}} = -1 - \zeta\left(\frac{1}{2}\right) = \frac{1}{2} \int_1^\infty \frac{\{v\}}{v^{3/2}} dv > 0. \quad (66)$$

Combining (64), (62), and (65) shows

$$A(X) < 0 \quad (67)$$

for all sufficiently large X .

8.3 Mellin transform

For $\Re z$ initially large, the Mellin transform of A has the form

$$\hat{A}(z) := \int_1^\infty A(X) X^{-z-1} dX = z^{-2} G\left(z + \frac{1}{2}\right), \quad (68)$$

where G is an explicit meromorphic combination of the logarithmic derivative of ζ and elementary polar terms. A nontrivial zero ρ with $\Re \rho > 1/2$ produces a nonreal singularity of the right-hand side at $z = \rho - 1/2$ on the boundary of its half-plane of holomorphy.

Landau’s theorem says that the Mellin transform of an eventually one-signed real function cannot have its first boundary singularity only at a nonreal point; the abscissa itself must be singular. Equation (67) therefore excludes $\Re \rho > 1/2$. The functional equation $\rho \mapsto 1 - \rho$ excludes $\Re \rho < 1/2$.

Theorem 8.1 (Endpoint consumer). *Assume the prime-square occupancy identity (65) and the Mellin identity (68). If $F_\Lambda(X) = o(\log^2 X)$ from above, then RH holds.*

Proof. The moat term in (65) dominates and makes A eventually negative. If an off-line zero existed to the right of the critical line, (68) would have a nonreal boundary singularity incompatible with Landau’s one-sign theorem. The zeta functional equation reflects any zero left of the line to one right of it. Hence all nontrivial zeros lie on $\Re s = 1/2$. $\square$

9 The conditional composition theorem

We can now state the certification package in one place.

Definition 9.1 (Factor-67 certification package). The package Cert_{67} consists of:

- (A) N_{67} : native normalization and benchmark growth, theorem 7.1;
- (B) F_{67} : exact compact and outward-rounded tail typed-leaf certificate, theorem 4.3;
- (C) O_{67} : the finite outer margin (37);
- (D) L_{67} : first-owner all-column localization, theorem 6.2;
- (E) exact terminal bounds (53)–(54);
- (F) the sparse-dual adjunction (44)–(45); and
- (G) the endpoint identities (65) and (68).

Every clause must be accompanied either by a symbolic proof in this manuscript or by a finite independently replayable artifact satisfying section 11.

Theorem 9.2 (Native factor-67 conditional theorem). *Assume Cert_{67} . For every $X \geq 10^{12}$, there exists a nonnegative native-feasible source d_X such that*

$$0 \leq J_{\text{nat}}(X) - H(d_X) < 60989. \quad (69)$$

Consequently the Riemann hypothesis holds.

Proof. Start with the exact native source c_X and split it by theorem 3.1. Compile every inner occurrence with theorem 4.4, preserving the target and score while retaining current-only bonuses in the same row. Compile each outer fibre with theorem 5.2; the vector p_s is never split. Assemble the unthinned block (42). The exact error is (43). Apply the common thinning (49). Clause L_{67} , the reserve gap $130 - 129$, and the terminal margin 581 give all-column feasibility by theorem 6.3. The sparse dual and the cost ledger give (69) by theorem 7.3. Feasibility implies (64), so $F_\Lambda = o(\log^2 X)$ from above. The endpoint consumer theorem 8.1 yields RH. $\square$

Corollary 9.3 (Exact location of the open frontier). *Within this architecture, no further asymptotic improvement is required. Closure reduces to certifying the finite clauses of Cert_{67} , with the presently known defects concentrated in F_{67} and N_{67} .*

Remark 9.4. The corollary is architectural, not epistemic. A future audit may discover another flaw in a clause presently regarded as proved. The point is that the dependency interface is now explicit enough for such a flaw to be localized.

10 Adversarial stress test

10.1 Failure ledger

Table 2: Known failure modes and the firewall used here.

Failure mode		Why it fails	Repair in this manuscript
One-sorted Hall	root	The $q = 2$ cone does not support target-null, exact-score, row-positive completion.	Residual source $\nu \in \mathbf{P}$ and current-only bonus $B \in \mathbf{B}$ are separate sorts.
Causal split of p_s		Exact counterexample (14) has a negative branch difference.	Rank-one coupling changes only scalar arithmetic coefficients at fixed s ; the fibre stays intact.
Rough lift = native marginal	na-	They agree on some aggregate data but are separated by the native $q = 2$ response.	The finite tree starts directly from native occurrence atoms (11).
Synthetic end-point parent	end-	A formally convenient parent may not belong to the native source cone.	Every leaf carries a first-owned native label (9).
Bonus promotion		A nonnegative row vector need not possess target, score, or descendant coordinates.	No coercion $\mathbf{B} \rightarrow \mathbf{P}$.
Signed comparison promoted to positivity	compari-	A bounded response difference is not a positive source.	Signed errors remain in $\mathbf{O}$ and are charged only through Y_4 .
Duplicate ownership	owner-	The same literal can be spent in the finite tree and again in localization.	One-use invariant, disjoint cell ranges, and first-owner labels.
Artificial atom	cutoff	Truncating a carry can create an unmatched endpoint mass.	Localization clause requires exact carry and no cutoff atom.
Nonterminal proof used at the top		Relative bounds degenerate in terminal columns.	Explicit $W = 10000$ collar and margin $5033 - 4452 = 581$.
Singleton “interval”	“inter-	Wrapping <code>std::sqrt</code> or <code>std::log</code> output as $[y, y]$ does not enclose the exact value.	Clause F_{67} requires MPFR/Arb outward rounding or exact dyadic transcendental tables.
Symbol collision		The same symbol J_Λ was used for both a prime sum and a native benchmark.	Notation firewall (8); clause N_{67} .

10.2 The invalid interval implementation

The current tail program declares an interval type with a standard-transcendental rounding policy, but constructs square-root and logarithm intervals from singleton evaluations of the platform functions. Such a value proves only that the floating-point program returned a number. It does not prove that the exact real value lies in the interval. Agreement between long-double and higher-precision point evaluations is useful debugging evidence, not an enclosure theorem.

This defect is load-bearing because the tail contains more than fifty million event boxes per grid. A single incorrectly signed lower endpoint invalidates the universal positivity claim.

Theorem 10.1 (Audit theorem for the tail program). *A computation in which a transcendental quantity $f(x)$ is represented by the singleton interval $[\text{fl}(f(x)), \text{fl}(f(x))]$, without a proof of correct rounding, does not certify any strict lower bound involving $f(x)$.*

Proof. The exact value may lie on either side of the rounded value. A singleton interval contains the exact value only if the floating operation is known to be exact or correctly rounded to that value, neither of which follows from the C++ standard call. Interval arithmetic is inclusion-isotone only when every input interval contains its exact operand and every operation encloses its exact range. The premise violates the first condition. $\square$

10.3 Stress test of the constant 60989

The numerical constant has three robustness properties and one vulnerability.

First, the nonterminal reserve has a clean unit gap $130 - 129$, so no equality case is used. Second, the terminal margin is $581X^{-3/2}$, again strict. Third, the cost table deliberately rounds individual estimates upward. The vulnerability is the thinning term: if J_{nat} is not the prime sum and has no independent $O(\sqrt{X})$ bound, the constant 12012 is unsupported. This is why N_{67} is part of the headline hypothesis rather than a footnote.

11 A rigorous replacement certificate

11.1 Certificate architecture

A valid computational proof should have a small trusted kernel and a large untrusted producer. The producer may search, partition, and optimize; the checker must verify a deterministic certificate using exact integers, rationals, or rigorously rounded balls.

Protocol 11.1 (Tail certificate contract). A replacement for the Target–Lorenz tail computation shall provide:

1. an exact list of event endpoints and a proof that these endpoints partition every floor-pattern region for $x \geq 166000$;
2. outward enclosures for every $\sqrt{r}$, $\log r$, power r^{-s} , determinant, derivative, and causal difference used in a sign test;
3. a rational or dyadic lower endpoint strictly above zero for every required inequality;
4. exact hashes of the event list, constants table, certificate stream, and checker source;
5. a record of the worst box for each inequality family;
6. a checker that rejects NaNs, infinities, reversed intervals, unproved rounding modes, and undeclared transcendental calls; and
7. an independent replay implementation using a second arithmetic backend.

11.2 Algebraic–transcendental firewall

The event endpoints have the form $x = cd$, where d divides the product of the primes up to 61 and c belongs to a small set generated by $1, j, j+1$ with $2 \leq j \leq 66$. This structure permits a substantial simplification.

Precompute outward dyadic enclosures for

$$\sqrt{p}, \quad \log p \quad (p \leq 61 \text{ prime}), \quad \sqrt{c}, \quad \log c \quad (1 \leq c \leq 67).$$

Then build

$$\sqrt{d} = \prod_{p|d} \sqrt{p}, \quad \log d = \sum_{p|d} \log p, \quad \sqrt{cd} = \sqrt{c}\sqrt{d}, \quad \log(cd) = \log c + \log d$$

with outward interval multiplication and addition. The millions of event checks then require no fresh call to a transcendental library. The trusted transcendental surface is reduced to a tiny table that can be certified independently by Arb or MPFR at, say, 256 and 512 bits.

Proposition 11.2 (Soundness of table-driven replay). *If each table interval contains its exact constant and every subsequent arithmetic operation is outward-rounded, then every derived event interval contains the exact event value. A strictly positive lower endpoint certifies the corresponding inequality.*

Proof. Products and sums of inclusion intervals are inclusion intervals. The event formulas are finite compositions of the table constants and rational operations. Induction on the expression tree gives containment. Strict positivity of the lower endpoint then implies positivity of the exact value. $\square$

11.3 Normalization certificate

The native-normalization clause should be checked symbolically, not numerically. A minimal certificate contains:

1. the exact matrix or kernel defining R , C , Ξ , and H ;
2. an exact derivation of $C_{c_X} = w_X$ and $\Xi(c_X) = \Omega_X$;
3. a declaration of which formula is P_Λ and which is J_{nat} ;
4. an exact proof of one alternative in (60); and
5. a unit test at small X that evaluates both sides from independent definitions, included only as a regression test, not as proof.

11.4 Recommended machine-readable manifest

A checker should consume a manifest of the following form.

```
{
  "schema": "factor67-certificate-v1",
  "base_sha": "079a80308a218e924d86030c4df40410df960592",
  "ranges": {"compact": [67,166000], "tail_start": 166000},
  "rows": [2,66],
  "arithmetic": {"backend": "arb", "precision_bits": 256,
                 "outward_rounding": true},
  "artifacts": {
    "event_partition": "sha256:...",
    "constant_table": "sha256:...",
    "compact_certificate": "sha256:...",
    "tail_certificate": "sha256:...",
    "independent_checker": "sha256:..."
  }
}
```

```

    "normalization_proof": "sha256:..."
  },
  "claimed_minima": {
    "target": "positive dyadic interval",
    "score": "positive dyadic interval",
    "row": "positive dyadic interval",
    "causal": "positive dyadic interval"
  }
}

```

No hash can substitute for sound arithmetic; hashes make a sound computation reproducible, not true.

12 Dependency-closed theorem ledger

table 3 maps the live repository components to the statements used here. The status column distinguishes symbolic arguments, finite certificates, and known gaps.

Table 3: Theorem and lemma ledger.

Repository ID	Role in the composition	Status here	Manuscript location
L-91870	Exact native fibre initialization and native/rough separator	Conditional normalization	section 3, clause N ₆₇
L-91880	Explicit native two-sorted source coupling	Reconstructed	sections 3 and 4
L-91881	Whole-cell block realization in one row	Reproved algebraically	theorems 4.1 and 4.4
L-91882	Same-row all-column terminal complement	Reconstructed	section 6
L-91883	Direct Y_4 cost and constant 60989	Reconstructed with normalization caveat	section 7
T-91880	End-to-end native hybrid successor theorem	Conditional composition	theorem 9.2
R-91880	Three type firewalls and counterexamples	Incorporated	theorem 2.1, equation (14), and section 10
L-91688	Rough-prime first-owner provenance	Used only for ownership	theorem 2.2
L-91690	Factor-67 root Hall and finite margins	Finite certificate clause	theorems 4.3 and 5.1
L-91733	All-column localization, constants 57, 971, 129	Certificate clause	theorem 6.2
L-91115	Top collar and terminal reserve	Symbolic plus finite constants	section 6
L-19885	Sparse Y_4 dual and recurrence	Restated	equation (45) and section 7
L-19887	Elementary Chebyshev estimate	Reproved for P_Λ	theorem 7.2

Repository ID	Role in the composition	Status here	Manuscript location
L-93782	Global Target–Lorenz certificate	Conditional	theorem 4.3
L-93783	Typed leaf realization	Reproved algebraically	theorem 4.1
L-93781	Directed transcendental tail sweep	Not certified	theorems 10.1 and 11.1
T-91750	Prime-square moat and Mellin–Landau consumer	Restated	section 8

13 What an independent reviewer should check first

A reviewer need not read the manuscript linearly. The highest-value order is:

1. **Normalization.** Expand the definitions of R, C, Ξ, H and verify N_{67} , including the distinction between P_Λ and J_{nat} .
2. **Tail arithmetic.** Reject any certificate that calls a non-rigorous transcendental function inside a singleton interval. Replay the event partition with Arb or MPFR.
3. **Type discipline.** At every Hall leaf, check that only the residual ν is recursively used. Search mechanically for any bonus receiving a target or score coordinate.
4. **Outer fibres.** Confirm that no code or proof step replaces p_s by branchwise pieces.
5. **Ownership.** Hash the literal-label ledger and verify that the finite tree, retained continuum, top collar, and localization errors form a partition.
6. **Endpoint consumer.** Re-derive the coefficient $C_{\text{pp}}/4$, signs in (65), and the location of Mellin singularities.
7. **Constants.** Recompute $130 > 129$, $5033 > 4452$, and the five entries of table 1 from exact upper bounds.

A successful review should produce either a signed certificate manifest or a minimal counterexample tied to one of these interfaces.

14 Discussion

The factor-67 architecture is unusually close to a sharply falsifiable endpoint. It no longer depends on an undefined global positivity miracle. Its main finite mechanism is ordinary Hall transport with a necessary type split; its continuum mechanism is a one-line rank-one coupling; its analytic repair is a common thinning with a visible unit gap; and its endpoint cost is bounded independently of X .

That concentration is scientifically valuable even if the proposal ultimately fails. A rigorous tail replay can return a negative box, immediately identifying the first false inequality. A normalization expansion can show whether the benchmark bound is genuine or whether a hidden prime-sum identification entered the proof. Either outcome advances the project more than another layer of conditional composition.

The strongest responsible conclusion is therefore two-sided:

If Cert_{67} is certified, the native factor-67 compiler yields RH;
the audited repository does not yet certify Cert_{67} .

15 Conclusion

We have assembled the live factor-67 route into a single arXiv-style proof proposal, made its source types explicit, reconstructed the exact finite–continuum composition, and carried its bounded defect through the sparse Y_4 dual to the Mellin–Landau endpoint. The architecture has an appealing quantitative core:

$$\tau_K = \frac{\sqrt{K}}{\sqrt{K} + 130}, \quad 130 > 129, \quad 5033 - 4452 = 581, \quad \Delta_X < 60989.$$

These constants are not the present obstacle. The obstacle is proof certification at two interfaces: rigorous transcendental enclosure for the Target–Lorenz tail and a clean native normalization that separates the prime sum from the benchmark. Until those are supplied, the manuscript remains a conditional proposal and RH remains unproved in the project.

A Algebraic replay of the two-sorted identity

For completeness, consider one negative atom o and positive atoms $e_1, \dots, e_r$. Let $t_i = t(o, e_i)$ and $\sum_i t_i = T(o)$. The residual target is

$$\sum_i (T(e_i) - t_i) = T(E) - T(o).$$

The residual score is

$$\begin{aligned} \sum_i \left(1 - \frac{t_i}{T(e_i)}\right) S(e_i) &= S(E) - \sum_i t_i \frac{S(e_i)}{T(e_i)} \\ &= S(E) - S(o) + \sum_i t_i \left(\frac{S(o)}{T(o)} - \frac{S(e_i)}{T(e_i)}\right). \end{aligned}$$

The normalized score order in (19) makes the last term the nonnegative slack σ . It remains a scalar score slack and is not inserted into a row. Similarly,

$$R_j(E) - R_j(o) - R_j(\nu) = \sum_i t_i \left(\frac{R_j(e_i)}{T(e_i)} - \frac{R_j(o)}{T(o)}\right) = B_j \geq 0.$$

This explicit calculation is the type boundary: B_j is a difference of normalized row coordinates, not a source coefficient.

B Prime-square constant

The positivity in (66) is immediate from the fractional-part integral. It is useful because it makes the endpoint argument insensitive to the exact bounded constant in (62): any $O(1)$ upper bound for F_Λ is swallowed by $-C_{\text{pp}} \log^2 X/4$. Thus future improvements should prioritize certification soundness over reducing 60989.

C Reproducibility and provenance

The proposal was reconstructed from the active pull-request graph rather than the outdated default branch. The primary live proposal was pull request #524 at commit

079a80308a218e924d86030c4df40410df960592.

The hostile audit included the exact review of the Target–Lorenz tail in pull request #516 and the type/counterexample records incorporated into the 91880 packet. The companion file `THEOREM_LEDGER.md` lists every repository component used and its status. The source archive contains this $\text{\LaTeX}$ file, the build script, the ledger, and the proposed pull-request description.

References

- [1] E. Landau. Ueber einen Satz von Tschebyschef. *Mathematische Annalen*, 61:527–550, 1905.
- [2] E. C. Titchmarsh. *The Theory of the Riemann Zeta-Function*. Second edition, revised by D. R. Heath-Brown, Oxford University Press, 1986.
- [3] H. Davenport. *Multiplicative Number Theory*. Third edition, revised by H. L. Montgomery, Springer, 2000.
- [4] R. E. Moore, R. B. Kearfott, and M. J. Cloud. *Introduction to Interval Analysis*. SIAM, 2009.
- [5] F. Johansson. Arb: efficient arbitrary-precision midpoint-radius interval arithmetic. *IEEE Transactions on Computers*, 66(8):1281–1292, 2017.
- [6] Agentic Polymath Project. Riemann research repository, active factor-67 proposal and review graph. Frozen provenance through 16 August 2026.