



# BG5S Function



Note:


- 1、 API call is parallel call and sequential execution.
- 2、 Function A should be called before Function B, otherwise the time of offline data may be incorrect.

# Function A: Sync offline data



- A-1**  
– (void)queryStateInfoWithSuccess:(BG5SStateInfoBlock)stateInfoBlock  
errorBlock:(BG5SSDKErrorBlock)errorBlock;
- A-2**  
– (void)queryRecordWithSuccessBlock:(BG5SRecordBlock)successBlock  
errorBlock:(BG5SSDKErrorBlock)errorBlock;
- A-3**  
– (NSArray \*)processData:(NSArray<BG5SRecordModel\*> \*)array deviceDate:(NSDate \*)deviceDate;
- A-4**  
– (void)deleteRecordWithSuccessBlock:(BG5SSuccessBlock)successBlock  
errorBlock:(BG5SSDKErrorBlock)errorBlock;

## Function B: Set time and unit




### B-1

```
- (void)setTimeWithDate:(NSDate *)date
    timezone:(float)timezone
    successBlock:(BG5SSuccessBlock)successBlock
    errorCallback:(BG5SSDKErrorBlock)errorBlock;
```

### B-2

```
- (void)setUnit:(BGUnit)unit
    successBlock:(BG5SSuccessBlock)successBlock
    errorCallback:(BG5SSDKErrorBlock)errorBlock;
```

# Function: Online measurement flow



## C-1

```
- (void)startMeasure:(BGMeasureMode)measureMode  
  WithSuccessBlock:(BG5SSuccessBlock)successBlock  
  errorCallback:(BG5SDKErrorBlock)errorBlock;
```

## C-2

```
- (void)disconnectDevice;
```