

Assignment 3

Q1] #include <stdio.h>

```
void printEven(int iNo)
{
    if (iNo <= 0)
    {
        return;
    }
}
```

```
int iCnt, iEven = 0;
for (iCnt = 1; iCnt <= iNo; iCnt++)
{
    iEven = 2 * iCnt;
    printf("%d", iEven);
}
```

```
}
```

```
int main()
{
```

```
    int iValue = 0;
    printf("Enter number: \n");
    scanf("%d", &iValue);
    printEven(iValue);
    return 0;
}
```


Q2] #include <stdio.h>

```
void displayFactor(int iNo)
```

```
{
```

```
    int i = 0;
```

```
    if (iNo <= 0)
```

```
    {
```

```
        iNo = -iNo;
```

```
    }
```

```
    for (i = 1; i <= iNo; i++)
```

```
    {
```

```
        if (iNo % i == 0)
```

```
        {
```

```
            printf("%d ", i);
```

```
        }
```

```
    }
```

```
}
```

```
int main()
```

```
{
```

```
    int iValue = 0;
```

```
    printf("Enter a number: ");
```

```
    scanf("%d", &iValue);
```

```
    displayFactor(iValue);
```

```
    return 0;
```

```
}
```


Q3] #include <stdio.h>

void displayEvenFactor (int iNo)

{

if (iNo <= 0)

{

iNo = -iNo;

}

for (int i = 1; i <= iNo; i++)

{

if ((iNo % i) == 0)

{

if (i % 2 == 0)

{

printf("%d", i);

}

}

}

}

Q4] #include <stdio.h>

char displayConvert(char cValue)

{

if (cValue >= 'a' && cValue <= 'z')

{

cValue = cValue - 32;

printf("%c\n", cValue);

}

else if (cValue >= 'A' && cValue <= 'Z')

{

cValue = cValue + 32;

printf("%c\n", cValue);

}

}

int main()

{

char cValue = '\0';

printf("Enter one character: ");

scanf("%c", &cValue);

displayConvert(cValue);

return 0;

}

Q5] #include <stdio.h>

typedef int BOOL;
#define TRUE 1;
#define FALSE 0;

char CheckVowel (char cValue)

{
if (cValue == 'a' || cValue == 'e' || cValue == 'i' ||
cValue == 'o' || cValue == 'u' ||
cValue == 'A' || cValue == 'E' || cValue == 'I' ||
cValue == 'O' || cValue == 'U') ?

{

return TRUE;

}

else

{

return FALSE;

}

}

int main()

{

char cValue = '\0';

BOOL bRet = FALSE;

printf("Enter Character : ");

scanf("%c", &cValue);

bRet = checkVowel(cValue);


```
if (bRet == TRUE)
```

```
{
```

```
    printf("%c is a vowel \n", cValue);
```

```
}
```

```
else
```

```
{
```

```
    printf("%c is not a vowel \n", cValue);
```

```
}
```

```
return 0;
```

```
}
```