

# Uncover viral sharing through global structure of host-virus meta-network

Mathis Gheno<sup>1,2,‡</sup> [Timothée Poisot](#)<sup>2,3,‡</sup>

<sup>1</sup> Université de Rennes   <sup>2</sup> Université de Montréal   <sup>3</sup> Québec Centre for Biodiversity Sciences

‡ Equal contributions

## Correspondance to:

Timothée Poisot — [timothee.poisot@umontreal.ca](mailto:timothee.poisot@umontreal.ca)

**Purpose:** This template provides a series of scripts to render a markdown document into an interactive website and a series of PDFs.

**Internals:** GitHub actions and a series of python scripts. The markdown is handled with pandoc.

**Motivation:** It makes collaborating on text with GitHub easier, and means that we never need to think about the output.

This work is released by its authors under a CC-BY 4.0 license



Last revision: *July 20, 2023*

## 1 Introduction

## 2 Methods

3 Communicability quantify how well information transit between two nodes by considering all possible path in a  
4 network and penalizing longer ones. It is compute with the exponent of the adjacency matrix of the network.

$$G = \sum_{k=0}^{\infty} \frac{(A^k)}{k!} = e^A$$

5 where  $G$  is the communicability matrix,  $A$  the adjacency matrix and  $k$  is used as a penalizing term. It is possible  
6 to compute the exponential of a matrix with the graph spectrum :

$$G = \sum_{j=1}^n \varphi_j \varphi_j^T e^{\lambda_j}$$

7 where  $\varphi_j$  and  $\lambda_j$  are respectively the  $j^{th}$  eigenvectors and eigenvalues of the matrix  $A$ . The spectral form of  $G$   
8 can be decompose by the following way :

$$G = \varphi_1 \varphi_1^T e^{\lambda_1} + \sum_{j=2}^n \varphi_j^+ \varphi_j^{+T} e^{\lambda_j} + \sum_{j=2}^n \varphi_j^- \varphi_j^{-T} e^{\lambda_j} + \sum_{j=2}^n \varphi_j^- \varphi_j^{+T} e^{\lambda_j} \quad (1)$$

9  
10  
11  
12 where  $\varphi^+$  or  $\varphi^-$  indicate respectively all the positives or negatives values of the  $j^{th}$  eigenvector. The first is not  
13 include because all the values the eigenvector the same sign. Estrada & Hatano (2008) explain that “two nodes  
14 have the same sign in an eigenvector if they can be considered as being in the same partition of the network,  
15 while those pairs having different signs correspond to nodes in different partitions.” So to make partition we are  
16 mostly interested by the sign of the sums in eq. 1 :

$$\sum_{j=2}^{intracluster} \varphi_j \varphi_j^T e^{\lambda_j} = \sum_{j=2}^n \varphi_j^+ \varphi_j^{+T} e^{\lambda_j} + \sum_{j=2}^n \varphi_j^- \varphi_j^{-T} e^{\lambda_j}$$

17 and

$$\sum_{j=2}^{intercluster} \varphi_j \varphi_j^T e^{\lambda_j} = \sum_{j=2}^n \varphi_j^- \varphi_j^{+T} e^{\lambda_j}$$

18 so the clustering matrix is obtain with

$$\Delta G = \sum_{j=2}^{intracluster} \varphi_j \varphi_j^T e^{\lambda_j} - \left| \sum_{j=2}^{intercluster} \varphi_j \varphi_j^T e^{\lambda_j} \right|$$

```
library(tidyverse)
library(lattice)
library(igraph)
library(colorRamps)
A = matrix(c(0,1,0,1,1,0,0,0,0,0,0,
             1,0,1,1,1,0,0,0,0,0,0,
             0,1,0,1,1,0,0,0,0,0,0,
             1,1,1,0,1,0,0,0,0,0,0,
             1,1,1,1,0,1,0,0,0,0,0,
             0,0,0,0,1,0,1,0,0,0,0,
             0,0,0,0,0,1,0,1,1,0,1,
             0,0,0,0,0,0,1,0,1,1,1,
             0,0,0,0,0,0,1,1,0,1,1,
             0,0,0,0,0,0,0,1,1,0,1,
             0,0,0,0,0,0,1,1,1,1,0), nrow =11, ncol =11)
grap = graph_from_adjacency_matrix(A, mode = "undirected")
plot(grap)
```

19 **Example** A graph with 11 nodes and 2 distinct group. First we need to compute the graph spectrum

```
spectra = eigen(A)
levelplot(spectra$vectors, ylab = "eigenvectors", xlab = "j th position")
```

20 Now let's take the  $2^{nd}$  dimension as an example.

```
##  
G_dim2 = spectra$ectors[,2]%*%t(spectra$ectors[,2])*exp(spectra$values[2])  
intra = G_dim2[G_dim2]  
levelplot(G_dim2, ylab = "node", xlab = "node", col.regions = rev(matlab.like(16)))
```

21 And that it ! The second dimension of the graph communicability identify 2 cluster (blue).

22 We can compute for the third dimension

```
G_dim3 = spectra$ectors[,3]%*%t(spectra$ectors[,3])*exp(spectra$values[3])  
levelplot(G_dim3, ylab = "node", xlab = "node", col.regions = rev(matlab.like(16)))
```

23 Which identify clusters between 5:6 and 6:7. The cluster of the third dimension are less “obvious” than those  
24 from the second dimension

25 Now if we want to use other communicability dimension we just have to add

```
levelplot(G_dim2+G_dim3, ylab = "node", xlab = "node", col.regions = rev(matlab.like(16)))
```

26 We could continue like that till the last dimension (11th), but it was for the explanation. So now we can compute  
27 directly  $\Delta G$  by adding all the 10 dimension

```
delta_G = matrix(0, nrow =11, ncol =11)  
for(dim in 2:11){  
  delta_G = delta_G + spectra$ectors[,dim]%*%t(spectra$ectors[,dim])*exp(spectra$values[dim])  
}  
levelplot(delta_G, ylab = "node", xlab = "node", col.regions = rev(matlab.like(16)))
```

28 **Results**

29 **Conclusion**

30 Estrada, E. & Hatano, N. (2008). [Communicability in complex networks](#). *Physical Review E*, 77, 036111.