Types, Initialization and Casts

Initialization forms and brace traps, `auto` and `decltype`, implicit conversions, `enum class`, the four named casts, `const` / `constexpr` / `static` and what C++14 to 20 added.

Initialization and brace traps

```
int a;          // default-initialized: INDETERMINATE value, never read it
int b{};        // value-initialized: zero
int c = 5;      // copy-initialized
int d(5);       // direct-initialized
int e{5};       // list-initialized: the preferred form, rejects narrowing
// int f{3.7};  // ERROR: narrowing double → int inside braces
int g = 3.7;    // compiles: silently truncates to 3
```

KIND	EXAMPLE	NOTES
aggregate	`Point p{1, 2};`	no constructors: members set in order
designated (C++20)	`Point p{.x = 3, .y = 4};`	names the members, order must match
value-initialize	`Point p{};`	every member zero

BRACES PREFER `INITIALIZER_LIST`

```
std::vector<int> v1(3, 7);   // parentheses: 3 elements, each 7
std::vector<int> v2{3, 7};   // braces: the initializer_list
constructor wins → the two elements 3 and 7
```

If a class has an `initializer_list` constructor, `{ ... }` picks it even when another constructor matches better (compiled: `Widget w{1, 2}` called the list constructor, `Widget w(1, 2)` the (int, int) one). Empty braces `{}` call the default constructor.

- **Initialize everything.** An uninitialized local is **indeterminate**; reading it is undefined behaviour.
- Braces catch accidental narrowing at compile time: a free safety check.
- A `static_cast` in braces (`int{x}`) is a conversion that must not narrow.

`auto` , `decltype` and modern syntax

```
int x = 0;
const int& r = x;
auto a = r;                 // int           auto drops const and the reference
decltype(r) b = x;          // const int&    decltype gives the exact declared
type
decltype(auto) c = r;       // const int&    decltype(auto) = "deduce like
auto, but keep it exact"

auto t = {1, 2, 3};         // std::initializer_list<int>, NOT a vector
```

AUTO TRAPS

`auto y = v[0];` *copies*: write `const auto&` to avoid it. Same for `for (auto [k, v] : map)` (a copy of each pair). `auto` hides what a function returns: fine for iterators and lambdas, poor for public interfaces.

FEATURE	INSTEAD OF	EXAMPLE
Range-based `for`	index / iterator loops	`for (const auto& x : v) {}`
`nullptr`	`NULL` / `0`	`int* p = nullptr;`
`using` alias	`typedef`	`using Map = std::map<int, std::string>;`
`override` / `final`	hoping you matched the signature	`void f() override;`
`= default` / `= delete`	empty bodies, private unimplemented copy	`Foo(const Foo&) = delete;`
`static_assert`	runtime checks of compile-time facts	`static_assert(sizeof(int) == 4);`
Structured bindings (C++17)	`.first` / `.second`	`for (auto& [key, val] : m) {}`
`if` with initializer (C++17)	variable leaking into outer scope	`if (auto it = m.find(k); it ≠ m.end()) {}`
`[[nodiscard]]`	ignored error codes	`[[nodiscard]] bool open();`

Implicit conversions and `enum class`

The compiler converts silently between arithmetic types. Compiled results of the classic surprises:

EXPRESSION	RESULT	WHY
`-1 < 1u`	**false**	the signed value is converted to unsigned and becomes huge
`uint8_t(200) + uint8_t(100)`	300, stored back as 44	small types are promoted to `int` before arithmetic; storing back wraps
`7 / 2`	3	integer division; `7 / 2.0` is 3.5
`static_cast<int>(-3.9)`	-3	conversion to an integer truncates toward zero
`char` 0xFF widened to `int`	-1 (signed `char`)	whether plain `char` is signed is implementation-defined

- **Usual arithmetic conversions:** smaller than `int` becomes `int`; mixing signed and unsigned of the same rank converts to unsigned; `int` with `double` becomes `double`.
- **Never compare signed with unsigned** (`-Wsign-compare`); use `std::ssize` or cast deliberately.
- Single-argument constructors are implicit conversions: mark them `explicit` (OOP lesson).

```
enum Color { Red, Green };                // plain enum: leaks names into the scope, converts to int silently
int n = Green;                            // compiles

enum class Level { Info = 1, Error = 2 };// scoped: Level::Error, no implicit conversion
int m = static_cast<int>(Level::Error);   // an explicit cast is required (compiled: 2)
```

Prefer `enum class`, with an explicit underlying type when the size matters: `enum class Side : std::uint8_t { Buy, Sell };`

Casts and type conversion

Four named casts replace the C cast `(T)x`: each states intent and is searchable.

CAST	USE FOR	DANGER
`static_cast<T>(x)`	well-defined conversions: `int` to `double`, base to derived pointer when you are sure	low
`dynamic_cast<T>(x)`	checked downcast in a polymorphic hierarchy. Returns `nullptr` (pointer) or throws `std::bad_cast` (reference) on failure	runtime cost; base needs a virtual function
`const_cast<T>(x)`	add or remove `const` (legacy APIs)	modifying a truly const object is UB
`reinterpret_cast<T>(x)`	reinterpret raw bits (pointer to integer, unrelated pointer types)	very high, rarely correct

```
double avg = static_cast<double>(total) / count;       // avoids integer division

Animal* a = getAnimal();
if (auto* d = dynamic_cast<Dog*>(a)) {                  // safe downcast: null if it is not a Dog
    d->fetch();
}
```

> **RULE** Many casts mean a design problem. Prefer virtual functions to `dynamic_cast` chains; no C casts.

`const`, `constexpr` and `static`

- `const`: unchangeable after initialization. Use everywhere.
- `constexpr`: computable **at compile time** (array sizes, template arguments), and still callable at runtime.

```cpp
constexpr int square(int x) { return x * x; }
constexpr int N = square(4);          // 16, computed by the compiler
std::array<int, square(3)> a;         // size 9: legal because it is a
constant expression
int runtime = readInput();
int r = square(runtime);              // also fine: same function runs at
runtime

static_assert(N == 16, "math is broken");   // checked at compile time
```

`static` means three things:

WHERE	MEANING
Local variable in a function	one instance that lives for the whole program and keeps its value between calls
Global / namespace scope	internal linkage: visible only inside this `.cpp` file
Class member	belongs to the class, shared by all objects

Linkage and `extern "C"`

C++ **mangles** function names (it encodes the parameter types so that overloads get different symbols); C does not. To call C code, or to be called by it, tell the compiler to use C linkage:

```cpp
extern "C" int compareInts(const void* a, const void* b);      // an
unmangled symbol, callable from C

std::qsort(arr, 5, sizeof(int), compareInts);                   // a C API
taking a callback (compiled: sorted 12345)

extern "C" {                                                    // a whole
header of C declarations
    #include "legacy.h"
}
```

- An `extern "C"` function cannot be overloaded and cannot be a template or a member.
- Pointers to `extern "C"` functions are technically a different type from C++ function pointers; compilers accept them for C callbacks in practice.

- **Linkage rules:** a non-`static`, non-`inline` function defined in a header and included twice gives a "multiple definition" link error; mark it `inline`. `extern` on a variable declares it without defining it.

What C++14, 17 and 20 added

A map of which standard added what, so you know which flag a feature needs:

STANDARD	FEATURE	ONE-LINER
C++11	move semantics, smart pointers, lambdas, `auto`, `constexpr`, `std::thread`, variadic templates, `nullptr`, range-for	The big modernisation.
C++14	generic lambdas, `make_unique`, return type deduction, binary literals `0b101`	Polishes C++11.
C++17	`std::optional`, `std::variant`, `std::string_view`, structured bindings, `if constexpr`, fold expressions, `std::filesystem`, parallel algorithms, `std::scoped_lock`, CTAD	Vocabulary types and compile-time branching.
C++20	concepts, ranges, `std::span`, `operator⟺`, coroutines, modules, `std::jthread`, `std::format`	Constraints on templates, composable algorithms.

The C++17 and C++20 vocabulary types (`optional`, `variant`, `span`, `string_view`) have their own lesson: Vocabulary Types. Full lists: modern-cpp-features, modern-cpp-tutorial. Your notes: Module 3.

Further reading by section

Where each section of this lesson is explained in more depth. Pages are PDF viewer pages (the number your PDF reader shows).

SECTION	BOOK	PART OF THE BOOK	PDF PAGES
Initialization and brace traps	C++ Primer	2.2 Variables	70 to 78
auto, decltype and modern syntax	C++ Primer	2.5 Dealing with types	96 to 100
	Programming: Principles and Practice	2.8 to 2.10 Type safety, conversions, type deduction with auto	56 to 60
	Effective Modern C++	Item 2, Understand auto type deduction	36 to 41
	Effective Modern C++	Item 5, Prefer auto to explicit type declarations	55 to 61
Implicit conversions and enum class	C++ Primer	2.1 Primitive built-in types	61 to 69
	C++ Primer	4.11 Type conversions	188 to 194
	C++ Primer	19.3 Enumerations	861 to 863
	Programming: Principles and Practice	8.4 to 8.6 Evolving a class (Date), enumerations, operator overloading	238 to 249
Casts and type conversion	C++ Primer	4.11 Type conversions	188 to 194
const, constexpr and static	C++ Primer	6.5 Features for specialized uses	265 to 270
	Effective Modern C++	Item 15, Use constexpr whenever possible	115 to 121