Invoice refactoring

Before and after: captured program output

PASS - IDENTICAL PRINTED OUTPUT

Byte-for-byte comparison passed: 554 bytes and 32 output lines per run.

BEFORE `s1.lab1.Main`

```
INVOICE INV-1
Bag x2 = 200.00
Pen x3 = 150.00
TOTAL: 402.50
INVOICE INV-2
Computer x1 = 500.00
Keyboard x2 = 150.00
TOTAL: 747.50
[INV-1;ali@gmail.com;402.50]
[INV-2;ahmad@gmail.com;747.50]
INVOICE INV-1
Bag x2 = 200.00
Pen x3 = 150.00
TOTAL: 402.50
Sending email...
INVOICE INV-2
Computer x1 = 500.00
Keyboard x2 = 150.00
TOTAL: 747.50
Sending email...
INVOICE INV-1
Bag x2 = 200.00
Pen x3 = 150.00
TOTAL: 402.50
Sending sendwhatsapp...
INVOICE INV-2
Computer x1 = 500.00
Keyboard x2 = 150.00
TOTAL: 747.50
Sending sendwhatsapp...
402.5
747.5
```

AFTER `s1.lab2.Main`

```
INVOICE INV-1
Bag x2 = 200.00
Pen x3 = 150.00
TOTAL: 402.50
INVOICE INV-2
Computer x1 = 500.00
Keyboard x2 = 150.00
TOTAL: 747.50
[INV-1;ali@gmail.com;402.50]
[INV-2;ahmad@gmail.com;747.50]
INVOICE INV-1
Bag x2 = 200.00
Pen x3 = 150.00
TOTAL: 402.50
Sending email...
INVOICE INV-2
Computer x1 = 500.00
Keyboard x2 = 150.00
TOTAL: 747.50
Sending email...
INVOICE INV-1
Bag x2 = 200.00
Pen x3 = 150.00
TOTAL: 402.50
Sending sendwhatsapp...
INVOICE INV-2
Computer x1 = 500.00
Keyboard x2 = 150.00
TOTAL: 747.50
Sending sendwhatsapp...
402.5
747.5
```

Verification statement

For the two invoice scenarios executed by Main, the old and refactored versions produce exactly the same printed output, including both storage records, email and WhatsApp sending lines, and final totals. Returned messages are not printed.

Run conditions

Executed on 24 October 2026 using OpenJDK 26.0.2.1; locale: en_US.
Both runs used freshly compiled, unchanged project sources and fresh JVM processes.
Scope: the current Main scenarios shown above, under these run conditions.

SHA-256 of both captured outputs:
`28a53cd888ec7bd10165f7bcd2081fec08bd319031d01ba6489153cf26a33ee1`