

OATH Typed Tool Surface · 16 MCP Tools

NO EXECUTE_SHELL · EVERY OUTPUT → SIGNED NOTARIZED<T>

11 FORENSIC WRAPPERS

each binds image_sha256 · args · stdout_blake3 · ed25519 sig

<code>parse_evtx</code>	EvtxECmd · Windows event logs
<code>parse_mft</code>	MFTECmd · NTFS \$MFT entries
<code>parse_registry</code>	RECmd · Windows registry hives
<code>parse_usnjrnl</code>	MFTECmd \$J · change journal
<code>parse_amcache</code>	AmcacheParser · Amcache.hve
<code>parse_prefetch</code>	PECmd · Prefetch run history
<code>run_hayabusa</code>	Hayabusa · Sigma triage on EVTX
<code>plaso_supertimeline</code>	plaso psort · cross-source timeline
<code>vol3_query</code>	Volatility 3 · memory image plugins
<code>find_strings_on_image</code>	Sleuthkit + scan · NIST String Search

enumerate_credential_artifacts

DPAPI · NTDS · browser DBs · hibernation files · SSH keys

*replay anchor: BLAKE3 of stdout · re-derived by
tool-specific reverify() at oath verify time*

no execute_shell · no arbitrary code paths

5 CONTROL · INSPECTION

preserves the typed boundary across runs

<code>oath_mount</code>	establishes read-only EvidenceHandle streams image SHA-256 · mounts via ewfmount + ntfs-3g
<code>oath_list_handles</code>	enumerates known handles
<code>oath_list_envelopes</code>	enumerates signed chains current run + read-only pre-staged chains under logs/ closes the "no way to inspect receipts without shell" gap
<code>oath_read_envelope</code>	fetches one envelope payload by content-addressed envelope_id
<code>oath_verify_claim</code>	routes through Witness Oath Verifier returns VERIFIED · QUARANTINED · RALPH_WIGGUM

DESIGN RATIONALE

Without oath_list_envelopes and oath_read_envelope an agent has no way to look at pre-existing receipts other than shelling out to JSONL files. Adding them to the typed surface keeps the typed-tool boundary intact across runs and across pre-staged evidence chains.

verify_claim is the only path DRAFT → CONFIRMED

the LLM has no bypass