


OpenGL Course Summer 2020



Texture

2


Texture

Texture


- ▶ Achieving a high level of realism with nothing but thousands or millions of tiny lit and shaded polygons is a matter of brute force and a lot of hard work. Unfortunately, the more geometry you throw at graphics hardware, the longer it takes to render. A clever technique allows you to use simpler geometry but achieve a higher degree of realism. This technique takes an image, such as a photograph of a real surface or detail, and then applies that image to the surface of a polygon.
- ▶ This technique of applying an image to a polygon to supply additional detail is called *texture mapping*

Texture

4



Before Using Texture



After Using Texture

Texture


5

Example



Texture

6



Texture

7

- ▶ There are various ways to do texture mapping. Some of them use a technique called **Bitmapping in OpenGL**, the others use a way that load ready images from some resource. We'll deal with the second way in this course.
- ▶ The second technique needs some way to load textures. We'll use a texture loader called 'texture.h'
- ▶ there is four steps to use texture in our scence.

Step 1

Texture

9

► Step 1:

Enable the texturing

- Function:

```
void glEnable(Glenum parameter);
```

- Parameters:

- i. GL_TEXTURE_1D
- ii. GL_TEXTURE_2D
- iii. GL_TEXTURE_3D

Step 2

Texture

11

Load Texture

► Step 2:

```
Image= LoadTexture("Pic.bmp");
```

- Function:

```
int LoadTexture(char* filename,int alpha=255);
```

- Example:

- We'll put the image in some integer defined before InitGL function:

```
int Image;
```

- Inside **InitGL** function we'll load the image, for example:
- Now the image is stored in the variable Image.

Step 3

Texture

13

► Step 3:

Bind Texture

- Function:


Now, the following work is inside **DrawGLScene** function.

```
void glBindTexture(GGLenum Target, GLuint Texture);
```

- **Target**
:GL_TEXTURE_1D, GL_TEXTURE_2D, GL_TEXTURE_3D
- **Texture**: the int that was returned by the LoadTexture function in step 2 ,of the texture we want to use now ('cause it's not necessary to have just one texture).


Step 4

► Step 4:



XYZ coordinates:

- Vertices defined in counter clockwise order
- Z grows inwards (meaning, a positive Z is "behind" you)



ST coordinates:

- Also known as UV coordinates
- T is flipped
- Each axis has a range of $[0, 1]$
- Tiling possible when exceeding the range

Texture

16

- Now we'll draw the primitive that we'll bind the texture on it. It's common to bind the texture on a quad. The function that is used to bind the vertex of the texture is:

glTexCoord2f (s,t);

- The values of x and y are 0 or 1, it's just used to specify the angle that contains the vertex.

Texture

17

- ▶ The code of drawing the quad that contains the image which we loaded:


```
glBegin(GL_QUADS);  
glTexCoord2f(0.0f, 0.0f);  
glVertex3f(-5.0f,0.0f,0.0f);  
glTexCoord2f(0.0f, 1.0f);  
glVertex3f(-5.0f,6.0f,0.0f);  
glTexCoord2f(1.0f, 1.0f);  
glVertex3f(5.0f,6.0f,0.0f);  
glTexCoord2f(1.0f, 0.0f);  
glVertex3f(5.0f,0.0f,0.0f);  
glEnd();
```

▶ Note

Texture

18

- ▶ The result:



Texture

19

□ Tips:


- ▶ To draw a quad with a texture, it's advisable to **enable texture** before drawing it immediately, **then disable the texture** after it immediately. Never forget to disable it. The reason is that it will affect the colors of the objects which is drawn after it.
- ▶ Use images with the extension **BMP**. Most of loaders use this extension to load images. (Sure, there are loaders that use other extensions)
- ▶ Use images with **size of powers of number 2** and their sum. For example, $128*128$, $64*64$, $256*128$, $384*256$, ..etc
 - ▶ Notice that 384 is not from the powers of 2, but it's the sum of $128+256$ ☺
 - ▶ The reason that it's easier for the loader to bind the images with these sizes.

Irregular
quadrilateral
polygon

Texture

21



- Irregular quadrilateral polygon



Texture

22

- Irregular quadrilateral polygon





Non quadrilateral
polygon

Texture

24


□ Non quadrilateral polygon



Texture

25


□ Non quadrilateral polygon



Repeating Texture

Texture

27



Texture

28

□ Repeating Texture



Texture

29

□ Repeating Texture

some times we need to repeat texture on the same polygon

- ▶ Function call **InitGL** function:

```
glTexParameteri(GL_TEXTURE_2D, GL_TEXTURE_WRAP_S, GL_REPEAT);
```


```
glTexParameterf(GL_TEXTURE_2D, GL_TEXTURE_WRAP_T, GL_REPEAT);
```

- ▶ GL_TEXTURE_WRAP_S and GL_TEXTURE_WRAP_T mean that we call glTexCoord2f (s,t) with parameters bigger than one, the texture will be repeated by the number mentioned.

Texture

30

□ Repeating Texture



Texture

- Example

31

Example

Texture


- Example

```
glBegin(GL_QUADS);  
glColor3f(1,1,1);  
glNormal3f(0,0,1);  
glTexCoord2f(0.0f, 0.0f);  
glVertex3f(-5.0f,0.0f,0.0f);  
glTexCoord2f(0.0f, 6.0f);  
glVertex3f(-5.0f,6.0f,0.0f);  
glTexCoord2f(10.0f, 6.0f);  
glVertex3f(5.0f,6.0f,0.0f);  
glTexCoord2f(10.0f, 0.0f);  
glVertex3f(5.0f,0.0f,0.0f);  
glEnd();
```

Texture

- Example

► The result:



Texture

- Example

- ▶ Example : **without** using glTexParameteri in InitGL function.

```
glBegin(GL_QUADS);  
glColor3f(1,1,1);  
glNormal3f(0,0,1);  
glTexCoord2f(0.0f, 0.0f);  
glVertex3f(-5.0f,0.0f,0.0f);  
glTexCoord2f(0.0f, 1.0f);  
glVertex3f(-5.0f,6.0f,0.0f);  
glTexCoord2f(1.0f, 1.0f);  
glVertex3f(5.0f,6.0f,0.0f);  
glTexCoord2f(1.0f, 0.0f);  
glVertex3f(5.0f,0.0f,0.0f);  
glEnd();
```

Texture

- Example

- ▶ The result:



Add texture.h

36

- ▶ Project □ property □ c/c++ □ preprocessor □
preprocessor definitions □
_CRT_SECURE_NO_WARNINGS

skybox

37

skybox

skybox

38




RAGE

© 2010 id Software LLC. All Rights Reserved.


Homework

39




skybox

40



skybox

41



Homework

42

- ▶ Add another library to load texture
- ▶ skybox
- ▶ Camera controller

skybox

43

