

OpenGL Course

IT ENGINEERING

3TH YEAR



Shadow

2

Shadow

Why Shadow?

- ▶ A chapter on color and lighting naturally calls for a discussion of shadows. Adding shadows to your scenes can greatly improve their realism and visual effectiveness.
- ▶ In Figures below, you see two views of a lighted cube. Although both are lit, the one with a shadow is more convincing than the one without the shadow:



What's Shadow In OpenGL


- ▶ There are two main types of graphics in general:
- **Raster graphics:** which uses the idea of coloring pixels or lighting pixels when the corresponding primitive is obvious. Like OpenGL. This type of graphics never creates shadows for objects by default. But it's faster than the other.
- **Ray tracing graphics:** this type of graphics uses the idea of tracing or chasing the rays of light which are reflected from objects to show the colors of shapes and objects which is affected with the colors of objects that the ray reflected from. This type of graphics gives more realistic scenes but in the other hand it's very slow. It contains shadows for objects by default.

What's Shadow In OpenGL

Conceptually, drawing a shadow is quite simple.

A shadow is produced when an object keeps light from a light source from striking some object or surface behind the object casting the shadow. The area on the shadowed object's surface, outlined by the object casting the shadow, appears dark. We can produce a shadow programmatically by flattening the original object into the plane of the surface in which the object lies. The object is then drawn in black or some dark color, perhaps with some translucence. There are many methods and algorithms for drawing shadows, some quite complex.

What's Shadow In OpenGL



Flattening an object to create a shadow.

- We squish an object against another surface by using some of the advanced matrix manipulations. we boil down this process to make it as simple as possible.

What's Shadow In OpenGL

- ▶ We need to flatten the modelview projection matrix so that any and all objects drawn into it are now in this flattened two-dimensional world. **so the position of the plane is the first important thing to know when we want to draw the shadow.**
- ▶ **The next two considerations are the distance and direction of the light source.** The direction of the light source determines the shape of the shadow and influences the size.


What's Shadow In OpenGL

8






What's Shadow In OpenGL

9





What's Shadow In OpenGL

10



What's Shadow In OpenGL

11




Plane Equation

12

Plane Equation

Plane Equation

- In order to find the equation of some plane, we need to know its equation.



- A plane in 3 dimensions can be defined by the equation:
$$Ax + By + Cz + D = 0$$
- Examples:

Math3d Library Functions

Math3d Library Functions

Math3d Library Functions

```
m3dGetPlaneEquation(M3DVector4f vPlaneEquation,  
    points[0], points[1], points[2]);
```

- ▶ We define points vector in this way:

```
M3DVector3f points[3] = {{x1, y1, z1}, {x2, y2, z2}, {x3,  
y3, z3}};
```

Math3d Library Functions

16

- ▶ We calculate the shadow matrix with:

```
m3dMakePlanarShadowMatrix (M3DMatrix44f shadowMat,  
                           M3DVector4f vPlaneEquation, GLfloat lightPos[4]);
```

The Shadow In OpenGL

17

To draw the shadow ,draw the original shape ,after that multiply modelview matrix by shadow matrix.


Some examples

18

Some examples

The Shadow In OpenGL


19



The Shadow In OpenGL

Some examples

20




Example

21

Example

Example

22



Example

23

- ▶ Firstly, we'll declare the following variables before *InitGL* function:
- The properties of light:

```
GLfloat lightPos[] = { -1.0f, 3.0f, 0.0f, 0.0f };  
GLfloat LightAmb[] = {1.0f,1.0f,1.0f,1.0f};  
GLfloat LightDiff[] = {0.6f,0.6f,0.6f,1.0f};
```

- Transformation matrix to project shadow:

```
M3DMatrix44f shadowMat;  
M3DVector4f vPlaneEquation;
```

Example

24

```
M3DVector3f points[3] = {{ -30.0f, -2.0f, -20.0f }, { -30.0f, -2.0f,
20.0f },
                        { 40.0f, -2.0f, 20.0f }};
glEnable(GL_DEPTH_TEST); // Hidden surface removal
// Enable lighting
glEnable(GL_LIGHTING);
glLightfv(GL_LIGHT1, GL_POSITION, lightPos);
glLightfv(GL_LIGHT1, GL_AMBIENT, lightAmb);
glLightfv(GL_LIGHT1, GL_DIFFUSE, lightDiff);
glEnable(GL_LIGHT1);
m3dGetPlaneEquation(vPlaneEquation, points[0], points[1],
points[2]);
// Calculate projection matrix to draw shadow on the ground
m3dMakePlanarShadowMatrix(shadowMat, vPlaneEquation,
lightPos);
```

Example

25

```
gluLookAt(0,0,10,0,0,0,0,1,0);
glBegin(GL_QUADS); //ground
    glColor3f(0,0.2,0);
    glVertex3f(40.0f, -2.0f, -40.0f);
    glVertex3f(-40.0f, -2.0f, -40.0f);
    glColor3f(0,1,0);
    glVertex3f(-40.0f, -2.0f, 40.0f);
    glVertex3f(40.0f, -2.0f, 40.0f);
glEnd();
glPushMatrix(); //light
glTranslatef(lightPos[0],lightPos[1], lightPos[2]);
glColor3ub(255,255,0);
auxSolidSphere(0.1f);
glPopMatrix();
```

Example

26

► Inside *DrawGLScene* (cont'd):

```
//the original shape  
glPushMatrix();  
glEnable(GL_LIGHTING);  
glRotatef(10, 1.0f, 0.0f, 0.0f);  
glRotatef(45, 0.0f, 1.0f, 0.0f);  
glColor3f(1,0,0);  
Draw_Cubic(2,1,3);  
glPopMatrix();
```


Example

27

```
glDisable(GL_DEPTH_TEST);  
glDisable(GL_LIGHTING);  
glPushMatrix(); //the shadow  
glMultMatrixf((GLfloat *)shadowMat);  
glRotatef(10, 1.0f, 0.0f, 0.0f);  
glRotatef(45, 0.0f, 1.0f, 0.0f);  
glColor3f(0,0,0);  
Draw_Cubic(2,1,3);  
glPopMatrix();  
glEnable(GL_DEPTH_TEST);
```

Example

28

Depth testing is some means to determine what is drawn in front of what. However, If two objects occupy the same location, usually the last one drawn is shown when depth testing is disabled.


Homework

29

Homework 😊

Homework 😊

- ▶ Add shadow to the house which you





The
End